

Yak

COLLABORATORS

	TITLE : Yak		
ACTION	NAME	DATE	SIGNATURE
WRITTEN BY		July 26, 2024	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	Yak	1
1.1	Yak v1.59 Documentation	1
1.2	Copyright	1
1.3	Current users: Notez-bien	2
1.4	Introduction	2
1.5	Jokes	3
1.6	Limitations	4
1.7	Starting Yak	4
1.8	Changing Yak's settings	5
1.9	Toggles	6
1.10	AutoPoint	6
1.11	AutoPopToFront	7
1.12	RMB Activate	7
1.13	MMB Activate	7
1.14	Key Activate	7
1.15	Click To Front	7
1.16	Click To Back	8
1.17	Cycle screens	8
1.18	Screen Activate	8
1.19	Wild star	8
1.20	No Click	9
1.21	Inclusion Patterns	9
1.22	AutoScreens	9
1.23	ClickScreens	9
1.24	Default title of a screen	9
1.25	PopWindows	10
1.26	ClickWindows	10
1.27	Miscellaneous Settings	10
1.28	ClickVolume	10
1.29	AutoPoint Delay	10

1.30 MMB replaces	10
1.31 Black border	11
1.32 Blanking Window	11
1.33 MouseBlank Method	11
1.34 Blank mouse on key pressed	11
1.35 TimeOut Settings	11
1.36 ScreenTimeOut	11
1.37 MouseTimeOut	12
1.38 Defining Yak Hotkeys	12
1.39 Hotkey Description String	12
1.40 Automatic Definition	13
1.41 Manual Definition	13
1.42 Hotkey Actions	13
1.43 Dos Command	14
1.44 Close Window	15
1.45 Zip Window	15
1.46 Shrink Window	15
1.47 Expand Window	15
1.48 Cycle Windows	15
1.49 Back Cycle Windows	15
1.50 Open Palette	16
1.51 Screen to Front	16
1.52 Screen to Back	16
1.53 Activate Workbench	16
1.54 Center Screen	16
1.55 Blank Display	17
1.56 Insert Text	17
1.57 Insert Date	17
1.58 Show Yak Interface	18
1.59 Set default public screen	18
1.60 Menu shortcut	18
1.61 AmigaDos Patterns	19
1.62 Date format strings	20
1.63 Problems	21
1.64 Program History	21
1.65 Compiling Yak	24
1.66 Yak development team	25
1.67 Credits	25
1.68 Contacting the Authors	26
1.69 More on HotKeys	26
1.70 Localization	30

Chapter 1

Yak

1.1 Yak v1.59 Documentation

Yak Version 1.59
by Gaël Marziou and Philippe Bastiani
released on 15 June 1994.

TABLE OF CONTENTS

Copyright and Distribution
Current users: Notez-bien
Introduction
Limitations
Starting Yak
Changing Yak's settings
 Toggles Patterns Blanking Miscellaneous Hotkeys
Hotkey Actions
AmigaDos Patterns
Date format strings
Problems
Localization
Program History
Compiling Yak
Credits and Thanks
Development team
Contacting the Authors

1.2 Copyright

Yak (the binary, sources and documentation) is
Copyright © 1993, 1994 Gaël Marziou & Philippe Bastiani. All Rights reserved.

Yak is freely redistributable. The source is included, and you are permitted to modify it for personal use, but any modifications made must NOT be distributed. If you have made changes you think others would like, send them to me and I'll include them in future versions.

Since Yak is free, it comes with NO WARRANTIES. The authors are not

responsible for any loss or damage arising from the use of Yak; the user takes all such responsibility.

No charge may be made for Yak, other than a nominal copy fee. Yak may not be distributed with a commercial product without the authors prior consent. Yak must be distributed with all documentation intact and unaltered, and preferably with source too. Permission is expressly granted to Fred Fish to distribute on his fine collection of disks.

Although Yak is freeware, DONATIONS WOULD BE GLADLY ACCEPTED, either money or stuff you've written yourself. See [Contacting the Authors](#) .

1.3 Current users: Notez-bien

Yak's preference file format has changed again, with preferences being split into two files, "S:Yak.prefs" and "S:Yak.hotkeys". A Convert program is supplied to create the 1.5 preference files from a 1.3/1.4 preference file. There are two flaws in the conversion: you must reenter the PopCommand and DateFormat strings using the new Hotkey Definition window (see section [Hotkeys](#) for details on how to do this); the other flaw is that a hotkey will be created to "Show settings window", which is probably superfluous, given the discussion on CX_POPKEY below.

There are some important changes between v1.4 and 1.5 of Yak. Most importantly, the stack requirement has been increased to 4500 bytes, so do remember to change the stack size in the icon you use to start Yak.

Secondly, the AppIcon is by default OFF, and should be explicitly enabled using the APPICON=TRUE tooltip. This tooltip replaces the NOICON tooltip.

Thirdly, the CX_POPKEY tooltip is used to determine the hotkey which opens Yak's settings window, and this key cannot be altered or overridden within the Hotkey definition window (unlike in previous versions); however, you can create other hotkeys which also open Yak's window.

Fourthly, Yak has been localized and supports now english as built-in language and french and german with catalogs provided. If you want to localize Yak into your own language, please contact me (see section [Contacting the authors](#) and [Localization](#)).

Of course, there have been many other changes, and you should browse through this document to accustomise yourself with them.

1.4 Introduction

Yak stands for "Yet Another Kommodity" (never was any good at spelling - see [Jokes](#)), and is a mouse/window manipulation program along the same lines as DMouse, MightyMouse etc.

Why write another one? None of the others (and I've looked at almost all of them) were quite right for me. Yak has the following features:

- o AutoPoint (sunmouse) that only activates when mouse stops
can also specify which screens to include/exclude.
(Compatible with popup-menu type programs)
- o AutoPop windows (bring them to front) when they're
auto-activated;
- o KeyActivate windows (when key pressed);
- o Activate windows when menu button pressed;
- o Click windows to front or back; may also specify which
screens/windows to include/exclude.
- o Cycle screens with mouse;
- o Mouse and Screen blanking (hotkey blanking too);
- o Extensible hotkey system (like FKey's) with actions to:
 - Execute a Dos Command;
 - Insert text (with embedded hotkeys);
 - Insert date (in custom format if locale present);
 - Close/Zip/Shrink/Enlarge windows;
 - Cycle screens and windows;
 - Activate Workbench;
 - Center frontmost screen;
 - Blank display;
 - Pop up a palette on front screen (needs reqtools);
- o KeyClick with adjustable volume;
- o No Click option (for drives).
- o Wildstar option (like StarBurst) lets you use '*' as wildcard.
- o Optional on-screen AppIcon to bring up preferences window.
- o Nice gadtools settings window;

Look familiar? It's a combination of the AutoPoint, ClickToFront, Blanker and IHelp/FKey standard commodities (on the Extras disk) with a hint of KCommodity and DMouse thrown in.

And it's quite small: it takes up about 29K on disk, and about the same when running. It achieves this memory efficiency by using overlays; the settings window code is only loaded when needed. That means that Yak uses more memory when you opens Yak window configuration (about 45K).

1.5 Jokes

These might be old, but they're good:

Q. What's the difference between a goldfish and a goat?

A. A goldfish mucks around in fountains!

And if you got that one, you'll definitely get this one...

Q. What's the difference between a magic wand and a truncheon (baton).

A. A magic wand is used for cunning stunts.

(I **always** say that last answer wrong)

1.6 Limitations

Yak only has a plain screen-blanker. Since the introduction of OS 2.0, there has been a profusion of fancy screen blankers, such as Spliner, ASwarm (various incarnations), FracBlank and more. I think most people have their own favourite fancy blanker, so I didn't include one in Yak.

There is no mouse-acceleration. The system default one (settable via the Input preferences) is more than adequate as far as I am concerned. If I get enough requests, I'll add faster acceleration (so far, hardly any received).

1.7 Starting Yak

Yak is designed to be run from the sys:WBStartup drawer, but may be 'run' from the Shell (not recommended, as it will use significantly more memory). All Yak settings are stored in two files, a prefs-file, "S:Yak.prefs", and a hotkey file, "S:Yak.hotkeys". The best thing to do is to use the installation script then when you first use Yak, configure it the way you like, then save that configuration for later invocations.

NB: Yak needs a stack size of 4500 bytes. You should set this in Yak's icon, or if starting it from the Shell, use the following commands:

```
stack 4500
run >nil: yak
```

The only tooltypes that Yak takes are the standard Workbench ones (such as DONOTWAIT), the standard Commodities ones (such as CX_POPUP), the AppIcon ones and the LANGUAGE one. Those tooltypes are:

ToolType	Category	Description	Default
CX_POPKEY	HOTKEY	Key to show settings window	RCommand Help
CX_PRIORITY	INTEGER	Priority of this commodity	0
CX_POPUP	BOOLEAN	Show settings window on startup	NO
APPICON	BOOLEAN	If TRUE, an AppIcon is made	FALSE
ICONNAME	STRING	Name of AppIcon	"Yak!"
ICONXPOS	INTEGER	x-coordinate of AppIcon	floating
ICONYPOS	INTEGER	y-coordinate of AppIcon	floating
LANGUAGE	STRING	Name of language to use	Not specified

You should also have the tooltype "DONOTWAIT" set if you want to start Yak from your SYS:WBStartup drawer.

The AppIcon facility is optional, and by default is off. Specify APPICON=TRUE if you want it. If you do, Yak puts an AppIcon onto the Workbench screen, and when it is double-clicked, the Settings Window is opened. The icon imagery is obtained from the icon Yak was started from, which allows you to customise the AppIcon to your colours/resolution simply by changing Yak's icon.

The CX_PRIORITY may be useful in enabling Yak and other commodities to work better together. See, for example, notes on the RMB/MMB Activate toggle below.

The LANGUAGE tooltype has been added for people using Workbench in one language and Yak in another one. For example, french friends of mine are used to english workbench but want to use Yak in french so they just have to set the LANGUAGE tooltype as this :

```
LANGUAGE=français
```

Of course, those of you who want to use same language for both Yak and workbench don't have to worry about this tooltype.

1.8 Changing Yak's settings

All of Yak's settings may be modified by means of it's settings window. Once Yak is started, you may bring up this window by the following means:

Pressing RCommand Help (i.e. the Right Amiga key and the Help key). This key-sequence is configurable (via the CX_POPKEY tooltype);

Double-clicking Yak's AppIcon (if this feature is set);

Start Yak again (from Workbench tool icon);

Via the Commodities Exchange (on the Extras disk).

The window then opened contains many gadgets, grouped into classes. These classes are:

- Toggles
- Patterns
- Blanking
- Miscellaneous
- Hotkeys

Remember that you must press the RETURN, ENTER or TAB key once you have edited a string gadget, so that the change is registered. Simply clicking outside it will lose the changes. (The TAB key activates the next string gadget for text entry).

Also (and this applies particularly to the hotkey window), Intuition by default does not let you cut and paste between string gadgets, but if you

want this, you should get "NewEdit" by Uwe Roehm, which adds clipboard copying and pasting (it's on a Fish disk and ftp sites).

Additionally, the two gadgets "Hide" and "Quit" perform the standard commodity operations respectively of hiding the settings window and terminating Yak. Clicking the window's close-gadget is equivalent to hiding the interface rather than ending Yak.

The settings window also has a menu with "Hide" and "Quit" items (which operate as the gadgets of the same name), plus items "Load" and "Save". All changes to Yak's settings will be lost unless you select the "Save" item. If you wish to restore you're last-saved settings, you may use the "Load" item.

1.9 Toggles

The following toggles are available:

AutoPoint

AutoPopToFront

Key Activate

Click To Front

Click To Back

MMB Activate

RMB Activate

Cycle Screens

Screen Activate

1.10 AutoPoint

Activate window under mouse. This behaves almost exactly like Commodore's AutoPoint commodity, in that it only activates a window when the mouse stops. AutoPoint is compatible with popup-menu type programs such as the excellent MagicMenu.

Note that the AutoPoint and AutoPopToFront functions only take place when NO qualifier (mouse or keyboard) is pressed. Not only does this avoid conflict with other programs, it provides a way of preventing activation/popping when it's not desired.

See also: AutoPopToFront AutoScreens

1.11 AutoPopToFront

Only operative when AutoPoint is set, this tells Yak to bring windows to the front as well as activating them. The exception is when the window under the mouse has a requester showing.

See also: AutoPoint AutoScreens PopWindows

1.12 RMB Activate

When selected, the window under the mouse will be activated when the right mouse button is pressed, regardless of the status of AutoPoint. This is useful in getting the menu you want without either waiting for AutoPoint to activate the window or clicking into the window to make it active.

For instance, when using the screen depth gadgets, the new front screen is not activated, but with this toggle set, clicking the RMB will get the correct menus.

Note 1: If there is no window under the mouse, the first window on the screen will be activated.

Note 2: To work properly with popupmenu-type programs, Yak's CX_PRIORITY may need to be higher than the popupmenu program's CX_PRIORITY.

1.13 MMB Activate

When selected, the window under the mouse will be activated when the middle mouse button is pressed, regardless of the status of AutoPoint. This is useful in getting the menu you want without either waiting for AutoPoint to activate the window or clicking into the window to make it active.

Note 1: If there is no window under the mouse, the first window on the screen will be activated.

1.14 Key Activate

Activates window under mouse when key is pressed. You should only need one of AutoPoint or KeyActivate.

1.15 Click To Front

Lets you bring a window to the front of others by double-clicking over it.

As with AutoActivate/AutoPopToFront features, clicking to front and back is disabled whilst a keyboard qualifier is pressed.

When `Cycle Screens` is activated, this feature works for screens, too.

See also: `ClickScreens` `ClickWindows`

1.16 Click To Back

Lets you push a window to the back of others by pressing and holding the left mousebutton, then clicking the right mousebutton.

As with `AutoActivate/AutoPopToFront` features, clicking to front and back is disabled whilst a keyboard qualifier is pressed.

When `Cycle Screens` is activated, this feature works for screens, too.

See also: `ClickScreens`

1.17 Cycle screens

Using the same mouse sequence as `Click To Back` (or `Click To Front`), move a screen to the back (or to the front) of others if:

- either the window under the mouse is a backdrop window (like the main Workbench window)
- or there is only one window on the screen.

See also: `Click To Back` `Click To Front`

1.18 Screen Activate

When checked, Yak will activate screens that it shuffles by hotkeys (i.e. `Screen Cycle` hotkey and `LCommand m` hotkey). This is a toggle because conflicts arise with some programs. This is similar (but not identical) to Steve Tibbet's `WindX`.

By activating screens I mean that it activates a window of this screen, this window can be :

- the window that was active last time you have visited this screen by cycling screens via Yak's hotkeys.
- the window under the mouse-pointer if this screen has never been visited before.
- the first window of this screens if both previous conditions failed.

1.19 Wild star

When `on`, enables the use of `*` as an AmigaDos pattern-matching character (like MSDOS and UNIX `*`). (This is what the StarBurst program does.)

1.20 No Click

When `on`, stops your floppy drives from "clicking" when they're empty.

1.21 Inclusion Patterns

The pattern gadgets allow you to specify which screens and windows are affected by various features of Yak. All patterns are inclusion patterns, i.e. the title of the window or screen must `MATCH` the pattern for the relevant feature to work. All patterns are standard AmigaDos Patterns.

The following patterns are available:

`AutoScreens`

`ClickScreens`

`PopWindows`

`ClickWindows`

1.22 AutoScreens

`AutoPoint` will work on screens whose default title matches this pattern.

Default title of a screen

1.23 ClickScreens

`Click To Front` and `Click To Back` will work on screens whose default title matches this pattern.

Default title of a screen

1.24 Default title of a screen

The default title of a screen doesn't vary. Windows of applications can change the screen title but not the default screen title. For example, the title of the workbench screen is often changed by applications when their own windows are active but the default title of the workbench screen remains unchanged.

So, when setting a screen pattern you should use the default title of the screen which can be found when no window is active on this screen. Most of the time, finding the default title will be very easy but in some rare case you will gain to use an utility such as ARTM.

See also `AmigaDos Patterns` .

1.25 PopWindows

`AutoPopToFront` will work on windows whose title matches this pattern.

1.26 ClickWindows

`Click To Front` will work on windows whose title matches this pattern.

1.27 Miscellaneous Settings

This window contains a few other features controlled by these gadgets. They are:

`Click Volume`

`AutoPoint Delay`

`Wild star` `Black border`

`No Click`

1.28 ClickVolume

Controls the volume of the `KeyClick` (the sound made when you press a key). A volume of zero means 'no click' (yes, that's obvious, but when set to zero, the audio device won't be opened at all). Maximum volume is 64.

1.29 AutoPoint Delay

Controls how long Yak should be waiting after mouse has stopped before activating window under mouse. This value must be into the 0 to 5 interval which correspond to 10 ms step.

A delay of zero means no delay, obvious isn't it ?.

1.30 MMB replaces

Controls what qualifier MMB (Middle Mouse Button) should replace.

1.31 Black border

When on, Yak will add a black border to all your screens. This feature is only available in 3.0+ system version as it uses a new flag of the graphics library.

1.32 Blanking Window

MouseBlank Method

Blank mouse on key pressed

TimeOut

1.33 MouseBlank Method

This gadget determines the method by which the mouse pointer is blanked. "None" disables mouse-blanking altogether, "Sprites" means blank mouse by disabling (all) sprites, and "Copper" means blank mouse by modifying copper list. This latter option only disables sprite 0 (the mouse-pointer), so terminal programs using a sprite for the cursor work okay, but the method is a bit less robust (the mouse occasionally comes back on).

See also: Problems

1.34 Blank mouse on key pressed

This is a toggle if set, mouse pointer will be blanked as soon as you hit the keyboard. If it is not set, mouse will be blanked only on time out.

1.35 TimeOut Settings

With this gadgets, you can set up timeout for screen and mouse blanking.

ScreenTimeOut

MouseTimeOut

1.36 ScreenTimeOut

If no user input (mouse or keyboard) occurs over this period (of seconds), the screen will blank. Set it to 0 to disable screen blanking altogether. The blanking is performed by opening a 2-color screen with the same displaymode as the frontmost screen.

1.37 MouseTimeOut

If mouse isn't moved in the period specified, the mouse pointer will blank. This is only operational if the MouseBlank Method is not set to "None".

1.38 Defining Yak Hotkeys

Clicking on the "Hotkeys..." gadget opens up a new window which lets you create, edit and delete hotkeys. Making a key a hotkey means that when the key is pressed, Yak performs some action (of which there are many to choose from). Hotkeys are defined using a hotkey description string, which is a very flexible method of defining input events.

You can have as many hotkeys as you like, and each action may pertain to more than one hotkey.

There are two lists in the Hotkey Definition window; the left-hand one lists the available actions, and the other lists the hotkeys currently defined for the selected action.

To add a new hotkey, first select the action you wish it to perform (by clicking its name in the left-hand list). Then click on the Add gadget below the Hotkey list.

To edit an existing hotkey, double-click its name in the right-hand list.

To delete a hotkey from Yak's list, use the Delete gadget.

For certain actions, other gadgets will become active. The Options gadget (the cycle gadget below the Actions list) determines what happens to screens when the hotkey is pressed. Currently, the options are to do nothing, to bring the Workbench to the front, and to bring the default public screen to the front. Typically this will be used in Dos Command hotkeys to automatically show the screen a window opens on.

The Argument gadget is a string gadget which becomes active for certain Action types, and provides a means of setting a string to be attached to the Hotkey.

When you're finished editing hotkeys, click on the "Ok" gadget to return to the main settings window, or the close gadget to 'hide' Yak. Remember to save your changes using the "Save" menu item of the main settings window.

See Hotkey Actions
Hotkey Description String

1.39 Hotkey Description String

You can define or modify hotkeys used by Yak here.

The current hotkey description is displayed within the string gadget.

There are two transparent ways to define a hotkey:

Automatic Definition

Manual Definition

Once you've finished editing a hotkey, click on the 'Ok' gadget to register the new description string.

Click on the 'Cancel' gadget to abort the hotkey definition.

1.40 Automatic Definition

Simply choose the hotkey class (by clicking on the left-hand cycle gadget); then hit the keys and mouse buttons, you want to use: Yak convert them into an input description string.

Toggle mode is used. So, if you press a key twice it will be removed from the definition.

With the stroke gadget (the right-hand cycle gadget) you can set the method by which the hotkey will be activated.

See also: [More on Hotkeys](#)

1.41 Manual Definition

Click on the string gadget and type in the hotkey description string: Yak parses string and updates gadgets.

NOTE: 'NewPrefs', 'PointerPos', 'Timer' and 'Event' classes are not supported yet!...

WARNING: The commodities.library is not bug free:

-here is a wrong description string:

`'NumericPad a'`

-here are some unusable description strings:

`'NumericPad ['` and `'NumericPad]'` (with a french keyboard)

See also: [More on Hotkeys](#)

1.42 Hotkey Actions

The many actions available are:

Dos Command
Close Window

- Zip Window
- Shrink Window
- Expand Window
- Cycle Windows
- Open Palette
- Screen to Front
- Screen to Back
- Activate Workbench
- Center Screen
- Blank Display
- Insert Text
- Insert Date
- Show Yak Interface
- Back Cycle Windows
- Set default public screen
- Menu shortcut

1.43 Dos Command

Argument: command to execute

Executes the Dos command as specified in the Argument string. Note that you may use the Options gadget to bring the Workbench or default public screen to the front (useful if the command causes a window to open).

The command is executed asynchronously, so there is no need to prepend a run command. Also, if the command generates any output (or requires input), a console window will open. You can of course specify redirection (as in the shell).

Examples:

A hotkey to open a shell:

This is traditionally attached to the hotkey "lcommand esc", and mine is set up to run the command

```
"NewShell CON:79/177/582/78/AmigaShell/CLOSE/ALT2/58/660/197"
```

Note the use of the ALT flag in the console specification, which is poorly documented (read "not mentioned"). I actually use two hotkeys, one to start a normal shell, and one to start a CShell.

A hotkey to free unused memory:

SAS/C uses shared libraries that can often fill precious chip memory. I have a hotkey set up with the command "avail >nil: flush" which frees this memory.

A hotkey to list contents of each disk inserted:

Set the hotkey to "diskinserted", and the Argstring to "Dir df0:".

See also: Problems More on Hotkeys

1.44 Close Window

Argument: NONE

Close the currently active window (this is equivalent to clicking on the window's close gadget).

1.45 Zip Window

Argument: NONE

Zip the currently active window (this is equivalent to clicking on the window's "Toggle size" gadget).

1.46 Shrink Window

Argument: NONE

Make the currently active window as small as possible.

1.47 Expand Window

Argument: NONE

Make the currently active window as large as possible.

1.48 Cycle Windows

Argument: NONE

Bring the rearmost window to the front. Useful for getting at deeply 'buried' windows.

1.49 Back Cycle Windows

Argument: NONE

Works the inverse way as "Cycle Windows": puts the frontmost window to background.

1.50 Open Palette

Argument: NONE

Open a palette on the frontmost screen. The palette is run asynchronously, and you can open as many as you want (subject to memory). However, Yak cannot be terminated while palettes remain open. The Options gadget is enabled for this command (so you can open a palette specifically on the Workbench screen, if you so wish).

NOTE: You must have `regtools.library` installed on your system for this action to work.

WARNING: Always close the palette window before causing the screen it's on to close, otherwise you'll at least be left with an open screen, and at worst crash the system.

1.51 Screen to Front

Argument: NONE

Bring the rearmost screen to front.

See also: `ScreenActivate`

1.52 Screen to Back

Argument: NONE

Push the front screen behind all others.

See also: `ScreenActivate`

1.53 Activate Workbench

Argument: NONE

Activate a Workbench window (and if necessary, bring the Workbench screen to the front). This enables you to access the Workbench menus without having to find a Workbench window to activate (if, for instance, you had a shell window the size of the screen).

1.54 Center Screen

Argument: NONE

Center horizontally the front screen.

1.55 Blank Display

Argument: NONE

Immediately blank the display.

See also: `ScreenTimeOut` .

1.56 Insert Text

Argument: text to be inserted

Inserts the text specified in the Argument string into the read stream. This string is preprocessed as follows:

<code>\n</code>	converted to carriage-return
<code>\r</code>	converted to carriage-return
<code>\t</code>	converted to tab
<code>\</code>	converted to backslash <code>\</code>
<code><hotkey desc></code>	converted to specified hotkey
<code>\<</code>	converted to <code><</code>

Because of this preprocessing, insertion strings can perform many useful tasks. For example, I have a hotkey set up to insert my name and the date, using the argument string (without the quotes):

```
"Martin W Scott, <lcommand d>"
```

Here, the hotkey "lcommand d" is another Yak hotkey I have set up to insert the date. By using more complicated strings, you can create simple macros for other programs.

CAVEAT: Embedded hotkey strings, though useful, should be used with care. In particular, you must avoid recursive definitions, e.g.

```
f1 insert text "<f2>"
f2 insert text "<f1>"
```

Pressing `f1` or `f2` results in an endless loop. If you are silly enough to do this, start the Commodities exchange and make Yak inactive. Then select the Exchange's Show Interface gadget and delete/redefine the offending hotkey(s).

Another thing to be aware of is that strings that call other hotkeys (e.g. the date insertion example above) may not work as you might think. Suppose the Argument string was "`<lcommand d>\n`". This would actually create a carriage return and THEN the date, because by the time Yak gets the "lcommand d" hotkey, the carriage return has gone through the input handler and been sent to the active window.

1.57 Insert Date

Argument: date format string

Insert the date into the read-stream (and so into the currently active window). If you are running AmigaDos 2.1 or above, you may customise the format of the date inserted. This format is specified in the Argument string. See Date format strings. If you are unlucky enough to be running AmigaDos 2.0, the date is in standard DD-MMM-YY format.

Example: the format "%e %B %Y" generates dates of the form "1 May 1993".

1.58 Show Yak Interface

Argument: NONE

Show Yak's settings window. This window will open on your current screen if it is a public screen otherwise it will bring to the front the default public screen before opening the window on it. This is the same function that the CX_POPKEY hotkey performs.

1.59 Set default public screen

Argument: NONE

Set the current screen as the default one. This will work only if the current screen is a public one.

1.60 Menu shortcut

Argument: menu, item and optionally subitem

Sends an input event to menu of the current active window, simulating a user choice in the menu (if any). This can be useful to add some keyboards shortcuts to applications that don't have ones or not enough.

The argument string specifies the menu number, the item number and optionally the subitem number. All these numbers are separated by white spaces and start at 0 following the Intuition rule (i.e first menu is menu 0 and not 1).

Note that a bar label counts as an item, if before the item you want to access there are several bar labels you must take them into account while specifying the item number.

However, don't be afraid if you make mistakes in specifying the argument string as Yak does all needed checkings before sending a menu event in order to avoid disturbing your application menu handler.

Here are some examples of argument string specification :

You find that the workbench has not enough menu shortcuts :

To access the "Last Message" item of the "Workbench" menu : "0 4"

To access the "Only Icons" subitem of the "Show" sub menu of the "Window" menu : "1 7 0"

1.61 AmigaDos Patterns

AmigaDos patterns are used to include/exclude a list of named screens/windows for a particular feature. These pattern specifications aid in compatibility with other programs you may use.

Pattern matching is case-sensitive. "Amiga" is not the same as "AMIGA". The standard AmigaDos patterns available are:

?	Matches a single character.
#	Matches the following expression 0 or more times.
(ab cd)	Matches any one of the items separated by ' '.
~	Negates the following expression. It matches all strings that do not match the expression (aka ~(foo) matches all strings that are not exactly "foo")
[abc]	Character class: matches any of the characters in the class.
a-z	Character range (only within character classes).
%	Matches 0 characters always (useful in "(foo bar %)").
*	Synonym for "#?", not available by default. Available if Wild star option is set.

If you're not used to patterns, you may find all of that quite daunting. Consult your system manual for further details. There are two basic things you'll want: either a finite list of names that the feature should be enabled on, or a finite list for which it should be disabled. To ENABLE a feature on all objects (be they screens or windows, as appropriate) use the "#?" pattern (matches everything). To enable a feature on N objects named "name1" to "nameN", use

```
(name1|name2| ... |nameN)
```

and to DISABLE the feature for these names, prepend a tilde ~, viz.

```
~(name1|name2| ... |nameN)
```

An example: I don't want AutoPopToFront popping the Workbench window or any Protect (WP from Arnor) window, so exclude them with the pattern

```
~(Workbench|#?Arnor#?)
```

Note that the second 'name' is actually a pattern, which matches any title with the text "Arnor" in it.

Another example: I don't want AutoActivation on Directory Opus's screen. It doesn't show its title in the program so I have to use ARTM or Xoper to find the screen's default title, and find that it's "DOPUS.1". Figuring that the "1" would bump to "2" if I ran two copies, I decide to exclude

all DOpus screens using

```
~(DOPUS#?)
```

Yet another example : I don't want AutoActivation on BrowserII's screen. The default title (when no window is active) is BrowserII followed by the names of the authors and the copyright years. As these years will evolve, I decide to exclude BrowserII screen by using :

```
~(BrowserII#?)
```

Note : Screens or windows with titles that are unset (i.e. are NULL) always pass the patterns.

1.62 Date format strings

For date-insertion hotkeys, you must specify a locale-style date format string (and need to be running AmigaDos 2.1 or higher). The available formatting options under locale.library are as follows:

```
%a - abbreviated weekday name
%A - weekday name
%b - abbreviated month name
%B - month name
%c - same as "%a %b %d %H:%M:%S %Y"
%C - same as "%a %b %e %T %Z %Y"
%d - day number with leading 0s
%D - same as "%m/%d/%y"
%e - day number with leading spaces
%h - abbreviated month name
%H - hour using 24-hour style with leading 0s
%I - hour using 12-hour style with leading 0s
%j - julian date
%m - month number with leading 0s
%M - the number of minutes with leading 0s
%n - insert a linefeed
%p - AM or PM strings
%q - hour using 24-hour style
%Q - hour using 12-hour style
%r - same as "%I:%M:%S %p"
%R - same as "%H:%M"
%S - number of seconds with leadings 0s
%t - insert a tab character
%T - same as "%H:%M:%S"
%U - week number, taking Sunday as first day of week
%w - weekday number
%W - week number, taking Monday as first day of week
%x - same as "%m/%d/%y"
%X - same as "%H:%M:%S"
%y - year using two digits with leading 0s
%Y - year using four digits with leading 0s
```

That list is pretty exhaustive, and should handle most needs; you can insert your own text freely in the format string. Some examples:

"The time is %X"	gives (e.g.)	"The time is 20:44:16"
"Have a nice %A!"	gives (e.g.)	"Have a nice Monday!"

If you need more details, consult the AutoDocs on locale.library if you have them.

1.63 Problems

There are a few problems that I am currently aware of. Firstly, a shell created by a Dos Command hotkey doesn't have the stack or current directory as set at boot-time (in the Startup-Sequence). It DOES retain your path, though. Your Shell-Startup file should set the CD and the stack you need. By default, processes started in this way have the system boot disk (SYS:) as their current directory.

If you're not happy with Yak's mouse-blanking, you could try the Commodore MouseBlank commodity (WB3.0), which should blank the mouse on all displays correctly. On AGA machines, Copper blanking causes problems if you are using an hires mouse pointer : use Sprites blanking or Commodore MouseBlank instead.

NOTE FOR OneKeyII USERS: disable OnekeyII when you edit a hotkey!

NOTE FOR AMOS USERS: I don't like AMOS (that's enough of my opinion), partly because it is so system unfriendly. It completely steals the input stream, so that mouse blankers (in programs like Yak) kick-in, thinking there's been no input, and the mouse isn't restored, because there's no mousemoves to unblank it. Because Yak uses a rather bad blanking method, problems can occur (mouse vanishes and won't come back). Two solutions:

- 1) Use 'Copper' blanking.
- 2) Set MouseBlankTime to zero. You'll still have key blank, but no timed blank.

Then the AMOS problem of the pointer disappearing should be solved.

1.64 Program History

(* = new feature)

v1.59 - Enforcer hit fixed when clicking on 'miscellaneous' gadget.

- Enforcer hit fixed when opening a palette.
 - Bug fixed : ClickToBack toggle had no effect.
 - Bug fixed : ScreenActivate toggle had no effect.
 - Bug fixed : NoClick and WildStar gadgets were inverted.
-

- Bug fixed : MouseBlank Method gadget had no effect.
- Bug fixed : automatic definition of hotkeys was using V38 keywords and so wasn't usable in V37.
- Bug fixed : ClickToBack and ClickToFront caused system to freeze.
- * Yak now remember the window that was activated last time it visited a screen via hotkey screen cycling.
- * New hotkey "Menu shortcut" to choose a menu item.

v1.58 - Bug fixed in 'BackCycle Windows' hotkey.

- Bug fixed in the GUI for AutoPoint delay and ClickVolume, values outside the valid range were causing crashes.
- Bug fixed in mouse blanking when disabling Yak with CLIXchange.
- Bug fixed when quitting Yak, it was a 1.57 regression.
- Bug fixed in ClickToBack.
- * Now when alt key is pressed, Yak doesn't blank the mouse so that accessing menus via keyboard is easier.
- * Now compilable with both SAS C 6.51 and with DICE !
- * Black border for screens (available only in 3.0+).
- * New layout of the GUI redesigned by Reza Elghazi.
- * Palette title localized.
- * Screen patterns now use screens default titles instead of current screen title. It makes easier writing patterns for screens such as workbench or BrowserII ones.
- * New hotkey to set default public screen.
- * New way to automatically define a hotkey by hitting it done by Philippe Bastiani.
- * Now Yak can open only one palette per screen.
- * Added a danish catalog, installation script and documentation.
- * Overlay code has been removed.

v1.57 - Main Window setting will now remember where the 2 other windows were before closing.

- Now compiled with SAS C 6.50, code size reduced by 2 Kb !

v1.56 - Windows setting will now open always just under screen title bar whatever is the height of the screen font.

- * Added a "MMB Activate" toggle.

- Close Window hotkey now works also for shell windows.

- * Added a swedish and a dutch catalog.

- * Windows setting will now open on current screen if it is a public one otherwise they will open on default public screen.

- Bug fixed in finding which window is under mouse when several screens are visible at the same time on display. Thanks to Pierre Carette who reported the bug and gave me a fix for it.

- * New behavior ClickToFront, it now behaves as ClickToBack regarding screens if "Cycle Screens" toggle is selected.

- * Added a window "Miscellaneous" to make easier integration of new features.

- * AutoPoint Delay is now configurable from 0 to 5 by step of 10 ms.

- * Added two new icons for MagicWB 8 colors environment.

- * Added german and italian amigaguide documentations.

v1.55 - Fixed a stupid bug that prevents Yak 1.54 from running under Workbench 2.04

- Windows settings layout enhanced when using small height font.

- Installer script now will not overwrite Yak's icon previously installed to avoid loosing tooltypes changes made by users.

- Changes in archive distributed on aminet, source has been put in another archive and the other icons have been removed from distribution.

- * Added a new hotkey "Back Cycle Windows"

- * Added an italian catalog and installation script.

v1.54 * Added a tooltype LANGUAGE to select a different language than the one saved in locale.prefs.

- * Added a NoClick feature for floppy drives.

- * Added a german catalog and its installation in the installer script.

- Greatly reduced size of Yak (about 10 kb less!) It has been obtained by using CATCOMP_BLOCK instead of CATCOMP_ARRAY.

v1.53 - Fixed a stupid bug that displayed an unneeded requester when using

other language than french.

- * Added localization for error messages (french catalog updated)

- Fixed a bug in the installer script about installation of french catalog.

v1.52 * Added localization and french catalog.

- * Added installer script.

- New version numbering to use RCS archiving.

- Fixed a little bug in NewMenus rendering in 3.0.

- Cosmetic changes to documentation and interface.

- Now compiled with SAS C 6.3

v1.5a - Stack requirement increased (may have been outgrowing previous stack size).

- NOICON tooltype removed, APPICON tooltype added in its place.

- Further tweaking of new Hotkey system.

v1.5 * Extensible hotkey system added.

- * Revamped GUI.

- * Documentation now in AmigaGuide format (oh really??).

- * Date insertion now also works on 2.0 machines.

- New preference file format, and now also uses a hotkey file.
Prefs files for earlier versions cannot be loaded.

<history for v1.4 and below has been omitted>

1.65 Compiling Yak

Yak has been written to compile under SAS/C, and as from v1.4a, using SAS/C version 6.2. The code passes cleanly with ANSI checking, so users of other ANSI-compliant compilers should have little problem recompiling - the only places changes may be needed are in SAS-specific keywords (like `__savesd`).

Yak uses overlays, but this can be compiled out by removing the definition `USE_OVERLAYS` in `SCOPTIONS`.

GTB 2.0b was used to generate the user-interface. The generated code (`popup.c`, `popup.h`) needs only minimal modification, specifically to use

NewLookMenus under WB3.0 and above; changes are indicated by comments beginning with four asterisks, e.g. /**** ADDED */.

1.66 Yak development team

Yak development is a team work.

Programming

Gael Marziou
Philippe Bastiani
Reza Elghazi (GUI)

Translations, suggestions and beta testing

Alex Galassi : italian doc, installer script and catalog.
Ingolf Koch : german doc, installer script and catalog.
Christian Høj : danish doc, installer script and catalog.
Patrick van Beem : dutch installer script and catalog.
Johan Billing : swedish catalog.
Peter Eriksson : swedish installer script.

1.67 Credits

Yak is written entirely in C, and compiled with SAS/C 6.3. Thanks to Reza Elghazi for help in the transition to 6.2.

The Settings window gadgetry was created using the excellent (apart from the v2.0 glitch:) GadToolsBox v2.0b, from Jaba Development.

Yak makes use of reqtools.library, which is Copyright Nico François. Thanks must also go to Steve Koren for SKsh, Matt Dillon for DMouse (which answered many of my how-to questions), and Kai Iske for KCommodity, which is where the KeyClick sound was 'borrowed'.

Yak also uses WB2CLI, a very useful little link-module by Mike Sinz.

Thanks also to Heinz Wrobel for his wonderful port of RCS to the Amiga, to Pierre Carette and Sylvain Rougier for BrowserII, Martin Korndörfer for his MagicMenu and to my friends of the french Amiga mailing list who helped me for the french localization of Yak.

The HotKey definition documentation is taken from the ToolsManager distribution, by kind permission of Stefan Becker.

Thanks to Stefan Sticht for his public domain MouseBlanker commodity - this is where I pinched the 'Copper' mouse-blanking method.

And a big thank-you to all those people who have written to me about Yak with suggestions and bug reports.

Thanks also to Martin Huttenloher for his wonderful icons package : MagicWB.

Thanks to Osma Ahvenlampi who draw a beautiful icon for Yak in MagicWB style.

Thanks to Nicola Salmoria who explained me the principle of the "black border" feature.

And last but not least, thanks to Martin Scott who created Yak.

1.68 Contacting the Authors

We can be reached with comments, suggestions, bug reports, praise, money etc. at the following addresses:

Gaël Marziou
Cidex 103
38920 CROLLES
FRANCE

OR BY EMAIL (preferred): gael@gnlab030.grenoble.hp.com

and:

Philippe Bastiani
7 Boulevard Ricard
13003 MARSEILLE
FRANCE

1.69 More on HotKeys

This information is adapted from the ToolManager V2 documentation, and is reproduced with kind permission of that program's author, Stefan Becker.

How to define a Hot Key
=====

This chapter describes how to define a Hot Key as an Input Description String, which is then parsed by Commodities. Each time a Hot Key is activated Commodities generates an event which is used by a Commodity in the chain. A description string has the following syntax:

```
[<class>] {[<qualifier>]} [-][upstroke] [<key code>]
```

All keywords are case insensitive.

'class' describes the InputEvent class. This parameter is optional and if it is missing the default 'rawkey' is used. See InputEvent classes.

Qualifiers are "signals" that must be set or cleared by the time the Hot Key is activated; otherwise no event will be generated. For each qualifier that must be set you supply its keyword. All other qualifiers are expected to be cleared by default. If you want to ignore a qualifier, just set a '-' before its keyword. See Qualifiers.

Normally a Hot Key event is generated when a key is pressed. If the event should be generated when the key is released, supply the keyword 'upstroke'. When both press and release of the key should generate an event, use '-upstroke'.

The key code is depending on the InputEvent class. See Key codes.

Note: Choose your hot keys *carefully*, because Commodities has a high priority in the InputEvent handler chain (i.e. will override existing definitions).

InputEvent classes

=====

Commodities supports most of the InputEvent classes that are generated by the input.device. This section describes those classes that are most useful for Hot Keys.

'rawkey'

This is the default class and covers all keyboard events. For example 'rawkey a' or 'a' creates an event every time when the key "a" is pressed. You must specify a key code for this class. See rawkey key codes.

'rawmouse'

This class describes all mouse button events. You must specify a key code for this class. See rawmouse key codes.

'diskinserted'

Events of this class are generated when a disk is inserted in a drive. This class has no key codes.

'diskremoved'

Events of this class are generated when a disk is removed from a drive. This class has no key codes.

Qualifiers

=====

Some keyword synonyms were added to Commodities V38. These are marked with an '*'.

'lshift', 'left_shift' *
Left shift key.

'rshift', 'right_shift' *
Right shift key.

`'shift'`
Either shift key.

`'capslock', 'caps_lock' *`
Caps lock key.

`'caps'`
Either shift key or caps lock key.

`'control', 'ctrl' *`
Control key.

`'lalt', 'left_alt' *`
Left alt key.

`'ralt', 'right_alt' *`
Right alt key.

`'alt'`
Either alt key.

`'lcommand', 'lamiga' *, 'left_amiga' *, 'left_command' *`
Left Amiga/Command key.

`'rcommand', 'ramiga' *, 'right_amiga' *, 'right_command' *`
Right Amiga/Command key.

`'numericpad', 'numpad' *, 'num_pad' *, 'numeric_pad' *`
This keyword *must* be used for any key on the numeric pad.

`'leftbutton', 'lbutton' *, 'left_button' *`
Left mouse button. See note below.

`'midbutton', 'mbutton' *, 'middlebutton' *, 'middle_button' *`
Middle mouse button. See note below.

`'rbutton', 'rightbutton' *, 'right_button' *`
Right mouse button. See note below.

`'repeat'`
This qualifier is set when the keyboard repeat is active. Only useful for InputEvent class `'rawkey'`.

Note: Commodities V37 has a bug which prevents the use of `'leftbutton'`, `'midbutton'` and `'rbutton'` as qualifiers. This bug is fixed in V38.

Key codes =====

Each InputEvent class has its own key codes:

Key codes for InputEvent class `'rawkey'`

Some keywords and synonyms were added to Commodities V38. These are marked with an '*'.

'a'-'z', '0'-'9', ...
ASCII characters.

'f1', 'f2', ..., 'f10', 'f11' *, 'f12' *
Function keys.

'up', 'cursor_up' *, 'down', 'cursor_down' *
'left', 'cursor_left' *, 'right', 'cursor_right' *
Cursor keys.

'esc', 'escape' *, 'backspace', 'del', 'help'
'tab', 'comma', 'return', 'space', 'spacebar' *
Special keys.

'enter', 'insert' *, 'delete' *
'page_up' *, 'page_down' *, 'home' *, 'end' *
Numeric Pad keys. Each of these key codes *must* be used with the
'numericpad' qualifier keyword!

Key codes for InputEvent class 'rawmouse'

These keywords were added to Commodities V38. They are not available in V37.

'mouse_leftpress'
Press left mouse button.

'mouse_middlepress'
Press middle mouse button.

'mouse_rightpress'
Press right mouse button.

Note: To use one of these key codes, you must also set the corresponding qualifier keyword, e.g.

rawmouse leftbutton mouse_leftpress

Examples for Hot Keys
=====

'ralt t'
Hold right Alt key and press "t"

'ralt lalt t'
Hold left *and* right Alt key and press "t"

'alt t'
Hold either Alt key and press "t"

```
`rcommand f2'
    Hold right Amiga key and press the second function key

`numericpad enter'
    Press the Enter key on the numeric pad

`rawmouse midbutton leftbutton mouse_leftpress'
    Hold middle mouse button and press the the left mouse button

`diskinserted'
    Insert a disk in any drive.
```

1.70 Localization

Yak is now localized. It currently supports english as built-in language and dutch, french, german, italian and swedish with supplied catalogs. If you want to localize Yak to your own language, then you're welcome. There's no need to be a developer to make a translation, the only requisite is to know very well your language :-)

Be aware that there are several things that can be translated :

Yak itself by writing a catalog.
The installer script.
The amigaguide documentation.

You can translate part of this or the whole as you want.

In the Catalogs directory, you will find a file named yak.ct which contains the strings used by Yak interface and which has been built from yak.cd that you can also find in the Catalogs directory..
It is ready to be translated, let's take an example :

```
MISCELLANEOUS_STRING

; Miscellaneous;
```

So, if you want to translate "Miscellaneous" into french, you should put its translation on the empty line as this :

```
MISCELLANEOUS_STRING
Divers
; Miscellaneous;
```

So, when you have translated all the strings of yak.ct you can either use catcomp or one of his PD replacements such as CatEdit, KitCat or FlexCat to generate your catalog or you can send me yak.ct so that I will generate the catalog myself.

There are 5 lines of credits in Yak menu reserved to the translator so don't hesitate to put your name here and your address.
