

# **Virus\_Checker**

John Veldthuis

COLLABORATORS

	TITLE : Virus_Checker		
ACTION	NAME	DATE	SIGNATURE
WRITTEN BY	John Veldthuis	December 7, 2024	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>Virus_Checker</b>	<b>1</b>
1.1	Virus_Checker Help . . . . .	1
1.2	important . . . . .	1
1.3	Shareware Notice . . . . .	2
1.4	Registration . . . . .	2
1.5	Danish Registration . . . . .	3
1.6	Presentation . . . . .	4
1.7	Main Window . . . . .	5
1.8	Command Line Options . . . . .	6
1.9	Icon ToolTypes . . . . .	8
1.10	Security . . . . .	9
1.11	PGP Key servers . . . . .	10
1.12	4eb9 Link Virus . . . . .	12
1.13	Locale . . . . .	13
1.14	How to install Elm . . . . .	13
1.15	Lha . . . . .	13
1.16	AppIcon . . . . .	14
1.17	Disclaimer . . . . .	14
1.18	Author Info . . . . .	15
1.19	Files . . . . .	15
1.20	Arexx . . . . .	16
1.21	Credits . . . . .	18
1.22	Options . . . . .	19
1.23	Watch . . . . .	20
1.24	Scan . . . . .	20
1.25	Quit . . . . .	20
1.26	Option XFDMaster . . . . .	20
1.27	Option UseWindow . . . . .	21
1.28	Option IgnoreBB . . . . .	21
1.29	Option Unpack . . . . .	21

---

1.30 Option DFxBB	21
1.31 Option Scan	21
1.32 Option Capture	22
1.33 Option UseBBLib	22
1.34 Option LHA	22
1.35 Option BBFile	22
1.36 Option DFxFull	22
1.37 Option HotKey	22
1.38 Option TempDir	23
1.39 Option Save	23
1.40 Option CloseWind	23
1.41 Option ArexxScan Window	23
1.42 Option AppIcon On	23
1.43 &	24
1.44 string	24
1.45 Add	24
1.46 Remove	24
1.47 CheckNow	24
1.48 Check	25
1.49 History	25

---

## Chapter 1

# Virus\_Checker

### 1.1 Virus\_Checker Help

Virus\_Checker v7, Copyright © 1990-1995 by John Veldthuis

~Presentation~~~~~	What is Virus_Checker
~Important~notes~~~~~	Please Read this
~Shareware~Notice~~~~~	Virus_Checker is not free
~Security/PGP~~~~~	How do I know this is not a virus
PGP Key Servers	How to get my public PGP key
~Registration~~~~~	Fill me out and mail me
~Danish Registration~~	Fill me out and mail me
~Main~Window~~~~~	Main Virus_Checker window
~Command~Line~Options~	Start Virus_Checker from SHELL
~Icon~ToolTypes~~~~~	ToolTypes Virus_Checker uses
~Workbench~AppIcon~~~~	Drag and Drop checks
~Files~Needed~~~~~	Files required by Virus_Checker
~Localization~~~~~	Yep Virus_Checker is locale aware
~Installing~~~~~	How to install Virus_Checker
~\$4eb9~Link~Virus~~~~~	SPECIAL NOTE ON THIS VIRUS
~LHA/LZH~Files~~~~~	Checking into LHA/LZH files
~Arexx~Port~~~~~	Arexx commands
~Disclaimer~~~~~	And now for something completely different
~Author~Info~~~~~	About the Author
~Credits~~~~~	Thanks Guys
~History~~~~~	How things got to here

### 1.2 important

Some important notes for Virus\_Checker

=====

The configuration file has changed for version 7 of Virus\_Checker. The old one is no longer valid so please delete the file s:Virus\_Checker.config

Also Virus\_Checker will now pick up all the files that it requires from at

least 2 places. It will first try PROGDIR: then the alternative place.  
Virus\_Checker will save any of the files it needs to back from where it read it from.

See Virus\_Checker Files for details

Please send bug reports to [vcbugs@tower.actrix.gen.nz](mailto:vcbugs@tower.actrix.gen.nz)

Please send suggestions to [vcsuggestions@tower.actrix.gen.nz](mailto:vcsuggestions@tower.actrix.gen.nz)

## 1.3 Shareware Notice

This program is SHAREWARE.

Virus\_Checker for me is mainly a hobby but it does cost quite a bit.  
Therefore I took the decision to make Virus\_Checker SHAREWARE.

The cost is a very small US\$20. For this you get some key details that will unlock a feature in Virus\_Checker. The key will be valid for all releases of Virus\_Checker so you don't need to get new details each time a new release is put out

The best way to send this to me is in cash. I can take just about any kind of cash as long as they are notes. Our banks will not take coins. Thus if you are in Australia then send Australian dollars. I prefer US dollars however.

If you cannot send cash then please send a bank draft drawn on a major bank. I cannot accept postal money orders. Our banks will just not accept them.

For my e-mail/postal address refer to the Author~Info. And please, include YOUR e-mail address if you send me letters.

If you are in a hurry to get your details and have an internet e-mail address and have a PGP public key then e-mail me your public key and I can send the details over internet.

Please fill out the Registration form and mail it to me with payment  
Please make sure that name and address is clear as it takes ages sometimes to decypher some peoples scrawls.

## 1.4 Registration

```
*****  
**          Virus_Checker Registration Form          **  
*****
```

Mail to: John Veldthuis  
21 Ngatai Street  
Manaia, Taranaki, 4851  
New Zealand

---

First Name: \_\_\_\_\_ Last Name: \_\_\_\_\_

Street: \_\_\_\_\_

City: \_\_\_\_\_

State/Province: \_\_\_\_\_

Country: \_\_\_\_\_

Email: \_\_\_\_\_

\*\*\*\*\*

Registration of Virus\_Checker will unlock a few features that are present in Virus\_Checker that will not work unless you have a key. At present this is the ability to check files inside LHA/LZH files.

This key will only work under WB2.04 or better but if you have WB1.3 then you can still send the fee in and I will send you a key. It will of course not do much. You will receive in the mail (or email if you have a PGP public key) details to enter into the MakeKey program that comes with the Virus\_Checker archive.

The cost of the Shareware fee is US\$20 or equivalent. By this I mean I can take other money as long as it is in notes. No coins will be accepted. Postal money orders are not accepted either due to our banks not taking them. Any bank drafts or cheques must be in US funds or New Zealand funds.

\*\*\*\*\*

\_\_\_\_\_  
Signature

\_\_\_\_\_  
Date

## 1.5 Danish Registration

-----

BY : \_\_\_\_\_

EMAIL (evt.) : \_\_\_\_\_

\_\_\_\_\_

TLF. (evt.) : \_\_\_\_\_

Prisen er dkr. 140,-, som jeg vedlgger p check, eller i kontanter  
(BEMRK: Virus Help Team Denmark ptager sig intet ansvar for kontanter der  
ikke er sendt anbefalet).

Leveringsform, afkryds venligst:

- ☐ Send mig koderne i et almindeligt brev.
- ☐ Send mig koderne til min Internetadresse.
- ☐ Send mig koderne crash til min fidonetadresse.

Koderne vil blive leveret s hurtigt som muligt, men det kan tage op til 4  
uger at behandle registreringen.

Jeg er inforstet med ovenstende samt at de tilsendte koder KUN er til  
personligt brug.

-----  
(Dato og underskrift)  
-----

## 1.6 Presentation

This piece of software is Shareware !  
-----

Virus\_Checker

Virus\_Checker, Copyright (c) 1990-1995 by John~Veldthuis  
=====

(johnv@tower.actrix.gen.nz)

Virus\_Checker is a program that can be used on any Amiga that is running  
Workbench 2.04 or better. Versions before version 7.0 will run on any Amiga  
regardless of the Workbench. Yep it should even work on 1.1

Virus\_Checker is designed to hunt out Amiga viri and kill them dead. It also  
scans memory on startup and checks all suspect vectors. It also checks

---



certain memory locations every 2 seconds for infection.

You will be able to use the program without reading this file but for best advantage you should read it all.

Any comments or problems with any of the documentation or the program itself are welcome; if you can't get electronic mail to me, please feel free instead to drop me a note via the overland mail~address given below.

Virus\_Checker is written in 100% Assembly code using Cygnus Ed, Macro68, and Debugged using Powervisor. Metascope is just not up with it anymore

## 1.7 Main Window

### Main Window and short intro =====

When Virus\_Checker starts up it will do a number of things before you even see anything appear. First thing it does is initialise itself and then checks itself for changes that have been made. It then loads the files it needs and checks them. Next it checks memory for any infection. Next on the list is to see if the user gave it a file to scan. If yes then it scans these file/files. Next it checks the first file in s:startup-sequence for any viri. This is a common place for infection. Last thing it does is check any floppy disks that may be in the drives.

At this stage the main window will open. It will not open if you told it not to though. The main window can open in 2 states. Full or ICON mode.

The layout is below

Closebutton	Zoom	ToBack
[.]	[[[]]]	[[[]]]
~Options~	File/Dir~Watch	~Scan~Files~
Check Now	~Quit~	

Clicking on the close gadget will make all the open Virus\_Checker windows close. This does not actually stop Virus\_Checker but just makes all the windows close. Virus\_Checker is still on guard.

Clicking on the Zoom gadget will make Virus\_Checker change back and forth from between it's normal open state and it's ICON state. The ICON state is basically just a TitleBar.

Clicking on the ToBack gadget will send the Virus\_Checker Main window behind all the other open windows.

MENUS

### Project/File Scan

This menu will bring up the Scan Requester so that you can enter a file or directory name to scan for viri.

### Project/Full Memory Check

This menu will cause Virus\_Checker to do another complete memory check. This is the same one that is done at start up.

### Project/Save Config

This menu will cause Virus\_Checker to save it's current configuration to it's configure file.

### Project/Stats

This menu just gives you some data on the disks checked, files scanned and viri found since it was started.

### Project/About

This menu tells you what version you are using of different things.

### Project/Quit

Causes Virus\_Checker to stop and remove itself from memory.

### Window/Snapshot window

This menu takes a snapshot of Virus\_Checker's current window position and saves it to it's internal data table. If you then select Save Config then Virus\_Checker will open up in the state that you snapshotted it in.

## 1.8 Command Line Options

### Command Line Options =====

Usage: Virus\_Checker U=UNPACKOFF/S,B=BOOTBLOCKLIB/S,N=NOWINDOW/S,  
CBB=CHECKRADBB/S,XFD/S,STDOUT/S,AUTOSCAN/S,CX\_POPKEY/K,  
A=APPICONNAME/K,QUIT/S,D=DIR/M

Available options: -----

#### U=UNPACKOFF

This option turns off the use of unpack.library for uncrunching files. It does not affect the LHA/ZOO unpacking in the registered version. The reason for this option is that unpack.library sometimes will crash the machine on certain crunched files it thinks it knows about but does not. If you have trouble with Virus\_Checker crashing try this one and see if it fixes the problems.

---

This can be also turned off using the Options Window.

#### B=BOOTBLOCKLIB

Using this option will tell Virus\_Checker to use BootBlock.library to check for bootblock viri. There are many viri in this library that Virus\_Checker does not know about so it is best to leave this on all the time anyway.

This can also be changed in the Options Window

#### N=NOWINDOW

This overrides the normal Virus\_Checker options and causes Virus\_Checker to run without opening it's window

This option can be set in the Options Window and saved

#### CBB=CHECKRADBB

This option makes Virus\_Checker check the RAD: bootblock for any viri. RAD: is a normal disk and can be infected as well.

#### XFD

This option turns on XFDMaster.library checking. It handles crunched files as well

#### STDOUT

This option works in tandem with the D=DIR/M keyword. If you give this option then Virus\_Checker will output anything it would normally display through a requester out through the shell it was started from. This includes virus information and error messages.

#### AUTOSCAN

This option affects what happens when Virus\_Checker gets a message from AmigaDOS that a file or directory has been changed. If this option is given then Virus\_Checker will automatically scan the file/dir before telling you that it changed.

This option can be changed in the Option Window

#### CX\_POPKEY

Using this you can tell Virus\_Checker which key you wish to use to pop up the interface.

#### A=APPICONNAME

Using this you can tell Virus\_Checker what to use as a name for it's AppIcon

#### QUIT

This option can be used to make an already running Virus\_Checker quit

#### DIR

---

If you supply a directory or file using this option then Virus\_Checker will start scanning it as soon as it has started up.

## 1.9 Icon ToolTypes

### Workbench ToolTypes =====

Virus\_Checker can also be started from Workbench either through it's icon or in the WBStartup drawer. In this case Virus\_Checker will then get it's commands through icon ToolTypes.

All of the ToolTypes are already in the Virus\_Checker.info file. They have been disabled (except 1) by putting a () around them. To enable a ToolType simply remove the () and save it.

ToolTypes available are

#### DONOTWAIT

This is a Workbench ToolType and is required to be left enabled so that Workbench does not wait for Virus\_Checker to finish.

#### UNPACKOFF

This option turns off the use of unpack.library for uncrunching files. It does not affect the LHA/ZOO unpacking in the registered version. The reason for this option is that unpack.library sometimes will crash the machine on certain crunched files it thinks it knows about but does not. If you have trouble with Virus\_Checker crashing try this one and see if it fixes the problems.

This can be also turned off using the Options Window.

#### BOOTBLOCKLIB

Using this option will tell Virus\_Checker to use BootBlock.library to check for bootblock viri. There are many viri in this library that Virus\_Checker does not know about so it is best to leave this on all the time anyway.

This can also be changed in the Options Window

#### NOWINDOW

This overrides the normal Virus\_Checker options and causes Virus\_Checker to run without opening it's window

This option can be set in the Options Window and saved

#### XFD

This turns on xfdmaster.library which handles uncrunching packed files

#### CHECKRADBB

This option makes Virus\_Checker check the RAD: bootblock for any viri. RAD: is a normal disk and can be infected as well.

---

## AUTOSCAN

This option affects what happens when Virus\_Checker gets a message from AmigaDOS that a file or directory has been changed. If this option is given then Virus\_Checker will automatically scan the file/dir before telling you that it changed.

This option can be changed in the Option Window

## CX\_POPKEY

Using this you can tell Virus\_Checker which key you wish to use to pop up the interface.

## APPICONNAME

Using this you can tell Virus\_Checker what to use as a name for it's AppIcon

## QUIT

This tells Virus\_Checker to preform it's checks and quit as soon as it is done instead of hanging around.

## DIR

If you supply a directory or file using this option then Virus\_Checker will start scanning it as soon as it has started up.

## 1.10 Security

### Security/PGP

=====

All versions of Virus\_Checker since 6.44 hav PGP sig files in the archive. This enables pgp to check that the file is in fact the same one I released.

Below you will find my signed public key. Save this to a file and then enter pgp <filename> to add it to your keyring. Follow the PGP instructions to add it.

If you do not trust this key (it can be substituted by someone) then get my current key from one of the pgp key servers

To check that the signature matches the file simply do

PGP <filename>.sig <filename>

PGP will warn you if the signature does not match the file.

An example of this is a recent hoax version of 6.6 which quick formats drives. If you had done the test above it would have told you it was fake.

Virus\_Checker also has it's own internal checking for changes as well. Again this is not 100% but guards against the simple changing of version numbers. It also means it takes a better hacker to change the checksums

---

Virus\_Checker will warn you of both checksum errors on itself and on the file VirusChecker.brain.

-----BEGIN PGP PUBLIC KEY BLOCK-----  
Version: 2.6.2i

```
mQCNAi6h70wAAAAEEANWu8csrvc6Z/JY21kiJwklSIDVltJKlxNGU47AFrIGUTcSD
12WNXFkSn/wdjVLJ6ATgRBeErtxPj8t9p7ple4/cN8uziYzC0gFbQdfH/CmcrM0e
sPQJxcmkUiFG7BpENF9uqS2hNyL1HL4xH0wFXcN1PUZf1GxtaQ0mtYy7jZfBAAUR
tCpKb2huIFZ1bGR0aHVpcyA8am9obnZAdG93ZXIuYWN0cm14Lmdlbi5uej6JAHUD
BRAurJ3meXjB5OBD6aEBASQAv46FGU1aiWZv3YCPsyDxUIfYe7Lz8iPnyJmLKec
QDlESHfac/9OuBQvp1KIUWDBFFLt+jOpEzZbCHkNWmgJtF8JhGjzJ6EUn3Z75nps
BbT6MJNYGptCQ3+xtTuTGBdun4CJAJUCBRAuskv2oNrznBERpEEBAS2qA/9GpqEY
N43g7kDZbWN8kx1FPhcIuDRRnZquLu/kdCyPMW0ZQ6SNWp+1+1J/MNdPVVmRvzxa
csnAmeKFDGfWATr3v5Z9aWRsfxcUQI0+1T5IAqzxyj1D5vexvd1+wytXVisDcqMD
djoZqbZmCL7cMBGerh1oWOD9AhiHqzTCx6/x44kAlQIFEC6wfvMNJrWMu42XwQEB
oBsD/0xFuFRRBvd1d94oTbMyBYensOB8iVPEE06W4Ai+CN4bUrwsEH0bossz51p
XtekSA4BgptWt9xtthr0S2N1jQwNbcmBOG+rkA0hrhTafX1jRr55zNjK38eeCwJCm
dGI5Z5xYLnzYe4hP5ToL1vTYQq+ZkMGZeZxTE/MAT5rr/I1F
=1nZv
-----END PGP PUBLIC KEY BLOCK-----
```

## 1.11 PGP Key servers

PGP Public Key servers  
-----

There are PGP public key servers which allow one to exchange public keys running through the Internet and UUCP mail systems.

NOTE!

This service is NOT supported in any way whatsoever by the schools or organizations on which these servers run. It is here only to help transfer keys between PGP users. It does NOT attempt to guarantee that a key is a valid key; use the signators on a key for that kind of security. This service can be discontinued at any time without prior notification.

Each keyserver processes requests in the form of mail messages. The commands for the server are entered on the Subject: line.

```
To: pgp-public-keys@pgp.mit.edu
From: johndoe@some.site.edu
Subject: help
```

Sending your key to ONE server is enough. After it processes your key, it will forward your add request to other servers automatically.

For example, to add your key to the keyserver, or to update your key if it is already there, send a message similar to the following to any server:

To: pgp-public-keys@pgp.mit.edu  
From: johndoe@some.site.edu  
Subject: add

-----BEGIN PGP PUBLIC KEY BLOCK-----  
Version: 2.6.2i

<blah blah blah>  
-----END PGP PUBLIC KEY BLOCK-----

COMPROMISED KEYS: Create a Key Revocation Certificate (read the PGP docs on how to do that) and mail your key to the server once again, with the ADD command.

Valid commands are:

Command	Message body contains
ADD	Your PGP public key (key to add is body of msg) (-ka)
INDEX	List all PGP keys the server knows about (-kv)
VERBOSE INDEX	List all PGP keys, verbose format (-kvv)
GET	Get the whole public key ring (-kxa *)
GET <userid>	Get just that one key (-kxa <userid>)
MGET <userid>	Get all keys which match <userid>
LAST <n>	Get all keys uploaded during last <n> days

Examples for the MGET command:

MGET michael	Gets all keys which have "michael" in them
MGET iastate	All keys which contain "iastate"
MGET 0AF605A5 683A738B	Those two keyids

If you wish to get the entire key ring and have access to FTP, it would be a lot more efficient to use FTP rather than e-mail. Using e-mail, the entire key ring can generate a many part message, which you will have to reconstruct into a single file before adding it to your key ring.

As of 21-Apr-95, these sites are running this system:

pgp-public-keys@pgp.mit.edu  
Derek Atkins <warlord@mit.edu>

pgp-public-keys@pgp.iastate.edu  
Michael Graff <explorer@iastate.edu>

pgp-public-keys@burn.ucsd.edu  
Andy Howard <ahoward@ucsd.edu>

pgp-public-keys@fbihh.informatik.uni-hamburg.de  
Vesselin V. Bontchev <bontchev@fbihh.informatik.uni-hamburg.de>

public-key-server@martigny.ai.mit.edu  
Brian A. LaMacchia <public-key-server-request@martigny.ai.mit.edu>

---

pgp-public-keys@pgp.ox.ac.uk  
Paul Leyland <pcl@ox.ac.uk>

pgp-public-keys@dsi.unimi.it  
David Vincenzetti <vince@dsi.unimi.it>

pgp-public-keys@kub.nl  
Teun Nijssen <teun@kub.nl>

pgp-public-keys@ext221.sra.co.jp  
Hironobu Suzuki <hironobu@sra.co.jp>

pgp-public-keys@sw.oz.au  
Jeremy Fitzhardinge <jeremy@sw.oz.au>

pgp-public-keys@kiae.su  
<blaster@rd.relcom.msk.su>

pgp-public-keys@srce.hr  
Cedomir Igaly <cigaly@srce.hr>

pgp-public-keys@pgp.pipex.net  
Mark Turner <markt@pipex.net>

Sites accessible via WWW:

<http://martigny.ai.mit.edu/~bal/pks-toplev.html>  
<http://ibd.ar.com/PublicKeys.html>

Key server keyrings accessible via FTP:

<ftp://pgp.iastate.edu/pub/pgp/public-keys.pgp>  
<ftp://pgp.mit.edu/pub/keys/public-keys.pgp>  
<ftp://burn.ucsd.edu/Crypto/public-keys.pgp>  
<ftp://alex.sp.cs.cmu.edu/links/security/pubring.pgp>  
<ftp://ftp.informatik.uni-hamburg.de/pub/virus/misc/pubkring.pgp>  
<ftp://ftp.dsi.unimi.it/pub/security/crypt/PGP/public-keys.pgp>

## 1.12 4eb9 Link Virus

Possible \$4eb9 Link Virus  
=====

This is a special check.

It warns you of a possible virus. The current practice in viri is to use a normal program of some fame, link in a virus and then call it something new and better. The lzx, dopus, etc fakes are all examples of this.

When you get this message come up it does not mean that the program is a virus but to be safe be extremely careful with it. Write protect all drives, switch off the computer for at least 30 seconds after you have finished running the program.

---



## 1.13 Locale

### Localization =====

Virus\_Checker is now localized and about 80 odd text strings can be altered. If you wish to translate these strings into another language then please contact me and I will send the information over to you.

Locale already done are

Netherlands  
Swedish  
Italian  
French  
Norwegian  
Danish  
Deutsch

## 1.14 How to install Elm

### Installing Virus\_Checker =====

Virus\_Checker comes with it's own installer script. This installs Virus\_Checker onto the disk of your choice. It then asks where you want to run it from. The choices are S:\User-Startup, SYS:\WBStartup or Manually. Depending on your choice Virus\_Checker may have to move a few files but it does tell you about this first.

## 1.15 Lha

### Checking into LHA/LZH Files =====

This option is only possible if you are registered. Once registered you can get Virus\_Checker to look into these files.

Virus\_Checker cannot remove any viri that are in the files but will warn you. When it finds one it will give a special out to the Scan window or the Arexx variables in the format

Lhafile.lha->infected = SCA Virus

The Lhafile.lha is the filename of the infected archive and infected is the name of the file inside the archive. It may be several directories down but it is the name.

---

## 1.16 Applcon

Virus\_Checker AppIcon  
=====

If Workbench is running when Virus\_Checker starts up it will put an Application Icon on the main Workbench Window. The reason for this AppIcon is for Workbench users who want to check files. Simply select the files/dirs you want to check, then drag them over to the Virus\_Checker AppIcon and drop them on it. Virus\_Checker will immediately start checking those things dropped on it.

\*\*\*\*\*NOTE\*\*\*\*\*

If Virus\_Checker finds a file called Virus\_Checker\_AppIcon.info in it's PROGDIR: then it will use this icon for the AppIcon instead of it's internal default one.

## 1.17 Disclaimer

Virus\_Checker is (c) Copyright 1990-1995  
by John Veldthuis, all rights reserved.

Any possesor of this version "Virus\_Checker" for the Amiga is hereby granted a non-exclusive license permitting its use and/or redistribution, subject to the following terms and conditions.

Permission is hereby granted to freely redistribute this version of "Virus\_Checker" via electronic bulletin board systems (BBS's), freely redistributable disk collections (such as provided by Fred Fish), service bureaus (BiX, GENie, CompuServe, etc), and networks such as USENET, BITNET, and Internet, provided that such distribution includes this unmodified License, and all of the documentation files (README and .doc files), in addition to the executable, and with all copyright notices intact. Access to the source code must also be available and allowed.

This archive may be freely redistributed, but only in totally unchanged state, i.e. no files can be added, deleted, modified etc. All copyright notices in the program and its documentation must remain on their places. Also ".displayme" and other files, usually with "wonderful" ANSI graphics, so obvious at various BBS's, cannot be added.

Without prior written permission from the author, it is prohibited to sell or otherwise convey this version of "Virus\_Checker" for monetary or other forms of compensation, other than the customary service and/or duplication fees as may be charged by the distribution mechanisms identified above.

It is further prohibited, without prior written permission from the author, to include this version of "Virus\_Checker" in whole or in part, in the distribution of any commercial hardware or software package, or component thereof.

---

This version of "Virus\_Checker" is provided "as is", without express or implied warranty. The author makes no claim or representation about the suitability of this software for any purpose.

The author disclaims any and all warranties with regard to this software, including all implied warranties of merchantability and fitness. In no event shall the author be liable for any special, indirect, or consequential damages, or any damages whatsoever resulting from loss of use, data, or profits, whether in an action of contract, negligence, or other tortious action, arising out of or in connection with the use or performance of this software.

---

AmigaGuide, AmigaGuide.info, amigaguide.library, WDisplay, WDisplay.info  
(c) Copyright 1992 Commodore-Amiga, Inc. All Rights Reserved.  
Reproduced and distributed under license from Commodore.

AMIGAGUIDE SOFTWARE IS PROVIDED "AS-IS" AND SUBJECT TO CHANGE;  
NO WARRANTIES ARE MADE. ALL USE IS AT YOUR OWN RISK. NO LIABILITY  
OR RESPONSIBILITY IS ASSUMED.

## 1.18 Author Info

Snail mail:

John Veldthuis  
21 Ngatai Street  
Manaia, Taranaki, 4851  
New Zealand  
New Zealand~

Phone: +64-(0)6-274-8409

UUCP/Internet:

johnv@tower.actrix.gen.nz

Internet Relay Chat (IRC) nick:

VirKiller or JohnV

## 1.19 Files

Files required by Virus\_Checker and where they hide  
=====

Virus\_Checker needs quite a few other files to function.

unpack.library

---

This library needs to be in LIBS: and is used for uncrunching packed files. It is also used to check into LHA/LZH files in the registered version.

xfdmaster.library

This library is used to also uncrunch packed files. If you want to use it then it must be in LIBS: as well. Also needed in LIBS: is the sub-directory XFD. This is where some of the decrunchers are held.

BootBlock.library

This library must also go into LIBS: it is used to check bootblocks of disks. See Bootblock.brain as well

BootBlock.brain

This file is used with BootBlock.library and must go into the L: directory to be of use.

Virus\_Checker.config

This holds the configuration data for Virus\_Checker. Once saved Virus\_Checker reads it on startup and sets it self up the way you tell it to. This file can be in one of 2 places. PROGDIR: or S:. Virus\_Checker knows where it loaded it from and will save it back there when told to. If the file does not exist at all and you save it it will be placed into PROGDIR:

Virus\_Checker.watch

This file is a text file and can be changed with just a normal text editor. It holds the names of the files/directories being watched for changes. This file will be in either PROGDIR: or S: Again Virus\_Checker knows where it loaded it from and will save it there. If it did not exist then it is saved to PROGDIR:

VirusChecker.brain

This file is used by Virus\_Checker to keep track of the non-standard bootblocks you tell Virus\_Checker to learn. It will be loaded from either PROGDIR: or L:. Again it will be saved back from where it was loaded from.

VCBrain

This file is found in PROGDIR: or s: and holds the Bootblocks learned

Virus\_Checker.key

This is the keyfile for Virus\_Checker and you should only have one of these if you have registered. It can be in one of 3 places. PROGDIR:, The directory pointed to by the ENV: variable KEYPATH or in S:

## 1.20 Arexx

---

### Virus\_Checker Arexx commands

=====

Virus\_Checker does have an Arexx port and the name of the port is Virus\_Checker. With this port you can get Virus\_Checker to do things from external programs. Commands supported so far are

#### QUIT

eg. address 'Virus\_Checker' 'quit'

This causes Virus\_Checker to shut down and quit

#### RELOADBRAIN

eg address 'Virus\_Checker' 'reloadbrain'

This will cause Virus\_Checker to reload it's brain file. With this command you can update the brain and get Virus\_Checker to reload it without having to get Virus\_Checker to stop

#### SCAN

eg address 'Virus\_Checker' 'scan filename'

This command causes Virus\_Checker to go out and scan the file or directory given. All requesters will be turned off so it can be used un-attended. The get the results back to the program Virus\_Checker sets some ARExx variables. These are a stem variable called VCHECK

VCHECK.0.0 holds how many viri where found. 0 = none.

VCHECK.i.1 holds the file names of the files infected

VCHECK.i.2 holds the name of the virus that infected the file

for example if Virus\_Checker found 2 files infected.

1. SYS:C/LIST infected with the SCA virus

2. SYS:WBStartup/runme infected with the Saddam virus and

SYS: was scanned the results would be

VCHECK.0.0 = 2

VCHECK.1.1 = SYS:C/LIST

VCHECK.1.2 = SCA

VCHECK.2.1 = SYS:WBStartup/runme

VCHECK.2.2 = Saddam

#### NOTIFYWATCH

eg address 'Virus\_Checker' 'NOTIFYWATCH password'

This command and the next are very special. They work in conjunction with the file watch list. Whenever Virus\_Checker gets a signal that a file or directory that it is watching has changed it will warn you. If you have Autoscan turned on and give this command to Virus\_Checker it will report to you the results. The command will not return to you until something has happened and that is why the following command is for.

If you need to cancel the notifywatch then you will need to use the

---

following command to get it to release your script.

This command is of ideal use for BBS systems. You could set Virus\_Checker to watch your uploads: directory and when a user uploads a file it will scan it and return the results to you.

An example is

```
/* Notifywatch example */
```

```
options results
address 'Virus_Checker' 'NOTIFYWATCH Mypassword'
if VCHECK.0.0 = 0 then do
    say 'No viruses found in scan'
    exit
end
say 'Viruses found: ='VCHECK.0.0
do i o 1 to VCHECK.0.0
    say 'Filename was 'VCHECK.i.1' and virus was 'VCHECK.i.2
end
exit
```

STOPNOTIFYWATCH

eg. address 'Virus\_Checker' 'STOPNOTIFYWATCH Mypassword'

This command will free a watch started by the NOTIFYWATCH command. You only need to give it the password given in the command above. You will need to do it from a separate script as the other one will be waiting for the return still.

NOTE: The password is case sensitive and needs to match the one given in the NOTIFYWATCH command

## 1.21 Credits

### CREDITS

=====

My thanks go out to...

Thomas Neumann For the inclusion of unpack.library

Georg Hörmann For the inclusion of xfdmaster.library.

David Dustin For the assembly code for the MakeKey program.  
and heaps of help with docs for WB3.1

Leo Davidson For Arexx script for use with Virus\_Checker and DOpus 5

ARexx Developed on an Amiga 1000 and is a 100% Amiga product.

Tim Nugent For picture of where I live

Markus Schmall For help with the Illegal Access virus

## Locale translations

Netherlands Jan Hendrik Lots (jhl@grafix.xs4all.nl)  
 Swedish Jon Malmquist (jon.malmquist@mailbox.swipnet.se)  
 Italian Francesco Dipietromaria (dpm@ns.sinet.it)  
 French Florent Monteilhet (florent.monteilhet@ramses.fdn.org)  
 Norwegian Morgan Jakobsen (remija@login.eunet.no)  
 Danish Henrik Lauridsen (hlau@dou.dk)  
 Deutsch Kersten Emmrich (emmy@ramses.fdn.org)  
 Deutsch Torsten Hiddessen (torsten.hiddessen@tu-clausthal.de)

And especially to my Beta Testers who found heaps of bugs and made many a good suggestion. In no particular order

Leo Davidson            Ben D. Rogers            David Oakes

Andrew Dowds           Brad Rogers

John Veldthuis  
=====

## 1.22 Options

### Virus\_Checker Options Window

```

=====
Close Gadget                                Window to Back
|                                           |
-[.]-----[]-|
|                                           |
|      Use XFD Master  ~ ~ Ignore Capture Vectors  |
|      Use Window     ~ ~ Use BootBlock.library    |
| Ignore BB Read Error ~ ~ Check into LHA/LZH Files |
|      Unpack Files   ~ ~ BootBlock File Check     |
| Check DF0 BootBlock ~ ~ Check DF0 Full           |
| Check DF1 BootBlock ~ ~ Check DF1 Full           |
| Check DF2 BootBlock ~ ~ Check DF2 Full           |
| Check DF3 BootBlock ~ ~ Check DF3 Full           |
|      Scan Watch Change ~ ~ Arexx Scan Window     |
|                                           ~ AppIcon On |
|                                           |
|      PopUp HotKey   lcommand~shift~help         |
|                                           |
| Temporary Directory RAM:VCTEMPArC/              |
|                                           |
|      Save~Options           Close~Window         |
|                                           |
-----
  
```





XFDMaster

Turning this Checkbox gadget on will cause Virus\_Checker to use the xfdmaster.library. This library is used to uncrunch files that are packed to save space. A virus could be packed inside one of these files.

## 1.27 Option UseWindow

Use Window

Setting this option causes Virus\_Checker to open it's main window when it starts up. With it off the window will not open

## 1.28 Option IgnoreBB

Ignore BB Read Error

By turning this Checkbox gadget on it will tell Virus\_Checker to ignore putting up a requester when it can't read a BootBlock from a disk. This is extremely handy if you use MSdos disks as Virus\_Checker cannot read them normally

## 1.29 Option Unpack

Unpack Files

Turning this Checkbox gadget off causes Virus\_Checker not to use unpack.library at all when loading files to be checked. unpack.library can cause crashes on some crunched files due to it thinking it knows what the cruncher is when it is in fact a different one (usually newer ones)

## 1.30 Option DFxBB

Check DFx Bootblock

Selecting these Checkbox gadgets tells Virus\_Checker to check the bootblock and the first file in the startup-sequence, plus a few other special files for viruses on any disk inserted into a floppy

## 1.31 Option Scan

Scan Watch Change

Selecting this Checkbox gadget tells Virus\_Checker to automatically scan any file or Directory that is being watched by Virus\_Checker should it change

## 1.32 Option Capture

Ignore Capture Vectors

Setting this Checkbox gadget tells Virus\_Checker to ignore anything in the capture vectors. These vectors are used to survive reboots so viri usually go for them.

## 1.33 Option UseBBLib

Use BootBlock.library

Setting this Checkbox gadget tells Virus\_Checker to use the BootBlock.library when checking Bootblocks for viri. This library knows about some viri that Virus\_Checker does not so it is best left on.

## 1.34 Option LHA

Check Into LHA/LZH Files

This Checkbox gadget is only active if you are a registered user. Selecting it will tell Virus\_Checker to look into the archive for any viri hiding there. Saves having to unpack the whole archive.

## 1.35 Option BBFile

BootBlock File Check

Selecting this Checkbox gadget tells Virus\_Checker to check any files that it checks for BootBlock viri. This is basically a tool for me but was added anyway. WARNING: If you turn this option on there may be some false detections in normal files. Use it with caution

## 1.36 Option DFxFull

Check DFx Full

Selecting these Checkbox gadgets compliments the bootblock checks. If selected and a floppy is put in the drive then Virus\_Checker will automatically start scanning the whole disk for viri.

## 1.37 Option HotKey

Popup HotKey

This is the key combination that is used to POP the Virus\_Checker main window open if it is not open already.

## 1.38 Option TempDir

Temporary Directory

This string gadget is only of use to registered users. When unpack.library looks into LHA/LZH files it requires a temporary directory to do so. This is that directory.

WARNING: WARNING: WARNING: unpack.library deletes anything in this directory when it removes it's files so make sure that nothing of importance is in them. You have been warned.

## 1.39 Option Save

Save Options

This will save all the options to the file PROGDIR:Virus\_Checker.config or S:Virus\_Checker.config depending on where it was loaded from.

## 1.40 Option CloseWind

Close Window

Pretty obvious what this one does. Closes the window

## 1.41 Option ArexxScan Window

Arexx Scan Window

Setting this button will tell Virus\_Checker to open the Scan display window when scanning files by ARExx. Turning it off will not see the files as they are scanned.

## 1.42 Option AppIcon On

AppIcon On

Turning this gadget on will allow Virus\_Checker to create an AppIcon on your Workbench. Workbench has to be running before Virus\_Checker so that

---

the AppIcon can be made. However if you start Workbench after Virus\_Checker has been started you can get Virus\_Checker to create an AppIcon by turning this option off (if needed) and then back on.

## 1.43 &

&

This gadget will bring up the ASL File Requester and you can enter a file or directory to watch. Selecting it will automatically enable the string gadget and enter the dir/file name in there. Then simply hit the return key to enter the name.

## 1.44 string

This string gadget is used to enter the name of the file or directory to be watched. If you selected a name in the ListView gadget then the name will automatically be put in here as well.

## 1.45 Add

Add

Clicking on this gadget will activate the string gadget above it and allow you to enter the name of a file or directory to watch

## 1.46 Remove

Remove

Clicking on this gadget will delete the name from the list of watched files/directories that is specified in the string gadget above it.

## 1.47 CheckNow

Check Files Now

=====

Close Window

Window To Back

```
|
|. ]-----[ ]-
|
| -----
| | |
```

					^	
					v	
-----						
	~~~~~	~~~~~	~~~~~	~~~~~	~~~~~	&
-----						
	~	Check Now	~ ~ ~	Add	~~	~~Remove~~

### 1.48 Check

Check Now

Selecting this gadget will start Virus\_Checker checking all files and directories listed in the Check Files Now Listview gadget.

## 1.49 History

Version 7.0

Internal release only. First runnable version after re-write.  
Done are Locale support, Options window, WatchList window, File Check requester, memory checks, bootblock checks.  
All files related to Virus\_Checker such as it's config, brain, and key files will be got first from PROGDIR: then from the default location.  
Libraries still need to be in libs:

Version 7.1

7/7/95

Got Display option working for Bootblock virus find. Found a buffer too small and overwriting memory not used by VC. Did not cause problems till something else tried to run.

8/7/95

Finished off bootblock stuff. learning stuff was last to go in. Maybe need better error messages. Sent out to beta testers for a try and look

Version 7.2

9/7/95

Put in Zoom gadget so can be used as titlebar again.

Added Snapshot window and Save config to Main menu.  
Fixed up Gadget display on GUI. Overlapped in topaz 8. Simple maths fault.  
However it did bring to light a new problem when window too big and dropped  
back to topaz 8. When window closed and another gadget clicked it changed  
to the font just used. Re-programmed Openwindow to correct.

10/7/95

Found bug in menu colors. Set the wrong Tags for LayoutMenuA(). That took  
alot of searching and head scratching.  
Added close button to file/dir window. Enabled R key in this window as well  
May have found bug in Enforcer hit with this window as well  
Started on adding file scanning in. Uses in the following manner. Check if  
XFD turned on. If on check if file crunched, if not then try to use  
unpack.library to read file, if unpack.library not there just read file in  
as is and check.  
Sent out for Beta testing

Version 7.3

11/7/95 -> 14/7/95

Away at a course for the next 4 days for work. Wont be doing much on this

15/7/95

Found bug causing crash when all windows closed and hide interface selected  
in commodities exchange program.  
Finally found bug in File/Dir watch window for enforcer hits. It was a call  
to FreeGadgets(). The gadget pointer should have been in A0. I had it in  
A1. I thought I checked that one 4 times as well.  
Now I can get back to the serious work. Yeaaaaa!  
Redid gui/font layout calculations. Looks okay in 6/8/9/11 point fonts.  
Added code to pop windows to front if already open when selected.

16/7/95

Worked on File checking stuff. Got basic 1 file check routine working. Have  
added Saddam virus check to floppy check.  
Added RLamer checking to floppy check.

Version 7.4

17/7/95

Added link virus tests to check1file code. Now can start adding in main  
scanning code. Will do multiscan first  
Found bug in Bootblock remove code. Installing either 1.3 or 2.0 bootblock  
would cause a read from a random address and stuff up the bootblock.  
Added single file check. If Scan Files selected om Main window and a file  
is selected then that file will be checked for file/link viruses.

18/7/95

Skiing today. Great weather but -12 was a bit cold.  
Added in Busy pointer/Gadget inhibit while scanning directories.  
Added in File scanning code. Works until it hits a virus

---

19/7/95

Fixed bug in scanning code. Register got corrupted in another routine.  
Added scan window to scanning code. Seems to be working 100%. Looking good so far.

Version 7.5

20/7/95

Added STDOUT option. This will run Virus\_Checker in a one shot mode. You need to give it a directory to scan. All stuff that would normally come up in a requester will be output to STDOUT. eg.  
Virus\_Checker stdout ram:  
would check ram: and exit. With the CCCP virus in ram: the following is output to the shell window  
WARNING The File "ram:CCCP" is infected with the "CCCP" virus  
ALL error messages will also go out to the shell  
Added Bootblock virus checking in files. That is now all the file scanning stuff working as in the old version.  
Added Stats menu option. Gives a few numbers  
Added in checking of first file in startup-sequence  
Added option to SHELL. if AUTOSCAN is on command line then when VC gets a signal saying a watched file/dir has changed then it will scan it before displaying requester.  
Put Options button for previous on.  
Started on Arexx stuff. Added QUIT arexx command. See notes  
Added in SCAN arexx command. See Notes  
Added in RELOADBRAIN arexx command. Forces a reload of the brainfile  
Added in popup when hidden and program run again.  
Added in Scan if running and run again with a dir given

21/7/95

Changed action of Exchange Hide Interface. Will close all windows open.  
Also changed close gadget on main window. Clicking it will close all windows  
Added in Icon stuff. Turned up a few new bugs as well. Getting close to a release though.  
Added keyfile checking back into checker. Even closer

22/7/95

Worked on the \*.guide most of day.  
Found a few small bugs going through when doing the docs.  
Fixed a bug with the default configuration. It was giving a legal path in the LHAPath.

Version 7.6

23/7/95

Added \$4eb9 Link detection to Link virus code. Will say Possible \$4eb9 Link Virus if it finds the right code  
Spent most of afternoon tracking down a bug with the File watching. If you watched any file and changed it the warning would be given. Then several

---

false warnings. Changed it so that the Notify was ended then restarted but then got crashes all the time. So cleared out Notify structure after EndNotify() and StartNotify(). Seems to have cleared the problem  
Got installer script working (I hope)

24/7/95

Bug with \$4eb9 link detection.  
Bug in LHA checking. It was actually a bug in the key checking. Checked the key to late so that it was never initialised.  
Corrected a few spelling mistakes.  
Corrected bug if first file in startup-sequence was not in SYS:c/

Version 7.7

25/7/95

Fixed a few enforcer hits. Also some more work on guide.  
Added XFD command line and WB options.

26/7/95

Fixed a few minor spelling mistakes.  
Got catalogs for dutch and swedish languages in.  
Seems to be good so far

27/7/95

Only a few bits on the guide file today. Things must be just about ready for a release.  
Started work on adding an AppIcon. May be in or not. Depends how it works.

28/7/95

Spent hours looking for a bug in the Notify code only to find it a simple exchange of registers. I used the wrong one again. Assembly is hard at times.  
Added online help (sortof). pressing Help in Main window will spawn Multiview. The Virus\_Checker.guide has to be in HELP:

Version 7.8

29/7/95

Added Option to turn off Scan window when scanning files from Arexx.  
Some more work on guide file  
Fixed bug in Watch save. When no files to save it did not delete the old file. So when re-started it would reload the file again.

30/7/95

Worked on AppIcon. Seems to be working well. Dropping icons onto it checks them for viruses okay.  
Put Checksum checking back into code. For those hackers who don't know what they are doing.

Version 7.9

---



31/7/95

Started working on ARexx interface to Autoscanning of changed files.  
Had to send this out due to a faulty script before

Version 7.10

1/8/95

Worked more on Arexx inface and autoscanning

2/8/95

Worked on bug with XFD and unpack both turned off.  
Added option to turn AppIcon on/off  
Fixed bug in Arexx Scan Window. If off then no scan window at all.  
Worked on guide file again as well

Version 7.11

5/8/95

Made it so help could be found in PROGDIR: or HELP:english/  
Fixed up Install script again.  
Finally got Notify watching working in a way that seems good.  
Fixed up guide file again.

6/8/95

Fixed up bug in first file check. Was causing odd address error  
Internal release only

Version 7.12

8/8/95

Changed install script to find VirusChecker.brain in L: and warn user if  
remove it or leave it. Leave only if running from WBStartup.

9/8/95

Found small bug in ASL code. d0 being set instead of d3. Didn't seem to do  
anything though. Crashes after ASL file selected and before scan window  
opens on WB2.1 machine???

10/8/95

Found bug. I was using a WB3.0 or better routine to set the busy pointer.  
In WB2.04 and WB2.1 it was not there so crash!. Will check for any others

Version 7.13

Obviously my maths is no good and I got the test around the wrong way.  
WB3.0 uses the WB2 code and WB2 uses the WB3 code. Result Boom! again.  
Fixed this time hopefully.

---

Version 7.14

12/8/95

Fixed bug when deselecting LHA/LZH. It would crash when checking a LHA file  
Corrected guide file again and fixed a few spelling mistakes in main file.

13/8/95

Started work on Check Now stuff. May not be in release version as  
functioning. After 4 hours got it completely working. Seems good.

Version 7.15

15/8/95

Corrected small problem with File Watch window gadgets appearing to high  
under WB2.04 and 2.1. gadtools.library must handle things differently in 3  
Updated nederlands catalog.

17/8/95

Changed how requester is displayed. Text is formatted first, then centred.  
Looks alot nicer. No bugs reports from beta testers yet.

22/8/95

Corrected small bug in Arexx interface. Not setting variables.

29/8/95

Corrected small mistake with CheckNow loading option. Watch file would save  
to PROGDIR: no matter what.

First release of file. Brainfile 1.22 in this version may vary from the  
released version but it is the same one.

Version 7.16

31/8/95

Added Illegal access virus to checker. Seems to detect it okay but stuffs  
up the removal. Time for real work so will work on it later

1/9/95

Fixed problem with crashing on 68000 machines when scanning bootblocks  
(I hope)  
Fixed illegal acces virus problems. Removes it now

2/9/95

Added FileGhost 2 virus to checker. Memory checks in brain file  
Fixed WatchNow window not closing on main window closure

3/9/95

---

Fixed problem where you could open CheckNow window multiple times

Version 7.17 Released 13 September 1995

Added Debugger virus to code

Fixed problem with CheckNow window. Optimizing it I somehow stuffed it up.

Changed size of CheckNow Window for NTSC 640x200 window. Should fit.

Added a special feature to the brain so that it can handle strange checks

Fixed problem with Locale not working. After I tested the locale files I changed the version numbers but forgot them in the program.

Spelled an Arexx command in the guide the wrong way.

Fixed a possible source of Can't lock "" requester

Fixed enforcer hit when CMDline Virus\_Checker cx\_popkey="alt r" given

Fixed bug with Blank requester if ASL.library not found.

Fixed so VC opens version 36 of DiskFont.library which WB2.04 uses unless version 37 has been installed manually

Fixed IgnoreCapture vectors. It was not ignoring them.

Added info to guide on PGP key servers to help getting my key.

Version 7.18 Released 30 September 1995

Small bug in installer. Was putting language files into LOCALE: instead of LOCALE:Catalogs/ when WBStartup given

Added Italian local to archive

Found bug in Icon tool types. Where parsed before the config was loaded so when config loaded it would overwrite changes

Fixed problem with NOWINDOW being ignored as a tooltype

Made Menus Locale aware

Added A=APPICONNAME to SHELL and ICON to set AppIcon name

Added QUIT to ICON type.

Added AppMenuItem. Now can select Check for Viruses from Workbench menu

Removed BootBlock File check. Every man and his dog where turning it on without reading the warnings and then emailing me when they keep getting the UltraFox BootBlock virus in all sorts of files. It is gone and wont be back.