

Most_engl

| |
|----------------------|
| COLLABORATORS |
|----------------------|

| | | | |
|---------------|-----------------------------|------------------|------------------|
| | <i>TITLE :</i> Most_engl | | |
| <i>ACTION</i> | <i>NAME</i> | <i>DATE</i> | <i>SIGNATURE</i> |
| WRITTEN BY | | December 8, 2024 | |

| |
|-------------------------|
| REVISION HISTORY |
|-------------------------|

| NUMBER | DATE | DESCRIPTION | NAME |
|--------|------|-------------|------|
| | | | |

Contents

| | | |
|----------|-----------------------------------|----------|
| 1 | Most_engl | 1 |
| 1.1 | Most_engl.guide | 1 |
| 1.2 | Most_engl.guide/Copyright | 1 |
| 1.3 | Most_engl.guide/Background | 2 |
| 1.4 | Most_engl.guide/Configuration | 3 |
| 1.5 | Most_engl.guide/FILES | 4 |
| 1.6 | Most_engl.guide/PORTNAME | 4 |
| 1.7 | Most_engl.guide/PUBSCREEN | 4 |
| 1.8 | Most_engl.guide/STARTUP | 4 |
| 1.9 | Most_engl.guide/WINDOWX | 5 |
| 1.10 | Most_engl.guide/WINDOWY | 5 |
| 1.11 | Most_engl.guide/WINDOWW | 5 |
| 1.12 | Most_engl.guide/WINDOWH | 6 |
| 1.13 | Most_engl.guide/SCREENMODE | 6 |
| 1.14 | Most_engl.guide/FONT | 6 |
| 1.15 | Most_engl.guide/FONTHEIGHT | 7 |
| 1.16 | Most_engl.guide/APPICON | 7 |
| 1.17 | Most_engl.guide/ICONX | 7 |
| 1.18 | Most_engl.guide/ICONY | 7 |
| 1.19 | Most_engl.guide/BUFLLEN | 8 |
| 1.20 | Most_engl.guide/PIPELEN | 8 |
| 1.21 | Most_engl.guide/QUOTES | 8 |
| 1.22 | Most_engl.guide/DIRS | 8 |
| 1.23 | Most_engl.guide/ENDS | 9 |
| 1.24 | Most_engl.guide/STACKSIZE | 9 |
| 1.25 | Most_engl.guide/Keyboard commands | 9 |
| 1.26 | Most_engl.guide/Scrolling | 10 |
| 1.27 | Most_engl.guide/Searching | 10 |
| 1.28 | Most_engl.guide/Open file | 11 |
| 1.29 | Most_engl.guide/Info requester | 11 |

| | | |
|------|--------------------------------------|----|
| 1.30 | Most_engl.guide/Help | 11 |
| 1.31 | Most_engl.guide/Edit file | 12 |
| 1.32 | Most_engl.guide/Quit file | 12 |
| 1.33 | Most_engl.guide/Menus | 12 |
| 1.34 | Most_engl.guide/Project | 12 |
| 1.35 | Most_engl.guide/Move | 13 |
| 1.36 | Most_engl.guide/Menu Search | 13 |
| 1.37 | Most_engl.guide/Extras | 13 |
| 1.38 | Most_engl.guide/Settings | 14 |
| 1.39 | Most_engl.guide/The main window | 14 |
| 1.40 | Most_engl.guide/The search requester | 15 |
| 1.41 | Most_engl.guide/The AppIcon | 16 |
| 1.42 | Most_engl.guide/XPK support | 16 |
| 1.43 | Most_engl.guide/Pipe support | 16 |
| 1.44 | Most_engl.guide/ARexx Port | 17 |
| 1.45 | Most_engl.guide/GetFileList | 18 |
| 1.46 | Most_engl.guide/GetScreenName | 18 |
| 1.47 | Most_engl.guide/Quit | 19 |
| 1.48 | Most_engl.guide/Request | 19 |
| 1.49 | Most_engl.guide/Set | 20 |
| 1.50 | Most_engl.guide/OpenNew | 20 |
| 1.51 | Most_engl.guide/Open | 20 |
| 1.52 | Most_engl.guide/Close | 21 |
| 1.53 | Most_engl.guide/ToFront | 21 |
| 1.54 | Most_engl.guide/GetWindowDims | 21 |
| 1.55 | Most_engl.guide/Edit | 22 |
| 1.56 | Most_engl.guide/Info | 22 |
| 1.57 | Most_engl.guide/FirstPage | 22 |
| 1.58 | Most_engl.guide/LastPage | 22 |
| 1.59 | Most_engl.guide/NextPage | 23 |
| 1.60 | Most_engl.guide/PrevPage | 23 |
| 1.61 | Most_engl.guide/NextLine | 23 |
| 1.62 | Most_engl.guide/PrevLine | 23 |
| 1.63 | Most_engl.guide/NextColumn | 24 |
| 1.64 | Most_engl.guide/PrevColumn | 24 |
| 1.65 | Most_engl.guide/NextTab | 24 |
| 1.66 | Most_engl.guide/PrevTab | 24 |
| 1.67 | Most_engl.guide/Goto | 25 |
| 1.68 | Most_engl.guide/Search | 25 |

| | | |
|------|---|----|
| 1.69 | Most_engl.guide/Known bugs | 25 |
| 1.70 | Most_engl.guide/Ideas - Bug reports | 26 |
| 1.71 | Most_engl.guide/Current version | 26 |
| 1.72 | Most_engl.guide/Greetings | 26 |
| 1.73 | Most_engl.guide/Index | 27 |

Chapter 1

Most_engl

1.1 Most_engl.guide

Most V1.56

| | |
|----------------------|--|
| Copyright | Guess what... |
| Background | General background information to Most |
| Configuration | How to start Most |
| Keyboard commands | Shortcuts, cursor movements and so on |
| Menus | Which menus are available |
| The main window | The main window and its functions |
| The search requester | The second important window |
| The AppIcon | How to use it. |
| XPk support | How Most supports XPk |
| Pipe support | Most can read out of a pipe |
| ARexx Port | The wonderful world of ARexx |
| Known bugs | Hopefully mostly empty... |
| Ideas - Bug reports | It's your turn |
| Current version | Where to get the latest Most |
| Greetings | Who helped me |
| Index | |

1.2 Most_engl.guide/Copyright

Copyright

Most 1.56 is published under the concept of GiftWare! So if you find Most a useful tool (and of course use it) please make me a present of any kind - and make me very happy.

Beside this I keep my Copyright:

Copyright (C) 1992/93/94 by Uwe Röhm

You must get my agreement if you wish to publish Most in a commercial product. Especially it is not allowed to use Most for military purposes of any kind which includes using Most in companies which plan or only support military products.

You are allowed to include Most in PD packages which cost less than \$10.- ! But I ask you to keep the archive together. You have to include the documentation with each version. Thank you!

1.3 Most_engl.guide/Background

Background

There are some goals I try to achieve with Most:

- full workbench support
- easy to use with mouse and keyboard
- flexibility
- memory friendly :-)

So Most uses a window for each text - there is no possibility to use it like Commodore's More in a shell. Of course you can choose another screen to open on or even an own CustomScreen. How much windows are opened by Most and where they are is absolut without interest and only limited by the amount of free (chip-) memory!

As each text is displayed in his own window there is also its own process behind. Cause of the windows are absolut independent of each other. Especially you can send ARexx commands to different windows simultaneous and you are free to open new Most windows even if previously opened windows are "busy" - there is Most's main process which handles all texts and some global ARexx commands (see ARexx Port).

To be memory friendly and to display very huge texts even on a 500KB system Most does buffering. Small texts, which fit completly into the buffer, are read only once and closed than so that you can e.g. edit and save it again. But if the text is larger than the configurated buffer length (yes, of course you can change the buffer size, but read on :-)) Most will do some sort of "paging". So memory usage will be limited by the buffer size you specified (little memory -> small buffer). On the other hand this slows scrolling and searching down!!! Sorry for this, but if you have enough memory just increase to buffer size to - let's say - 2 MB. Don't be afraid. Of course Most only uses the amount of memory it needs if a text is smaller than the buffer ;-)

There is one exception of the paging method: XPK packed files. In

the current version Most does no paging to XPK files but reads the complete file into memory (see XPK support). Perhaps this will change in future, perhaps it will stay...

Oh, I nearly forgot that Most can display all ANSI sequences. Without this it wouldn't be a real text viewer. As I don't want to do old work again and again I decided to use the console.device. This enables you to mark lines and copy them with Amiga C into the clipboard! I regret that there are also some problems:

- You can only mark text inside the visible text portion.
- Scrolling is quiet annoying on an Amiga without 680x0 (x > 1).
- Don't load binary files. I warned you!!!

1.4 Most_engl.guide/Configuration

Configuration

Most does the following configuration steps on startup:

1. internal defaults
2. Environments Most/Most and Most/FileReq (When used from shell local environments will be read first!)
3. Shell-start: parse command line
 WB-start : parse ToolTypes
4. NEW since Most 1.53: For each text loaded Most will read the project icon (if exists) and use the new tooltypes. You can also include all ARexx commands in the tooltypes which will be executed just after loading the new text! So you can write local ARexx scripts directly into the icons of texts. For a list of the possible commands see ARexx Port.

And now, ladys and gentlemen, here are the options to be used in 2.), 3.) and 4.):

| | |
|------------|--|
| FILES | list of filenames to be displayed |
| PORTNAME | name of global ARexx port. |
| PUBSCREEN | name of a PubScreen to open Most's window on |
| STARTUP | ARexx script to be executed |
| WINDOWX | x-coordinate of window |
| WINDOWY | y-coordinate of window |
| WINDOWW | width of window |
| WINDOWH | height of window |
| SCREENMODE | screenmode to open an own screen with |
| FONT | fontname to use |
| FONTHEIGHT | height of a given font |
| APPICON | to show the AppIcon |

| | |
|-----------|--|
| ICONX | x-coordinate of AppIcon |
| ICONY | y-coordinate of AppIcon |
| BUFLN | length of read buffer |
| PIPELEN | length of pipe buffer |
| QUOTES | possible characters for include file recognition |
| DIRS | search paths for includes |
| ENDS | endings of include files |
| STACKSIZE | adjust editor's stack size |

1.5 Most_engl.guide/FILES

FILES

=====

Usage

A list of filenames to be displayed (only on shell command line!).
You can use any AmigaDOS wildcards. Since version 1.55 Most also
finds files with names, which include wildcards itself (like
"(test)").

1.6 Most_engl.guide/PORTNAME

PORTNAME

=====

Usage

Custom name of global ARexx Port of Most. Overrides the default
name.

Default

MOSTPORT

1.7 Most_engl.guide/PUBSCREEN

PUBSCREEN

=====

Usage

Name of PubScreen where Most will open its windows on.

1.8 Most_engl.guide/STARTUP

STARTUP
=====

Usage

Name of an ARexx script which will be executed every time Most opens a window. (see ARexx Port).

Remember that you can use directly all ARexx commands as tooltypes in project icons of text files (as a sort of "tooltype script").

1.9 Most_engl.guide/WINDOWX

WINDOWX
=====

Shortcut
WX

Usage

X-coordinate of The main window

1.10 Most_engl.guide/WINDOWY

WINDOWY
=====

Shortcut
WY

Usage

Y-coordinate of The main window. -1 for centered windows

1.11 Most_engl.guide/WINDOWW

WINDOWW
=====

Shortcut
WW

Usage

Width of windows. If you specify negative values or 0, the width of the screen will be used instead.

Default
600

1.12 Most_engl.guide/WINDOWH

WINDOWH
=====

Shortcut
WH

Usage
Height of windows. If you specify negative values or 0, the height of the screen (without its title bar) will be used instead.

Default
400

1.13 Most_engl.guide/SCREENMODE

SCREENMODE
=====

Shortcut
SM

Usage
A valid screenmode Most will use to open its on screen with (which will be a PubScreen named Most). You can get a list of the available screenmodes of your system if you start Prefs/ScreenMode.

Attention! The names of the screenmodes are different for most versions of the monitor files. Remember that you must specify a valid name, which means, that you must spell it exactly as in the monitor files. If in doubt start Prefs/ScreenMode and read the listview.

Example
SCREENMODE "Pal:HighRes"

1.14 Most_engl.guide/FONT

FONT
=====

Usage
name of a font to be used. The name must include the .font postfix. The height of the font can be adjusted with the FONTHEIGHT option. Be careful with proportional fonts.

Example
FONT "helvetica.font"

1.15 Most_engl.guide/FONTHEIGHT

FONTHEIGHT
=====

Usage

Tells Most which font height it should use. Works only together with the FONT option. If not specified Most uses the system default font's height.

1.16 Most_engl.guide/APPICON

APPICON
=====

Usage

A switch, which lets Most use an AppIcon on workbench. If you start Most with the APPICON option and without further file names, Most will only put its AppIcon onto workbench and stay in background. (see The AppIcon)

1.17 Most_engl.guide/ICONX

ICONX
=====

Usage

X-coordinate of Most's APPICON on workbench

1.18 Most_engl.guide/ICONY

ICONY
=====

Usage

Y-coordinate of Most's APPICON on workbench

1.19 Most_engl.guide/BUFLEN

BUFLEN
=====

Usage

Very interesting option to justify Most's buffer size. In general: On small systems use small values, on larger systems try higher buffer sizes. BUFLEN defaults to 50 KB (which is quiet small :-). Texts smaller than the buffer size will be read complete into memory and use only the necessary amount of memory.

Default

50 000 Bytes

1.20 Most_engl.guide/PIPELEN

PIPELEN
=====

Usage

Most can also read out of a pipe. Normally it would allocate a buffer of BUFLEN/10 Bytes for reading. With this option you can justify the buffer length for pipes by hand.

Example

PIPELEN 8192

1.21 Most_engl.guide/QUOTES

QUOTES
=====

Usage

You can specify a sequence of quote characters. These characters will be used for the "click-and-load" option: If you doubleclick on a word which stands between a quote character Most will try to load a text named like this word. This is very useful for programmers as you can view include files very easy!

Default

"' <> () {} []

1.22 Most_engl.guide/DIRS

DIRS

====

Usage

Specify one or more directories Most will search through if you use the "click-and-load" function (see QUOTES). All directories must be separated by |.

Example

```
DIRS "Include:|TexInputs:|LC:Include/"
```

1.23 Most_engl.guide/ENDS

ENDS

====

Usage

Postfixes to be appended on include files with the "click-and-load" function in the given order (see DIRS, see QUOTES).

Example

```
ENDS ".c.h.tex"
```

1.24 Most_engl.guide/STACKSIZE

STACKSIZE

=====

Usage

Adjust the size of the editor's stack. Useful for example for the emacs ("Eight Megabytes And Constantly Swapping"?)...

Example

```
STACKSIZE 50000
```

Default

8192 bytes

1.25 Most_engl.guide/Keyboard commands

Keyboard commands

In the current version Most supports all (and more!) keyboard shortcuts well known from More. Future versions will allow custom

keyboard commands...

- Scrolling
- Searching
- Open file
- Edit file
- Info requester
- Help
- Quit file

1.26 Most_engl.guide/Scrolling

Scrolling
=====

one line forwards
CURSOR DOWN NUMERICPAD 2 RETURN ENTER

one line backwards
CURSOR UP NUMERICPAD 8 DELETE

one page forwards
SHIFT CURSOR DOWN SPACE PAGE DOWN

one page backwards
SHIFT CURSOR UP BACKSPACE PAGE UP b

Jump to beginning of text
HOME <

Jump to end of text
END >

oen column to the right
CURSOR RIGHT NUMERICPAD 6

one column to the left
CURSOR LEFT NUMERICPAD 4

8 columns to the right
SHIFT CURSOR RIGHT

8 columns to the left
SHIFT CURSOR LEFT

jump to first column
NUMERICPAD 5

1.27 Most_engl.guide/Searching

```
Searching
=====

search actual searchstring again
    n

ignore upper/lower case
    .

searching with distinction of upper/lower case
    /

Open the search requester
    f s
```

1.28 Most_engl.guide/Open file

```
Open file
=====

    Load new text with l (a filerequester shows up).
```

1.29 Most_engl.guide/Info requester

```
Info requester
=====

    Beside the usual Copyright you find here some information about the
    current text: Its filename, the filelength, the number of lines and the
    visual number of lines, and also the name of the XPK packer (or just
    "---" if the file isn't packed). At last there's a message indicating
    that the current text has been read completely into memory or - if not -
    the length of the used read buffer.
```

The Info requester can be opened with h.

1.30 Most_engl.guide/Help

```
Help
=====

    If you press HELP, the AmigaGuide will be started with the
    documentation of Most. Of course this requires the AmigaGuide be
    installed correctly. If Most can't open the amigaguide.library it will
    open the Info requester.
```

AmigaGuide searches its documents in the current directory and also in the paths listed in the environment variable AmigaGuide/Path.

1.31 Most_engl.guide/Edit file

Edit file
=====

If you press e, the current text will be loaded into an editor. The editor will be started in the background. The name of the editor must be configured in the environment variable EDITOR. You can adjust the editor's stack size with the STACKSIZE option.

1.32 Most_engl.guide/Quit file

Quit file
=====

Close the text window with ESCAPE, CTRL-C or q.

1.33 Most_engl.guide/Menus

Menus

There are the following menus available:

| | |
|-------------|--|
| Project | Commands to open, edit, print, close and info about the text |
| Move | different movements in the text |
| Menu Search | searching in the text |
| Extras | misc |
| Settings | save settings |

1.34 Most_engl.guide/Project

Project
=====

New...

Opens a new window and brings up a filerequester where you can choose a text file to be displayed in the new window. If you cancel the filerequester the window will be closed. The position

and dimensions of the filerequester can be stored in Settings.

Open...

Asks you for a new file to be loaded into the current window.

Edit...

Starts the editor with the current text via RUN. The name of the editor can be configurated in ENV:Editor (see Edit), its stack size can be adjusted with the STACKSIZE option.

Print

Simply prints the current text to PRT:.

Info...

Pops up the Info requester where you find some useful information to the current text like name, length, line count, visible lines, XPK packername and a short comment if the text has been loaded completely into memory or if it uses an buffer.

Quit

Quits the current window (and if it was the last one Most at all)

1.35 Most_engl.guide/Move

Move

====

Move through the current text as the menus describe.

With the menu "Jump to line..." you can specify a certain line number in a requester where you will jump to.

1.36 Most_engl.guide/Menu Search

Menu Search

=====

searching...

The search requester will be opened with its stringgadget activated.

If the search requester is open this menu is disabled.

forwards/backwards

Search string forwards/backwards (only with open search requester)

1.37 Most_engl.guide/Extras

Extras
=====

Refresh page
Reset console and redraw page

Set tabulator width...
Enter new numeric value for the tabulator width (per default
every 8th character there's a tab).

Execute ARexx Macro...
Asks for an ARexx Macro to be executed (see ARexx Port).

1.38 Most_engl.guide/Settings

Settings
=====

save
global Prefs
Save actual settings in two environments in ENV: and ENVARC:.
A subdirectory Most will be created automatically. All known
options from workbench or shell start are saved and also the
dimensions and position and the pattern string of the file
requester.

local Prefs
Does the same as above, but uses local shell variables. This
only works if you started Most from a Shell!

1.39 Most_engl.guide/The main window

The main window

Title
In the title the filename and on the right hand side the current
column and line numbers are displayed. Format:
 <filename> <column>/<line>

Gadgets
Beside the system gadgets there are three further ones which
control text scrolling:

You can use the scroller continuously by click-and-dragging or for
scrolling one page forwards/backwards if you click under/above the
knob. The knob's position represents the current text position, its
height the relation between the visible and the total text length.
Use the arrows to scroll one line in the correspondending

direction.

Mouse

"Click-And-Load" function.

If you doubleclick into the window Most will look at this position to find a word which is limited by one of the configured quote characters (see QUOTES). This word (can include spaces!!) will be treated as a filename for which Most searches first in the current directory and then in each further configured (see DIRS) directory. Most will also try the plain filename and then (if not found) append each prefix given with the ENDS option. The first found file will be displayed in a new window. If no name matches, the screen will flash (DisplayBeep).

Example:

Doubleclick on ``#include <exec/exec.h>'' between ``<'' and ``>''. the file Include:Exec/Exec.h will be loaded, if you specified ``DIRS Include:'' on startup.

Clipboard

You can easily mark any text in the visible text by click-and-dragging (drag without releasing the mouse button). Copy the marked block with Amiga-C into the clipboard. The current version doesn't support paste from the clipboard.

AppWindow

Take any "real" icon (no AppIcon) on workbench and drop it in Most's window. It will be loaded into the current window. If you drop more than one icons Most will open further windows.

1.40 Most_engl.guide/The search requester

The search requester

Here you can enter a search string and also manipulate the three search options. Therefore you can use the mouse and/or the keyboard shortcuts indicated by the underlined characters. Additionally you have the same functionality as in the main window! So no annoying re-activation of The main window.

- All menus are available as in the text window. Only the Menu Search will be disabled and instead "search forwards" and "search backwards" are unghosted.
- Beside the mentioned Requester shortcuts you can use all normal Keyboard commands like scrolling with the cursor keys!!! (Be sure the string gadget isn't activated)

1.41 Most_engl.guide/The AppIcon

The AppIcon

The AppIcon has two functions

Doubleclick

A filerequester will come up where you can choose a file to be loaded and displayed. If you select "Cancel" Most will show a security requester where you can quit Most.

Icons

Drag-and-drop one or more icons on the AppIcon and they will be loaded.

Comments:

Most uses his own program icon as its APPICON. Perhaps I will support custom icons in the future but not yet ;-). The coordinates of the AppIcon can be saved in the menu Settings. Use the options ICONX and ICONY for exact placement of the AppIcon.

1.42 Most_engl.guide/XPK support

XPK support

Main goal of Most's XPK support is to hide any consequences of packed data from the user. This means, that any packed file (with XPK) will automatically be unpacked from Most if the XPK packages is correct installed. The only hint you get is in the information requester, where the line "XPK-packer:" will show you the used packer (usually you see "---" there). There is only one thing special with XPK packed data: The file will be loaded completely into memory and no buffering will be done!

If Most finds an encrypted files (with XPK of course), it opens a password requester and prompts you for the password. Be careful, because this is your only chance! If you give the wrong answer, you will see the encrypted file and have to reload it.

On the other hand if you don't have XPK you can use Most without any difference. The xpkmaster.library is not required by Most to run at all. Of course in this case XPK packed data will not be unpacked :-)

1.43 Most_engl.guide/Pipe support

Pipe support

As a special feature Most 1.42 supports pipes. This means, that you can type something like "type foo | Most" at your (W)Shell prompt and Most will show the output of the first type command in its window!

As I said this feature is brand new. So I regret that I couldn't test it for all possibilities. Please report me any failure.

There are two small problems:

1. XPK doesn't work with pipes.
2. Second there is the problem with pipes that you cannot know how much data therein will be... So one effect is, that you cannot scroll back to the start of an file if you scrolled over the bounds of a buffer and the other one is that the size of the buffer will be (maximum BUFLen / 10) every time (you can set the pipe's buffer size with the PIPELEN option). If the pipe's data fits completly into the buffer you have no restrictions for scrolling. But if the data is to large - Sorry.

1.44 Most_engl.guide/ARexx Port

ARexx Port

Beside the global ARexx port MOSTPORT (or the name you gave it with the option PORTNAME on startup) of Most's main process each text window has his own private ARexx port. To select a window first send the command GetFileList to the global port. You will receive a list of the avaible windows and its portnames.

All following ARexx commands can be send to a private window port, but Most's main port does only understand the first 6 commands GetFileList, GetScreenName, Quit, OpenNew, Set and Request.

In RC Most will return an errorcode of

- * 0 for no errors
- * 5 if it couldn'd open a new text with Open or OpenNew
- * 10 if the parameters for a command were wrong
- * 20 for an unknown ARexx command

All other commands will return an errorcode of 20 if send to MOSTPORT. Sorry, but the ARexx port isn't complete today. But I'm working on it :-)

The following ARexx commands are supported:

| | |
|---------------|--|
| GetFileList | get a list of available text windows and their portnames |
| GetScreenName | ask for the name of the screen, where Most is running on |
| Quit | quit Most |
| Request | open a custom requester |

| | |
|---------------|---|
| Set | set some options |
| OpenNew | open a text in a new window |
| Open | load a new text in the current window |
| Close | close the current window |
| ToFront | get the current window in front of you and visible |
| GetWindowDims | ask for position and dimensions of the current window |
| Edit | edit the current text |
| Info | open the information requester |
| FirstPage | jump to first page |
| LastPage | jump to last page |
| NextPage | show next page |
| PrevPage | show previous page |
| NextLine | scroll down up line |
| PrevLine | scroll down one line |
| NextColumn | scroll to the left |
| PrevColumn | scroll to the right |
| NextTab | scroll 8 chars to the left |
| PrevTab | scroll 8 chars to the right |
| Goto | goto a certain line and column |
| Search | search |

1.45 Most_engl.guide/GetFileList

GetFileList
=====

Template
 GetFileList

Result
 In RESULT you get a list of all available text windows and their
 port names. RESULT looks like this: {<window's name> <port name>
 }^+

Example
 GetFileList
 RESULT: "Most.dok MOST.0 Most.doc MOST.1"

1.46 Most_engl.guide/GetScreenName

GetScreenName
=====

Template
 GetScreenName

Result
 RESULT contains screen name.

Usage

Get the name of the screen, where the current window is on.

Example

```
GetScreenName
RESULT - "Workbench"
```

1.47 Most_engl.guide/Quit

Quit
=====

Template
Quit

Usage

Quits Most and closes all windows. The AppIcon of Most will be deleted - if there is one at all.

Example

Quit

1.48 Most_engl.guide/Request

Request
=====

```

Template
Request  TITLE/K/A  TEXT/K/A  GADGETS/K/A

```

```

Resultat
    RESULT contains number of selected gadget:

```

```
0      the most right gadget (should be "Cancel")
```

```
1 bis n-1
    the other gadgets from left to right
```

Usage

A simple method of asking the user silly questions via requester. Title and text are simple strings. With GADGETS you specify the texts of the gadgets (and how much gadgets there are), seperated with '|'|.

Example

```
Request TITLE "Test" TEXT "All OK?" GADGETS "YES|No"
RESULT - 1 if YES has been selected, else 0
```


1.49 Most_engl.guide/Set

Set
===

Template
Set CASE/S WORD/S BACK/S

Usage
Set some internal parameters like
CASE
 ignore upper/lower case on/off

WORD
 search only for whole words on/off

BACK
 search backwards on/off
All parameters will be set if specified, and disabled otherwise.

Example
Set CASE ON
Enables casesensitiv searching, but disables the other two options.

1.50 Most_engl.guide/OpenNew

OpenNew
=====

Template
OpenNew FILE/K

Usage
Load a new text in a new window. The filename is optional. If you don't specify a name a filerequester opens.

You don't need to select a current window before. This command doesn't return until the new window is closed again!

Example
OpenNew FILE Most.dok

1.51 Most_engl.guide/Open

Open
=====

Template
Open FILE/K

Usage

Load a new text in the current window. The filename is optional.
If you don't specify a name a filerequester opens. This command
doesn't return until the window is closed again!

Example

Open FILE Most.dok

1.52 Most_engl.guide/Close

Close

=====

Template

Close

Usage

Closes the current window.

1.53 Most_engl.guide/ToFront

ToFront

=====

Template

ToFront

Usage

Makes the current visible: It will be made the frontmost window
and the screen it's on will be activated and go to front.

1.54 Most_engl.guide/GetWindowDims

GetWindowDims

=====

Template

GetWindowDims

Result

In RESULT stands <xpos> <ypos> <breite> <höhe>

Usage

Get the position and dimensions of the current window in RESULT

Example

GetWindowDims

RESULT - "40 40 600 180"

1.55 Most_engl.guide/Edit

Edit
====

Template
 Edit

Usage
Edit the current text (runs editor).

1.56 Most_engl.guide/Info

Info
====

Template
 Info

Usage
 Opens the Info requester to the current window.

1.57 Most_engl.guide/FirstPage

FirstPage
=====

Template
 FirstPage

Usage
 Show the first page of the current text.

1.58 Most_engl.guide/LastPage

LastPage
=====

Template
 LastPage

Usage

Show the last page of the current text.

1.59 Most_engl.guide/NextPage

NextPage

=====

Template

NextPage

Usage

Show the next page of the current text.

1.60 Most_engl.guide/PrevPage

PrevPage

=====

Template

PrevPage

Usage

Show the previous page of the current text.

1.61 Most_engl.guide/NextLine

NextLine

=====

Template

NextLine

Usage

Scroll up one line.

1.62 Most_engl.guide/PrevLine

PrevLine

=====

Template

PrevLine

Usage
Scroll down one line.

1.63 Most_engl.guide/NextColumn

NextColumn
=====

Template
NextColumn

Usage
Scroll left one column.

1.64 Most_engl.guide/PrevColumn

PrevColumn
=====

Template
PrevColumn

Usage
Scroll right one column.

1.65 Most_engl.guide/NextTab

NextTab
=====

Template
NextTab

Usage
Scroll left 8 columns.

1.66 Most_engl.guide/PrevTab

PrevTab
=====

Template

PrevTab

Usage

Scroll right 8 columns.

1.67 Most_engl.guide/Goto

Goto

====

Template

Goto LINE/K/N/A COLUMN/K/N

Usage

Jump to the specified line. Optional you can specify a new first column.

Example

Goto LINE 142

1.68 Most_engl.guide/Search

Search

=====

Template

Search TEXT/K

Usage

Without argument: The search requester opens or if allready open the current string will be search again.

With searchstring: Search for the given string.

Example

Search TEXT foobar

1.69 Most_engl.guide/Known bugs

Known bugs

- Several control sequences for cursor movements trash the display.
 - Most has problems with the pipe of WShell.
-

- An Enforcer-hit with Most 1.53 has been reported which may be still there. The input buffer seems to overflow after havy input...
- Bruno Lacombe reported a Mungwall hit with Most 1.53 I couldn't reproduce here...

1.70 Most_engl.guide/Ideas - Bug reports

Ideas - Bug reports

As mentioned before Most isn't complete today. There are some points I will improve in the future but I can't promise it. Please remember that I write Most in my spare time without gaining any money for it!

Nevertheless I'm absolutely interested in any kind of responds - ideas, enhancements requests, criticism or bug reports. Call me, write me, mail me. I will hear you! YOU make Most alive and better for the future.

My address:

Uwe Roehm
Woerthstr. 18
D - 94032 Passau
Germany

EMail:

bugs@roemer.deg.sub.org

Fido:

2:2494/22.5

1.71 Most_engl.guide/Current version

Current version

You can download the current version of Most from ftp.uni-passau.de (132.231.1.10) in the directory pub/amiga/local/UweR. You will also find other interesting software in pub/amiga/local ...

I try to upload new releases of Most on AmiNet and on our local BBS "Die Box Passau" (2:2494/22.0) as soon as possible.

1.72 Most_engl.guide/Greetings

Greetings

Till now I worked about two years on Most. And still there're old (and new bugs) to be found. If there weren't the response from you, the user, I couldn't make Most to what it is now. There've been many enhancements I included in new releases and a lot of bugs I removed. I can't mention everyone who wrote me but want to list the most important ones:

Karl "Charly" Skibinski, David Göhler, Uli Zukowski, Stefan Sticht, Matthias "Tron" Scheler, Jan Holler, Dirk Federlein, Markus Uhlendahl

If you want to send me new translations for Most, please do this via snail mail or at least use uuencode sending an e-mail! I received some translations which I couldn't use or unpack. Sorry! The current translations are done by:

- Paul van der Heu (holländisch)
- Frank Geider (french)
- Francesco Dipietromaria (italian)
- Magnus Holmgren (swedish)
- Antonio Joaquin Gomez Gonzalez (spanish)

A special thanks to Urban for his sugesstions and XPK. And a great thank you to everyone who wrote me bug reports, suggestions and of course sent me gifts!!!!

1.73 Most_engl.guide/Index

Index

| | |
|-----------------|---------------------|
| XPK | XPK support |
| AINSI Sequences | Background |
| AmigaGuide | Help |
| AppIcon | The AppIcon |
| AppWindow | The main window |
| ARexx | ARexx Port |
| ARexx Port | ARexx Port |
| Author | Ideas - Bug reports |
| Background | Background |
| Bugs | Known bugs |
| Clipboard | The main window |
| Commandline | Configuration |
| Configuration | Configuration |
| Copyright | Copyright |
| Criticism | Ideas - Bug reports |
| Current version | Current version |

Default values
Edit
encrypted files
Environments
Extras
Gadgets
Giftware
Greetings
Help
Ideas
Includefiles
Info requester
Keyboard commands
Macros
Memory managment
Menu Search
Menus
Mouse
Move
packed files
Paging
Parameter
Pipe support
Processes
Project
Refreshing
Scripts
Search
search requester
Searching
Settings
Shell start
Startup
Suggestions
Text managment
Text marking
Thanks
Title
ToolTypes
Variables
Window
Workbench start

Configuration
Edit file
XPK support
Configuration
Extras
The main window
Copyright
Greetings
Help
Ideas - Bug reports
The main window
Info requester
Keyboard commands
Extras
Background
Menu Search
Menus
The main window
Move
XPK support
Background
Configuration
Pipe support
Background
Project
Extras
ARexx Port
The search requester
The search requester
Searching
Settings
Configuration
Configuration
Ideas - Bug reports
Background
The main window
Greetings
The main window
Configuration
Configuration
The main window
Configuration