

Functions

P!\K/AVOP|Un0X

COLLABORATORS

	TITLE : Functions		
ACTION	NAME	DATE	SIGNATURE
WRITTEN BY	P\K/AVOP Un0X	June 8, 2025	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	Functions	1
1.1	Functions	1
1.2	Trigonometric functions	2
1.3	Functions - abs	3
1.4	Functions - addrows	3
1.5	Functions - combine	3
1.6	Functions - const	4
1.7	Functions - debug	4
1.8	Functions - det	4
1.9	Functions - diff	4
1.10	Functions - dispose	5
1.11	Functions - disposeall	5
1.12	Functions - do	5
1.13	Functions - eq	5
1.14	Functions - eqlleft	6
1.15	Functions - eqlright	6
1.16	Functions - eval	6
1.17	Functions - exp	6
1.18	Functions - fak	6
1.19	Functions - include	6
1.20	Functions - inv	7
1.21	Functions - ln/log	7
1.22	Functions - matrix	7
1.23	Functions - multrow	7
1.24	Functions - neg	7
1.25	Functions - rang	8
1.26	Functions - sign	8
1.27	Functions - solve	8
1.28	Functions - spur	8
1.29	Functions - sqrt	8

1.30 Functions - swaprows	9
1.31 Functions - taylor	9
1.32 Functions - trans	9
1.33 Functions - umatrix	9
1.34 Functions - vector	10
1.35 Functions - window	10

Chapter 1

Functions

1.1 Functions

Functions :

[Click here](#) for the main documentation.

Laplace offers a lot (really? ;-) internal functions. Call them with the parameters separated by commas embedded in () brackets, e.g.

`sin(pi)`

`exp(1)`

`parameter : ...` means that the parameter must evaluate to one of the given object types.

`result : ...` means that the result is of the given object types. If there are more than one type, each type corresponds to a type in the parameter.

`abs(expr)`

`acos(expr)`

`acosh(expr)`

`acot(expr)`

`addrows(matrix,row1,row2,expr)`

`asin(expr)`

`asinh(expr)`

`atan(expr)`

`atanh(expr)`

`combine(list)`

`const(list)`

`cos(expr)`

`cosh(expr)`

`cot(expr)`

`debug(string)`

`det(expr)`

`diff(function,variable)`

dispose(list)
disposeall()
do(list)
eq(expr,expr)
eqleft(eq)
eqright(eq)
eval(expr)
exp(expr)
fak(expr)
include(path)
inv(expr)
ln(expr)
log(expr)
matrix([list],[list],...)
multrow(matrix,row1,expr)
neg(expr)
rang(expr)
sign(expr)
sin(expr)
sinh(expr)
solve(expr)
spur(expr)
sqrt(expr)
swaprows(matrix,row1,row2)
tan(expr)
tanh(expr)
taylor(function,a,grade)
trans(expr)
umatrix(size)
vector(list)
window(reference)

1.2 Trigonometric functions

sin(expression) :
cos(expression) :
tan(expression) :
cot(expression) :
asin(expression) :

`acos(expression) :`

`atan(expression) :`

`acot(expression) :`

`sinh(expression) :`

`cosh(expression) :`

`tanh(expression) :`

`asinh(expression) :`

`acosh(expression) :`

`atanh(expression) :`

`expression` : real, equation

`result` : real, equation

Calculate those well known trigonometric functions.

1.3 Functions - abs

`abs(expression) :`

`expression` : real, vector, equation

`result` : real, vector, equation

Real : Returns the absolute of the real.

Vector : Returns the absolute of the vector, which is defined as $\sqrt{a_1^2 + a_2^2 + \dots}$ where a_1, a_2 are the components of the vector. (Physically this is the length of the vector.)

1.4 Functions - addrows

`addrows(matrix,r1,r2,expression) :`

`matrix` : matrix (must be variable or parameter)

`r1` : real (should be integer)

`r2` : real (should be integer)

`expression` : real

`result` : matrix

This will copy the input matrix, except that row `r1` will be replace by $(\text{row } r1) + \text{expression} * (\text{row } r2)$

1.5 Functions - combine

`combine(list) :`

`result` : matrix

List is a list of object names of vectors or matrices (may be mixed).

This will create a matrix that is a combination of the input vectors/matrices. E.g.

`combine(matrix([1,2],[3,4]),vector(a,b))`

`/1 3 a\`

`\2 4 b/`

1.6 Functions - const

const(list) :

List is a list of object names separated by commas, where name is name[:type] the object name with an optional type specifier :

r, real - real object (default)

v, vec, vector - vector object, any dimension

v[d], vec[d], vector[d] - vector object, dimension d

m, mat, matrix - matrix object, any size

m[r,c], mat[r,c], matrix[r,c] - matrix object, size r*s

const() will create the named objects.

1.7 Functions - debug

debug(string) :

This will add the string to the debug list.

1.8 Functions - det

det(expression) :

expression : matrix, equation

result : real, equation

Returns the determinant of the matrix.

1.9 Functions - diff

diff(function,variable) :

This will calculate the first derivation of the given function.

There are different kinds of syntax for this command :

1) Calculate the derivation of an already defined function of one variable :

diff(functionname) - e.g.

$f(x)=x^2$

diff(f)

2) Calculate the (partial) derivation of an already defined function of one or more variables :

diff(functionname,variable) - e.g.

$f(x,y)=x^2+y^3$

diff(f , x)

diff(f , y)

3) Calculate the (partial) derivation of an already defined function of two or more variables, setting some variable to constant values :

diff(functionname(parameterlist),variable) - e.g.

$f(x,y)=x^2+y^3*x$

`diff(f(x,1) , x)`

`g(x)=diff(f(x,y) , y)`

4) Calculate the (partial) derivation of an explicit given function of one or more variables :

`diff((expression),variable)` - e.g.

`diff((x^2*sin(x)) , x)`

Don't forget the brackets, otherwise Laplace cannot realize, that this is not a reference.

Usually a function has free variables x, y or z. If you want to other variable names, you have to declare them as **constants** before using `diff()`, or use `diff()` inside of a function definition. E.g.

`diff((urps^2*sin(urps)),urps) -> Error : undefined reference.`

use instead :

`const(urps)`

`diff((urps^2*sin(urps)) , urps)`

or

`f(urps)=diff((urps^2*sin(urps)) , urps)`

1.10 Functions - dispose

`dispose(list)` :

This will dispose the previously defined objects. List is a list of object names separated by commas.

1.11 Functions - disposeall

`disposeall()` :

This will dispose all previously defined objects.

1.12 Functions - do

`do(list)` :

This is a synonym for an expression list. E.g.

`{debug("Hello world !"), sin(2)}` and

`do(debug("Hello world !"), sin(2))` are equal.

1.13 Functions - eq

`eq(expression, expression)` :

expression : real, vector, matrix

result : equation

This will create an equation object.

1.14 Functions - eqleft

eqleft(equation) :

Get the left side of an equation.

1.15 Functions - eqright

eqright(equation) :

Get the right side of an equation.

1.16 Functions - eval

eval(expression) :

expression : real, vector, matrix, equation

result : depends on expression

This will evaluate the given expression. Parameter references are replaced, too.

1.17 Functions - exp

exp(expression) :

expression : real, equation

result : real, equation

Returns e^x of the real. Use this functions instead of entering e^x directly

1.18 Functions - fak

fak(expression) :

expression : real, equation

result : real, equation

Returns $x!$ (factorial) of a whole reals. $x!$ for $x \leq 0$ is 0.

1.19 Functions - include

include(path) :

This will load and process a file from the directory Include.

See also Libraries.

1.20 Functions - inv

inv(expression) :

expression : real, matrix, equation

result : real, matrix, equation

Real : Return the invers of the real, which is simple $1/x$

Matrix : Return the invers of the matrix, which is defined that $m \cdot \text{inv}(m)$ is the standart matrix.

1.21 Functions - ln/log

ln(expression) :

log(expression) :

expression : real, equation

result : real, equation

Returns the natural/common logarithm of the real.

1.22 Functions - matrix

matrix([list],[list],...) :

This will create a matrix object. [list] is a column of the matrix, and list is a list of expressions seperated by commas. The components must evaluate to real. E.g.

matrix([1,2,3],[4,5,6],[7,8,9])

/1 4 7\

|2 5 8|

\3 6 9/

1.23 Functions - multrow

multrow(matrix,r,expression) :

matrix : matrix (must be variable or parameter)

r : real (should be integer)

expression : real

result : matrix

This will copy the input matrix, except that row r will be replace by $\text{expression} \cdot (\text{row } r)$

1.24 Functions - neg

neg(expression) :

expression : real, vector, matrix, equation

result : real, vector, matrix, equation

Returns the negative of the expression.

1.25 Functions - rang

`rang(expression)` :

expression : matrix, equation

result : real, equation

Returns the rang of the matrix. This is the number of non-zero rows of `solve(expression)`.

1.26 Functions - sign

`sign(expression)` :

expression : real, equation

result : real, equation

Return 1 if expression is > 0

Return 0 if expression is $= 0$

Return -1 if expression is < 0

1.27 Functions - solve

`solve(expression)` :

expression : matrix

result : matrix

Returns the solution of the matrix. This is the result of basic matrix transformations to convert the left square of the matrix into a standart matrix. This usually make only sense for non-square matrices.

1.28 Functions - spur

`spur(expression)` :

expression : matrix, equation

result : real, equation

Returns the spur of the matrix.

1.29 Functions - sqrt

`sqrt(expression)` :

expression : real, equation

result : real, equation

Returns the square root of the expression.

1.30 Functions - swaprows

swaprows(matrix,r1,r2) :

matrix : matrix (must be variable or parameter)

r1 : real (should be integer)

r2 : real (should be integer)

result : matrix

This will copy the input matrix, except that row r1 and row r2 are swapped.

1.31 Functions - taylor

taylor(function,a,grade) :

This will calculate a taylor approximation for the given function of one variable at a of the given grade. If you omit the grade, a default of 2 will be used.

There are different kinds of syntax for this command :

1) Taylor approximation for an already defined function of one variable :

taylor(functionname, a, grade) - e.g.

f(x)=sin(x)

taylor(f, 0, 2)

2) Taylor approximation for an explicit given function of one variables :

taylor((expression)(var), a, grade) - e.g.

taylor((sin(x))(x) , 0, 2)

1.32 Functions - trans

trans(expression) :

expression : matrix, equation

result : matrix, equation

Returns the transposition of the matrix.

1.33 Functions - umatrix

umatrix(size) :

result : matrix

This will create a standard matrix of the given size.

1.34 Functions - vector

`vector(list) :`

This will create a vector object. list is a list of expressions separated by commas. The components must evaluate to real. E.g.

`vector(1,2,3)`

`/1\`

`|2|`

`\3/`

1.35 Functions - window

`window(name) :`

This will open a window, displaying the named object.