

iffparse

COLLABORATORS

	<i>TITLE :</i> iffparse		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		July 19, 2024	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	iffparse	1
1.1	iffparse.doc	1
1.2	iffparse.library/AllocIFF	2
1.3	iffparse.library/AllocLocalItem	2
1.4	iffparse.library/CloseClipboard	3
1.5	iffparse.library/CloseIFF	3
1.6	iffparse.library/CollectionChunk	4
1.7	iffparse.library/CollectionChunks	4
1.8	iffparse.library/CurrentChunk	5
1.9	iffparse.library/EntryHandler	6
1.10	iffparse.library/ExitHandler	7
1.11	iffparse.library/FindCollection	8
1.12	iffparse.library/FindLocalItem	9
1.13	iffparse.library/FindProp	9
1.14	iffparse.library/FindPropContext	10
1.15	iffparse.library/FreeIFF	10
1.16	iffparse.library/FreeLocalItem	11
1.17	iffparse.library/GoodID	11
1.18	iffparse.library/GoodType	12
1.19	iffparse.library/IDtoStr	12
1.20	iffparse.library/InitIFF	13
1.21	iffparse.library/InitIFFasClip	14
1.22	iffparse.library/InitIFFasDOS	15
1.23	iffparse.library/LocalItemData	15
1.24	iffparse.library/OpenClipboard	16
1.25	iffparse.library/OpenIFF	16
1.26	iffparse.library/ParentChunk	17
1.27	iffparse.library/ParseIFF	18
1.28	iffparse.library/PopChunk	19
1.29	iffparse.library/PropChunk	19

1.30	iffparse.library/PropChunks	20
1.31	iffparse.library/PushChunk	20
1.32	iffparse.library/ReadChunkBytes	21
1.33	iffparse.library/ReadChunkRecords	22
1.34	iffparse.library/SetLocalItemPurge	22
1.35	iffparse.library/StopChunk	23
1.36	iffparse.library/StopChunks	24
1.37	iffparse.library/StopOnExit	24
1.38	iffparse.library/StoreItemInContext	25
1.39	iffparse.library/StoreLocalItem	25
1.40	iffparse.library/WriteChunkBytes	26
1.41	iffparse.library/WriteChunkRecords	27

Chapter 1

iffparse

1.1 iffparse.doc

AllocIFF ()
AllocLocalItem ()
CloseClipboard ()
CloseIFF ()
CollectionChunk ()
CollectionChunks ()
CurrentChunk ()
EntryHandler ()
ExitHandler ()
FindCollection ()
FindLocalItem ()
FindProp ()
FindPropContext ()
FreeIFF ()
FreeLocalItem ()
GoodID ()
GoodType ()
IDtoStr ()
InitIFF ()
InitIFFasClip ()
InitIFFasDOS ()
LocalItemData ()
OpenClipboard ()
OpenIFF ()
ParentChunk ()
ParseIFF ()
PopChunk ()
PropChunk ()
PropChunks ()
PushChunk ()
ReadChunkBytes ()
ReadChunkRecords ()
SetLocalItemPurge ()
StopChunk ()
StopChunks ()
StopOnExit ()
StoreItemInContext ()
StoreLocalItem ()

```
WriteChunkBytes()  
WriteChunkRecords()
```

1.2 iffparse.library/AllocIFF

NAME

AllocIFF -- create a new IFFHandle structure. (V36)

SYNOPSIS

```
iff = AllocIFF()  
D0
```

```
struct IFFHandle *AllocIFF(VOID);
```

FUNCTION

Allocates and initializes a new IFFHandle structure. This function is the only supported way to create an IFFHandle structure since there are private fields that need to be initialized.

RESULT

iff - pointer to IFFHandle structure or NULL if the allocation failed.

SEE ALSO

FreeIFF(), <libraries/iffparse.h>

1.3 iffparse.library/AllocLocalItem

NAME

AllocLocalItem -- create a local context item structure. (V36)

SYNOPSIS

```
item = AllocLocalItem(type, id, ident, dataSize);  
D0          D0    D1  D2    D3
```

```
struct LocalContextItem *AllocLocalItem(LONG, LONG, LONG, LONG);
```

FUNCTION

Allocates and initializes a LocalContextItem structure with "dataSize" bytes of associated user data. This is the only supported way to create such an item. The user data can be accessed with the LocalItemData() function. An item created with this function automatically has its purge vectors set up correctly to dispose of itself and its associated purge user data area. Any additional cleanup should be done with a user-supplied purge vector.

INPUTS

type, id - additional longword identification values
ident - longword identifier for class of context item
dataSize - number of bytes of user data to allocate for this item

RESULT

item - pointer to initialized LocalContextItem or NULL if the

allocation failed.

SEE ALSO

FreeLocalItem(), LocalItemData(), StoreLocalItem(),
StoreItemInContext(), SetLocalItemPurge(), <libraries/iffparse.h>

1.4 iffparse.library/CloseClipboard

NAME

CloseClipboard -- close and free an open ClipboardHandle. (V36)

SYNOPSIS

```
CloseClipboard(clipHandle);  
                A0
```

```
VOID CloseClipboard(struct ClipboardHandle *);
```

FUNCTION

Closes the clipboard.device and frees the ClipboardHandle structure.

INPUTS

clipHandle - pointer to ClipboardHandle struct created with
OpenClipboard(). Starting with V39, this may be NULL.

SEE ALSO

OpenClipboard(), InitIFFasClip(), <libraries/iffparse.h>

1.5 iffparse.library/CloseIFF

NAME

CloseIFF -- close an IFF context. (V36)

SYNOPSIS

```
CloseIFF(iff);  
                A0
```

```
VOID CloseIFF(struct IFFHandle *);
```

FUNCTION

Completes an IFF read or write operation by closing the IFF context established for this IFFHandle structure. The IFFHandle structure itself is left ready for re-use and a new context can be opened with OpenIFF(). This function can be used for cleanup if a read or write fails partway through.

As part of its cleanup operation, CloseIFF() calls the client-supplied stream hook vector. The IFFStreamCmd packet will be set as follows:

```
sc_Command:  IFFCMD_CLEANUP  
sc_Buf:      (Not applicable)  
sc_NBytes:   (Not applicable)
```

This operation is NOT permitted to fail; any error code returned will be ignored (best to return 0, though). DO NOT write to this structure.

INPUTS

iff - pointer to IFFHandle structure previously opened with OpenIFF(). Starting with V39, this may be NULL.

SEE ALSO

OpenIFF(), InitIFF(), <libraries/iffparse.h>

1.6 iffparse.library/CollectionChunk

NAME

CollectionChunk -- declare a chunk type for collection. (V36)

SYNOPSIS

```
error = CollectionChunk(iff, type, id);
D0                A0  D0  D1
```

```
LONG CollectionChunk(struct IFFHandle *, LONG, LONG);
```

FUNCTION

Installs an entry handler for chunks with the given type and id so that the contents of those chunks will be stored as they are encountered. This is like PropChunk() except that more than one chunk of this type can be stored in lists which can be returned by FindCollection(). The storage of these chunks still follows the property chunk scoping rules for IFF files so that at any given point, stored collection chunks will be valid in the current context.

INPUTS

iff - pointer to IFFHandle structure (does not need to be open)
 type - type code for the chunk to declare (ex. "ILBM")
 id - identifier for the chunk to declare (ex. "CRNG")

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful.

SEE ALSO

CollectionChunks(), FindCollection(), PropChunk(), <libraries/iffparse.h>

1.7 iffparse.library/CollectionChunks

NAME

CollectionChunks -- declare many collection chunks at once. (V36)

SYNOPSIS

```
error = CollectionChunks(iff, propArray, numPairs);
D0                A0  A1  D0
```

```
LONG CollectionChunks(struct IFFHandle *, LONG *, LONG);
```

FUNCTION

Declares multiple collection chunks from a list. The propArray argument is a pointer to an array of longwords arranged in pairs. The format for the list is as follows:

```
TYPE1, ID1, TYPE2, ID2, ..., TYPEn, IDn
```

The argument numPairs is the number of pairs. CollectionChunks() just calls CollectionChunk() numPairs times.

INPUTS

iff - pointer to IFFHandle structure (does not need to be open)
propArray - pointer to array of longword chunk types and identifiers
numPairs - number of pairs in array.

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful

SEE ALSO

CollectionChunk(), <libraries/iffparse.h>

1.8 iffparse.library/CurrentChunk

NAME

CurrentChunk -- get context node for current chunk. (V36)

SYNOPSIS

```
top = CurrentChunk(iff);  
D0                   A0
```

```
struct ContextNode *CurrentChunk(struct IFFHandle *);
```

FUNCTION

Returns the top context node for the given IFFHandle structure. The top context node corresponds to the chunk most recently pushed on the stack, which is the chunk where the stream is currently positioned. The ContextNode structure contains information on the type of chunk currently being parsed (or written), its size and the current position within the chunk.

INPUTS

iff - pointer to IFFHandle structure

RESULT

top - pointer to top context node or NULL if none

SEE ALSO

PushChunk(), PopChunk(), ParseIFF(), ParentChunk(),
<libraries/iffparse.h>

1.9 iffparse.library/EntryHandler

NAME

EntryHandler -- add an entry handler to the IFFHandle context. (V36)

SYNOPSIS

```
error = EntryHandler(iff, type, id, position, handler, object);
D0                A0   D0   D1  D2                A1       A2
```

```
LONG EntryHandler(struct IFFHandle *, LONG, LONG, LONG,
                  struct Hook *, APTR);
```

FUNCTION

Installs an entry handler vector for a specific type of chunk into the context for the given IFFHandle structure. Type and id are the longword identifiers for the chunk to handle. The handler is a client-supplied standard Hook structure, properly initialized. position tells where to put the handler in the context. The handler will be called whenever the parser enters a chunk of the given type, so the IFF stream will be positioned to read the first data byte in the chunk. The handler will execute in the same context as whoever called ParseIFF(). The handler will be called (through the hook) with the following arguments:

A0: the Hook pointer you passed.
 A2: the 'object' pointer you passed.
 A1: pointer to a LONG containing the value
 IFFCMD_ENTRY.

The error code your call-back routine returns will affect the parser in three different ways:

Return value	Result
0:	Normal success; ParseIFF() will continue through the file.
IFF_RETURN2CLIENT:	ParseIFF() will stop and return the value 0. (StopChunk() is internally implemented using this return value.)
Any other value:	ParseIFF() will stop and return the value you supplied. This is how errors should be returned.

INPUTS

iff - pointer to IFFHandle structure.
 type - type code for chunk to handle (ex. "ILBM").
 id - ID code for chunk to handle (ex. "CMAP").
 position - local context item position. One of the IFFSLI_#? codes.
 handler - pointer to Hook structure.
 object - a client-defined pointer which is passed in A2 during call-back.

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful.

BUGS

Returning the values IFFERR_EOF or IFFERR_EOC from the call-back routine *may* confuse the parser.

There is no way to explicitly remove a handler once installed. However, by installing a do-nothing handler using IFFSLI_TOP, previous handlers will be overridden until the context expires.

SEE ALSO

ExitHandler(), StoreLocalItem(), StoreItemInContext(),
<utility/hooks.h>, <libraries/iffparse.h>

1.10 iffparse.library/ExitHandler

NAME

ExitHandler -- add an exit handler to the IFFHandle context. (V36)

SYNOPSIS

```
error = ExitHandler(iff, type, id, position, handler, object);
D0                A0  D0  D1  D2                A1      A2
```

```
LONG ExitHandler(struct IFFHandle *, LONG, LONG, LONG,
                 struct Hook *, APTR object);
```

FUNCTION

Installs an exit handler vector for a specific type of chunk into the context for the given IFFHandle structure. Type and id are the longword identifiers for the chunk to handle. The handler is a client-supplied standard Hook structure, properly initialized. Position tells where to put the handler in the context. The handler will be called just before the parser exits the given chunk in the "pause" parse state. The IFF stream may not be positioned predictably within the chunk. The handler will execute in the same context as whoever called ParseIFF(). The handler will be called (through the hook) with the following arguments:

A0: the Hook pointer you passed.
A2: the 'object' pointer you passed.
A1: pointer to a LONG containing the value
IFFCMD_EXIT.

The error code your call-back routine returns will affect the parser in three different ways:

Return value	Result
0:	Normal success; ParseIFF() will continue through the file.
IFF_RETURN2CLIENT:	ParseIFF() will stop and return the value 0. (StopChunk() is internally implemented using this return value.)
Any other value:	ParseIFF() will stop and return the value you supplied. This is how errors should be returned.

INPUTS

iff - pointer to IFFHandle structure.
 type - type code for chunk to handle (ex. "ILBM").
 id - identifier code for chunk to handle (ex. "CMAP").
 position - local context item position. One of the IFFSLI_#? codes.
 handler - pointer to Hook structure.
 object - a client-defined pointer which is passed in A2 during call-back.

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful.

BUGS

Returning the values IFFERR_EOF or IFFERR_EOC from the call-back routine **may** confuse the parser.

There is no way to explicitly remove a handler once installed. However, by installing a do-nothing handler using IFFSLI_TOP, previous handlers will be overridden until the context expires.

SEE ALSO

EntryHandler(), StoreLocalItem(), StoreItemInContext(),
 <utility/hooks.h>, <libraries/iffparse.h>

1.11 iffparse.library/FindCollection

NAME

FindCollection -- get a pointer to the current list of collection items. (V36)

SYNOPSIS

```
ci = FindCollection(iff, type, id);
D0                A0   D0   D1
```

```
struct CollectionItem *FindCollection(struct IFFHandle *, LONG, LONG);
```

FUNCTION

Returns a pointer to a list of CollectionItem structures for each of the collection chunks of the given type encountered so far in the course of parsing this IFF file. The items appearing first in the list will be the ones encountered most recently.

INPUTS

iff - pointer to IFFHandle structure.
 type - type code to search for.
 id - identifier code to search for.

RESULT

ci - pointer to last collection chunk encountered with links to previous ones.

SEE ALSO

CollectionChunk(), CollectionChunks(), <libraries/iffparse.h>

1.12 iffparse.library/FindLocalItem

NAME

FindLocalItem -- return a local context item from the context stack.
(V36)

SYNOPSIS

```
lci = FindLocalItem(iff, type, id, ident);
D0          A0   D0   D1  D2
```

```
struct LocalContextItem *FindLocalItem(struct IFFHandle *,
                                       LONG, LONG, LONG);
```

FUNCTION

Searches the context stack of the given IFFHandle structure for a local context item which matches the given ident, type and id. This function searches the context stack from the most current context backwards, so that the item found (if any) will be the one with greatest precedence in the context stack.

INPUTS

iff - pointer to IFFHandle structure.
 type - type code to search for.
 id - ID code to search for.
 ident - ident code for the class of context item to search for
 (ex. "exhd" -- exit handler).

RESULT

lci - pointer to local context item, or NULL if nothing matched.

SEE ALSO

StoreLocalItem(), <libraries/iffparse.h>

1.13 iffparse.library/FindProp

NAME

FindProp -- search for a stored property chunk. (V36)

SYNOPSIS

```
sp = FindProp(iff, type, id);
D0          A0   D0   D1
```

```
struct StoredProperty *FindProp(struct IFFHandle *, LONG, LONG);
```

FUNCTION

Searches for the stored property which is valid in the given context. Property chunks are automatically stored by ParseIFF() when pre-declared by PropChunk() or PropChunks(). The StoredProperty struct, if found, contains a pointer to a data buffer containing the contents of the stored property.

INPUTS

iff - pointer to IFFHandle structure.
 type - type code for chunk to search for (ex. "ILBM").

id - identifier code for chunk to search for (ex. "CMAP").

RESULT

sp - pointer to stored property, or NULL if none found.

SEE ALSO

PropChunk(), PropChunks(), <libraries/iffparse.h>

1.14 iffparse.library/FindPropContext

NAME

FindPropContext -- get the property context for the current state.
(V36)

SYNOPSIS

```
cn = FindPropContext(iff);  
D0                                A0
```

```
struct ContextNode *FindPropContext(struct IFFHandle *);
```

FUNCTION

Locates the context node which would be the scoping chunk for properties in the current parsing state. (Huh?) This is used for locating the proper scoping context for property chunks i.e. the scope from which a property would apply. This is usually the FORM or LIST with the highest precedence in the context stack.

If you don't understand this, read the IFF spec a couple more times.

INPUTS

iff - pointer to IFFHandle structure.

RESULT

cn - ContextNode of property scoping chunk.

SEE ALSO

CurrentChunk(), ParentChunk(), StoreItemInContext(),
<libraries/iffparse.h>

1.15 iffparse.library/FreeIFF

NAME

FreeIFF -- deallocate an IFFHandle structure. (V36)

SYNOPSIS

```
FreeIFF(iff);  
A0
```

```
VOID FreeIFF(struct IFFHandle *);
```

FUNCTION

Deallocates all resources associated with this IFFHandle structure.

The structure MUST have already been closed with `CloseIFF()`.

INPUTS

`iff` - pointer to `IFFHandle` structure to free. Starting with V39, this may be `NULL`.

SEE ALSO

`AllocIFF()`, `CloseIFF()`, `<libraries/iffparse.h>`

1.16 iffparse.library/FreeLocalItem

NAME

`FreeLocalItem` -- deallocate a local context item structure. (V36)

SYNOPSIS

```
FreeLocalItem(localItem);  
                A0
```

```
VOID FreeLocalItem(struct LocalContextItem *);
```

FUNCTION

Frees the memory for the local context item and any associated user memory as allocated with `AllocLocalItem()`. User purge vectors should call this function after they have freed any other resources associated with this item.

Note that `FreeLocalItem()` does NOT call the custom purge vector set up through `SetLocalItemPurge()`; all it does is free the local context item. (This implies that your custom purge vector would want to call this to ultimately free the `LocalContextItem`.)

INPUTS

`localItem` - pointer to `LocalContextItem` created with `AllocLocalItem`. Starting with V39, this may be `NULL`.

SEE ALSO

`AllocLocalItem()`, `<libraries/iffparse.h>`

1.17 iffparse.library/GoodID

NAME

`GoodID` -- test if an identifier follows the IFF 85 specification. (V36)

SYNOPSIS

```
isok = GoodID(id);  
D0                D0
```

```
LONG GoodID(LONG);
```

FUNCTION

Tests the given longword identifier to see if it meets all the EA IFF 85 specifications for a chunk ID. If so, it returns non-zero,

otherwise 0.

INPUTS

id - potential 32 bit identifier.

RESULT

isok - non-zero if this is a valid ID, 0 otherwise.

SEE ALSO

GoodType()

1.18 iffparse.library/GoodType

NAME

GoodType -- test if a type follows the IFF 85 specification. (V36)

SYNOPSIS

```
isok = GoodType(type)
```

```
D0          D0
```

```
LONG GoodType(LONG);
```

FUNCTION

Tests the given longword type identifier to see if it meets all the EA IFF 85 specifications for a FORM type (requirements for a FORM type are more stringent than those for a simple chunk ID). If it complies, GoodType() returns non-zero, otherwise 0.

INPUTS

type - potential 32 bit format type identifier.

RESULT

isok - non-zero if this is a valid type id, 0 otherwise.

SEE ALSO

GoodID()

1.19 iffparse.library/IDtoStr

NAME

IDtoStr -- convert a longword identifier to a null-terminated string.
(V36)

SYNOPSIS

```
str = IDtoStr(id, buf);
```

```
D0          D0  A0
```

```
STRPTR IDtoStr(LONG, STRPTR);
```

FUNCTION

Writes the ASCII equivalent of the given longword ID into buf as a null-terminated string.

INPUTS
id - longword ID.
buf - character buffer to accept string (at least 5 chars).

RESULT
str - the value of 'buf'.

1.20 iffparse.library/InitIFF

NAME
InitIFF -- initialize an IFFHandle structure as a user stream. (V36)

SYNOPSIS
InitIFF(iff, flags, streamHook);
 A0 D0 A1

VOID InitIFF(struct IFFHandle *, LONG, struct Hook *);

FUNCTION
Initializes an IFFHandle as a general user-defined stream by allowing the user to declare a hook that the library will call to accomplish the low-level reading, writing, and seeking of the stream. Flags are the stream I/O flags for the specified stream; typically a combination of the IFFF_?SEEK flags.

The stream vector is called with the following arguments:

A0: pointer to streamhook.
A2: pointer to IFFHandle structure.
A1: pointer to IFFStreamCmd structure.

The IFFStreamCmd packet appears as follows:

sc_Command: Contains an IFFCMD_#? value
sc_Buf: Pointer to memory buffer
sc_NBytes: Number of bytes involved in operation

The values taken on by sc_Command, and their meaning, are as follows:

IFFCMD_INIT:
Prepare your stream for reading. This is used for certain streams that can't be read immediately upon opening, and need further preparation. (The clipboard.device is an example of such a stream.) This operation is allowed to fail; any error code will be returned directly to the client. sc_Buf and sc_NBytes have no meaning here.

IFFCMD_CLEANUP:
Terminate the transaction with the associated stream. This is used with streams that can't simply be closed. (Again, the clipboard is an example of such a stream.) This operation is not permitted to fail; any error returned will be ignored (best to return 0, though). sc_Buf and sc_NBytes have no meaning here.

IFFCMD_READ:

Read from the stream. You are to read `sc_NBytes` from the stream and place them in the buffer pointed to by `sc_Buf`. Any (non-zero) error returned will be remapped by the parser into `IFFERR_READ`.

IFFCMD_WRITE:

Write to the stream. You are to write `sc_NBytes` to the stream from the buffer pointed to by `sc_Buf`. Any (non-zero) error returned will be remapped by the parser into `IFFERR_WRITE`.

IFFCMD_SEEK:

Seek on the stream. You are to perform a seek on the stream relative to the current position. `sc_NBytes` is signed; negative values mean seek backward, positive values mean seek forward. `sc_Buf` has no meaning here. Any (non-zero) error returned will be remapped by the parser into `IFFERR_SEEK`.

All errors are returned in `D0`. A return of 0 indicates success. UNDER NO CIRCUMSTANCES are you permitted to write to the `IFFStreamCmd` structure.

INPUTS

`iff` - pointer to `IFFHandle` structure to initialize.

`flags` - stream I/O flags for the `IFFHandle`.

`streamHook` - pointer to `Hook` structure.

SEE ALSO

<utility/hooks.h>, <libraries/iffparse.h>

1.21 iffparse.library/InitIFFasClip

NAME

`InitIFFasClip` -- initialize an `IFFHandle` as a clipboard stream. (V36)

SYNOPSIS

```
InitIFFasClip(iff);
                A0
```

```
VOID InitIFFasClip(struct IFFHandle *);
```

FUNCTION

Initializes the given `IFFHandle` to be a clipboard stream. The function initializes the stream processing vectors to operate on streams of the `ClipboardHandle` type. The `iff_Stream` field will still need to be initialized to point to a `ClipboardHandle` as returned from `OpenClipboard()`.

INPUTS

`iff` - pointer to `IFFHandle` structure.

SEE ALSO

`InitIFF()`, `OpenClipboard()`, <libraries/iffparse.h>

1.22 iffparse.library/InitIFFasDOS

NAME

InitIFFasDOS -- initialize an IFFHandle as a DOS stream. (V36)

SYNOPSIS

```
InitIFFasDOS(iff)
                A0
```

```
InitIFFasDOS(struct IFFHandle *);
```

FUNCTION

The function initializes the given IFFHandle to operate on DOS streams. The iff_Stream field will need to be initialized as a BPTR returned from the DOS function Open().

INPUTS

iff - pointer to IFFHandle structure.

SEE ALSO

InitIFF()

1.23 iffparse.library/LocalItemData

NAME

LocalItemData -- get pointer to user data for local context item. (V36)

SYNOPSIS

```
data = LocalItemData(localItem);
D0                                A0
```

```
APTR LocalItemData(struct LocalContextItem *);
```

FUNCTION

Returns pointer to the user data associated with the given local context item. The size of the data area depends on the "dataSize" argument used when allocating this item. If the pointer to the item given (localItem) is NULL, this function returns NULL.

INPUTS

localItem - pointer to local context item or NULL.

RESULT

data - pointer to user data area or NULL if localItem is NULL.

BUGS

Currently, there is no way to determine the size of the user data area; you have to 'know'.

SEE ALSO

AllocLocalItem(), FreeLocalItem(), <libraries/iffparse.h>

1.24 iffparse.library/OpenClipboard

NAME

OpenClipboard -- create a handle on a clipboard unit. (V36)

SYNOPSIS

```
ch = OpenClipboard(unitNumber)
D0                                D0
```

```
struct ClipboardHandle *OpenClipboard(LONG);
```

FUNCTION

Opens the clipboard.device and opens a stream for the specified unit (usually PRIMARY_CLIP). This handle structure will be used as the clipboard stream for IFFHandles initialized as clipboard streams by InitIFFasClip().

INPUTS

unitNumber - clipboard unit number (usually PRIMARY_CLIP).

RESULT

ch - pointer to ClipboardHandle structure or NULL if unsuccessful.

BUGS

This function had several bugs prior to V39.

First bug was that if the clipboard.device couldn't open, two calls to FreeSignal() were made with uninitialized values as parameters. The result of this was a corrupt signal mask in the Task field.

Second bug was that OpenDevice() was called with an IO request that didn't have a valid MsgPort pointer in it.

Third bug was that the two message ports allocated by the function (ClipboardHandle->cbh_CBport and ClipboardHandle->cbh_SatisfyPort) were not being initialized correctly and would cause a system crash if a message ever got to either of them.

SEE ALSO

InitIFFasClip(), CloseClipboard(), <libraries/iffparse.h>

1.25 iffparse.library/OpenIFF

NAME

OpenIFF -- prepare an IFFHandle to read or write a new IFF stream.
(V36)

SYNOPSIS

```
error = OpenIFF(iff, rwMode);
D0                                A0    D0
```

```
LONG OpenIFF(struct IFFHandle *, LONG);
```

FUNCTION

Initializes an IFFHandle structure for a new read or write. The direction of the I/O is given by the value of `rwMode`, which can be either `IFFF_READ` or `IFFF_WRITE`.

As part of its initialization procedure, `OpenIFF()` calls the client-supplied stream hook vector. The `IFFStreamCmd` packet will contain the following:

```
sc_Command:  IFFCMD_INIT
sc_Buf:      (Not applicable)
sc_NBytes:   (Not applicable)
```

This operation is permitted to fail. DO NOT write to this structure.

INPUTS

`iff` - pointer to IFFHandle structure. Starting with V39, this may be NULL, in which case `IFFERR_NOMEM` is returned.
`rwMode` - `IFFF_READ` or `IFFF_WRITE`

RESULT

`error` - contains an error code or 0 if successful

SEE ALSO

`CloseIFF()`, `InitIFF()`, `<libraries/iffparse.h>`

1.26 iffparse.library/ParentChunk

NAME

`ParentChunk` -- get the nesting context node for the given chunk. (V36)

SYNOPSIS

```
parent = ParentChunk(contextNode);
D0                      A0
```

```
struct ContextNode *ParentChunk(struct ContextNode *);
```

FUNCTION

Returns a context node for the chunk containing the chunk for the given context node. This function effectively moves down the context stack into previously pushed contexts. For example, to get a `ContextNode` pointer for the enclosing FORM chunk while reading a data chunk, use: `ParentChunk(CurrentChunk(iff))` to find this pointer. The `ContextNode` structure contains information on the type of chunk and its size.

INPUTS

`contextNode` - pointer to a context node.

RESULT

`parent` - pointer to the enclosing context node or NULL if none.

SEE ALSO

`CurrentChunk()`, `<libraries/iffparse.h>`

1.27 iffparse.library/ParseIFF

NAME

ParseIFF -- parse an IFF file from an IFFHandle structure stream. (V36)

SYNOPSIS

```
error = ParseIFF(iff, control);  
D0                A0    D0
```

```
LONG ParseIFF(struct IFFHandle *, LONG);
```

FUNCTION

This is the biggie.

Traverses a file opened for read by pushing chunks onto the context stack and popping them off directed by the generic syntax of IFF files. As it pushes each new chunk, it searches the context stack for handlers to apply to chunks of that type. If it finds an entry handler it will invoke it just after entering the chunk. If it finds an exit handler it will invoke it just before leaving the chunk. Standard handlers include entry handlers for pre-declared property chunks and collection chunks and entry and exit handlers for stop chunks - that is, chunks which will cause the ParseIFF() function to return control to the client. Client programs can also provide their own custom handlers.

The control flag can have three values:

IFFPARSE_SCAN:

In this normal mode, ParseIFF() will only return control to the caller when either:

- 1) an error is encountered,
- 2) a stop chunk is encountered, or a user handler returns the special IFF_RETURN2CLIENT code, or
- 3) the end of the logical file is reached, in which case IFFERR_EOF is returned.

ParseIFF() will continue pushing and popping chunks until one of these conditions occurs. If ParseIFF() is called again after returning, it will continue to parse the file where it left off.

IFFPARSE_STEP and _RAWSTEP:

In these two modes, ParseIFF() will return control to the caller after every step in the parse, specifically, after each push of a context node and just before each pop. If returning just before a pop, ParseIFF() will return IFFERR_EOC, which is not an error, per se, but is just an indication that the most recent context is ending. In STEP mode, ParseIFF() will invoke the handlers for chunks, if any, before returning. In RAWSTEP mode, ParseIFF() will not invoke any handlers and will return right away. In both cases the function can be called multiple times to step through the parsing of the IFF file.

INPUTS

iff - pointer to IFFHandle structure.
 control - control code (IFFPARSE_SCAN, _STEP or _RAWSTEP).

RESULT
 error - 0 or IFFERR_#? value or return value from user handler.

SEE ALSO
 PushChunk(), PopChunk(), EntryHandler(), ExitHandler(),
 PropChunk(), CollectionChunk(), StopChunk(), StopOnExit(),
 <libraries/iffparse.h>

1.28 iffparse.library/PopChunk

NAME
 PopChunk -- pop top context node off context stack. (V36)

SYNOPSIS
 error = PopChunk(iff);
 D0 A0

LONG PopChunk(struct IFFHandle *);

FUNCTION
 Pops top context chunk and frees all associated local context items.
 The function is normally called only for writing files and signals
 the end of a chunk.

INPUTS
 iff - pointer to IFFHandle structure.

RESULT
 error - 0 if successful or an IFFERR_#? error code if unsuccessful.

SEE ALSO
 PushChunk(), <libraries/iffparse.h>

1.29 iffparse.library/PropChunk

NAME
 PropChunk -- specify a property chunk to store. (V36)

SYNOPSIS
 error = PropChunk(iff, type, id);
 D0 A0 D0 D1

LONG PropChunk(struct IFFHandle *, LONG, LONG);

FUNCTION
 Installs an entry handler for chunks with the given type and ID so
 that the contents of those chunks will be stored as they are
 encountered. The storage of these chunks follows the property chunk
 scoping rules for IFF files so that at any given point, a stored

property chunk returned by FindProp() will be the valid property for the current context.

INPUTS

iff - pointer to IFFHandle structure (does not need to be open).
 type - type code for the chunk to declare (ex. "ILBM").
 id - identifier for the chunk to declare (ex. "CMAP").

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful.

SEE ALSO

PropChunks(), FindProp(), CollectionChunk(), <libraries/iffparse.h>

1.30 iffparse.library/PropChunks

NAME

PropChunks -- declare many property chunks at once. (V36)

SYNOPSIS

```
error = PropChunks(iff, propArray, numPairs);
D0                A0  A1      D0
```

```
LONG PropChunks(struct IFFHandle *, LONG *, LONG);
```

FUNCTION

Declares multiple property chunks from a list. The propArray argument is a pointer to an array of longwords arranged in pairs, and has the following format:

```
TYPE1, ID1, TYPE2, ID2, ..., TYPEn, IDn
```

The argument numPairs is the number of pairs. PropChunks() just calls PropChunk() numPairs times.

INPUTS

iff - pointer to IFFHandle structure.
 propArray - pointer to array of longword chunk types and identifiers.
 numPairs - number of pairs in the array.

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful.

SEE ALSO

PropChunk(), <libraries/iffparse.h>

1.31 iffparse.library/PushChunk

NAME

PushChunk -- push a new context node on the context stack. (V36)

SYNOPSIS

```
error = PushChunk(iff, type, id, size);
D0          A0   D0   D1  D2
```

```
LONG PushChunk(struct IFFHandle *, LONG, LONG, LONG);
```

FUNCTION

Pushes a new context node on the context stack by reading it from the stream if this is a read file, or by creating it from the passed parameters if this is a write file. Normally this function is only called in write mode, where the type and id codes specify the new chunk to create. If this is a leaf chunk, i.e. a local chunk inside a FORM or PROP chunk, then the type argument is ignored. If the size is specified then the chunk writing functions will enforce this size. If the size is given as IFFSIZE_UNKNOWN, the chunk will expand to accommodate whatever is written into it.

INPUTS

iff - pointer to IFFHandle structure.
 type - chunk type specifier (ex. ILBM) (ignored for read mode or leaf chunks).
 id - chunk id specifier (ex. CMAP) (ignored for read mode).
 size - size of the chunk to create or IFFSIZE_UNKNOWN (ignored for read mode).

RESULT

error - 0 if successful or an IFFERR_#? error code if not unsuccessful.

SEE ALSO

PopChunk(), WriteChunkRecords(), WriteChunkBytes(),
 <libraries/iffparse.h>

1.32 iffparse.library/ReadChunkBytes

NAME

ReadChunkBytes -- read bytes from the current chunk into a buffer.
 (V36)

SYNOPSIS

```
actual = ReadChunkBytes(iff, buf, numBytes);
D0          A0   A1   D0
```

```
LONG ReadChunkBytes(struct IFFHandle *, APTR buf, LONG);
```

FUNCTION

Reads the IFFHandle stream into the buffer for the specified number of bytes. Reads are limited to the size of the current chunk and attempts to read past the end of the chunk will truncate. This function returns positive number of bytes read or a negative error code.

INPUTS

iff - pointer to IFFHandle structure.
 buf - pointer to buffer area to receive data.
 numBytes - number of bytes to read.

RESULT
actual - (positive) number of bytes read if successful or a
(negative) IFFERR_#? error code if unsuccessful.

SEE ALSO
ReadChunkRecords(), ParseIFF(), WriteChunkBytes(),
<libraries/iffparse.h>

1.33 iffparse.library/ReadChunkRecords

NAME
ReadChunkRecords -- read record elements from the current chunk into
a buffer. (V36)

SYNOPSIS
actual = ReadChunkRecords(iff, buf, bytesPerRecord, numRecords);
D0 A0 A1 D0 D1

LONG ReadChunkRecords(struct IFFHandle *, APTR, LONG, LONG);

FUNCTION
Reads records from the current chunk into buffer. Truncates attempts
to read past end of chunk (only whole records are read; remaining
bytes that are not of a whole record size are left unread and
available for ReadChunkBytes()).

INPUTS
iff - pointer to IFFHandle structure.
buf - pointer to buffer area to receive data.
bytesPerRecord - size of data records to read.
numRecords - number of data records to read.

RESULT
actual - (positive) number of whole records read if successful or a
(negative) IFFERR_#? error code if unsuccessful.

SEE ALSO
ReadChunkBytes(), ParseIFF(), WriteChunkRecords(),
<libraries/iffparse.h>

1.34 iffparse.library/SetLocalItemPurge

NAME
SetLocalItemPurge -- set purge vector for a local context item. (V36)

SYNOPSIS
SetLocalItemPurge(localItem, purgeHook);
 A0 A1

VOID SetLocalItemPurge(struct LocalContextItem *, struct Hook *);

FUNCTION

Sets a local context item to use a client-supplied cleanup (purge) vector for disposal when its context is popped. The purge vector will be called when the ContextNode containing this local item is popped off the context stack and is about to be deleted itself. If the purge vector has not been set, the parser will use FreeLocalItem() to delete the item, but if this function is used to set the purge vector, the supplied vector will be called with the following arguments:

A0: pointer to purgeHook.
 A2: pointer to LocalContextItem to be freed.
 A1: pointer to a LONG containing the value
 IFFCMD_PURGELCI.

The user purge vector is then responsible for calling FreeLocalItem() as part of its own cleanup. Although the purge vector can return a value, it will be ignored -- purge vectors must always work (best to return 0, though).

INPUTS

localItem - pointer to a local context item.
 purgeHook - pointer to a Hook structure.

SEE ALSO

AllocLocalItem(), FreeLocalItem(), <utility/hooks.h>
 <libraries/iffparse.h>

1.35 iffparse.library/StopChunk

NAME

StopChunk -- declare a chunk which should cause ParseIFF to return.
 (V36)

SYNOPSIS

```
error = StopChunk(iff, type, id);
D0          A0   D0   D1
```

```
LONG StopChunk(struct IFFHandle *, LONG, LONG);    type;
```

FUNCTION

Installs an entry handler for the specified chunk which will cause the ParseIFF() function to return control to the caller when this chunk is encountered. This is only of value when ParseIFF() is called with the IFFPARSE_SCAN control code.

INPUTS

iff - pointer to IFFHandle structure (need not be open).
 type - type code for chunk to declare (ex. "ILBM").
 id - identifier for chunk to declare (ex. "BODY").

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful.

SEE ALSO

StopChunks(), ParseIFF(), <libraries/iffparse.h>

1.36 iffparse.library/StopChunks

NAME

StopChunks -- declare many stop chunks at once. (V36)

SYNOPSIS

```
error = StopChunks(iff, propArray, numPairs);
D0                A0  A1      D0
```

```
LONG StopChunks(struct IFFHandle *, LONG *, LONG);
```

FUNCTION

(is to StopChunk() as PropChunks() is to PropChunk().)

INPUTS

iff - pointer to IFFHandle structure.
propArray - pointer to array of longword chunk types and identifiers.
numPairs - number of pairs in the array.

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful.

SEE ALSO

StopChunk(), <libraries/iffparse.h>

1.37 iffparse.library/StopOnExit

NAME

StopOnExit -- declare a stop condition for exiting a chunk. (V36)

SYNOPSIS

```
error = StopOnExit(iff, type, id);
D0                A0  D0  D1
```

```
LONG StopOnExit(struct IFFHandle *, LONG, LONG);
```

FUNCTION

Installs an exit handler for the specified chunk which will cause the ParseIFF() function to return control to the caller when this chunk is exhausted. ParseIFF() will return IFFERR_EOC when the declared chunk is about to be popped. This is only of value when ParseIFF() is called with the IFFPARSE_SCAN control code.

INPUTS

iff - pointer to IFFHandle structure (need not be open).
type - type code for chunk to declare (ex. "ILBM").
id - identifier for chunk to declare (ex. "BODY").

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful.

SEE ALSO
ParseIFF(), <libraries/iffparse.h>

1.38 iffparse.library/StoreItemInContext

NAME
StoreItemInContext -- store local context item in given context node.
(V36)

SYNOPSIS
StoreItemInContext(iff, localItem, contextNode);
 A0 A1 A2

VOID StoreItemInContext(struct IFFHandle *, struct LocalContextItem *,
 struct ContextNode *);

FUNCTION
Adds the LocalContextItem to the list of items for the given context node. If an LCI with the same Type, ID, and Ident is already present in the ContextNode, it will be purged and replaced with the new one. This is a raw form of StoreLocalItem().

INPUTS
iff - pointer to IFFHandle structure for this context.
localItem - pointer to a LocalContextItem to be stored.
contextNode - pointer to context node in which to store item.

SEE ALSO
StoreLocalItem(), <libraries/iffparse.h>

1.39 iffparse.library/StoreLocalItem

NAME
StoreLocalItem -- insert a local context item into the context stack.
(V36)

SYNOPSIS
error = StoreLocalItem(iff, localItem, position);
D0 A0 A1 D0

LONG StoreLocalItem(struct IFFHandle *, struct LocalContextItem *,
 LONG);

FUNCTION
Adds the local context item to the list of items for one of the context nodes on the context stack and purges any other item in the same context with the same ident, type and id. The position argument determines where in the stack to add the item:

IFFSLI_ROOT:
 Add item to list at root (default) stack position.

IFFSLI_TOP:

Add item to the top (current) context node.

IFFSLI_PROP:

Add element in top property context. Top property context is either the top FORM chunk, or the top LIST chunk, whichever is closer to the top of the stack.

Items added to the root context, or added to the top context before the IFFHandle has been opened or after it has been closed, are put in the default context. That is, they will be the local items found only after all other context nodes have been searched. Items in the default context are also immune to being purged until the IFFHandle structure itself is deleted with FreeIFF(). This means that handlers installed in the root context will still be there after an IFFHandle structure has been opened and closed. (Note that this implies that items stored in a higher context will be deleted when that context ends.)

INPUTS

iff - pointer to IFFHandle structure.

localItem - pointer to LocalContextItem struct to insert.

position - where to store the item (IFFSLI_ROOT, _TOP or _PROP).

RESULT

error - 0 if successful or an IFFERR_#? error code if unsuccessful.

SEE ALSO

FindLocalItem(), StoreItemInContext(), EntryHandler(), ExitHandler(), <libraries/iffparse.h>

1.40 iffparse.library/WriteChunkBytes

NAME

WriteChunkBytes -- write data from a buffer into the current chunk.
(V36)

SYNOPSIS

```
error = WriteChunkBytes(iff, buf, numBytes);
```

```
D0                A0  A1  D0
```

```
LONG WriteChunkBytes(struct IFFHandle *, APTR, LONG);
```

FUNCTION

Writes "numBytes" bytes from the specified buffer into the current chunk. If the current chunk was pushed with IFFSIZE_UNKNOWN, the size of the chunk gets increased by the size of the buffer written. If the size was specified for this chunk, attempts to write past the end of the chunk will be truncated.

INPUTS

iff - pointer to IFFHandle structure.

buf - pointer to buffer area with bytes to be written.

numBytes - number of bytes to write.

RESULT

error - (positive) number of bytes written if successful or a
(negative) IFFERR_#? error code if unsuccessful.

SEE ALSO

PushChunk(), PopChunk(), WriteChunkRecords(), <libraries/iffparse.h>

1.41 iffparse.library/WriteChunkRecords

NAME

WriteChunkRecords -- write records from a buffer to the current
chunk. (V36)

SYNOPSIS

```
error = WriteChunkRecords(iff, buf, recsize, numrec);  
D0                A0  A1  D0      D1
```

```
LONG WriteChunkRecords(struct IFFHandle *, APTR, LONG, LONG);
```

FUNCTION

Writes record elements from the buffer into the top chunk. This
function operates much like ReadChunkBytes().

INPUTS

iff - pointer to IFFHandle structure.
buf - pointer to buffer area containing data.
recsize - size of data records to write.
numrec - number of data records to write.

RESULT

error - (positive) number of whole records written if successful
or a (negative) IFFERR_#? error code if unsuccessful.

SEE ALSO

WriteChunkBytes(), <libraries/iffparse.h>
