

**String**

**COLLABORATORS**

	<i>TITLE :</i> String		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		January 19, 2025	

**REVISION HISTORY**

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>String</b>	<b>1</b>
1.1	String V1.10 . . . . .	1
1.2	asc . . . . .	1
1.3	findstring . . . . .	1
1.4	val . . . . .	2
1.5	striplead . . . . .	2
1.6	striptrail . . . . .	2
1.7	len . . . . .	2
1.8	mid . . . . .	3
1.9	chr . . . . .	3
1.10	right . . . . .	3
1.11	left . . . . .	3
1.12	str . . . . .	3
1.13	ucase . . . . .	4
1.14	lcase . . . . .	4

---

# Chapter 1

## String

### 1.1 String V1.10

PureBasic - String library V1.10

String is the way to store a list of characters. With the commands supplied in this library, you can perform some essentials actions on the strings

Commands summary:

- Asc
- Chr
- FindString
- LCase
- Left
- Len
- Mid
- Right
- Str
- StripLead
- StripTrail
- UCase
- Val

### 1.2 asc

SYNTAX

```
Ascii = Asc(String$)
```

FUNCTION

Return the ascii value of the first string letter.

### 1.3 findstring

---

## SYNTAX

```
Position = FindString(String$, StringToSearch$, StartPosition.w)
```

## FUNCTION

Try to find the StringToSearch\$ into the given String\$ starting from the given position. If the string is found, so its position is returned (in character, starting from 1). If the string is not found, it returns NULL.

## 1.4 val

## SYNTAX

```
Result.l = Val(String$)
```

## FUNCTION

Transform a string into a numeric value. The string must be an integer in decimal format. ←

Exemple:

```
Result = Val("1024") ; Result will be filled with 1024.
```

## 1.5 striplead

## SYNTAX

```
Result$ = StripLead(String$)
```

## FUNCTION

Remove all the 'space' characters located in front of a string.

## 1.6 striptrail

## SYNTAX

```
Result$ = StripTrail(String$)
```

## FUNCTION

Remove all the 'space' characters located at the end a string.

## 1.7 len

## SYNTAX

```
length = Len(String$)
```

## FUNCTION

Return the character length of the string.

---

## 1.8 mid

### SYNTAX

```
Result$ = Mid(String$, StartPosition, Length)
```

### FUNCTION

Extract a string of the given Length from the given 'String\$'.

## 1.9 chr

### SYNTAX

```
Text$ = Chr(ASCII Value)
```

### FUNCTION

Return the letter associated to the given ASCII value.

## 1.10 right

### SYNTAX

```
Result$ = Righth(String$, Length)
```

### FUNCTION

Return the characters from right of the string with the given length. This function doesn't crash if you give incorrect value for the length parameter, it will return the best matching result.

## 1.11 left

### SYNTAX

```
Result$ = Left(String$, Length)
```

### FUNCTION

Return the characters from left of the string with the given length. This function doesn't crash if you give incorrect value for the length parameter, it will return the best matching result.

## 1.12 str

### SYNTAX

```
Result$ = Str(Value)
```

### FUNCTION

Convert a numeric number into a string.

---

## 1.13 ucase

### SYNTAX

```
Result$ = UCase(String$)
```

### FUNCTION

Return the original string converted in Upper Case characters (if possible). This command also support accent letter, so if an 'é' is found, it will be tranformed into Upper 'É'.

## 1.14 lcase

### SYNTAX

```
Result$ = LCase(String$)
```

### FUNCTION

Return the original string converted in Lower Case characters (if possible). This command also support accent letter, so if an Upper 'É' is found, it will be tranformed into 'é'.