



# Macintosh Quadra 630

## Features

### Power and speed

- 66/33-MHz 68040 microprocessor with 32-bit data bus
- Integrated math coprocessor
- 4MB of RAM, expandable to 36MB

### Display support

- 1MB of video memory supports Apple displays of up to 15 inches
- Works with a wide range of VGA and SVGA monitors

### Expansion

- Can be upgraded to PowerPC
- Comes with built-in ports for hard drives, printers, scanners, and modems
- Supports most processor-direct cards compatible with Macintosh Quadra 605 and Macintosh LC series of computers via an internal expansion slot
- Includes a communications slot for an Ethernet connection or 14.4-baud fax/data modem
- Has video slot for NTSC, PAL, and SECAM video-input card
- Includes expansion bay for television tuner
- External drop box provides expansion for NTSC or PAL video output
- Includes bay for CD-ROM player

### Convenience

- Offers power on and off controls from the keyboard
- Includes an energy-saving feature that reduces power consumption by 50 percent for EPA Energy Star compliance

## Features Built Into Every Macintosh

### Usability

- Runs thousands of Macintosh applications
- Easy to set up, learn, use, and expand

### System software

- System software version 7.1 with multitasking, file sharing, QuickTime, Balloon Help, TrueType fonts, and more

### Networking

- Built-in AppleTalk networking
- File sharing without a dedicated server

### Compatibility

- Reads and writes Macintosh, MS-DOS, OS/2, and ProDOS disks

The Apple Macintosh Quadra 630 computer is the most advanced CD-ROM-capable Apple multimedia system. And it's upgradeable to take advantage of PowerPC technology, so it can bring you multimedia opportunities for years to come.

Its advanced multimedia expansion options offer new ways to interact with information. You can connect to an external video source such as a VCR or camcorder to cut and paste video images. You can also add an option to connect your computer to a large-screen TV for displaying presentations. And you can add an internal TV tuner to view television channels in a window on your display.

As your needs grow, you can expand the Macintosh Quadra 630 to up to 36 megabytes of RAM.

Multiple ports allow you to connect it to peripherals such as external

disk drives or scanners. And a flexible communications slot makes it easy to add a modem or an Ethernet networking card.

Like all Macintosh computers, it's very easy to learn about and use, and it runs thousands of Macintosh programs, allowing you to work with leading business, multimedia, and education applications as well as interactive CD-ROM titles.

The affordable Macintosh Quadra 630 includes many standard features that are expensive add-ons for other computers. These include 16-bit CD stereo sound, support for Apple and third-party displays, and AppleTalk networking for access to printers, electronic mail, and file sharing.

The Macintosh Quadra 630, with its optional CD-ROM player, adds up to an expandable, advanced multimedia Macintosh system—while its price adds up to less than \$1,700.





# Macintosh Quadra 630

## Ordering Information

### Macintosh Quadra 630 4/250

Order No. M3491LL/A

- Macintosh Quadra 630 personal computer with 4MB of RAM, 1MB of video memory, a built-in 1.4MB Apple SuperDrive, floppy disk drive, and an internal 250MB hard disk drive
- Mouse
- Complete setup, learning, and reference documentation
- System software version 7.1
- Limited warranty

### Apple Video System

Order No. M2894LL/A

### Apple Video/TV System

Order No. M2896LL/A

### Apple Presentation System

Order No. M2895LL/A

### Macintosh 10BaseT Ethernet Port Kit

Order No. M3065LL/A

### Macintosh 10Base2 Ethernet Port Kit

Order No. M2708LL/A

### Macintosh AAUI Ethernet Port Kit

Order No. M3066LL/A

### Macintosh 14.4 Fax/Modem Kit

Order No. M2480LL/A

Product specifications are subject to change. Check with your authorized Apple reseller for the most current information about product specifications and configurations.

## Technical Specifications

### Microprocessor

- 66/33-MHz Motorola 68040 with 32-bit data bus (66-MHz processor/33-MHz data bus)
- Integrated math coprocessor, Page Memory Management Unit (PMMU), and 8K cache

### Memory

- 4MB of RAM, expandable to 36MB using one 72-pin SIMM (dealer installation recommended)

### Disk storage

- One built-in 1.4MB Apple SuperDrive floppy disk drive that uses high-density floppy disks and reads, writes, and formats Macintosh, MS-DOS, OS/2, and ProDOS disks
- One internal 250MB hard disk
- Internal bay for CD-ROM player

### Displays

- Supports Apple displays of up to 15 inches
- Works with a wide range of third-party VGA and SVGA displays

### Display support

- 1MB DRAM display support, independent from system DRAM

### Color depth support

- Standard 16-bit color for display of up to 32,768 colors on monitors of up to 14 inches and on 15-inch monitors at 640- by 480-pixel resolution
- Standard 8-bit color for display of 256 colors on 15-inch monitors at 800- by 600-pixel resolution

### Interfaces

- One Apple Desktop Bus (ADB) port supports a keyboard, mouse, and other devices
- Two (RS-232/RS-422) serial ports
- SCSI interface port for connecting up to six external peripheral devices (five in configurations with internal CD-ROM player)
- Internal expansion slot compatible with most Macintosh Quadra 605, Macintosh LC II, LC III, LC 475, LC 520, LC 575, and Macintosh Performa processor-direct cards
- Communications slot for either Ethernet card or 14.4-baud fax/modem card
- Video slot for NTSC, PAL, and SECAM video-input card
- Dedicated connector for internal TV tuner
- One standard monitor port also supports connection to external video-out (NTSC or PAL) drop box

### Networking

- Serial port for AppleTalk

### Sound

- Stereo 8-bit sound capable of driving stereo headphones or other stereo equipment through the sound jack
- Stereo 16-bit CD playback
- One sound-in port
- Front and rear headphone jacks

### Keyboard and mouse

- Compatible with all Apple keyboards
- Apple Desktop Bus Mouse II

### Clock/calendar

- Custom integrated circuit with long-life battery

### Disability access

- Close View, Easy Access, and the ability to substitute visual cue for beep included with system software. These built-in solutions and third-party options provide alternative input and output devices for people with disabilities.

### Electrical requirements

- Line voltage: 100 to 240 volts AC, RMS, single phase, nominal
- Frequency: 50 to 60 Hz
- Power: 45 W maximum, not including monitor

### ADB power requirements

- Maximum current draw for all ADB devices: 500 mA (a maximum of three ADB devices is recommended)
- Mouse draws 10 mA
- Keyboard draws 25 to 80 mA (varies with keyboard model used)

### Size and weight

- Height: 4.3 in. (10.95 cm)
- Width: 12.6 in. (32 cm)
- Depth: 16.5 in. (41.95 cm)
- Weight: 19 lb. (8.6 kg) with CD-ROM player (varies based on internal devices installed)

### Operating environment

- Operating temperature: 50° to 104° F (10° to 40° C)
- Storage temperature: -40° to 116.6° F (-40° to 47° C)
- Relative humidity: 5% to 95% noncondensing
- Maximum altitude: 10,000 ft. (3,048 m)

## Apple Computer, Inc.

1 Infinite Loop  
Cupertino, CA 95014  
(408) 996-1010  
TLX 171-576

© 1994 Apple Computer, Inc. All rights reserved. Apple, the Apple logo, AppleTalk, Macintosh, Macintosh Quadra, Performa, and ProDOS are trademarks of Apple Computer, Inc., registered in the U.S.A. and other countries. AppleCD, Apple Desktop Bus, Apple SuperDrive, Balloon Help, Power Macintosh, QuickTime, and TrueType are trademarks of Apple Computer, Inc. OS/2 is a trademark of International Business Machines Corporation. PowerPC is a trademark of International Business Machines Corporation, used under license therefrom. MS-DOS is a registered trademark of Microsoft Corporation. Mention of non-Apple products is for informational purposes and constitutes neither an endorsement nor a recommendation. Apple assumes no responsibility with regard to the selection, performance, or use of these products. All understandings, agreements, or warranties, if any, take place directly between the vendors and the prospective users.

June 1994. Product specifications are subject to change without notice. Printed in the United States of America.  
L00727A