

Figures, Tables, and Listings

Chapter 2

Messaging Service Access Modules 2-1

Figure 2-1	Adding an MSAM	2-7	
Figure 2-2	An MSAM's relationship to AOCE software	2-8	
Figure 2-3	Communication between the IPM Manager and an MSAM	2-8	2-8
Figure 2-4	Personal MSAM with its slots and queues	2-10	
Table 2-1	Differences between personal MSAMs and server MSAMs	2-11	2-11
Figure 2-5	Store-and-forward gateway model	2-13	
Figure 2-6	Online model	2-13	
Table 2-2	MSAM operating modes	2-16	
Table 2-3	Predefined letter block types	2-18	
Figure 2-7	Nested letters	2-20	
Figure 2-8	How the nesting level increments	2-21	
Figure 2-9	Structure of a letter	2-22	
Figure 2-10	AOCE system connected to external messaging systems	2-24	2-24
Figure 2-11	Adding a dNode for a messaging system	2-26	
Figure 2-12	MSAMs, messaging system names, and extension types	2-27	2-27
Figure 2-13	Exploded view of an <code>OCERecipient</code> structure	2-28	
Table 2-4	External address: Contents of an <code>OCERecipient</code> structure	2-29	
Table 2-5	AOCE address: Contents of an <code>OCERecipient</code> structure	2-30	2-30
Table 2-6	AOCE extension types	2-31	
Table 2-7	Sample addresses	2-32	
Table 2-8	Selected Catalog record attributes	2-40	
Table 2-9	Outgoing tasks and functions	2-44	
Listing 2-1	Enumerating outgoing messages	2-45	
Listing 2-2	Reading letter attributes	2-48	
Listing 2-3	Getting resolved and original recipients	2-53	
Listing 2-4	Reading addresses from an outgoing message	2-55	2-55
Listing 2-5	Reading a letter's content block	2-58	
Table 2-10	Incoming tasks and functions	2-63	
Listing 2-6	Creating a message summary	2-67	
Listing 2-7	Creating a letter	2-70	
Listing 2-8	Adding attributes to a letter header	2-72	
Listing 2-9	Adding recipients to a letter	2-74	
Listing 2-10	Adding a specific type of recipient	2-75	
Listing 2-11	Writing letter content	2-78	
Listing 2-12	Submitting a letter	2-80	
Listing 2-13	Building SMTP addresses	2-84	
Listing 2-14	Converting from AOCE to SMTP address	2-87	
Listing 2-15	Building an <code>OCERecipient</code> structure	2-90	
Listing 2-16	Calling an MSAM function from assembly language	2-130	2-130

Figure 3-1	Relationship of an application, the Catalog Manager, and a CSAM	3-4
Figure 3-2	Calling relationships	3-6
Figure 3-3	Who calls the CSAM driver subroutines and the catalog service and parse functions	3-7
Listing 3-1	A sample CSAM's driver resource header	3-8
Listing 3-2	A CSAM's driver name string resource	3-9
Figure 3-4	Relationship of 'DRVR' and 'STR' resources	3-10
Listing 3-3	A catalog service function	3-13
Listing 3-4	Calling an application's callback routine	3-15
Listing 3-5	Setting the feature flags for a catalog	3-21
Table 3-1	Determining the scrolling method for a catalog	3-26
Listing 3-6	Calling an application's completion routine	3-28
Listing 3-7	'DRVR' resource definition	3-40

Listing 4-1	Combined catalog and mail service setup template	4-6
Listing 4-2	Matching an MSAM file ID	4-12
Listing 4-3	Inserting a record reference into a record	4-21
Listing 4-4	Mail service setup template	4-23
Figure 4-1	Catalog-choice dialog box	4-26
Figure 4-2	Alternate forms of a single address information page	4-31
Listing 4-5	Address template	4-31
Listing 4-6	Main routines of the address template code resource	4-41
Listing 4-7	Input subroutines for the address template code resource	4-48
Listing 4-8	Output subroutines for the address template code resource	4-52
Listing 4-9	Miscellaneous subroutines used by the address template code resource	4-57
Table 4-1	Setup-catalog record types	4-64
Table 4-2	Attributes of an MSAM record	4-65
Table 4-3	Attributes of a CSAM record	4-66
Table 4-4	Attributes of a Mail Service record	4-67
Table 4-5	Attributes of a Catalog record	4-68
Table 4-6	Attributes of a Combined record	4-70
Table 4-7	Required resources for setup aspect templates	4-73