


### Mode Pins During Standby Operation

H8/300 devices operate in one of four modes as shown below:

MD1	MD0	MODE
Low	Low	Programming
Low	High	Mode 1
High	Low	Mode 2
High	High	Mode 3

To ensure normal operation according to specification one or both of the MD0/1 inputs must be maintained at V<sub>cc</sub> or above 2.2 V during standby mode. Boards designed for low power operation should not use system V<sub>cc</sub> to control this input. Instead the input should be controlled by the V<sub>cc</sub> supply and battery back-up to the H8/300 V<sub>cc</sub> input as shown below. This configuration guarantees MD0/1 will be maintained at the correct level when system V<sub>cc</sub> is lost. If the mode pins are not held at the correct levels, I<sub>cc</sub> will be erratic and higher than specified.



The information in this document has been carefully checked; however, the contents of this document may be changed and modified without notice. Hitachi America, Ltd. shall assume no responsibility for inaccuracies, or any problem involving a patent infringement caused when applying the descriptions in this document. This material is protected by copyright laws. Hitachi America, Ltd. reserves all rights.

written by: Carol Jacobson, Application Engineering

Hitachi America, Ltd. Semiconductor and I.C. Division  
2000 Sierra Point Parkway, Brisbane, CA 94005-1819 (415)589-8300