Replace…

Choosing the Replace... command from the Utility menu allows you to replace a given search string with a replacement string within the current document, or globally over all documents contained within the editor.

If you create a text selection before choosing the Replace… command, it will be used as the search string.

Options
All Occurrences
When checked, all occurrences of the search text will be replaced with the replacement text. If left unchecked, only the first occurrence in the document will be replaced.

All Documents
When checked, all occurrences of the search text will be replaced with the replacement text. If left unchecked, only the first occurrence in the document will be replaced. If you want to perform a global replacement (all occurrences in all documents), be sure to check All Occurrences checkbox as well, or only the first instance of the search text found within all documents will be replaced. Note that global changes of this type cannot be undone. See the Undo HTML command for more information.

MiniGREP
When checked, several GREP-like codes will be interpreted as ASCII codes according to the table below. When unchecked, the codes will be treated as normal text. To use miniGREP codes, type the codes as show in the table below directly into either the Search for: or Replace With: text areas and check the miniGREP checkbox before performing the replacement.

MiniGREP Table

Code	Replacement	ASCII#	
\l	linefeed	10	
\n	return+linefeed	10+13	
\r	return	10	
\s	space	32	
\t	tab	09	
\(10)	any ASCII char	(n)	(not implemented)
\U	convert to UPPERCASE		(not implemented)
\L	convert to LOWERCASE		(not implemented)

Back to Utility menu, on to HyperText menu, or return to Contents.