

mmu

COLLABORATORS

	TITLE : mmu		
ACTION	NAME	DATE	SIGNATURE
WRITTEN BY		August 16, 2024	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	mmu	1
1.1	mmu.doc	1
1.2	mmu.library/--Background--	2
1.3	mmu.library/--Patches--	3
1.4	mmu.library/CreateMMUContext	5
1.5	mmu.library/DeleteMMUContext	12
1.6	mmu.library/EnterMMUContext	13
1.7	mmu.library/LeaveMMUContext	13
1.8	mmu.library/CurrentContext	14
1.9	mmu.library/AddContextHook	15
1.10	mmu.library/RemContextHook	17
1.11	mmu.library/AddMessageHook	17
1.12	mmu.library/RemMessageHook	19
1.13	mmu.library/ActivateException	20
1.14	mmu.library/DeactivateException	20
1.15	mmu.library/GetPageSize	21
1.16	mmu.library/RemapSize	22
1.17	mmu.library/SetProperties	23
1.18	mmu.library/SetPageProperties	29
1.19	mmu.library/RebuildTree	31
1.20	mmu.library/RebuildTrees	32
1.21	mmu.library/GetProperties	33
1.22	mmu.library/GetPageProperties	35
1.23	mmu.library/AllocAligned	36
1.24	mmu.library/LockMMUContext	37
1.25	mmu.library/UnlockMMUContext	38
1.26	mmu.library/AttemptLockMMUContext	39
1.27	mmu.library/LockContextList	39
1.28	mmu.library/UnlockContextList	40
1.29	mmu.library/AttemptLockContextList	41

1.30	mmu.library/AllocLineVec	42
1.31	mmu.library/PhysicalPageLocation	43
1.32	mmu.library/PhysicalLocation	43
1.33	mmu.library/DMAInitiate	44
1.34	mmu.library/DMATerminate	46
1.35	mmu.library/GetMapping	47
1.36	mmu.library/ReleaseMapping	48
1.37	mmu.library/NewMapping	48
1.38	mmu.library/CopyMapping	49
1.39	mmu.library/DupMapping	50
1.40	mmu.library/CopyContextRegion	51
1.41	mmu.library/SetPropertiesMapping	52
1.42	mmu.library/SetMappingProperties	53
1.43	mmu.library/GetMappingProperties	54
1.44	mmu.library/SetPropertyList	55
1.45	mmu.library/GetMMUType	56
1.46	mmu.library/SuperContext	56
1.47	mmu.library/DefaultContext	57
1.48	mmu.library/WithoutMMU	58
1.49	mmu.library/RunOldConfig	58
1.50	mmu.library/SetBusError	59
1.51	mmu.library/GetMMUContextData	60
1.52	mmu.library/SetMMUContextData	61
1.53	mmu.library/BuildIndirect	62
1.54	mmu.library/SetIndirect	65
1.55	mmu.library/SetIndirectArray	66
1.56	mmu.library/GetIndirect	68

Chapter 1

mmu

1.1 mmu.doc

```
--Background--
--Patches-- ()
ActivateException ()
AddContextHook ()
AddMessageHook ()
AllocAligned ()
AllocLineVec ()
AttemptLockContextList ()
AttemptLockMMUContext ()
BuildIndirect ()
CopyContextRegion ()
CopyMapping ()
CreateMMUContext ()
CurrentContext ()
DeactivateException ()
DefaultContext ()
DeleteMMUContext ()
DMAInitiate ()
DMATerminate ()
DupMapping ()
EnterMMUContext ()
GetIndirect ()
GetMapping ()
GetMappingProperties ()
GetMMUContextData ()
GetMMUType ()
GetPageProperties ()
GetPageSize ()
GetProperties ()
LeaveMMUContext ()
LockContextList ()
LockMMUContext ()
NewMapping ()
PhysicalLocation ()
PhysicalPageLocation ()
RebuildTree ()
RebuildTrees ()
ReleaseMapping ()
```

```
RemapSize()
RemContextHook()
RemMessageHook()
RunOldConfig()
SetBusError()
SetIndirect()
SetIndirectArray()
SetMappingProperties()
SetMMUContextData()
SetPageProperties()
SetProperties()
SetPropertiesMapping()
SetPropertyList()
SuperContext()
UnlockContextList()
UnlockMMUContext()
WithoutMMU()
```

1.2 mmu.library/--Background--

PURPOSE

The mmu.library provides functions for MMU related operations as write- or read-protecting certain areas of memory for a given set of tasks, or marking memory regions as "swapped" virtual memory support. It offers an abstraction level on top of the actual MMU and a unified interface for MMU purposes.

The MMU lib does NOT implement virtual memory, that's the purpose of another library - the memory.library. There's no much reason why any application except the memory.library and probably some debugging tools should call this library directly. The memory.library functions on top of this library should suffer for "all day purposes".

The basic object administrated by this library is the "context". A "context" is the software abstraction of a MMU translation tree, it keeps the information of the status of memory. The mmu.library provides a "global" context that represents the MMU translation tree for all tasks. It is build by the init code of the library either by snooping the already existing MMU translation tree or by building an own tree by looking at the available memory and expansion devices.

Programs can build own contexts by using the MMU library functions and may enter or leave the contexts generated in this way. Several tasks may share one context, as they represent, for example, multiple "threads" of one single program. Thus, the notation used here is somehow turned around: A "context" in the amiga world is called "process" in unix, and a "task" or "process" in the amiga world is called a "thread" usually.

Tasks that do not enter an own context explicitly share the common global context. Even though it is possible to change the global context, this technique should be used only by debugging tools as the enforcer. It could, for example, mark unused areas of the memory as well as the first 4K as "invalid".

The MMU library provides two "hooks" for each context, the "bus error hook" and the "segmentation fault" hook. The first hook is called if an access to an invalid memory location is detected, or a write to a read-only memory area. The second is called if an access to a memory page marked as "swapped out" is detected. It's part of the service of the MMU library to keep these two access violations apart.

The default hooks call simply the exception handler of the running task, which generates by default the well known "guru". It's up to programs on top of the MMU library to setup useful hooks. An enforcer like tool might set "bus error hook" to print some useful information about the access violation, the memory.library will set the "segmentation fault" hook to swap in the memory in question.

The hooks are really "low-level" routines and are executed in supervisor mode, and therefore very limited in power.

The library provides itself a ready-for-use hook function which sends a message to a task to be specified and suspends the task that caused the bus error until the message is replied.

MMU trees are managed on two levels, a "software abstraction level" which is comfortable and easy to use. Memory "properties" of large regions of memory can be redefined quite easily with one single call, but rebuilding the MMU table tree from this abstraction layer is a lengthy operation and requires quite a lot of CPU power not available in critical applications.

Therefore, a more "hardware based" approach is available which modifies the existing MMU table "on the fly" and is therefore rather fast. However, memory pages to be handled like this must be marked with the MAPP_SINGLE property to tell the library to build the MMU table in a special way to allow fast modification and to bypass some possible optimizations (e.g. "early page terminators" and "invalid descriptors not at page level"). Modifications on this level are never seen by the abstraction level above and should be used only once the MMU tree is complete.

If that is, too, not fast enough, the MMU library allows building pages using "indirect descriptors". That is, the page property flags are given by a true hardware descriptor you provide. This makes code CPU specific, obviously, but has the advantage that page properties can be modified by a single long word "poke" in your program, and the proper ATC flush. This is almost "hardware banging", with some support.

This method has one important drawback, namely that the library is no longer able to disable caching for DMA transfer to and from this page. Hence, NEVER EVER access an indirect page by DMA.

1.3 mmu.library/--Patches--

To perform its job, the mmu.library has to install a number of system patches. I tried avoid this as best as possible, but some installations have to be done.

The following patches are installed:

`exec/CacheControl:` Replaced partially by a function that guarantees that the data cache remains off when the `mmu.library` builds descriptors.

`exec/ColdReboot:` Replaced partially by a function that removes the `mmu.library` installed MMU trees. This is done to restart the processor with a clean MMU setup.

`exec/Alert:` Replaced partially. The `Alert()` replacement routine will check whether the alert caused is fatal or not, and will `Disable()` and unload the `mmu.library` installed MMU tree if this is the case. Since a deadend alert will go over into a reset without calling `ColdReboot()`, this must be done here separately to ensure that the machine restarts properly.

`exec/AddMem:` Adding memory with a MMU setup active would or would not mean that the MMU table must be adjusted to reflect the changes. This function should not be called once the system is setup and running.

V42 and up implementations adds the memory to the system and, additionally, modifies the MMU tree of the public user and supervisor contexts to make this memory visible and available. Caching modes are set accordingly: `Imprecise` for `MEMF_CHIP`, `Copyback` for all others.

I'm not quite positive that this is the best way how to handle `AddMem()`, though. This function shouldn't be called after bootstrap anyhow.

`exec/AddConfigDev:` Called to make new hardware known to the system. This function shouldn't be called by user code after bootstrap anyhow.

The `>=V42` implementation modifies the public user and supervisor contexts to make the added hardware visible, provided it is not memory. In the former case, the address range is set to `cacheinhibited`. In the latter, nothing is done as `AddMem()` should be called instead.

After MMU modifications, either the old expansion library function is called, or an internal replacement routine is made use of if expansion has been patched over. This is necessary, unfortunately, since some third-party libraries hack here the MMU tree, which is undesirable.

`exec/CachePreDMA:` Replaced completely by a MMU library routine that disables copyback mode for non-aligned pages and

translates the logical address passed in to the physical address, by means of the mmu.library public context.

exec/CachePostDMA: Ditto. Replaced completely by the MMU.library.

1.4 mmu.library/CreateMMUContext

NAME

CreateMMUContext - Build a new MMU context.

SYNOPSIS

```
context = CreateMMUContextA ( tags );
d0      a0
```

```
context = CreateMMUContext ( tag1, ... );
```

```
struct MMUContext * CreateMMUContextA ( struct TagItem *);
```

```
struct MMUContext * CreateMMUContext ( Tag tag1, ... );
```

FUNCTION

This function builds a new MMU context.

INPUTS

tags - Tag items for the context to be created.

Currently defined tags are:

MCXTAG_COPY - build a copy of the context * passed in, if the pointer is NULL, build a copy of the global default context.

If this tag item is not given, all context addresses will be marked as MAPP_BLANK. Most likely not what you want.

If you specify a different page size than that of the context you want to clone, you should specify the MCXTAG_ERRORCODE as well and study the return code carefully. The mmu library might have performed some rounding to fit the old table specifications into the new table layout. In worst case, this will make your new table unusable. It is therefore in general not a good idea to specify a page size larger than that of the cloned context. Even though the library itself allocates all its internal structures aligned to "worst case" page sizes, this might not be true for external user programs.

MCXTAG_SHARE - (V43 and up)
Share parts of the context * passed in, or the global user context if this pointer is NULL.
(RECOMMENDED!)

The difference between this tag and the previous is that changes of the shared = "parent" context are handed thru to this "child" context automatically, whereas a context created by MCXTAG_COPY detaches from its parent.

MCXTAG_SHARE implies several restrictions, though. Sharing contexts *must* use the same table layout as the parent context, especially must use the same page size. They must use the global supervisor context, and therefore cannot allocate a private supervisor context.

If this tag item is given, all of the context will be initialized as MAPP_SHARED, i.e. the child uses the same MMU setup as the parent.

MCXTAG_EXECBASE - allow accesses of AbsExecBase and all accesses to valid memory in the first page, even if this page in the MMU tree - the "zeropage" - is marked as invalid. This is an important feature if the mmu.library is used to implement an Enforcer type program.
Accesses will be emulated in software and are hence *slow*. They should be avoided, either by running Os 3.0 or better, or by using a tool like "MuMove4k".

AbsExecBase accesses are handled with highest priority and might be faster than the rest of the emulation, even faster than the Enforcer, even though they're still slower than "the real thing". It is not guaranteed that the library will really read AbsExecBase from location four, dependent on some internals, it might give you a cached copy instead. This means usually no problem since AbsExecBase must not change while the machine is up and running.

This option defaults to TRUE.

For more quirks about the zeropage, read the MCXTAG_ZEROBASE tag documentation below.

MCXTAG_BLANKFILL - defines a ULONG word fill value for blank memory regions.

This ULONG is read by the CPU in case a program tries an access to "empty" memory regions. It defaults to 0L, but other values might be useful for debugging.

MCXTAG_MEMORYATTRS- An exec memory attributes specifier to be used for allocating memory for the (hardware) MMU tables. Defaults to MEMF_PUBLIC, check exec/memory.h for other possibilities.

MCXTAG_PRIVATESUPER A boolean value, either TRUE or FALSE. If TRUE, build a private MMU supervisor table for this context, independent of the default supervisor Context. BE WARNED! This means specifically that possible modifications of the default supervisor context will not be carried over to your private supervisor table.

Even if you pass in FALSE here, the library might still ignore your choice and build a private supervisor table anyways. This happens if the table layout you've chosen is different to the default table layout, making the user tree incompatible to the default supervisor tree.

Not available for sharing contexts, i.e. if MCXTAG_SHARE has been specified.

MCXTAG_ZEROBASE - This option takes only effect if MCXTAG_EXECBASE is TRUE and the first page of the MMU table is invalid. This means that the MMU library will emulate accesses to valid memory in the first page which remains unavailable to implement an "Enforcer" function. This tag provides a base address to be used by the emulation as physical base address.

This tag defaults to NULL meaning that the library will redirect accesses to the true zeropage, making it available temporarily, but any other memory location - provided it is page aligned - can be specified here as well. This is important if the zero page gets remapped to a different location, and an Enforcer type program is run later on. The zero page remapper should specify this tag to redirect accesses transparently, even if an Enforcer type application invalidates the zero page. Failing to do so would make the MMU library emulating the access to the incorrect, non-remapped memory location. Since other programs might want to build a private MMU table with a different table size, it is *NOT* enough to align the remap destination of the zeropage to GetPageSize() boundaries, RemapSize() alignment is required! THIS IS AN ADVANCED FEATURE.

MCXTAG_DISCACHEDES A boolean tag item. If set to TRUE, the memory that keeps the descriptors is cache-inhibited. This works around some problems that appear if a program attempts to hack on the MMU itself. The mmu.library code has no problems with descriptors in non-cacheable memory. Note, however, that the memory will be only non-cacheable "as seen" from

the context itself. It will **NOT** change the cache mode as seen from other contexts, even from the supervisor Context of the given Context.

HACKING THE MMU TABLES IS ILLEGAL

MCXTAG_LOWMEMORYLIMIT Define a boundary in the zero page such that accesses to addresses higher than this boundary will be emulated in software. This is mainly for 68060/68040 support under Os V37 and V38 where chip memory started at 0x400 inside the zero page. (NEW for V42)
The MuLib checks the chip memory base address on startup and provides a useful default.

MCXTAG_SHAREABLE (V43 and up)
A boolean TRUE/FALSE indicator, default is FALSE. If set to TRUE, this context is shareable and allows child contexts to share parts of the table layout of this context by specifying this context as argument to MCXTAG_SHARE.

This implies various restrictions for the context, though. First of all, you must use the global supervisor context as your supervisor context, and hence must use the same table layout than the default user context. Second, special care must be taken when shutting down the context with DeleteMMUContext() as this call may now fail, simply because some child contexts are still attached to your context. The next two tags offer a mechanism to control this shutdown.

MCXTAG_SHUTDOWNTASK (V43 and up)
Takes a pointer to a "struct Task" as argument. If non-NULL, then the mmu.library will send a signal mask, specified by the next tag, to this task as soon as the last task leaves this context by means of LeaveMMUContext(), or as soon as the last child context of this context gets deleted by DeleteMMUContext(). Hence, if this signal arrives, you may try (again) to call DeleteMMUContext(). Note that even then this call may fail.

MCXTAG_SHUTDOWNMASK (V43 and up)
Takes a ULONG as argument that defines a signal mask (not a signal bit!) that will be sent to the task specified above, as soon as the last child detaches from this context.

The next tag items define the MMU table layout. A logical address, used as input for the MMU, consists of exactly 32 bits. These bits are now split from the left to the right into groups to define a "path" in the MMU tree. Each "level" of the MMU tree should be considered as an array of pointers, pointing to the next lower level of the tree. The nodes of the tree are contain the descriptors that define how the address belonging to the path from the root to

this descriptor should be handled. For example, consider a three-level tree with 7 bits for level A and B, 6 bits for level C and 12 bits for the page. The address 0x01feabcd would be used like this to find an descriptor:

hex 0x01feabcd is binary

```

-----7--- -----7----- ---6--- -----12----- bits
0000 000|1 1111 11|10 1010| 1011 1100 1101
\_____/ \_____/ \_____/ \_____/
  | | |   |
  | | |   |
  V | |   |

```

Index into level A of the MMU tree is 0, hence the first pointer is read. The MMU obtains now another array of pointers, called the level B. | |

```

| | |
V | |

```

Index into level B of the MMU tree is 127. The MMU uses the last pointer from the table obtained in the previous step. | |

```

| |
V |

```

Index into level C of the MMU tree is 42. The MMU uses, hence, the 42nd pointer of the array pointed to by the 127th pointer of the level B array. This is now the "page descriptor", defining the base address for the next step.

```

|
|
V

```

This is now finally the page offset, 0xbcd in this example. It is added to the base address from the page descriptor in level C. If the address is not "remapped", the base address would be identically to the first 32-12 = 20 bits of the physically address.

Note that you cannot use all of the following tags if you share parts of a parent context by MCXTAG_SHARE. The table layout of the child must then be identical to that of the parent.

MCXTAG_DEPTH - Depth of the MMU tree to build. Defaults to the depth of the global public context.

Legal values are 1..4 for the 68020/68851 and the 68030, but the 68040/68060 supports only trees of depth 3.

MCXTAG_LEVELABITS - Number of bits of the logical address that make up the level A of the MMU tree. 2^bits is the number of entries on this level of the tree.

The 68020/68851 and the 68030 support here values from 1..15, the only legal value for the 68040 and 68060 is 7.

The MMU library will pick a reasonable and

system dependent default for you if you don't specify this tag item.

MCXTAG_LEVELBBITS - Number of bits for the level B of the MMU tree, unused if the depth is smaller than two.

Legal values are 1..15 for the 851 and 030, and 7 as only possible value for the 040 and 060.

MCXTAG_LEVELCBITS - Number of bits of the level C of the MMU tree, unused if the depth is smaller than three.

Arguments may range from 1..15 for the 851 and 030, and must be either 5 or 6 for the 040 and 060.

MCXTAG_LEVELDBITS - Number of bits in the level D of the MMU tree, only used if the depth is four and therefore unused on the 040 and 060.

Must range from 1..15.

MCXTAG_PAGEBITS - Number of bits to be used from the logical address as the page offset. 2^{bits} is the page size.

Legal values are 8..15, giving 256 bytes up to 32K pages for the 68020/68851 and 68030, or 12..13 defining 4K resp. 8K pages for the 68040 and 68060.

The default is the page size of the global context.

All the "...BITS specifications MUST sum up to 32 since a logical address consists of exactly 32 bits. You may leave out some or all of these tags, the MMU library will keep care of the rest and will chose reasonable defaults for you.

MCXTAG_ERRORCODE - pointer to a ULONG the MMU library will fill in with an error code in case building the MMU tree failed. It will be set to 0L if the function succeeds. The following error codes have been defined:

CCERR_NO_FREE_STORE - the library went out of memory.
 CCERR_INVALID_PARAMETERS - the parameters specified by the tags are invalid.
 CCERR_UNSUPPORTED - the parameters are valid, but not supported by the hardware.
 CCERR_TRIMMED - the library performed some minor adjustments on the MMU table passed in for cloning. The cache modes might not be optimal due to some roudings that have to be performed, but the MMU table should work in

general.

THIS IS NOT AN ERROR, you will get your new context.

CCERR_UNALIGNED - the library had to perform heavy rounding in the MMU table passed in, it might be unusable. For example, remapped pages were misaligned and due to the rounding accesses might go to wrong locations. If you get this return code, you should possibly deallocate the new context and inform the user that the request could not be satisfied.

Still, THIS IS NOT AN ERROR. You get a new context, but possibly an unusable one.

CCERR_SHARENCOPY (V43 and up)
MCXTAG_SHARE and MCXTAG_COPY were found both on the tag list, this is illegal.

CCERR_NOTSHAREABLE (V43 and up)
The parent context you specified with MCXTAG_SHARE does not support page sharing and is therefore not shareable. The global user context is always shareable for V43 and up.

CCERR_SHAREOVERLEVELS (V43 and up)
You specified MCXTAG_SHARE and MCXTAG_SHAREABLE simultaneously and hence tried to build a context that shares a parent and can be shared as well. The current library release does not support sharing over levels, though.

CCERR_NOPRIVSUPER (V43 and up)
You tried to build a context with MCXTAG_SHARE that uses page sharing but that requires a private supervisor MMU tree. This is currently unsupported.

RETURNS

NULL if the new context couldn't be created or a handle to the new context, as parameter to all MMU library functions.

NOTES

This call makes NOT the current task entering the new context, you've to call EnterMMUContext() explicitly for that purpose.

The context structure is not documented intentionally. It depends on the implementation.

BUGS

SEE ALSO

DeleteMMUContext(), mmu/mmutags.h, mmu/context.h

BUGS

1.5 mmu.library/DeleteMMUContext

NAME

DeleteMMUContext - delete an MMU context build with CreateMMUContext.

SYNOPSIS

```
DeleteMMUContext ( context );  
                a0
```

```
BOOL DeleteMMUContext ( struct MMUContext * );
```

FUNCTION

This function deletes a context build with CreateMMUContext().

INPUTS

A handle to the context to be deleted.

RETURNS

For V43: a boolean success/failure indicator. Old code need not to check this, but note that the prototypes always specified a boolean success indicator. In fact, this indicator was delivered correctly for all releases of the mmu.library, even for V40. Hence, you need no version check here to evaluate the result code safely.

NOTES

This call doesn't remove any task from the context, especially the current task is NOT removed from the context. You've to call LeaveMMUContext() before.

(V43) In case some tasks are still attached to this context, DeleteMMUContext() will fail. Similary, it will fail if some child contexts still share this context. V42 and below will have crashed here.

If your context was created with a private supervisor context included, you must call this function only **once**, with the user context created. It will automatically deallocate the attached supervisor context as well.

BUGS

SEE ALSO

CreateMMUContext(), mmu/context.h

1.6 mmu.library/EnterMMUContext

NAME

EnterMMUContext - let a task enter a specific context.

SYNOPSIS

```
context = EnterMMUContext( context , task );  
d0          a0          a1
```

```
struct MMUContext * EnterMMUContext( struct MMUContext * ,  
                                     struct Task * );
```

FUNCTION

Add a given task to a context. This makes the MMU settings defined by the context available for the task in question.

INPUTS

context - the context to enter or NULL for the global context.
task - a pointer to the task structure that should enter the context.

RETURNS

a handle to the context the task participated before or NULL if this function failed. The task will stay in the last context used in this case.

NOTES

This call uses the tc_Switch() and tc_Launch() functions of the task structure. What basically happens here is that these functions are set to internal procedures that swap the context specific MMU table or the global MMU in and flush the ATC of the MMU.

This call may fail, check the return code for NULL - either due to lack of memory or because the task is part of a protected context the current task hasn't entered.

If you want to use the tc_Switch() and tc_Launch() functions yourself, you should install a task specific context hook, see AddContextHook().

This function can be used to change the context of a task by adding it to a new context. The task specific context switch and launch hooks will be "carried over" to the new context, but all other MMU specific exceptions are now the matter of the new context.

BUGS

SEE ALSO

LeaveMMUContext(), exec/tasks.h

1.7 mmu.library/LeaveMMUContext

NAME

LeaveMMUContext - remove a given task from a context.

SYNOPSIS

```
context = LeaveMMUContext( task );
d0      a1
```

```
struct MMUContext * LeaveMMUContext( struct Task * );
```

FUNCTION

The specified task leaves its context and enters the global context.

INPUTS

task - the task that should leave a private context and enter the global default context.

RETURNS

the context the task was added to or NULL on failure.
Might be the global default context if the task did not enter any context.

NOTES

It is safe to call this function even if the task wasn't added to any context. The function returns the global context in this case.

This function must be called to any task participating a given context to be able to delete that context.

This function is equivalent to `EnterMMUContext(NULL,task)`.

This function makes use of the `tc_Switch()` and `tc_Launch()` functions of the task structure to be able to set the MMU root pointer.

Make sure that you check for failure. This call may return NULL if the task entered a protected context the current task does not participate or if switch and launch exceptions are in use.

BUGS

SEE ALSO

`EnterMMUContext()`, `DeleteMMUContext()`,
`RemContextHook()`, `exec/tasks.h`

1.8 mmu.library/CurrentContext

NAME

`CurrentContext` - find out the current context of a task.

SYNOPSIS

```
context = CurrentContext( task );
d0      a1
```

```
struct MMUContext * CurrentContext( struct Task * );
```

FUNCTION

This function is used to get a handle to the context the given task is added to, or to return the context of the calling task.

INPUTS

task - the address of the task structure you like to investigate or NULL to get a handle to the currently active context.

RETURNS

a handle to the context the given task is added to, the global context if the task is not attached to any context or the currently active context if the argument is NULL.

NOTES

This call fails only if the given task is part of a protected context which is not shared by the current task. The NULL argument is always safe.

BUGS

SEE ALSO

FindTask()

1.9 mmu.library/AddContextHook

NAME

AddContextHook - set an exception handler to a Context

SYNOPSIS

```
hook = AddContextHookA ( tags );
                a0
```

```
hook = AddContextHook ( tag1, ... );
```

```
struct ExceptionHook * AddContextHookA ( struct TagItem * );
```

```
struct ExceptionHook * AddContextHook ( Tag tag1, ... );
```

FUNCTION

This call installs an exception hook for a given context for various exception types the MMU library can provide.

INPUTS

tags - A taglist defining the type of the exception hook to be added.

Currently defined are:

MADTAG_CONTEXT - The context to which this exception hook should be added. This MUST be given for "swapped" handlers. If it is left blank or set to NULL for segmentation fault handlers, you define a global segmentation fault handler.

MADTAG_TASK - If the hook should be called only if a specific task is running, specify a pointer

to the task structure here.
 Warning! Adding too many task specific
 hooks slows things down unnecessary.
 Remember that a MMU Context may hold more
 than one task.
 This MUST be given for the switch and launch
 hooks.

MADTAG_TYPE - Type of the exception hook to build. The
 following types are available:

MMUEH_SEGFAULT - Called on segmentation fault, i.e. write to
 a write protected page or access of an
 invalid page. Most useful for "Enforcer"
 like tools.

MMUEH_SWAPPED - Called on access for a "swapped out" page.
 Most useful to implement virtual memory.

MMUEH_SWITCH - Called when the task loses the CPU.
 MMUEH_LAUNCH - Called when the task gains the CPU.
 Remember that the tc_Switch() and tc_Launch()
 function pointers are no longer available
 if the task has been added to a MMUContext.

MMUEH_PAGEACCESS - Called whenever a MAPP_SINGLE page gets
 build by the context. This could be used to
 modify the MMU tree "on the fly" if
 necessary, the required parameters are passed
 thru.

MADTAG_CODE - A function pointer to the code to be called.
 This should be an assembly language function.
 It is called like this:

Register a0 - Pointer to the ExceptionData structure or
 the PageAccessData.
 Register a1 - loaded with the MADTAG_DATA provided data.
 Register a4 - Ditto.
 Register a5 - Pointer to the code itself.
 Register a6 - MMUBase. NOT A SCRATCH.

Registers d0-d1/a0-a1/a4-a5 are scratches and are available for the
 Exception handler. You *MUST* set the "Z" condition code and
 clear d0 on exit in case you handled the exception. Details on
 how to write an exception handler are in the "Exception.doc" file.

MADTAG_DATA - Data to be loaded for the hook function.
 MADTAG_NAME - A name for the hook. Currently unused.
 MADTAG_PRI - A priority, ranging from -128...+127.
 Hooks of higher priorities are called first.

RESULTS

A handle to the exception hook. Do not interpret this handle.
 Or NULL on failure.

NOTES

this call is used by the high-level function `AddMessageHook()`. The global segmentation fault hook is set by a debugging tool like `MuForce`.

The exception will not be activated, you need to call `ActivateException()` explicitly to make the library call it.

Much more needs to be said about this function, see `Exception.doc` and the MMU Manual for details about the exception handlers.

BUGS

SEE ALSO

`RemContextHook()`, `AddMessageHook()`, `ActivateException()`, `exec/interrupts.h`, `Exception.doc`

1.10 mmu.library/RemContextHook

NAME

`RemContextHook` - remove an exception handler from a Context

SYNOPSIS

```
RemContextHook( hook )
    al
```

```
void RemContextHook( struct ExceptionHook * );
```

FUNCTION

This function removes a previously installed context hook from the hook list.

INPUTS

The handle of the hook, as obtained by `AddContextHook()`.

RESULTS

none.

NOTES

You must call `DeactivateException()` on your hook before you remove it.
Be aware that the library will call the `exec` exception handler, i.e. will generate a guru in case no exception handler is available.

SEE ALSO

`AddContextHook()`, `DeactivateException()`, `exec/interrupts.h`

1.11 mmu.library/AddMessageHook

NAME

`AddMessageHook` - install a high-level hook function.

SYNOPSIS

```
hook = AddMessageHookA ( tags );
    a0
```

```
hook = AddMessageHook ( tag1, ... );
```

```
struct ExceptionHook * AddMessageHookA ( struct TagItem * );
```

```
struct ExceptionHook * AddMessageHook ( Tag tag1, ... );
```

FUNCTION

Installs a high-level hook of the tag-given properties. As soon as an exception of the requested type occurs, an exception message (see below) will be sent to the port. The task that caused the exception will be halted until the message gets replied.

BE WARNED: Message hooks perform only operation if task switching is enabled and interrupts are allowed and the code failed in User mode. They will just "drop thru" to the next handler if this is not the case.

INPUTS

tags - A taglist defining the type of the exception hook to be added.

Currently defined are:

MADTAG_CONTEXT - The context to which this exception hook should be added. This MUST be given.

MADTAG_TASK - If the hook should be called only if a specific task is running, specify a pointer to the task structure here.
Warning! Adding too many task specific hooks slows things down unnecessary.
Remember that a MMU Context may hold more than one task.

MADTAG_TYPE - Type of the exception hook to build. The following types are available:

MMUEH_SEGFAULT - Called on segmentation fault, i.e. write to a write protected page or access of an invalid page. Most useful for "Enforcer" like tools.

MMUEH_SWAPPED - Called on access for a "swapped out" page. Most useful to implement virtual memory.

MADTAG_CATCHERPORT - The port to sent the data to.

MADTAG_NAME - A name for the hook. Currently unused.

MADTAG_PRI - A priority, ranging from -128...+127.
Hooks of higher priorities are called first.

On an exception, the following message will be sent to the port:

```
struct ExceptionMessage {
    struct Message    exm_msg;
    struct ExceptionData exm_Data;
};
```

For details about the ExceptionData structure, see Exception.doc or the MMU Manual.

Once the message gets replied, the faulted task is restarted.

RESULTS

a handle for the exception that must be passed back to RemMessageHook() for removal or NULL on failure.
Do not interpret this handle.

NOTES

The handler must have been added to a context with EnterMMUContext() before this function can be used. Unlike the AddContextHook() function, this DOES NOT work for "plain" tasks without a context.

The hook must be activated with ActivateException() before it gets called.

This function is used by the memory.library to install its exception handler. The port will be in this case the port of the swapper daemon that loads swapped out pages from disk.

BUGS

SEE ALSO

AddContextHook(), RemContextHook(), RemMessageHook(),
ActivateException(), Exception.doc

1.12 mmu.library/RemMessageHook

NAME

RemMessageHook - remove a high-level hook from a context.

SYNOPSIS

```
RemMessageHook( handle );
    al
```

```
void RemMessageHook( struct ExceptionHook * );
```

FUNCTION

This function removed a previously installed Message hook from the hook list of the context.

INPUTS

handle - a handle to the message hook as returned by the AddMessageHook function.

RESULTS

none.

NOTES

To remove a message hook safely, deactivate it first with `DeactivateException()`, then tell the daemon to reply all exceptions of this hook, then remove it.

Not following these rules may cause deadlocks.

BUGS

SEE ALSO

`AddMessageHook()`, `AddContextHook()`, `RemContextHook()`, `DeactivateException()`, `Exception.doc`

1.13 mmu.library/ActivateException

NAME

`ActivateException` - enable an exception hook.

SYNOPSIS

```
ActivateException( hook );  
    al
```

```
void ActivateException( struct ExceptionHook * );
```

FUNCTION

Activates a formerly installed exception hook, either a low level context hook or a high-level message hook.

RETURNS

NOTES

Hooks of either kind must be activated before the `mmu.library` will call them. Hooks are deactivated after creation and must be deactivated before they get removed.

This call can be safely used within interrupts and from supervisor mode.

BUGS

SEE ALSO

`DeactivateException()`, `AddContextHook()`, `AddMessageHook()`, `Exception.doc`

1.14 mmu.library/DeactivateException

NAME

`DeactivateException` - enable an exception hook.

SYNOPSIS

```
DeactivateException( hook );
```

a1

```
void DeactivateException( struct ExceptionHook * );
```

FUNCTION

Deactivates a formerly installed exception hook, either a low level context hook or a high-level message hook, i.e. disables it from being called.

RETURNS

NOTES

Hooks of either kind must be activated before the mmu.library will call them. Hooks are deactivated after creation and must be deactivated before they get removed.
This call can be safely used within interrupts and from supervisor mode.

BUGS

SEE ALSO

ActivateException(), RemContextHook(), RemMessageHook(),
Exception.doc

1.15 mmu.library/GetPageSize

NAME

GetPageSize - return the page size of a context.

SYNOPSIS

```
pagesize = GetPageSize( context );  
d0          a0
```

```
ULONG GetPageSize( struct MMUContext * );
```

FUNCTION

This function returns the page size selected by the MMU library for the given context. Possible page sizes are limited by the hardware and cannot be adjusted from the outside. The page size is set up by the MMU library for the global public context, and it can be selected from the available page sizes for private MMUContexts, see CreateMMUContext().

INPUTS

context - a handle to the context to be investigated or NULL for the active context.

RESULTS

the page size in bytes

NOTES

BUGS

SEE ALSO

CreateMMUContext()

1.16 mmu.library/RemapSize

NAME

RemapSize - return the block size for memory remapping.

SYNOPSIS

```
remapsize = RemapSize( context );  
d0          a0
```

```
ULONG RemapSize( struct MMUContext * );
```

FUNCTION

This function returns the smallest possible block size, and therefore the alignment restrictions for remapping of memory that should be added to the exec memory pool. Since the MMU tables have to be placed in non-fragmented memory, certain alignment restrictions for the memory blocks the MMU tables are placed in arise.

This harder alignment condition is only required for memory that is put into the exec free list, but as long as remapped memory is never returned from AllocMem, the page size is good enough.

INPUTS

context - a handle to the context to be investigated or NULL for the active context.

RESULTS

the smallest admissible block size for memory returned by AllocMem().

NOTES

The call will fail if the given context is protected, the result will be zero in this case.

Even though the mmu.library does support memory remapping, this does not mean all other programs do. For example, remember that the inputs to the "MAPP_REMAPPED" pages is a physical page size, hence your program has to translate the logical address obtained by AllocMem() to a physical address at first. This can be done with the PhysicalLocation() function.

Additionally, DMA devices might or might not support memory remapping, just for the same reason: They require physical, not logical addresses. The MMU library provides a translation mechanism in form of the CachePreDMA() and CachePostDMA() functions of ExecBase, but not all DMA device drivers call these functions properly. Certain patches might be made available for devices not following this rule.

BUGS

Adding remapped memory to the freelist is highly untested and not recommended because of the quirks of this mechanism.

SEE ALSO
 PhysicalLocation(), GetPageSize(), exec/CachePreDMA(),
 DMAInitiate()

1.17 mmu.library/SetProperties

NAME
 SetProperties - set memory attributes for a given logical range.

SYNOPSIS

```
result = SetPropertiesA( context, flags, mask, lower, size, tags);
d0      a0      d1      d2      a1      d0      a2
```

```
BOOL SetPropertiesA( struct MMUContext *, ULONG, ULONG, ULONG, ULONG,
                    struct TagItem *);
```

```
result = SetProperties( context, flags, mask, lower, size, tag1, ...);
```

```
BOOL SetProperties( struct MMUContext *, ULONG, ULONG, ULONG, ULONG,
                    Tag tag1, ...);
```

FUNCTION
 This call sets attributes of a certain memory range of the software abstraction layer of the MMU tree, aligned to page boundaries.

INPUTS
 context - a handle to the context to modify or NULL for the active context.

flags - a binary flags field for the attributes to define. The following bits have been defined:

MAPP_WRITEPROTECTED - The page will be write protected. Writes to this area will cause a segmentation fault.

MAPP_ROM - Read only memory, writes tolerated. This is almost identically to MAPP_WRITEPROTECTED except that writes into this area will not cause a call of the segmentation fault handler. The library will filter them out. This property can be used to simulate a ROM in RAM and might be useful for kickstart remappers.

MAPP_USED - The "used" bit of the pages will be set. The CPU will set this bit automatically as soon as the pages are accessed.

This flag will turn on the "USED" bit in the hardware MMU bit. NOT setting this flag means that the USED bit in the hardware tree is preserved, regard-

less of the mask value.

MAPP_MODIFIED - The "modified" bit of the pages will be set. The CPU will set this bit automatically as soon as a write is performed to the page in question. DO NOT SET THIS BIT TOGETHER WITH MAPP_WRITEPROTECTED OR WITHOUT MAPP_USED or the CPU might hang.

This flag will turn on the "MODIFIED" bit in the hardware MMU bit. NOT setting this flag means that the MODIFIED bit in the hardware tree is preserved, regardless of the mask value.

MAPP_PRIVATE - The page will be marked invalid for all but the given contexts.
(Not yet implemented in V43)

MAPP_INVALID - The page will be marked as invalid. Accessing it will invoke the bus error hook. User data can be provided for this property mode, provided you don't select MAPP_SINGLEPAGE or MAPP_REPAIRABLE as well.

MAPP_SWAPPED - The page will be marked as swapped out.
A block ID *MUST* be provided for this property mode.

MAPP_CACHEINHIBIT - The page will be marked as non-cacheable.

MAPP_IMPRECISEEXCEPTION - The page will be marked as "imprecise exception". MAPP_CACHEINHIBIT is mandatory in this case or this flag does nothing.
Only available for the 68060, but does not harm for other MMUs.

MAPP_NONSERIALIZED - The page will be marked as serialized. MAPP_CACHEINHIBIT is mandatory if this property is selected.
Only available for the 68040, but does not harm for other MMUs.

MAPP_COPYBACK - The page will be marked as "copyback" instead of "writethrough". Generally recommended since this is faster for the '40 and '60. Only available for 68040 and 68060, but does not harm if selected for other MMUs. MAPP_CACHINHIBIT MUST NOT be selected.

MAPP_REMAPPED - Map the page to a different memory location. Parameters are given in the tag items.

Even though this seems simple, remapping memory is full of quirks. Obviously, DMA devices and the MMU itself see the true physical addresses and not the logical addresses as filtered by the MMU. Therefore, adding remapped memory to the exec.library freelist

will cause nothing than trouble and hard to trace disk faults and crashes as soon as this memory is used by a DMA device or the mmu.library itself. (Note that even though the library is supposed to support this, this is currently untested) Even though there *are* documented methods how to prepare a DMA transfer for remapped memory, USING these exec function calls is unfortunately the exceptions. Therefore, this method is currently unsupported, by most (!really!) DMA device drivers. Amongst the broken devices are the gvp SCSI device and the cyb SCSI device, to give just two examples.

The omni SCSI device (the "Guru ROM") can be fixed with the MuOmniScsiPatch.

If you really *MUST* remap public memory, then align it *AT LEAST* to the border given by RemapSize(). Just page alignment WILL NOT BE ENOUGH due to the way how the library works internally.

YOU HAVE BEEN WARNED!

MAPP_SUPERVISORONLY - The page will be not available for user programs.

NOTE: This mode is currently implemented using invalid page descriptors for the user pages and is ignored when building supervisor tables. This method saves some space for the 68040 and 68060 and was the only way how it could be done for the 68030 and 68851 without using MMU tables twice as large.

MAPP_USERPAGE0 - Set user page attribute 0.
This selects the user page attribute 0 for the 68040 and 68060. "USER" DOES NOT MEAN YOU!
The status of this bit appears on special pins of the CPU and might be required by some hardware, so don't play with this. You should not change this bit, by no means.

MAPP_USERPAGE1 - Set user page attribute 1.
This selects the user page attribute 0 for the 68040 and 68060. See above for warnings.

MAPP_GLOBAL - The pages are part of the global (public) memory.
You should not set this bit manually, it is under control of the library to optimize table flushes. (Not yet supported)

MAPP_BLANK - Blank memory.
The pages are mapped to one special area in RAM so erroneous reads and writes to these pages won't harm. MAPP_BLANK should ONLY be used to mark special memory areas as "non-available" and un-handled by the hardware, nothing else.

MAPP_SHARED (V43) - Properties are (partially) identical to the context specified by MAPP_SHARE on CreateMMUContext(). If MAPP_SHARE has not been given on context creation, this tag is illegal and will cause a Guru on RebuildTree(s).

Unlike specified before, MAPP_SHARED pages are updated automatically as soon as the shared parent context gets modified.

You may tell the mmu.library to selectively share only some properties of the parent. Use the MAPTAG_SHAREMASK to setup this mask, and control all other properties that are not shared by or-ing them to MAPP_SHARED.

This mechanism has some restrictions as you may currently not enable MAPP_REMAPPED, MAPP_SWAPPED, MAPP_INDIRECT, MAPP_BUNDLED and MAPP_INVALID selectively here, i.e. the mentioned properties cannot be or'ed to MAPP_SHARED. If you want to enable these properties in the child context without having them enabled in the parent, detach the corresponding page from the parent completely.

However, it is perfectly fine to share the mentioned properties from the parent by having them set in the MAPTAG_SHAREMASK, or to disable these properties selectively by setting the appropriate bits to zero within the MAPTAG_SHAREMASK.

MAPP_TRANSLATED - Under control of the TTx registers.
 NEVER SET THIS BIT YOURSELF.
 Pages with the "MAPP_TRANSLATED" bit set are under control of the "transparent translation registers" of the MMU and are "out of scope" for the mmu.library. Defining any properties for this domain will do nothing (or little, dependent on the TTx register configuration). A virtual memory program MUST NOT use virtual addresses which are transparently translated, this won't work. The mmu.library tries to be smart about the TTx registers and disables "unuseful" TTx settings itself.

MAPP_INDIRECT - Map to a user provided page descriptor.
 The provided pages(s) are mapped by a user provided page descriptor. This page descriptor MUST BE aligned to a long word address, and it MUST BE a valid page descriptor for the MMU used.

NEVER EVER attempt DMA, such as harddisk reads or writes to a memory domain marked as MAPP_INDIRECT.

Due to some cache peculatities, the data might be incorrect and the result would be corrupt data.

The library will be able to mark pages as non-cacheable if this is required for the DMA transfer, but this

magic does not work for indirect pages.

JUST DON'T DO THAT, MAPP_INIDIRECT is definitely an advanced feature.

MAPP_BUNDLED - Map all pages in range to a single page in RAM.

The main purpose of this function is to provide a MAPP_BLANK property with a user-selectable target page.

MAPP_SINGLEPAGE - Make this page available for SetPageProperties().

WARNING! Setting this bit shortcuts some optimizations the library might perform on the MMU table. The system may easily run out of memory if you select this property for "too many" pages.

MAPP_REPAIRABLE - Inform the exception handler to provide write data and to allow pipeline fill.

If this bit is set, the exception handler gets informed that you want to know the write data in case writes fail, or you want to provide the read data in case reads fail. The read/write data is available in the ExceptionData structure, read the exception handler documentation.

This flag should be combined with MAPP_INVALID, MAPP_WRITEPROTECTED, MAPP_SWAPPED or MAPP_SUPERVISORONLY

However, this technique requires a lot of "trickery" and should be expected to be slow and to create sub-optimal and over-sized MMU tables. Use it with care, on as few pages as possible and only if your exception handler is "not on a hurry".

This tag is NOT required in case you want to repair a page fault by providing the faulty page. This will work always, and a typical VMM implementation need not, and in fact, should not set this.

This tag is required as soon as you need to access the CPU pipelines and require access to the data the CPU "shall read" or "tried to write".

MAPP_USERATTRIBUTE0 - This is for your private use. This bit does not have any specific function, it is for your private use.

MAPP_USERATTRIBUTE1 - This is for your private use.
MAPP_USERATTRIBUTE2
MAPP_USERATTRIBUTE3

mask - A bit mask of the attributes to be changed.

Note that the hardware USED and MODIFIED bits will never be cleared, even though the properties say so and the corresponding bits in the mask are set. However, you can force them "ON" if you like, this saves unnecessary write-backs of the MMU.

lower - The lower boundary of the logical address to be modified. This must be aligned to the page size or this call will guru.

size - Size of the region to be modified. Must be a multiple of the page size.

tags - A tag array with additional data. Currently defined:

MAPTAG_DESTINATION - the physical destination of the logical address. Must be provided for the MAPP_MAPPED or MAPP_BUNDLED bits.

MAPTAG_BLOCKID - a unique ID the MMU.library doesn't care about, for external usage of the memory.library. Must be provided for the MAPP_SWAPPED flag and may be used to indicate where on disk the swapped page is kept.

MAPTAG_USERDATA - a unique cookie you might provide for MAPP_INVALID pages and which is passed thru to the segmentation fault exception handler.

MAPTAG_DESCRIPTOR - a pointer to a long word aligned table descriptor for MAPP_INDIRECT.

MAPTAG_SHAREMASK - a bitmask used for MAPP_SHARED only that defines which properties of the parent shall be carried over to the child. Defaults to ~0, i.e. all properties.

RESULTS

A boolean success/failure indicator. Might fail if the context is protected or no memory is available for the modification.

NOTES

This call adjusts only the abstraction layer of the MMU table and marks the pages as "dirty". An explicit call to RebuildTree() is required to make the changes active. You should bundle changes to the MMU table and call RebuildTree() once when you're done because rebuilding the MMU tree is a costly operation.

If you need to modify the MMU table "on the fly" then consider using "SetPageProperties()", even though its use is restricted to single pages. Even faster are MAPP_INDIRECT pages, but - to say that again - DO NOT PERFORM DMA ON THESE PAGES.

The page size can be read with GetPageSize().

SUPERVISORONLY, SWAPPED and INVALID memory are implemented using the same MMU attributes (invalid, namely), but the library exception handler will filter them out and call the appropriate hook.

Write protection goes only for the context specified. It usually makes sense to mark the memory region as PRIVATE as well, unless you modify the public hook.

(Note that MAPP_PRIVATE is currently not implemented because it will slow down things considerably.)

You may freely mark the first memory page as INVALID provided the context MCXTAG_EXECBASE flag is set (it usually is). Long word read accesses to AbsExecBase will be filtered out by the exception handler of the library and will be satisfied transparently to the program, as well as all other accesses except those into the first 1024 bytes.

BUGS

If the mask contains any property that requires user data, i.e. MAPP_REMAPPED or MAPP_SWAPPED, you *have* to redefine the user data by tag items and MAY NOT leave them out, as the library WILL NOT be able to restore the previously defined user data.

Some combinations will simply not work, namely those that require more than one user data at once. Hence, MAPP_INVALID, MAPP_SWAPPED, MAPP_BUNDLED, MAPP_INDIRECT, MAPP_REMAPPED and MAPP_SHARED are mutually exclusive.

SEE ALSO

GetProperties(), AddContextHook(), GetPageSize(), RemapSize(), RebuildTree(), SetPageProperties(), SetMappingProperties()

1.18 mmu.library/SetPageProperties

NAME

SetPageProperties - set hardware memory attributes for a single page.

SYNOPSIS

```
result = SetPagePropertiesA( context, flags, mask, lower, tags);
d0      a0  d1    d2    a1    a2
```

```
BOOL SetPagePropertiesA( struct MMUContext *, ULONG, ULONG, ULONG,
                        struct TagItem *);
```

```
result = SetPageProperties( context, flags, mask, lower, tag1, ...);
```

```
BOOL SetPageProperties( struct MMUContext *, ULONG, ULONG, ULONG,
                        Tag tag1, ...);
```

FUNCTION

This call sets the hardware attributes of a memory page.

INPUTS

context - a handle to the context to modify or NULL for the active context.

flags - a binary flags field for the attributes to define. For the available attributes, see the SetProperties() function.

Differences:

MAPP_MODIFIED and MAPP_USED are really set or cleared in the true hardware table, the mask is considered correctly.

Note that this function is the only method to clear these two hardware flags, SetProperties() or RebuildTree() don't do this.

mask - a bit mask of all bits to be changed.

tags - A tag array with additional data. Check SetProperties() for details.

RESULTS

A boolean success/failure indicator. Might fail if the context is protected or no memory is available for the modification or the page is not marked with MAPP_SINGLEPAGE.

NOTES

BE WARNED! This function is very restricted in its use. It may well return FALSE even if all parameters are valid due to hardware restrictions. This function does never ever rebuild an MMU tree, it just modifies "what is there". If the library choose to optimize the MMU library tree and to map a couple of pages by one descriptor, for what reasons ever, this call will fail. The details when this happens depends not only on the MMU, but on the general system layout.

The ONLY documented way to get a mapping for a page that can be adjusted using this call is to set the page to MAPP_SINGLEPAGE using SetProperties() before.

This call adjusts the hardware level of the MMU table if a descriptor is available for a single page. It does not modify more than one page at once.

It might happen that the library does not satisfy a request setting a page as "cacheable" if a DMA operation is currently in progress and the page must remain "nonacheable". However, the function will not fail in this case, but just delay the operation until the DMA is complete. The properties will always fall back to the next available option.

This routine is safe to be called from within interrupts, it does

not break any `Forbid()` or `Disable()` and is ideal for quick-and-dirty repair operations within exceptions handlers, provided the `MAPP_SINGLEPAGE` flag has been set.

`MAPP_SHARED` does not have the "obvious meaning" here. If a page is build with `MAPP_SHARED` enabled, `GetPageProperties()` will return the effective properties for this page which are build from combining the properties of the parent context, filtered by the `MAPTAG_SHAREMASK` of the page, or'ed by the remaining properties. Similarly, `SetPageProperties()` with `MAPP_SHARED` set will not automatically carry any properties from the parent over in any event. In fact, it is ignored by the low-level functions completely.

BUGS

Note that `MAPP_SINGLEPAGE` is the flag you want here, not `MAPP_REPAIRABLE`. That's something different!

If the mask contains any property that requires user data, i.e. `MAPP_REMAPPED` or `MAPP_SWAPPED`, you *have* to redefine the user data by tag items and MAY NOT leave them out, as the library WILL NOT be able to restore the previously defined user data.

SEE ALSO

```
GetPageProperties(), AddContextHook(),
GetPageSize(), RebuildTree(), SetProperties(),
SetMappingProperties()
```

1.19 mmu.library/RebuildTree

NAME

`RebuildTree` - build a MMU hardware tree from the software abstraction layer.

SYNOPSIS

```
result = RebuildTree( context );
d0      a0
```

```
BOOL RebuildTree ( struct MMUContext * );
```

FUNCTION

This function adjusts the MMU hardware tree to reflect the settings of the software abstraction layer defined with `SetProperties()`.

INPUTS

`context` - a handle to the context to investigate or `NULL` for the active context.

RESULTS

a boolean success/failure indicator. `TRUE` if the operation was performed successfully.

NOTES

This is the big - and admittedly - slow one.

Rebuilding the MMU tree is a relatively slow operation. The library

tries to be smart about it and rebuilds only the pages whose mappings have been adjusted, but it's still a heavy beast. This goes even more for contexts that are shared by several children as a `RebuildTree()` on the parent will trigger a partial(!) table rebuild for the child.

Properties temporarily defined with `SetPageProperties()` will be lost after the rebuild, except for the `MAPP_USED` and `MAPP_MODIFIED` bits. If you want to avoid this, you need to install a page access handler into your context and modify the properties installed by the `mmu.library` "on the fly" while it is rebuilding your context, see `AddContextHook()`.

In case of failure, the hardware layer will remain valid and unchanged, but the context remains marked as "dirty".

BE WARNED! A consistent use of the two flags is only possible if the pages are marked as `MAPP_SINGLE`. The page building algorithm does not guarantee consistent use of these two bits except for `MAPP_SINGLEPAGE` pages. Even though it *might* look well most the time, it is not documented that these two bits are kept correctly for non-`SINGLE` pages. If you need `MODIFIED` or `USED` page information, the only way to get them is to mark these pages as `MAPP_SINGLE`. There's no consistent use for these flags if early termination descriptors (hence, w/o `MAPP_SINGLE`) are used by the library.

Even though some pages in the abstraction layer might be marked as un-`USED` or un-`MODIFIED`, this routine NEVER clears the hardware bits. It requires a call to `SetPageProperties()`, and hence the `MAPP_SINGLE` attribute (once again!) to do this.

BUGS

Much more should be said about this function.

SEE ALSO

`SetProperties()`, `SetPageProperties()`, `GetProperties()`, `GetPageProperties()`, `RebuildTrees()`

1.20 mmu.library/RebuildTrees

NAME

`RebuildTree` - build a MMU hardware tree from the software abstraction layer for several contexts at once. (V41)

SYNOPSIS

```
result = RebuildTreesA( contextptrptr );
d0          a0

result = RebuildTrees( context, context, ... );

BOOL RebuildTreesA ( struct MMUContext ** );

BOOL RebuildTrees ( struct MMUContext, ... );
```

FUNCTION

This function adjusts the MMU hardware tree to reflect the settings of the software abstraction layer defined with `SetProperties()`.

INPUTS

`contextptr` - a pointer to a NULL terminated array of context handles.

RESULTS

a boolean success/failure indicator. TRUE if the operation was performed successfully and all context could have been rebuild.

NOTES

See the notes for `RebuildTree()`.

BUGS**SEE ALSO**

`SetProperties()`, `SetPageProperties()`, `GetProperties()`, `GetPageProperties()`, `RebuildTree()`

1.21 mmu.library/GetProperties

NAME

`GetProperties` - read memory attributes for a given logical page from the MMU table abstraction layer.

SYNOPSIS

```
flags = GetPropertiesA( context, lower, tags);
d0      a0      a1      a2
```

```
ULONG GetPropertiesA( struct MMUContext *, void *, struct TagItem *);
```

```
flags = GetProperties( context, lower, tag1, ...);
```

```
ULONG GetProperties( struct MMUContext *, void *, Tag tag1, ...);
```

FUNCTION

This call reads the page properties of a certain address in memory from the software abstraction layer. It is the counterpart of `SetProperties()`.

INPUTS

`context` - a handle to the context to investigate or NULL for the active context.

`lower` - the logical address of the page to investigate. The size of the page depends on the hardware and is selected by the MMU library. The number of bytes in a page is returned by `GetPageSize()`.

`tags` - additional tags. Currently defined are:

- MAPTAG_DESTINATION - a pointer to a void * where the physical destination of the logical address is filled in. Only available if the page is physically mapped to somewhere. Not filled in otherwise.
- MAPTAG_BLOCKID - read the a unique ID for the MAPP_SWAPPED property. Untouched if the page isn't swapped. The tag data points to a long word which will be filled in for swapped out pages.
- MAPTAG_USERDATA - read the unique cookie for INVALID pages, fill in the long word pointed to by the tag data field.
- MAPTAG_DESCRIPTOR - fill in the location of the indirect descriptor which is used to perform the mapping. Only used if MAPP_INDIRECT is used.
- MAPTAG_SHAREMASK - in case of MAPP_SHARED pages, fill in the properties that are carried over from the parent to the child.

RESULTS

Returns a binary flags field for the attributes to define. See SetProperties() for details. Remember that MAPP_USED or MAPP_MODIFIED reflect the bits on the abstraction layer, not the true hardware bits. You MUST call GetPageProperties() to read them, and hence *MUST* use MAPP_SINGLEPAGE pages.

NOTES

The page size can be read with GetPageSize(). Check the return code of this call!

The flags returned are valid for the given context, a different context may return a different flag setting and even a different physical locations.

WARNING: The flags returned DO NOT reflect the hardware flags in the MMU table for the context. They DO reflect the settings installed with SetProperties() on the abstraction layer of the MMU tables.

The hardware table might differ for the following reasons:

- SetProperties() was called, but the changes haven't been made active with RebuildTree() yet.
- A program modified the hardware layer directly using SetPageProperties().
- DMA is currently active and the page in question has therefore been marked as non-cacheable temporarily.

Additionally, the library might have adjusted the abstraction layer itself by allocating non-cacheable memory for its MMU tables.

This routine is *NOT* safe to be called from within interrupts.

BUGS

SEE ALSO

SetProperties(), AddContextHook(), GetMappingProperties(),
GetPageSize(), GetPageProperties(), RebuildTree()

1.22 mmu.library/GetPageProperties

NAME

GetPropertiesA - read memory attributes from the hardware level
for a given logical page.

SYNOPSIS

```
flags = GetPagePropertiesA( context, lower, tags);
d0          a0          a1          a2
```

```
ULONG GetPagePropertiesA( struct MMUContext *, void *,
                          struct TagItem *);
```

```
result = GetPageProperties( context, lower, tag1, ...);
```

```
ULONG GetPageProperties( struct MMUContext *, void *, Tag tag1, ...);
```

FUNCTION

This call reads the page properties of a certain address in
memory directly from the hardware. It is the counterpart
of SetPageProperties().

INPUTS

context - a handle to the context to investigate or NULL for the
active context. The library might use the MMU hardware directly
if NULL is passed in, this call might be faster therefore.

lower - the logical address of the page to investigate. The
size of the page depends on the hardware and is selected by
the MMU library. The number of bytes in a page is returned
by GetPageSize().

tags - additional tags. See GetProperties() for details.

RESULTS

Returns a binary flags field of the attributes found. See
SetProperties() for details.

NOTES

The page size can be read with GetPageSize().

The flags returned are valid for the given context, a different
context may return a different flag setting and even a different
physical location.

WARNING: The flags returned reflect the NOT the hardware flags in the MMU table for the context except for the MODIFIED and USED properties, even though the hardware level is **almost** consistent with these flags.

The hardware table might differ slightly in the following situations:

- DMA is currently active and the page in question has therefore been marked as non-cacheable temporarily. Therefore, the cache settings returned are what will be re-installed here when DMA is finished. The library will "fake" the flags you have installed for the page investigated.
- The library will use invalid descriptors to implement supervisor only or swapped pages.

However, even though the flags might differ from the hardware flags, you're always safe to re-install the properties with `SetPageProperties`, there's no need to keep track of peculiarities like cache disabling for DMA pages. The library does this for you.

`MAPP_MODIFIED` and `MAPP_USED` are always read from the hardware directly.

KEEP IN MIND that these two bits are only set and handled consistently for `MAPP_SINGLE` pages. You MUST NOT interpret them in all other cases, their values might get lost on a `RebuildTree()` call.

This routine is safe to be called from within interrupts, most useful within exception handlers.

`MAPP_SHARED` will not be returned here in the "obvious meaning". If a page is build with `MAPP_SHARED` enabled, `GetPageProperties()` will return the effective properties for this page which are build from combining the properties of the parent context, filtered by the `MAPTAG_SHAREMASK` of the page, or'ed by the remaining properties.

BUGS

SEE ALSO

`GetProperties()`, `AddContextHook()`,
`GetPageSize()`, `SetPageProperties()`, `RebuildTree()`

1.23 mmu.library/AllocAligned

NAME

`AllocAligned` - allocate memory aligned to a memory border.

SYNOPSIS

```
mem = AllocAligned( bytesize, reqments, align );
d0      d0      d1 a0
```

```
void * AllocAligned( ULONG, ULONG, ULONG);
```

FUNCTION

Allocate memory aligned to certain boundaries.

INPUTS

bytesize - the size of the memory to allocate.

reqments - exec style memory attributes

align - the alignment restrictions of the page.
MUST be a power of two.

RETURNS

a pointer to the allocated memory, aligned to the given border or
NULL if no free physical memory could be found.

NOTES

Examples of how to use the "align" parameter:

```
mem = AllocAligned(123, MEMF_PUBLIC | MEMF_CLEAR, 1024);
```

will allocate 123 bytes starting at a 1024 byte border, i.e.
the address returned will be divisible by 1024. The call will
clear the 123 bytes, NOT MORE.

This is a service routine for the memory.library and shouldn't be
used for all-day purposes.

A DOS process will have its pr_Result2 field set to
ERROR_NO_FREE_STORE if the memory allocation fails.

The mmu.library calls this function by using its LVO library entry,
so it can be patched to a smarter implementation if desired.

BUGS

SEE ALSO

GetPageSize(), exec/memory.h

1.24 mmu.library/LockMMUContext

NAME

LockMMUContext - lock a MMU context

SYNOPSIS

```
LockMMUContext( context );  
a0
```

```
void LockMMUContext( struct MMUContext * );
```

FUNCTION

Lock the software abstraction layer of the MMU table against
modifications from other tasks.

INPUTS

A handle to a MMUContext or NULL for the active context.

RETURNS

NOTES

This mechanism DOES NOT avoid changes of the MMU table on a lower level by SetPageProperties(), only SetProperties() from other tasks will be locked.

Hence, it locks the abstraction layer, but not the hardware level.

DO NOT lock more than one context at once, unless you locked also the context list with LockContextList(). Not following this rule might cause deadlocks.

BUGS

SEE ALSO

UnlockMMUContext(), SetPageProperties(), SetProperties(), LockContextList().

1.25 mmu.library/UnlockMMUContext

NAME

UnlockMMUContext - release a MMU context

SYNOPSIS

```
UnlockMMUContext( context );  
                a0
```

```
void UnlockMMUContext( struct MMUContext * );
```

FUNCTION

Release the software abstraction layer of the MMU table, allow modifications from other tasks.

INPUTS

A handle to a MMUContext or NULL for the active context.

RETURNS

NOTES

This mechanism DOES NOT avoid changes of the MMU table on a lower level by SetPageProperties(), only SetProperties() from other tasks will be locked.

Hence, it locks the abstraction layer, but not the hardware level.

BUGS

SEE ALSO

LockMMUContext(), SetPageProperties(), SetProperties(), AttemptLockMMUContext()

1.26 mmu.library/AttemptLockMMUContext

NAME

AttemptLockMMUContext - attempt to lock a MMU context

SYNOPSIS

```
ok = AttemptLockMMUContext( context );  
a0
```

```
struct MMUContext * AttemptLockMMUContext( struct MMUContext * );
```

FUNCTION

Grants non-blocking access to a MMU context.
Attempts to lock the software abstraction layer of the MMU table against modifications from other tasks.

INPUTS

A handle to a MMUContext or NULL for the active context.

RETURNS

A context pointer in case of success - the context is then locked for you and this lock must be released with UnlockMMUContext().
NULL in case any other task holds a lock.

NOTES

This mechanism DOES NOT avoid changes of the MMU table on a lower level by SetPageProperties(), only SetProperties() from other tasks will be blocked.
Hence, it locks the abstraction layer, but not the hardware level.

DO NOT lock more than one context at once, unless you locked also the context list with LockContextList(). Not following this rule might cause deadlocks.

BUGS

In pre-V39 machines, this call does not lock the context again in case you already hold a lock. This is a bug of the pre-V39 AttemptSemaphore(), read the exec autodocs for a workaround.

SEE ALSO

UnlockMMUContext(), SetPageProperties(), SetProperties(),
LockContextList(), AttemptSemaphore()

1.27 mmu.library/LockContextList

NAME

LockContextList - arbitrate a master lock.

SYNOPSIS

```
LockContextList( );
```

```
void LockContextList( void );
```

FUNCTION

Arbitrates a master lock that allows locking more than one context at once to avoid deadlocks.

INPUTS**RETURNS****NOTES**

This lock grants access for locking more than one context at once, to avoid deadlocks. I.e. in case you need to lock more than one context at a time, get this lock FIRST, then lock the contexts in any order you prefer.

This call DOES NOT avoid modification of the context list or individual contexts at all, i.e. other tasks are still able to create and to dispose contexts. To avoid this, you must lock the contexts afterwards.

When you're done with the contexts, unlock the contexts first, THEN release this lock with `UnlockContextList()`. NOTE THE ORDER!

BUGS**SEE ALSO**

`UnlockContextList()`, `LockMMUContext()`, `AttemptLockContextList()`

1.28 mmu.library/UnlockContextList

NAME

`UnlockContextList` - release the master context lock

SYNOPSIS

```
UnlockContextList( );
```

```
void UnlockContextList( void );
```

FUNCTION

Releases the master lock that allows locking more than one context at once to avoid deadlocks.

INPUTS**RETURNS****NOTES**

This lock grants access for locking more than one context at once, to avoid deadlocks. I.e. in case you need to lock more than one context at a time, get this lock FIRST, then lock the contexts in any order you prefer.

This call DOES NOT avoid modification of the context list or individual contexts at all, i.e. other tasks are still able to create and to dispose contexts. To avoid this, you must lock the contexts afterwards.

When you're done with the contexts, unlock the contexts first,
THEN release this lock with `UnlockContextList()`. NOTE THE ORDER!

BUGS

SEE ALSO

`LockContextList()`, `LockMMUContext()`, `AttemptLockContextList()`

1.29 mmu.library/AttemptLockContextList

NAME

`AttemptLockContextList` - attempt to arbitrate the master lock.

SYNOPSIS

```
ok = AttemptLockContextList( );
```

```
LONG AttemptLockContextList( void );
```

FUNCTION

Attempts granting the context master lock in a non-blocking fashion.

INPUTS

RETURNS

TRUE in case the master lock could be arbitrated. You have then to release it with `UnlockContextList()`.
FALSE in case it is already locked and access could not be granted.

NOTES

This lock grants access for locking more than one context at once, to avoid deadlocks. I.e. in case you need to lock more than one context at a time, get this lock FIRST, then lock the contexts in any order you prefer.

This call DOES NOT avoid modification of the context list or individual contexts at all, i.e. other tasks are still able to create and to dispose contexts. To avoid this, you must lock the contexts afterwards.

When you're done with the contexts, unlock the contexts first,
THEN release this lock with `UnlockContextList()`. NOTE THE ORDER!

BUGS

In pre-V39 machines, this call does not lock the context again in case you already hold a lock. This is a bug of the pre-V39 `AttemptSemaphore()`, read the exec autodocs for a workaround.

SEE ALSO

`UnlockContextList()`, `LockMMUContext()`, `LockContextList()`,
`AttemptLockSemaphore()`

1.30 mmu.library/AllocLineVec

NAME

AllocLineVec - allocate cache line aligned, keep size

SYNOPSIS

```
AllocLineVec ( bytesize , attributes );  
             d0         d1
```

```
void * AllocLineVec ( ULONG, ULONG );
```

FUNCTION

Allocates memory like AllocVec(), but the memory is guaranteed to be aligned to cache lines of the processors in the system, even though the pointer returned IS NOT. Minimal guaranteed alignment is currently 32 bytes, i.e. a PPC cache line. Future hardware may require stricter alignments.

AllocLineVec'd memory is released with FreeVec() from the exec.library.

INPUTS

bytesize - the size of the memory block in bytes.
attributes - memory attributes, see exec.library/AllocMem.

RETURNS

a pointer to the memory allocated or NULL on failure.

A DOS process will have its pr_Result2 field set to ERROR_NO_FREE_STORE if the memory allocation fails.

NOTES

BIG WARNING: The pointer returned IS NEVER cache line aligned itself, but the complete memory block together with the vector size is kept in a cache line, regardless of the size passed in. Due to alignment restrictions, the routine might allocate a larger memory block than requested. It is however guaranteed that AT LEAST the size requested is returned, and that a FreeVec() will, indeed, free all memory.

If MEMF_CLEAR is requested, the memory is cleared on the MC68K side, but the "zeros written" might be still in the cache. Hence, it is a good idea to flush the cache if the memory is passed over to the PPC.

However, the vector size itself is always "pushed" to memory, it is therefore guaranteed to be properly written back to the memory.

The memory allocated this way is released by FreeVec() of the exec.library.

BUGS

SEE ALSO

exec.library/AllocVec(), exec.library/FreeVec(), AllocLineVec()

1.31 mmu.library/PhysicalPageLocation

NAME

PhysicalPageLocation - translate logical address to physical

SYNOPSIS

```
addr = PhysicalPageLocation( context , addr );
d0      a0      a1
```

```
void * PhysicalPageLocation( struct MMUContext * , void * );
```

FUNCTION

This function finds the physical address for the logical address passed in by scanning the MMU hardware table.
If the physical address is not available, NULL is returned.

INPUTS

context - the context to enter or NULL for the current context.
addr - the logical address to be translated.

RETURNS

the physical address of the logical address passed in, or NULL in case the logical address is not swapped in or otherwise out of control of the library.

NOTES

This is the low-level function, consider using the high-level function PhysicalLocation() when possible.
This call can be safely used within interrupts.

BUGS

The function will also return NULL in case the logical address is translated to the address 0L. However, 0L should never be used as physical address anyhow.

SEE ALSO

GetPageProperties(), PhysicalLocation()

1.32 mmu.library/PhysicalLocation

NAME

PhysicalLocation - translate logical address to physical

SYNOPSIS

```
props = PhysicalLocation( context, addrptr, lenptr );
d0      d1      a0      a1
```

```
ULONG PhysicalLocation( struct MMUContext * , void ** , ULONG * );
```

FUNCTION

This function finds the physical address for the logical address passed in by scanning the software abstraction layer.
If the physical address is not available, NULL is returned.

INPUTS

context - the context to enter or NULL for the current context.

addrptr - points to the logical address to be translated.

The physical address is filled in here, or NULL in case the logical address passed in is not available.

lenptr - Points to the length of the address range to be translated. The function returns the length of the largest possible continuous memory range contained in the memory range passed in. Hence, this function may shorten the memory block for fragmented memory models. It will return NULL in case the memory is not available.

RETURNS

the properties of the memory range.

NOTES

This is the high-level function, it is not callable from within interrupts.

In case you've to operate on a range of physical memory, start the translation with this call, then compare the size returned with the size of the memory block passed in. Because this function may shorten the memory size in case the physical memory is fragmented, you should be prepared that the size returned is smaller than what was passed in. In this case, operate on the memory region returned, then add the returned size to the original logical address and call this function again to get the physical location of the next chunk.

BUGS

The function will also return NULL in case the logical address is translated to the address 0L. However, 0L should never be used as physical address anyhow.

SEE ALSO

GetProperties(), PhysicalPageLocation()

1.33 mmu.library/DMAInitiate

NAME

DMAInitiate - start a DMA transport given a logical address.

SYNOPSIS

```
fine = DMAInitiate( context, addrptr, lenptr, write );
                dl      a0    a1      d0
```

```
BOOL DMAInitiate( struct MMUContext * , void ** , ULONG * , BOOL );
```

FUNCTION

This function finds the physical address for the logical address passed in by scanning a backup of the MMU translation tree. It ignores modifications made by the high-level and low-level functions unless RebuildTree() is called.

INPUTS

context - the context to enter or NULL for the current context.
NOTE: This parameter is currently a dummy and should be set to NULL. The mmu.library will always use the public context for translation.
addrptr - points to the logical address to be translated.
The physical address is filled in here.
lenptr - Points to the length of the address range to be translated. The function returns the length of the largest possible continuous memory range contained in the memory range passed in. Hence, this function may shorten the memory block for fragmented memory models.
write - set this to TRUE for transports from a DMA device INTO the memory, i.e. device reads. Set this to FALSE for writes from memory to the device.

RETURNS

fine - TRUE if the address and length passed in pointed to available memory. FALSE if the requested DMA transfer was invalid.

The result code is new for V42, do not check it for V41 or below.

NOTES

The function checks whether the memory range passed in is available for DMA. It will guru in case it is not, i.e. the page is either swapped out, invalid, indirect, or write protected for DMA device reads. Reads into ROM addresses are silently tolerated, and, hence, are translations to and from blank dummy pages.

This function is callable from within interrupts, but does only use a backup of the high-level table for its translation. Changes to the software abstraction level are not visible for this function unless RebuildTree() is called. Changes to the hardware level are not at all visible to this (and all other high-level) functions.

In case you've to operate on a range of physical memory, start the translation with this call, then compare the size returned with the size of the memory block passed in. Because this function may shorten the memory size in case the physical memory is fragmented, you should be prepared that the size returned is smaller than what was passed in. With the physical address returned, start the DMA and call DMATerminate() when done.

In case the returned size is smaller than the block passed in, add the returned size to the original logical address and call this function again to get the physical location of the next chunk.

EACH CALL TO DMAInitiate() must be matched by ONE AND PRECISELY ONE call to DMATerminate().

Even though this function does not require locking the context, I highly recommend doing so. It won't crash if you don't, but someone else could modify the MMU translation table in between. The library can deal with that, but the result of the DMA operation might be different from what you expect.

The pre-V42 releases did not return a result code but generated an alert in case illegal memory has been passed in. This changed for V42. DO NOT assume a meaningful result code for V41 or below.

BUGS

This function should really use the context passed in, but since most (if not all) DMA device drivers do not keep the context of the task that actually initiated the transfer and hence would use the wrong context anyhow, DMA is currently limited to the public context.

SEE ALSO

`DMATerminate()`, `PhysicalPageLocation()`, `exec/CachePreDMA()`

1.34 mmu.library/DMATerminate

NAME

`DMATerminate` - end a DMA transfer initiated by `DMAInitiate`.

SYNOPSIS

```
DMATerminate( context );  
    dl
```

```
void DMATerminate( struct MMUContext * );
```

FUNCTION

This function ends a DMA transfer initiated by `DMAInitiate`. It releases the resources by the first call.

INPUTS

`context` - the context to enter or `NULL` for the current context.

NOTE: This parameter is currently a dummy and should be set to `NULL`. The `mmu.library` will always use the public context for translation.

RETURNS

NOTES

This function is callable from within interrupts, but does only use a backup of the high-level table for its translation. Changes to the software abstraction level are not visible for this function unless `RebuildTree()` is called. Changes to the hardware level are not at all visible to this (and all other high-level) functions.

EACH CALL TO `DMAInitiate()` must be matched by ONE AND PRECISELY ONE call to `DMATerminate()`.

For details, check the `DMAInitiate()` function.

BUGS

This function should really use the context passed in, but since most (if not all) DMA device drivers do not keep the context of the task that actually initiated the transfer and

hence would use the wrong context anyhow, DMA is currently limited to the public context.

SEE ALSO

DMAInitiate(), PhysicalPageLocation(), exec/CachePostDMA()

1.35 mmu.library/GetMapping

NAME

GetMapping - get access to the memory map of a MMUContext

SYNOPSIS

```
list = GetMapping( context );
d0      a0
```

```
struct MinList * GetMapping( struct MMUContext * );
```

FUNCTION

This function makes a copy of the MapNodes for the given context. The nodes in this list describe the memory map as seen from tasks attached to this context, sorted by logical addresses. The list must be released afterwards with ReleaseMapping().

INPUTS

context - the context to enter or NULL for the current context.

RETURNS

a pointer to a struct MinList which contains the MapNodes for this context, sorted by physical address, or NULL in case of failure.

NOTES

The nodes are just a copy of the real nodes within the context.

This function is most useful to make a backup of the context memory map before altering it. In case any of the modifications fail, you are able to undo all modifications completely with a call to SetPropertyList() - which can't fail.

To give an example:

```
/* make a backup of the context how it looks now */
```

```
LockMMUContext(ctx);
```

```
if (list=GetMapping(ctx)) {
    fine=TRUE;
```

```
    /* Try to alter it, step by step. */
```

```
    if (!SetProperties(...))
    fine=FALSE;
```

```
    if (!SetProperties(...))
    fine=FALSE;
```

```

    /* etc, etc.... */

    /* Oops, we failed! Re-install the old setup. */
    if (!fine)
        SetPropertyList(ctx, list);
}

ReleaseMapping(ctx, list);
UnlockMMUContext(ctx);
/* and so on... */

```

Note that you've still to call `ReleaseContextList()`, even in case of failure when you've already re-installed backup property list.

BUGS

SEE ALSO

`ReleaseMapping()`, `SetPropertyList()`, `mmu/context.h`

1.36 mmu.library/ReleaseMapping

NAME

`ReleaseMapping` - get access to the memory map

SYNOPSIS

```
ReleaseMapping( context , list );
    a0 a1
```

```
void ReleaseMapping( struct MMUContext * , struct MinList * );
```

FUNCTION

This function releases the list of MapNodes arbitrated by `GetMapping`.

INPUTS

`context` - the context the nodes where taken from.
`list` - the backup property list to release.

RETURNS

NOTES

This function **MUST** be called, even in case the property list was re-installed with `SetPropertyList()`.

BUGS

SEE ALSO

`NewMapping()`, `GetMapping()`, `SetPropertyList()`

1.37 mmu.library/NewMapping

NAME
 NewMapping - build a new memory map

SYNOPSIS

```
list = NewMapping ( );
d0
```

struct MinList * NewMapping (void);

FUNCTION
 Build and initialize a new memory map list. All addresses in this list will be marked as MAPP_BLANK.

INPUTS
 nothing.

RESULTS
 a MinList structure, initialized with MapNodes representing a completely blank memory layout or NULL on failure. You either need to copy the layout from a context with CopyContextRegion(), or define your own layout with calls to SetMappingProperties().

NOTES
 Don't forget to release the list (and its contents) with ReleaseMapping() when you're done.

BUGS

SEE ALSO
 CopyContextRegion(), SetMappingProperties(), ReleaseMapping(), GetMapping()

1.38 mmu.library/CopyMapping

NAME
 CopyMapping - transfer memory properties between lists

SYNOPSIS

```
fine = CopyMapping ( from , to , base , length , mask );
d0          a0      a1      d0          d1          d2
```

BOOL CopyMapping (struct MinList * , struct MinList * ,
 ULONG , ULONG , ULONG);

FUNCTION
 Copy the memory properties from one memory map to another, thru a mask.

INPUTS
 from - the memory map which is (partially) to be transferred.
 to - the destination of the copy operation.
 base - base address. Memory properties will be copied starting

at this address.

length - length of the memory region in bytes whose properties shall be transferred.

mask - a mask of property bits which are to be transferred. A zero bit in this mask indicates that the corresponding property in the destination will not be touched. For all the properties, check the `SetProperties()` function.

RESULTS

a boolean success/failure indicator. It is `TRUE` in case the operation was performed, `FALSE` otherwise. The destination will not have been touched at all in this case.

NOTES

this call does not copy memory. It just copies memory attributes from one memory map to another.

Check `CopyContextRegion()` to copy the properties from a context instead from a list.

Since this call is not context based, the library will not be able to perform checks for correct page alignment, you have to do that yourself. Especially, note that `SetPropertyList()` - which attaches a memory map to a context - does not perform any check on this list either. Hence, **NOT** checking for page alignment here might result in an invalid context if you try to attach an incorrectly aligned list to a context later on.

BUGS

SEE ALSO

`SetPropertyList()`, `ReleaseMapping()`, `DupMapping()`, `SetProperties()`, `CopyContextRegion()`

1.39 mmu.library/DupMapping

NAME

`DupMapping` - make a one-to-one copy of a memory map

SYNOPSIS

```
dup = DupMapping ( list );
d0      a0
```

```
struct MinList * DupMapping( struct MinList * );
```

FUNCTION

this call builds an identical copy of the memory map passed in.

INPUTS

list - the memory map to be copied.

RESULTS

another memory list, identical to the list passed in, or `NULL` on failure.

NOTES

Don't forget to release the memory list with `ReleaseMapping()` if you're done with it. You need to release both, the original as well as the duplicate.

In case you want to make a copy of the memory map of a context, use `GetMapping()` instead.

BUGS

SEE ALSO

`GetMapping()`, `ReleaseMapping()`

1.40 mmu.library/CopyContextRegion

NAME

`CopyContextRegion` - transfer properties from a context to a list

SYNOPSIS

```
fine = CopyContextRegion ( ctx, list, base, length, mask );
d0      a0  a1  d0  d1  d2
```

```
BOOL CopyContextRegion ( struct MMUContext *, struct MinList *,
                        ULONG, ULONG, ULONG );
```

FUNCTION

Copy the properties of a memory region defined by a context to another memory map, thru a mask.

INPUTS

```
ctx      - source context whose memory map shall be transfered.
list     - the destination memory map which is to be altered.
base     - base address of the memory region whose properties are
           to be copied.
length  - length of the memory region in bytes whose properties
           will be transfered.
mask     - a mask of property bits, see the SetProperties()
           function for a detailed explanation. A zero bit in this
           mask means that the corresponding property in the
           destination will be left alone and will remain unchanged.
```

RESULTS

a boolean success/failure indicator, `TRUE` for success. On failure, the destination memory map will not have been touched at all.

NOTES

This call does not copy memory at all, it just defines the memory properties of a given memory map from that of a given context.

Check `CopyMapping()` to transport memory properties from one list to another.

Since this call is not context based, the library will not be able to perform checks for correct page alignment, you have to do that yourself. Especially, note that `SetPropertyList()` - which attaches

a memory map to a context - does not perform any check on this list either. Hence, **NOT** checking for page alignment here might result in an invalid context if you try to attach an incorrectly aligned list to a context later on.

BUGS

SEE ALSO

SetPropertyList(), ReleaseMapping(), SetProperties(),
SetPropertiesMapping()

1.41 mmu.library/SetPropertiesMapping

NAME

SetPropertiesMapping - transfer properties from a map list
to a context

SYNOPSIS

```
fine = SetPropertiesMapping ( ctx, list, base, length, mask );
d0      a0  a1  d0  d1  d2
```

```
BOOL SetPropertiesMapping ( struct MMUContext *, struct MinList *,
                           ULONG, ULONG, ULONG );
```

FUNCTION

Copy the properties of a memory map to a context, thru a mask. This is equivalent to SetProperties(), except that the source data is contained in a memory map instead given as function arguments. This function is reverse to CopyContextRegion().

INPUTS

```
ctx      - destination context whose memory map shall be set.
list     - the source memory map, containing the data to be
           transfered.
base     - base address of the memory region whose properties are
           to be copied.
length   - length of the memory region in bytes whose properties
           will be transfered.
mask     - a mask of property bits, see the SetProperties()
           function for a detailed explanation. A zero bit in this
           mask means that the corresponding property in the
           destination will be left alone and will remain unchanged.
```

RESULTS

a boolean success/failure indicator, TRUE for success. On failure, the destination context will not have been touched at all.

NOTES

This call does not copy memory at all, it just defines the memory properties of the context passed in.

Check CopyMapping() to transport memory properties from one list to another, or CopyContextRegion() to transfer properties from a context to a list (the other direction).

The library will not be able to perform checks for correct page alignment, you have to do that yourself.

BUGS

SEE ALSO

SetPropertyList(), ReleaseMapping(), SetProperties(),
CopyContextRegion()

1.42 mmu.library/SetMappingProperties

NAME

SetMappingPropertiesA - set memory attributes in a memory map.

SYNOPSIS

```
result = SetMappingPropertiesA( list, flags, mask, lower, size, tags);
d0      a0      d1      d2      a1      d0      a2
```

```
int SetMappingPropertiesA( struct MinList *, ULONG, ULONG,
                          ULONG, ULONG, struct TagItem *);
```

```
result = SetMappingProperties( list, flags, mask,
                              lower, size, tag1, ...);
```

```
int SetMappingProperties( struct MinList *, ULONG, ULONG,
                          ULONG, ULONG, Tag tag1, ...);
```

FUNCTION

This call sets attributes of a certain memory range of a given memory map.

INPUTS

list - a minlist structure keeping the memory map to be altered.
 flags - a binary flags field for the attributes to define. Check SetProperties() for details about the defined bits.
 mask - A bit mask of the attributes to be changed.
 lower - The lower boundary of the logical address to be modified.
 size - Size of the region to be modified.
 tags - A tag array with additional data, identical to the tags defined for SetProperties().

RESULTS

Unlike SetProperties() or SetPageProperties(), this does not return a boolean value! The result code is 0 on failure, and different from zero on success, though. To be more precise, this routine will return "1" in case of success, and "2" in case the memory map was really altered and is now "dirty", hence upper software layers might require a "rebuild".

NOTES

This call really doesn't do anything to the MMU, it is just an administration call to modify a memory map - a handy data structure you might want to use for your own memory administration. Its

context-based equivalent `SetProperties()` will, hence, adjust the memory map which is kept by a context, and `SetPageProperties()` will perform the same operation truly on the hardware.

Since this call is not context based, the library will not be able to perform checks for correct page alignment, you have to do that yourself. Especially, note that `SetPropertyList()` – which attaches a memory map to a context – does not perform any check on this list either. Hence, **NOT** checking for page alignment here might result in an invalid context if you try to attach an incorrectly aligned list to a context later on.

BUGS

SEE ALSO

`SetPropertyList()`, `ReleaseMapping()`, `SetProperties()`, `SetPageProperties()`, `GetMappingProperties()`

1.43 mmu.library/GetMappingProperties

NAME

`GetMappingPropertiesA` – read memory attributes from a memory map.

SYNOPSIS

```
flags = GetMappingPropertiesA( list, lower, tags);
d0      a0      a1      a2
```

```
ULONG GetMappingPropertiesA( struct MinList *, ULONG,
                           struct TagItem *);
```

```
result = GetMappingProperties( list, lower, tag1, ...);
```

```
ULONG GetMappingProperties( struct MinList *, ULONG, Tag tag1, ...);
```

FUNCTION

This call reads the page properties of a certain address in memory from a memory map. It is the counterpart of `SetMappingProperties()` and the memory map analogue of `GetProperties()`.

INPUTS

`list` – a `MinList` holding the memory map, obtained from either `GetMapping()`, `DupMapping()` or `NewMapping()`.
`lower` – the logical address of the address to investigate.
`tags` – additional tags, identical to those defined for `GetProperties()`. Check the documentation of this function for details.

RESULTS

Returns a binary flags field for the attributes to define. See `SetProperties()` for details.

NOTES

This call is the analogue of the `GetProperties()` call. It operates

directly on memory maps, unlike the former which operates only on the memory map of a context. This function does not require page alignment because the mmu.library does not have a context to check the alignment restrictions, but you should note that a memory map that is to be attached to a context with DefineMapping() **HAS** to be correctly aligned.

This routine is **NOT** safe to be called from within interrupts.

BUGS

SEE ALSO

SetMappingProperties(), SetPropertyList(), GetPageProperties(),
GetProperties()

1.44 mmu.library/SetPropertyList

NAME

SetPropertyList - re-install a backup memory map

SYNOPSIS

```
SetPropertyList ( context, list );
                a0      a1
```

```
void SetPropertyList ( struct MMUContext * , struct MinList * );
```

FUNCTION

This call re-installes a property list, i.e. a complete memory map of a context, obtained from GetMapping() before.

INPUTS

context - the context the list should be installed in.
This should be the same context the list was
taken from.
list - the property list to install.

This list **MUST** have been obtained with GetMapping() before.

RESULTS

Nothing. The big advantage of this call is that it cannot fail.

NOTES

The property list will become part of the context and is empty after this call. You can't re-use it for that reason. However, you still need to call ReleaseMapping() with the list pointer you've obtained before.

For additional tips how this function should be used, see the GetMapping() function; especially, you can only un-do changes to the software abstraction level of a MMU-tree, and only as long as you haven't called RebuildTree() to translate these into hardware MMU tables. Trying to un-do these changes with SetPropertyList() will fail, and it will even fail if you call RebuildTree() afterwards. SetPropertyList() **does not** inform the software abstraction level about any changes, it is just a

quick un-do operation. (For the experts: It even re-installs the "dirty" flags).

BUGS

SEE ALSO

GetMapping(), ReleaseMapping(), RebuildTree()

1.45 mmu.library/GetMMUType

NAME

GetMMUType - return the type of the MMU available in the system.

SYNOPSIS

```
mmu = GetMMUType( );
```

```
char GetMMUType( void );
```

FUNCTION

Returns an identifier for the MMU available in the system or NUL in case no MMU is installed.

INPUTS

RETURNS

a character identifying the MMU type:

MUTYPE_NONE	no working MMU detected.
MUTYPE_68851	a 68020 system with an external 68851 MMU.
MUTYPE_68030	a 68030 MMU.
MUTYPE_68040	the internal 68040 MMU.
MUTYPE_68060	the 68060 MMU.

NOTES

The mmu library is smart enough to detect EC processors without a working MMU, but the library does not detect multiple MMUs in the system. (How?)

BUGS

SEE ALSO

mmu/mmubase.h

1.46 mmu.library/SuperContext

NAME

SuperContext - find the supervisor context for a given context.

SYNOPSIS

```
super = SuperContext( context );
```

d0 a0

```
struct MMUContext * SuperContext( struct MMUContext * );
```

FUNCTION

Returns the context that manages the supervisor mode for the user mode context passed in.

INPUTS

A user mode context or NULL for the current context.

RETURNS

A pointer to the context managing the supervisor type accesses within the current context.

NOTES

All contexts build by CreateMMUContext are by default user mode contexts. The current version of the library manages one global supervisor tree, and optionally private supervisor trees for private contexts if you ask for one on context creation.

To find the public supervisor mode context, call DefaultContext() first and pass in its return value to this function.

BUGS

SEE ALSO

DefaultContext(), CreateMMUContext()

1.47 mmu.library/DefaultContext

NAME

DefaultContext - get the global default context

SYNOPSIS

```
public = DefaultContext( );
d0
```

```
struct MMUContext * DefaultContext( void );
```

FUNCTION

Returns the global default user mode context which is used for tasks that are not attached to any other private context.

INPUTS

RETURNS

A pointer to the context managing the user mode accesses for "context less" tasks.

NOTES

A task is by default part of this default context unless you call EnterMMUContext() and attach it to a different context.

Note that you might have to enter even the default context

explicitly to be able to use certain features of the exception hook mechanism.

BUGS

SEE ALSO

SuperContext()

1.48 mmu.library/WithoutMMU

NAME

WithoutMMU - execute a short subroutine with the MMU disabled.

SYNOPSIS

```
result = WithoutMMU( userFunc );  
d0      a5
```

```
ULONG WithoutMMU(void *);
```

FUNCTION

Executes a small assembly language routine pointed to in a5 in supervisor mode, with all interrupts disabled, and the MMU disabled. All registers are preserved by this call. The function must end with an RTS instruction.

INPUTS

userFunc - A pointer to a *short* assembly language routine, ending with RTS. The function has full access to all registers.

RETURNS

whatever was left in register d0 by the called function.

NOTES

This is a low-level function. Remember that disabling the MMU might or might not be what you want, especially if memory is remapped.

Note that this function works even without a MMU. It just calls the routine in a5 in this case.

BUGS

Big trouble if the supervisor stack is in remapped memory.

SEE ALSO

exec/Supervisor(), RunOldConfig()

1.49 mmu.library/RunOldConfig

NAME

RunOldConfig - execute a short subroutine with the old MMU configuration. (V42)

SYNOPSIS

```
result = RunOldConfig( userFunc );
d0      a5
```

```
ULONG RunOldConfig(void *);
```

FUNCTION

Executes a small assembly language routine pointed to in a5 in supervisor mode, with all interrupts disabled, and the MMU configuration the library found when it was started. This could or could not be a disabled MMU.

The function must end with an RTS instruction.

INPUTS

userFunc - A pointer to a *short* assembly language routine, ending with RTS. The function has full access to all registers.

RETURNS

whatever was left in register d0 by the called function.

NOTES

This is a low-level function. Remember that reloading the MMU with the last MMU configuration might or might not be what you want, especially if memory is remapped or the MMU tables of the old configuration has been released.

Note that this function works even without a MMU. It just calls the routine in a5 in this case.

BUGS

Big trouble if the supervisor stack is in remapped memory.

SEE ALSO

exec/Supervisor(), WithoutMMU()

1.50 mmu.library/SetBusError

NAME

SetBusError - define the bus error handler.

SYNOPSIS

```
SetBusError ( newfuncptr , oldfuncptrptr );
d0      a0      a1
```

```
void SetBusError ( void (*)() , void (**)() );
```

FUNCTION

This defines the bus error handler which is called in case the MMU library exception handler was not able to handle the fault.

This happens for true physical bus errors and errors initiated by the unsupported TAS, CAS and CAS2 instructions using "locked

transfers" not supported by the amiga hardware.

The default bus error handler is whatever the library finds in the autovectors of the CPU when starting up. It is usually the exec exception handler which presents the nice guru 80000002.

INPUTS

`newfuncptr` - A pointer to the new bus error handler. It is called without any parameters in supervisor state, with the exception stack frame on the stack.
`oldfuncptrptr` - A pointer to a pointer filled in with the previously defined handler, or NULL.

RETURNS

NOTES

The function pointer is guaranteed to be flushed to memory by the library, the function pointer pointer could be used, for example, to modify the destination of a JMP instruction.

The bus error handler **MUST BE IMMEDIATELY** ready for run after this function has to be called.

This is a low-level function. You do not want to call it.

BUGS

SEE ALSO

1.51 mmu.library/GetMMUContextData

NAME

`GetMMUContextData` - read MMUContext specific data

SYNOPSIS

```
GetMMUContextData ( ctx , id );
d0          a0      d0
```

```
ULONG GetMMUContextData ( struct MMUContext * , ULONG );
```

FUNCTION

This function reads various parameters of the MMU context, indexed by an ID from `mmu/mmutags.h`. All legal tag items of `CreateMMContext()` are available, plus the following:

`MGXTAG_PAGESIZE` - Return the page size in bytes of the input context. Unlike `MCXTAG_PAGEBITS`, this is **NOT** an exponent. This is identical to `GetPageSize()`.

`MGXTAG_REMAPSIZE` - Returns the alignment restriction for remapped memory to be added to the exec memory free list. This is identical to `RemapSize()`.

MGXTAG_ROOT - Return the pointer to the root of the MMU tree. You have to cast the result to an ULONG *.

Note that you DO NOT WANT to modify this tree directly.

MGXTAG_CONFIG - Returns the pointer to a struct MMUConfig * specifying the complete MMU configuration for this context. You usually DO NOT NEED to touch this.

MGXTAG_PARENT (V43) - Returns the pointer to the parent context of a sharing context that has been created by MCXTAG_SHARE. Returns NULL otherwise.

INPUTS

ctx - A pointer to a struct MMUContext *.

id - An ID specifying which data you want to read.
NOTE THAT THIS IS NOT A TAG LIST, but just the tag item id from mmutags.h.

RETURNS

the data requested. You need to cast it to the correct type.

NOTES

BUGS

SEE ALSO

CreateMMUContext(), mmu/config.h

1.52 mmu.library/SetMMUContextData

NAME

SetMMUContextData - define MMU context specifications on the fly

SYNOPSIS

```
SetMMUContextDataA ( ctx , tags );
    a0      a1
```

```
SetMMUContextData ( ctx , ... );
```

```
void SetMMUContextDataA ( struct MMUContext * , struct TagItem * );
```

```
void SetMMUContextData ( struct MMUContext * , Tag tag1 , ... );
```

FUNCTION

This function allows to adjust *some* of the MMUContext specifications on the fly. The following tag items of the CreateMMUContext() call are supported:

MCXTAG_BLANKFILL - define the data to read from the dummy "blank" pages. Note that a **working** program should never read this data.

MCXTAG_EXECBASE - specify whether or not page 0 will be threatened specially and accesses to the first Kbyte should be emulated. If set to FALSE, the first page will be threatened as all other pages.

MCXTAG_ZEROBASE - Specify a base address for where possibly emulated zero page accesses have to be redirected to. This address is usually ignored unless the zero-page is invalidated and MCXTAG_EXEBASE is TRUE. For the messy details, check the CreateMMUContext() autodocs.

MCXTAG_LOWMEMORYLIMIT - Define the lower boundary of valid memory, used to emulate access to the zero page. Defaults to the lower boundary of chip memory. (V42)

No other tag items are valid here.

INPUTS

ctx - A pointer to a struct MMUContext *.

tags - A tag list containing the parameters to be adjusted.

RETURNS

NOTES

BUGS

SEE ALSO

CreateMMUContext(), exec/memory.h

1.53 mmu.library/BuildIndirect

NAME

BuildIndirect - build a true hardware page descriptor.

SYNOPSIS

```
descr = BuildIndirect ( ctx , address , props );
d0      a0      d0  d1
```

```
ULONG  BuildIndirect ( struct MMUContext * , ULONG , ULONG );
```

FUNCTION

This function builds a true hardware page descriptor, to be used for the MAPP_INDIRECT property.

INPUTS

ctx - the MMUContext handle in which this descriptor is to be used as the destination of a MAPP_INDIRECT descriptor.

address - in case this descriptor is "valid", this is the PHYSICAL destination address, to be told to the MMU, to which accesses will be redirected to. Unlike SetProperties(), there is **NO** MAPP_REMAPPED bit. In case you do not want remapping, set this to the logical address. DO NOT LEAVE THIS BLANK or accesses will be redirected to address 0 - which is most likely not what you want. Note that this address must be, as all other addresses the MMU cares about, page aligned! In case this descriptor is of invalid type, the address can be used for your purposes, but note that this *MUST STILL* be a number which is page aligned for the given context. It **MAY NOT** be arbitrary.

props - Properties for the descriptor to be defined. NOTE THAT THIS IS A TRUE HARDWARE DESCRIPTOR! The library WILL NOT BE ABLE to help you out by emulating missing features of one MMU or another. Instead, it will just ignore them. This means for you, specifically, that only a minor subset of the usual properties may be used safely here, and that parsing the hardware properties later on with GetIndirect() might result in different properties than you intended because of missing features of the MMU in use. To be precise, the following properties **might** be available - meaning that all others ARE NOT!

MAPP_WRITEPROTECTED - The page will be write protected. Writes to this area will cause a segmentation fault.

MAPP_USED - The "used" bit of the pages will be set. The CPU will set this bit automatically as soon as the pages are accessed.

MAPP_MODIFIED - The "modified" bit of the pages will be set. The CPU will set this bit automatically as soon as a write is performed to the page in question. DO NOT SET THIS BIT TOGETHER WITH MAPP_WRITEPROTECTED OR WITHOUT MAPP_USED or the CPU might hang.

MAPP_INVALID - The page will be marked as invalid. Accessing it will invoke the bus error hook. See below for how to mark this page as REPAIRABLE. Note that the MAPP_REPAIRABLE bit is **here** not available.

MAPP_CACHEINHIBIT - The page will be marked as non-cacheable.

MAPP_IMPRECISE - The page will be marked as "imprecise exception". MAPP_CACHEINHIBIT is mandatory in this case or this flag does nothing. Only available for the 060, ignored and read as zero

by all others.

MAPP_NONSERIALIZED - The page will be marked as serialized. MAPP_CACHEINHIBIT is mandatory if this property is selected. Only available for the 040, ignored and read as zero by all others.

MAPP_COPYBACK - The page will be marked as "copyback" instead of "writethrough". Generally recommended since this is faster for the '40 and '60. MAPP_CACHEINHIBIT *MUST* be disabled for this to work. Only available for the 040 and 060, ignored and read as zero by others.

MAPP_USERPAGE0 - Set user page attribute 0, only available for the 040 and 060, ignored and read as zero by all others.
The status of this bit appears on special pins of the CPU and might be required by some hardware, so don't play with this.

MAPP_USERPAGE1 - Set user page attribute 1, see above for details.

MAPP_GLOBAL - DIFFERENT TO SetProperties() and others!
Set the GLOBAL bit in the page descriptor, only available for the 040 and 060, ignored and read as zero by all others.
Setting this bit means that certain specialized instructions will not flush this descriptor from the cache (the ATC) of the MMU.
The mmu.library writes only descriptors without this bit set and does not use these instructions. It will always flush descriptors independent of the G bit.
There is little use of this bit.

RESULTS

a page descriptor for the current MMU in use, designed and to be used for as the destination of an MAPP_INDIRECT descriptor. NOT to be used as a true page descriptor, and NOT to be used as a table descriptor.

In case the library finds no MMU or the alignment restrictions aren't satisfied, it will return BAD_DESCRIPTOR (0x03), it WILL NOT return NULL as this is a "valid invalid" descriptor.

NOTES

Note specifically that MAPP_SUPERVISORONLY *IS NOT* supported. The mmu.library enforces a distinct user/supervisor model and as such you might want to install an invalid descriptor into the user table and a valid descriptor into the supervisor table to emulate this feature. True "supervisor only" descriptors are available for the 040 and 060 anyways, but this "emulation" works for all MMUs.

MAPP_REMAPPED is not supported either because you have to specify a physical destination address in all cases, even if no remapping has to be performed. Use the logical address as physical address in

case remapping is not desired.

MAPP_REPAIRABLE is not available because this flag is in fact an emulation provided by the library. However, you may make access faults to this page repairable by setting the MAPP_REPAIRABLE bit for the MAPP_INDIRECT descriptor that POINTS to the descriptor you're building by this call. This will be enough to inform the library about how to treat access faults.

How to use this function:

Allocate four bytes of memory, long-word aligned, or even 16 bytes line (16 byte) aligned in case you want to read back the descriptor later by GetIndirect() and calculate its TRUE PHYSICAL location with PhysicalLocation(). Use the return code of this function to mask in your properties, DO NOT ASSUME fixed properties. Build a descriptor with BuildIndirect() and install it into this memory by calling SetIndirect(). *DO NOT* write it to the memory yourself! Due to CPU caching effects, this must be done by the library. Then build a MAPP_INDIRECT descriptor, and tell the library with the MAPTAG_DESCRIPTOR tag of SetProperties() to make it point to your memory. In case you want access faults on this to be repairable, set the MAPP_REPAIRABLE bit for this call. In case you want it write protected but want to ignore write accesses, set MAPP_ROM, too. Then call RebuildTree() as usual. In case you want to exchange descriptors really fast - this is after all what indirect descriptors are designed for - build all descriptors you require in a first step and keep them. A single call to SetIndirect() will exchange them VERY RAPIDLY which is ideal for certain applications. For details, study the example code in the MMU Manual.

BUGS

Much more must be said about this function. It is definitely an advanced feature, so don't play with this in case you don't know what it does.

SEE ALSO

SetIndirect(), SetIndirectArray(), GetIndirect()

1.54 mmu.library/SetIndirect

NAME

SetIndirect - Write a page descriptor to memory

SYNOPSIS

```
SetIndirect ( destination , logical , descriptor );
           a0          a1      d0
```

```
void SetIndirect ( ULONG *, ULONG, ULONG );
```

FUNCTION

Write a page descriptor, used as the destination of one or several MAPP_INDIRECT descriptors, out to memory and make the MMU aware of the change.

INPUTS

`destination` - the memory location to which the descriptor should be written to. This is the same address specified by `MAPTAD_DESCRIPTOR` in the corresponding `SetProperties()` call. NOTE THAT THIS IS A PHYSICAL, NOT A LOGICAL ADDRESS. This must be long-word aligned, or even 16 bytes line-aligned (16 bytes aligned) in case you want to read the descriptor later with `GetIndirect()`.

`logical` - The logical address covered by this descriptor, i.e. the address of the page which this descriptor is managing. In case you installed the same descriptor for several logical addresses, specify `-1L` (this will be slower, though.)

`descriptor` - The descriptor to install.

RESULTS

doesn't return a result.

NOTES

Do NOT try to install a descriptor yourself, even though this **seems** to be more effective. Somewhat more must be done than just writing the descriptor to memory. This call ensures that the descriptor is really written out to memory, and really fetched by the MMU. Specifying `-1L` as logical address is possible and supported but **slightly** less efficient than giving the correct logical address.

This call DOES NOT ensure that all data in the page to be modified is really written out. Hence, if you change the cache mode, the protection status or the validity status of a page, you should call `CacheClearU()` or `CacheClearE()` before. This step is, however, not required in case you just changed the physical destination. The library keeps then care about the necessary cache operations itself.

This call is **very** effective, there is little reason to try this yourself, not counting the portability problems.

In case you want to install more than about four descriptors at once, you should consider using `SetIndirectArray()` which causes even less overhead in this situation.

BUGS

SEE ALSO

`SetIndirectArray()`, `GetIndirect()`, `BuildIndirect()`

1.55 mmu.library/SetIndirectArray

NAME

`SetIndirectArray` - Write multiple page descriptors to memory

SYNOPSIS

```
SetIndirectArray ( destination , descriptors , number );  
    a0    a1    d0
```

```
void SetIndirectArray ( ULONG *, ULONG *, ULONG );
```

FUNCTION

Write a complete array of page descriptors at once, re-defining the mapping for more than one page, and make the MMU aware of the changes.

INPUTS

destination - an array in memory which keeps the true hardware MMU descriptors. This address, and all subsequent addresses must have been used in the corresponding SetProperties() call to setup the descriptor.

NOTE THAT THIS IS A PHYSICAL ADDRESS. Note further that it is up to you to ensure that the (obviously continuous) array of logical addresses is not fragmented into several physical memory blocks. If this happens, you would have to call this routine several times, once for each discontinuous block.

This must be long-word aligned, or even a multiple of a 16 byte line-aligned array in case you want to read the descriptor later with GetIndirect().

descriptors - An array of pre-calculated descriptor values to be filled in. This is a logical address. Effectively, this call copies this array to its first argument.

number - The number of the descriptors to be defined. Zero is allowed here, and is a no-op.

RESULTS

doesn't return a result.

NOTES

Do NOT try to install descriptors yourself, even though this **seems** to be more effective. Somewhat more must be done than just writing the descriptors to memory. This call ensures that the descriptors are really written out to memory, and really fetched by the MMU. Note that this call does not require the logical address of the page(s) which are about to be changed, quite different to SetIndirect(). It will be therefore slower than SetIndirect() if only very descriptors are to be written.

This call DOES NOT ensure that all data in the page(s) to be modified is really written out. Hence, if you change the cache mode, the protection status or the validity status of a page, you should call CacheClearU() or CacheClearE() before.

This step is not required in case you just change the physical destination of the pages involved, the library is able to handle this transparently.

This call is **very** effective, there is little reason to try this yourself, not counting the portability problems.

If you install only one descriptor, SetIndirect() is more effective.

Note further that this call does not require the logical address of the page(s) to be provided, it will flush the complete ATC of the MMU and is therefore slower if only a few pages or even a single page has to be modified.

BUGS

SEE ALSO

SetIndirect(), GetIndirect(), BuildIndirect()

1.56 mmu.library/GetIndirect

NAME

GetIndirect - Read a hardware page descriptor from memory

SYNOPSIS

```
GetIndirect ( ctx , adt , address );
             a0    a1    d0
```

```
void GetIndirect ( struct MMUContext *,
                  struct AbstractDescriptor *, ULONG * );
```

FUNCTION

Reads a true hardware page descriptor, used as the destination of one or several MAPP_INDIRECT descriptors, and places its data in the AbstractDescriptor structure.

INPUTS

ctx - the MMU context handle this page descriptor belongs.

adt - An abstract table descriptor, to be filled out with the descriptor data.

address - the address from where the descriptor is to be read. This is the same address which has been passed as argument to the MAPTAG_DESCRIPTOR tag of the SetProperty() call when building the indirect descriptor.

All descriptors to be read by this function must reside in a separate cache line, i.e. must be part of a line (16 byte) aligned array which is a multiple of 16 bytes long. In all other cases, this call could return improper results due to cache clashes.

RESULTS

no direct result code, but the AbstractDescriptor is filled in as follows:

```
struct AbstractDescriptor {
    ULONG    atd_Pointer;
    ULONG    atd_Properties;
    UWORD    atd_LowerLimit;
    UWORD    atd_UpperLimit;
    UBYTE    atd_ThisType;
    UBYTE    atd_NextType;
```



```
        UWORD        atd_reserved;  
};
```

atd_Pointer is either the physical address the accesses to the page(s) this descriptor is installed for are redirected to, or the user data if this descriptor is of invalid type. This is the same value that was passed in as "address" argument to the corresponding BuildIndirect() call.

atd_Properties is the set of MMU properties read from the descriptor. This NEED NOT to be identical to the properties setup by BuildIndirect(), for two reasons: First, the MMU sets the USED and MODIFIED attributes as soon as any access or a write access happens to the page(s) handled by the descriptor. Second, not all MMUs support all properties. Unavailable properties are ignored by BuildIndirect(), and read as zero by this function.

All other fields are currently not documented and should not be read.

NOTES

Do NOT try to read a descriptor yourself, even though this **seems** to be more effective. Somewhat more care must be kept for doing this. NOT following this rule might even lock up your machine!

This call is **very** effective, there is little reason to try this yourself, not counting the portability problems.

BUGS

SEE ALSO

SetIndirect(), BuildIndirect(), mmu/descriptor.h