

**diff.info**

<b>COLLABORATORS</b>
----------------------

	<i>TITLE :</i> diff.info		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		August 30, 2024	

<b>REVISION HISTORY</b>
-------------------------

NUMBER	DATE	DESCRIPTION	NAME

# Contents

<b>1</b>	<b>diff.info</b>	<b>1</b>
1.1	diff.info	1
1.2	diff.info/Overview	1
1.3	diff.info/Comparison	3
1.4	diff.info/Hunks	4
1.5	diff.info/White Space	4
1.6	diff.info/Blank Lines	5
1.7	diff.info/Case Folding	5
1.8	diff.info/Specified Folding	6
1.9	diff.info/Brief	6
1.10	diff.info/Binary	7
1.11	diff.info/Output Formats	7
1.12	diff.info/Sample diff Input	8
1.13	diff.info/Normal	9
1.14	diff.info/Detailed Normal	9
1.15	diff.info/Example Normal	10
1.16	diff.info/Context	10
1.17	diff.info/Context Format	11
1.18	diff.info/Detailed Context	11
1.19	diff.info/Example Context	12
1.20	diff.info/Less Context	13
1.21	diff.info/Unified Format	14
1.22	diff.info/Detailed Unified	14
1.23	diff.info/Example Unified	15
1.24	diff.info/Sections	15
1.25	diff.info/Specified Headings	15
1.26	diff.info/C Function Headings	16
1.27	diff.info/Alternate Names	16
1.28	diff.info/Side by Side	17
1.29	diff.info/Side by Side Format	18

1.30	diff.info/Example Side by Side . . . . .	18
1.31	diff.info/Scripts . . . . .	19
1.32	diff.info/ed Scripts . . . . .	19
1.33	diff.info/Detailed ed . . . . .	20
1.34	diff.info/Example ed . . . . .	21
1.35	diff.info/Forward ed . . . . .	21
1.36	diff.info/RCS . . . . .	21
1.37	diff.info/If-then-else . . . . .	22
1.38	diff.info/Line Group Formats . . . . .	23
1.39	diff.info/Line Formats . . . . .	26
1.40	diff.info/Detailed If-then-else . . . . .	27
1.41	diff.info/Example If-then-else . . . . .	28
1.42	diff.info/Comparing Directories . . . . .	29
1.43	diff.info/Adjusting Output . . . . .	30
1.44	diff.info/Tabs . . . . .	30
1.45	diff.info/Pagination . . . . .	31
1.46	diff.info/diff Performance . . . . .	31
1.47	diff.info/Comparing Three Files . . . . .	32
1.48	diff.info/Sample diff3 Input . . . . .	32
1.49	diff.info/Detailed diff3 Normal . . . . .	33
1.50	diff.info/diff3 Hunks . . . . .	33
1.51	diff.info/Example diff3 Normal . . . . .	34
1.52	diff.info/diff3 Merging . . . . .	35
1.53	diff.info/Which Changes . . . . .	36
1.54	diff.info/Marking Conflicts . . . . .	36
1.55	diff.info/Bypassing ed . . . . .	38
1.56	diff.info/Merging Incomplete Lines . . . . .	39
1.57	diff.info/Saving the Changed File . . . . .	39
1.58	diff.info/Interactive Merging . . . . .	39
1.59	diff.info/sdiff Option Summary . . . . .	40
1.60	diff.info/Merge Commands . . . . .	40
1.61	diff.info/Merging with patch . . . . .	41
1.62	diff.info/patch Input . . . . .	42
1.63	diff.info/Imperfect . . . . .	42
1.64	diff.info/Changed White Space . . . . .	43
1.65	diff.info/Reversed Patches . . . . .	43
1.66	diff.info/Inexact . . . . .	43
1.67	diff.info/Empty Files . . . . .	45
1.68	diff.info/Multiple Patches . . . . .	45

---

1.69	diff.info/patch Messages . . . . .	45
1.70	diff.info/Making Patches . . . . .	46
1.71	diff.info/Invoking cmp . . . . .	47
1.72	diff.info/cmp Options . . . . .	48
1.73	diff.info/Invoking diff . . . . .	49
1.74	diff.info/diff Options . . . . .	49
1.75	diff.info/Invoking diff3 . . . . .	55
1.76	diff.info/diff3 Options . . . . .	55
1.77	diff.info/Invoking patch . . . . .	57
1.78	diff.info/patch Directories . . . . .	58
1.79	diff.info/Backups . . . . .	59
1.80	diff.info/Rejects . . . . .	60
1.81	diff.info/patch Options . . . . .	60
1.82	diff.info/Invoking sdiff . . . . .	63
1.83	diff.info/sdiff Options . . . . .	64
1.84	diff.info/Incomplete Lines . . . . .	66
1.85	diff.info/Projects . . . . .	66
1.86	diff.info/Shortcomings . . . . .	67
1.87	diff.info/Changing Structure . . . . .	67
1.88	diff.info/Special Files . . . . .	68
1.89	diff.info/Unusual File Names . . . . .	68
1.90	diff.info/Arbitrary Limits . . . . .	68
1.91	diff.info/Large Files . . . . .	68
1.92	diff.info/Ignoring Changes . . . . .	69
1.93	diff.info/Bugs . . . . .	69
1.94	diff.info/Concept Index . . . . .	70

# Chapter 1

## diff.info

### 1.1 diff.info

This file documents the the GNU diff, diff3, sdiff, and cmp commands for showing the differences between text files and the patch command for using their output to update files.

This is Edition 1.2, for diff 2.4 and patch 2.1.

Overview      Preliminary information.

Comparison      What file comparison means.

Output Formats      Formats for difference reports.

Comparing Directories      Comparing files and directories.

Adjusting Output      Making diff output prettier.

diff Performance      Making diff smarter or faster.

Comparing Three Files      Formats for three-way difference reports.

diff3 Merging      Merging from a common ancestor.

Interactive Merging      Interactive merging with sdiff.

Merging with patch      Using patch to change old files into new ones.

Making Patches      Tips for making patch distributions.

Invoking cmp      How to run cmp and a summary of its options.

Invoking diff      How to run diff and a summary of its options.

Invoking diff3      How to run diff3 and a summary of its options.

Invoking patch      How to run patch and a summary of its options.

Invoking sdiff      How to run sdiff and a summary of its options.

Incomplete Lines      Lines that lack trailing newlines.

Projects      If you think you've found a bug or other shortcoming.

Concept Index      Index of concepts.

### 1.2 diff.info/Overview

---

## Overview

\*\*\*\*\*

Computer users often find occasion to ask how two files differ. Perhaps one file is a newer version of the other file. Or maybe the two files started out as identical copies but were changed by different people.

You can use the `diff` command to show differences between two files, or each corresponding file in two directories. `diff` outputs differences between files line by line in any of several formats, selectable by command line options. This set of differences is often called a diff or patch. For files that are identical, `diff` normally produces no output; for binary (non-text) files, `diff` normally reports only that they are different.

You can use the `cmp` command to show the offsets and line numbers where two files differ. `cmp` can also show all the characters that differ between the two files, side by side. Another way to compare two files character by character is the Emacs command `M-x compare-windows`. See Other Window, for more information on that command.

You can use the `diff3` command to show differences among three files. When two people have made independent changes to a common original, `diff3` can report the differences between the original and the two changed versions, and can produce a merged file that contains both persons' changes together with warnings about conflicts.

You can use the `sdiff` command to merge two files interactively.

You can use the set of differences produced by `diff` to distribute updates to text files (such as program source code) to other people. This method is especially useful when the differences are small compared to the complete files. Given `diff` output, you can use the `patch` program to update, or `patch`, a copy of the file. If you think of `diff` as subtracting one file from another to produce their difference, you can think of `patch` as adding the difference to one file to reproduce the other.

This manual first concentrates on making diffs, and later shows how to use diffs to update files.

GNU `diff` was written by Mike Haertel, David Hayes, Richard Stallman, Len Tower, and Paul Eggert. Wayne Davison designed and implemented the unified output format. The basic algorithm is described in "An O(ND) Difference Algorithm and its Variations", Eugene W. Myers, 'Algorithmica' Vol. 1 No. 2, 1986, pp. 251-266; and in "A File Comparison Program", Webb Miller and Eugene W. Myers, 'Software--Practice and Experience' Vol. 15 No. 11, 1985, pp. 1025-1040. The algorithm was independently discovered as described in "Algorithms for Approximate String Matching", E. Ukkonen, 'Information and Control' Vol. 64, 1985, pp. 100-118.

GNU `diff3` was written by Randy Smith. GNU `sdiff` was written by Thomas Lord. GNU `cmp` was written by Torbjorn Granlund and David MacKenzie.

---

patch was written mainly by Larry Wall; the GNU enhancements were written mainly by Wayne Davison and David MacKenzie. Parts of this manual are adapted from a manual page written by Larry Wall, with his permission.

## 1.3 diff.info/Comparison

### What Comparison Means

\*\*\*\*\*

There are several ways to think about the differences between two files. One way to think of the differences is as a series of lines that were deleted from, inserted in, or changed in one file to produce the other file. diff compares two files line by line, finds groups of lines that differ, and reports each group of differing lines. It can report the differing lines in several formats, which have different purposes.

GNU diff can show whether files are different without detailing the differences. It also provides ways to suppress certain kinds of differences that are not important to you. Most commonly, such differences are changes in the amount of white space between words or lines. diff also provides ways to suppress differences in alphabetic case or in lines that match a regular expression that you provide. These options can accumulate; for example, you can ignore changes in both white space and alphabetic case.

Another way to think of the differences between two files is as a sequence of pairs of characters that can be either identical or different. cmp reports the differences between two files character by character, instead of line by line. As a result, it is more useful than diff for comparing binary files. For text files, cmp is useful mainly when you want to know only whether two files are identical.

To illustrate the effect that considering changes character by character can have compared with considering them line by line, think of what happens if a single newline character is added to the beginning of a file. If that file is then compared with an otherwise identical file that lacks the newline at the beginning, diff will report that a blank line has been added to the file, while cmp will report that almost every character of the two files differs.

diff3 normally compares three input files line by line, finds groups of lines that differ, and reports each group of differing lines. Its output is designed to make it easy to inspect two different sets of changes to the same file.

Hunks	Groups of differing lines.
White Space	Suppressing differences in white space.
Blank Lines	Suppressing differences in blank lines.
Case Folding	Suppressing differences in alphabetic case.
Specified Folding	Suppressing differences that match regular expressions.



Brief        Summarizing which files are different.  
Binary       Comparing binary files or forcing text comparisons.

## 1.4 diff.info/Hunks

Hunks  
=====

When comparing two files, diff finds sequences of lines common to both files, interspersed with groups of differing lines called hunks. Comparing two identical files yields one sequence of common lines and no hunks, because no lines differ. Comparing two entirely different files yields no common lines and one large hunk that contains all lines of both files. In general, there are many ways to match up lines between two given files. diff tries to minimize the total hunk size by finding large sequences of common lines interspersed with small hunks of differing lines.

For example, suppose the file F contains the three lines a, b, c, and the file G contains the same three lines in reverse order c, b, a. If diff finds the line c as common, then the command diff F G produces this output:

```
1,2d0
< a
< b
3a2,3
> b
> a
```

But if diff notices the common line b instead, it produces this output:

```
1c1
< a
---
> c
3c3
< c
---
> a
```

It is also possible to find a as the common line. diff does not always find an optimal matching between the files; it takes shortcuts to run faster. But its output is usually close to the shortest possible. You can adjust this tradeoff with the -minimal option (see diff Performance).

## 1.5 diff.info/White Space

---

### Suppressing Differences in Blank and Tab Spacing

=====

The `-b` and `-ignore-space-change` options ignore white space at line end, and considers all other sequences of one or more white space characters to be equivalent. With these options, `diff` considers the following two lines to be equivalent, where `$` denotes the line end:

```
Here lyeth  mucho rychnesse  in lytell space.  -- John Heywood$
Here lyeth mucho rychnesse in lytell space. -- John Heywood  $
```

The `-w` and `-ignore-all-space` options are stronger than `-b`. They ignore difference even if one file has white space where the other file has none. White space characters include tab, vertical tab, form feed, carriage return, and space; some locales may define additional characters to be white space. With these options, `diff` considers the following two lines to be equivalent, where `$` denotes the line end and `^M` denotes a carriage return:

```
Here lyeth  mucho  rychnesse in lytell space.-- John Heywood$
He relyeth much erychnes  seinly tells pace. --John Heywood  ^M$
```

## 1.6 diff.info/Blank Lines

### Suppressing Differences in Blank Lines

=====

The `-B` and `-ignore-blank-lines` options ignore insertions or deletions of blank lines. These options normally affect only lines that are completely empty; they do not affect lines that look empty but contain space or tab characters. With these options, for example, a file containing

```
1. A point is that which has no part.

2. A line is breadthless length.
-- Euclid, The Elements, I
```

is considered identical to a file containing

```
1. A point is that which has no part.
2. A line is breadthless length.
```

```
-- Euclid, The Elements, I
```

## 1.7 diff.info/Case Folding

### Suppressing Case Differences

=====

GNU diff can treat lowercase letters as equivalent to their uppercase counterparts, so that, for example, it considers Funky Stuff, funky STUFF, and fUNKy stuFF to all be the same. To request this, use the `-i` or `-ignore-case` option.

## 1.8 diff.info/Specified Folding

### Suppressing Lines Matching a Regular Expression

=====

To ignore insertions and deletions of lines that match a regular expression, use the `-I regexp` or `-ignore-matching-lines=regexp` option. You should escape regular expressions that contain shell metacharacters to prevent the shell from expanding them. For example, `diff -I '[0-9]'` ignores all changes to lines beginning with a digit.

However, `-I` only ignores the insertion or deletion of lines that contain the regular expression if every changed line in the hunk--every insertion and every deletion--matches the regular expression. In other words, for each nonignorable change, diff prints the complete set of changes in its vicinity, including the ignorable ones.

You can specify more than one regular expression for lines to ignore by using more than one `-I` option. diff tries to match each line against each regular expression, starting with the last one given.

## 1.9 diff.info/Brief

### Summarizing Which Files Differ

=====

When you only want to find out whether files are different, and you don't care what the differences are, you can use the summary output format. In this format, instead of showing the differences between the files, diff simply reports whether files differ. The `-q` and `-brief` options select this output format.

This format is especially useful when comparing the contents of two directories. It is also much faster than doing the normal line by line comparisons, because diff can stop analyzing the files as soon as it knows that there are any differences.

You can also get a brief indication of whether two files differ by using `cmp`. For files that are identical, `cmp` produces no output. When the files differ, by default, `cmp` outputs the byte offset and line number where the first difference occurs. You can use the `-s` option to suppress that information, so that `cmp` produces no output and reports whether the files differ using only its exit status (see Invoking `cmp`).

Unlike diff, `cmp` cannot compare directories; it can only compare two

---

files.

## 1.10 diff.info/Binary

### Binary Files and Forcing Text Comparisons

=====

If diff thinks that either of the two files it is comparing is binary (a non-text file), it normally treats that pair of files much as if the summary output format had been selected (see Brief), and reports only that the binary files are different. This is because line by line comparisons are usually not meaningful for binary files.

diff determines whether a file is text or binary by checking the first few bytes in the file; the exact number of bytes is system dependent, but it is typically several thousand. If every character in that part of the file is non-null, diff considers the file to be text; otherwise it considers the file to be binary.

Sometimes you might want to force diff to consider files to be text. For example, you might be comparing text files that contain null characters; diff would erroneously decide that those are non-text files. Or you might be comparing documents that are in a format used by a word processing system that uses null characters to indicate special formatting. You can force diff to consider all files to be text files, and compare them line by line, by using the `-a` or `-text` option. If the files you compare using this option do not in fact contain text, they will probably contain few newline characters, and the diff output will consist of hunks showing differences between long lines of whatever characters the files contain.

You can also force diff to consider all files to be binary files, and report only whether they differ (but not how). Use the `-brief` option for this.

If you want to compare two files byte by byte, you can use the `cmp` program with the `-l` option to show the values of each differing byte in the two files. With GNU `cmp`, you can also use the `-c` option to show the ASCII representation of those bytes. See Invoking `cmp`, for more information.

If diff3 thinks that any of the files it is comparing is binary (a non-text file), it normally reports an error, because such comparisons are usually not useful. diff3 uses the same test as diff to decide whether a file is binary. As with diff, if the input files contain a few non-text characters but otherwise are like text files, you can force diff3 to consider all files to be text files and compare them line by line by using the `-a` or `-text` options.

## 1.11 diff.info/Output Formats

## diff Output Formats

\*\*\*\*\*

diff has several mutually exclusive options for output format. The following sections describe each format, illustrating how diff reports the differences between two sample input files.

Sample diff Input	Sample diff input files for examples.
Normal	Showing differences without surrounding text.
Context	Showing differences with the surrounding text.
Side by Side	Showing differences in two columns.
Scripts	Generating scripts for other programs.
If-then-else	Merging files with if-then-else.

## 1.12 diff.info/Sample diff Input

### Two Sample Input Files

=====

Here are two sample files that we will use in numerous examples to illustrate the output of diff and how various options can change it.

This is the file lao:

```
The Way that can be told of is not the eternal Way;
The name that can be named is not the eternal name.
The Nameless is the origin of Heaven and Earth;
The Named is the mother of all things.
Therefore let there always be non-being,
    so we may see their subtlety,
And let there always be being,
    so we may see their outcome.
The two are the same,
But after they are produced,
    they have different names.
```

This is the file tzu:

```
The Nameless is the origin of Heaven and Earth;
The named is the mother of all things.

Therefore let there always be non-being,
    so we may see their subtlety,
And let there always be being,
    so we may see their outcome.
The two are the same,
But after they are produced,
    they have different names.
They both may be called deep and profound.
Deeper and more profound,
The door of all subtleties!
```

In this example, the first hunk contains just the first two lines of `lao`, the second hunk contains the fourth line of `lao` opposing the second and third lines of `tzu`, and the last hunk contains just the last three lines of `tzu`.

## 1.13 diff.info/Normal

Showing Differences Without Context

=====

The "normal" diff output format shows each hunk of differences without any surrounding context. Sometimes such output is the clearest way to see how lines have changed, without the clutter of nearby unchanged lines (although you can get similar results with the context or unified formats by using 0 lines of context). However, this format is no longer widely used for sending out patches; for that purpose, the context format (see Context Format) and the unified format (see Unified Format) are superior. Normal format is the default for compatibility with older versions of diff and the Posix standard.

Detailed Normal      A detailed description of normal output format.  
 Example Normal      Sample output in the normal format.

## 1.14 diff.info/Detailed Normal

Detailed Description of Normal Format

-----

The normal output format consists of one or more hunks of differences; each hunk shows one area where the files differ. Normal format hunks look like this:

```
change-command
< from-file-line
< from-file-line ...
---
> to-file-line
> to-file-line ...
```

There are three types of change commands. Each consists of a line number or comma-separated range of lines in the first file, a single character indicating the kind of change to make, and a line number or comma-separated range of lines in the second file. All line numbers are the original line numbers in each file. The types of change commands are:

lar

Add the lines in range `r` of the second file after line `l` of the first file. For example, `8a12,15` means append lines 12-15 of file

2 after line 8 of file 1; or, if changing file 2 into file 1, delete lines 12-15 of file 2.

fct

Replace the lines in range f of the first file with lines in range t of the second file. This is like a combined add and delete, but more compact. For example, 5,7c8,10 means change lines 5-7 of file 1 to read as lines 8-10 of file 2; or, if changing file 2 into file 1, change lines 8-10 of file 2 to read as lines 5-7 of file 1.

rdl

Delete the lines in range r from the first file; line l is where they would have appeared in the second file had they not been deleted. For example, 5,7d3 means delete lines 5-7 of file 1; or, if changing file 2 into file 1, append lines 5-7 of file 1 after line 3 of file 2.

## 1.15 diff.info/Example Normal

An Example of Normal Format

Here is the output of the command `diff lao tzu` (see Sample diff Input, for the complete contents of the two files). Notice that it shows only the lines that are different between the two files.

```
1,2d0
< The Way that can be told of is not the eternal Way;
< The name that can be named is not the eternal name.
4c2,3
< The Named is the mother of all things.
---
> The named is the mother of all things.
>
11a11,13
> They both may be called deep and profound.
> Deeper and more profound,
> The door of all subtleties!
```

## 1.16 diff.info/Context

Showing Differences in Their Context

Usually, when you are looking at the differences between files, you will also want to see the parts of the files near the lines that differ, to help you understand exactly what has changed. These nearby parts of the files are called the context.

GNU diff provides two output formats that show context around the

differing lines: context format and unified format. It can optionally show in which function or section of the file the differing lines are found.

If you are distributing new versions of files to other people in the form of diff output, you should use one of the output formats that show context so that they can apply the diffs even if they have made small changes of their own to the files. patch can apply the diffs in this case by searching in the files for the lines of context around the differing lines; if those lines are actually a few lines away from where the diff says they are, patch can adjust the line numbers accordingly and still apply the diff correctly. See Imperfect, for more information on using patch to apply imperfect diffs.

Context Format	An output format that shows surrounding lines.
Unified Format	A more compact output format that shows context.
Sections	Showing which sections of the files differences are in.
Alternate Names	Showing alternate file names in context headers.

## 1.17 diff.info/Context Format

Context Format

-----

The context output format shows several lines of context around the lines that differ. It is the standard format for distributing updates to source code.

To select this output format, use the `-C` lines, `-context[=lines]`, or `-c` option. The argument lines that some of these options take is the number of lines of context to show. If you do not specify lines, it defaults to three. For proper operation, patch typically needs at least two lines of context.

Detailed Context	A detailed description of the context output format.
Example Context	Sample output in context format.
Less Context	Another sample with less context.

## 1.18 diff.info/Detailed Context

Detailed Description of Context Format

.....

The context output format starts with a two-line header, which looks like this:

```
*** from-file from-file-modification-time
--- to-file to-file-modification time
```



You can change the header's content with the `-L label` or `-label=label` option; see Alternate Names.

Next come one or more hunks of differences; each hunk shows one area where the files differ. Context format hunks look like this:

```
*****
*** from-file-line-range ****
    from-file-line
    from-file-line ...
--- to-file-line-range ----
    to-file-line
    to-file-line ...
```

The lines of context around the lines that differ start with two space characters. The lines that differ between the two files start with one of the following indicator characters, followed by a space character:

!

A line that is part of a group of one or more lines that changed between the two files. There is a corresponding group of lines marked with ! in the part of this hunk for the other file.

+

An "inserted" line in the second file that corresponds to nothing in the first file.

-

A "deleted" line in the first file that corresponds to nothing in the second file.

If all of the changes in a hunk are insertions, the lines of from-file are omitted. If all of the changes are deletions, the lines of to-file are omitted.

## 1.19 diff.info/Example Context

An Example of Context Format

.....

Here is the output of `diff -c lao tzu` (see Sample diff Input, for the complete contents of the two files). Notice that up to three lines that are not different are shown around each line that is different; they are the context lines. Also notice that the first two hunks have run together, because their contents overlap.

```
*** lao  Sat Jan 26 23:30:39 1991
--- tzu  Sat Jan 26 23:30:50 1991
*****
*** 1,7 ****
- The Way that can be told of is not the eternal Way;
- The name that can be named is not the eternal name.
```

```

    The Nameless is the origin of Heaven and Earth;
! The Named is the mother of all things.
    Therefore let there always be non-being,
        so we may see their subtlety,
    And let there always be being,
--- 1,6 ----
    The Nameless is the origin of Heaven and Earth;
! The named is the mother of all things.
!
    Therefore let there always be non-being,
        so we may see their subtlety,
    And let there always be being,
*****
*** 9,11 ****
--- 8,13 ----
    The two are the same,
    But after they are produced,
        they have different names.
+ They both may be called deep and profound.
+ Deeper and more profound,
+ The door of all subtleties!

```

## 1.20 diff.info/Less Context

An Example of Context Format with Less Context

.....

Here is the output of `diff -context=1 lao tzu` (see Sample diff Input, for the complete contents of the two files). Notice that at most one context line is reported here.

```

*** lao  Sat Jan 26 23:30:39 1991
--- tzu  Sat Jan 26 23:30:50 1991
*****
*** 1,5 ****
- The Way that can be told of is not the eternal Way;
- The name that can be named is not the eternal name.
  The Nameless is the origin of Heaven and Earth;
! The Named is the mother of all things.
  Therefore let there always be non-being,
--- 1,4 ----
  The Nameless is the origin of Heaven and Earth;
! The named is the mother of all things.
!
  Therefore let there always be non-being,
*****
*** 11 ****
--- 10,13 ----
        they have different names.
+ They both may be called deep and profound.
+ Deeper and more profound,
+ The door of all subtleties!

```

## 1.21 diff.info/Unified Format

### Unified Format

-----

The unified output format is a variation on the context format that is more compact because it omits redundant context lines. To select this output format, use the `-U` lines, `-unified[=lines ]`, or `-u` option. The argument `lines` is the number of lines of context to show. When it is not given, it defaults to three.

At present, only GNU diff can produce this format and only GNU patch can automatically apply diffs in this format. For proper operation, patch typically needs at least two lines of context.

Detailed Unified      A detailed description of unified format.

Example Unified      Sample output in unified format.

## 1.22 diff.info/Detailed Unified

### Detailed Description of Unified Format

.....

The unified output format starts with a two-line header, which looks like this:

```
--- from-file from-file-modification-time
+++ to-file to-file-modification-time
```

You can change the header's content with the `-L label` or `-label=label` option; see See Alternate Names.

Next come one or more hunks of differences; each hunk shows one area where the files differ. Unified format hunks look like this:

```
@@ from-file-range to-file-range @@
   line-from-either-file
   line-from-either-file ...
```

The lines common to both files begin with a space character. The lines that actually differ between the two files have one of the following indicator characters in the left column:

```
+
  A line was added here to the first file.
```

```
-
  A line was removed here from the first file.
```

## 1.23 diff.info/Example Unified

An Example of Unified Format

.....

Here is the output of the command `diff -u lao tzu` (see Sample diff Input, for the complete contents of the two files):

```
--- lao   Sat Jan 26 23:30:39 1991
+++ tzu   Sat Jan 26 23:30:50 1991
@@ -1,7 +1,6 @@
-The Way that can be told of is not the eternal Way;
-The name that can be named is not the eternal name.
  The Nameless is the origin of Heaven and Earth;
-The Named is the mother of all things.
+The named is the mother of all things.
+
+Therefore let there always be non-being,
+    so we may see their subtlety,
+And let there always be being,
@@ -9,3 +8,6 @@
  The two are the same,
  But after they are produced,
    they have different names.
+They both may be called deep and profound.
+Deeper and more profound,
+The door of all subtleties!
```

## 1.24 diff.info/Sections

Showing Which Sections Differences Are in

-----

Sometimes you might want to know which part of the files each change falls in. If the files are source code, this could mean which function was changed. If the files are documents, it could mean which chapter or appendix was changed. GNU diff can show this by displaying the nearest section heading line that precedes the differing lines. Which lines are "section headings" is determined by a regular expression.

Specified Headings	Showing headings that match regular expressions.
C Function Headings	Showing headings of C functions.

## 1.25 diff.info/Specified Headings

Showing Lines That Match Regular Expressions

.....

To show in which sections differences occur for files that are not

source code for C or similar languages, use the `-F regexp` or `-show-function-line=regexp` option. `diff` considers lines that match the argument `regexp` to be the beginning of a section of the file. Here are suggested regular expressions for some common languages:

```
^[A-Za-z_]
    C, C++, Prolog

^(
    Lisp

^@\(chapter\|appendix\|unnumbered\|chapheading\)
    Texinfo
```

This option does not automatically select an output format; in order to use it, you must select the context format (see Context Format) or unified format (see Unified Format). In other output formats it has no effect.

The `-F` and `-show-function-line` options find the nearest unchanged line that precedes each hunk of differences and matches the given regular expression. Then they add that line to the end of the line of asterisks in the context format, or to the `@@` line in unified format. If no matching line exists, they leave the output for that hunk unchanged. If that line is more than 40 characters long, they output only the first 40 characters. You can specify more than one regular expression for such lines; `diff` tries to match each line against each regular expression, starting with the last one given. This means that you can use `-p` and `-F` together, if you wish.

## 1.26 diff.info/C Function Headings

Showing C Function Headings  
 .....

To show in which functions differences occur for C and similar languages, you can use the `-p` or `-show-c-function` option. This option automatically selects the context output format (see Context Format), with the default number of lines of context. You can override that number with `-C` lines later in the command line. You can override both the format and the number with `-U` lines later in the command line.

The `-p` and `-show-c-function` options are equivalent to `-c -F'^[_a-zA-Z$]'` (see Specified Headings). GNU `diff` provides them for the sake of convenience.

## 1.27 diff.info/Alternate Names

Showing Alternate File Names  
 -----

---

If you are comparing two files that have meaningless or uninformative names, you might want diff to show alternate names in the header of the context and unified output formats. To do this, use the `-L label` or `-label=label` option. The first time you give this option, its argument replaces the name and date of the first file in the header; the second time, its argument replaces the name and date of the second file. If you give this option more than twice, diff reports an error. The `-L` option does not affect the file names in the pr header when the `-l` or `-paginate` option is used (see [Pagination](#)).

Here are the first two lines of the output from `diff -C2 -Loriginal -Lmodified lao tzu`:

```
*** original
--- modified
```

## 1.28 diff.info/Side by Side

Showing Differences Side by Side

=====

diff can produce a side by side difference listing of two files. The files are listed in two columns with a gutter between them. The gutter contains one of the following markers:

white space

The corresponding lines are in common. That is, either the lines are identical, or the difference is ignored because of one of the `-ignore` options (see [White Space](#)).

| The corresponding lines differ, and they are either both complete or both incomplete.

< The files differ and only the first file contains the line.

> The files differ and only the second file contains the line.

( Only the first file contains the line, but the difference is ignored.

) Only the second file contains the line, but the difference is ignored.

\ The corresponding lines differ, and only the first line is incomplete.

/

The corresponding lines differ, and only the second line is incomplete.

Normally, an output line is incomplete if and only if the lines that it contains are incomplete; See Incomplete Lines. However, when an output line represents two differing lines, one might be incomplete while the other is not. In this case, the output line is complete, but its the gutter is marked \ if the first line is incomplete, / if the second line is.

Side by side format is sometimes easiest to read, but it has limitations. It generates much wider output than usual, and truncates lines that are too long to fit. Also, it relies on lining up output more heavily than usual, so its output looks particularly bad if you use varying width fonts, nonstandard tab stops, or nonprinting characters.

You can use the `sdiff` command to interactively merge side by side differences. See Interactive Merging, for more information on merging files.

Side by Side Format	Controlling side by side output format.
Example Side by Side	Sample side by side output.

## 1.29 diff.info/Side by Side Format

Controlling Side by Side Format  
=====

The `-y` or `-side-by-side` option selects side by side format. Because side by side output lines contain two input lines, they are wider than usual. They are normally 130 columns, which can fit onto a traditional printer line. You can set the length of output lines with the `-W` columns or `-width=columns` option. The output line is split into two halves of equal length, separated by a small gutter to mark differences; the right half is aligned to a tab stop so that tabs line up. Input lines that are too long to fit in half of an output line are truncated for output.

The `-left-column` option prints only the left column of two common lines. The `-suppress-common-lines` option suppresses common lines entirely.

## 1.30 diff.info/Example Side by Side

An Example of Side by Side Format  
-----

Here is the output of the command `diff -y -W 72 lao tzu` (see

---

Sample diff Input, for the complete contents of the two files).

```

The Way that can be told of is n    <
The name that can be named is no    <
The Nameless is the origin of He    The Nameless is the origin of He
The Named is the mother of all t    | The named is the mother of all t
                                     >

Therefore let there always be no    Therefore let there always be no
    so we may see their subtlety,    so we may see their subtlety,
And let there always be being,      And let there always be being,
    so we may see their outcome.     so we may see their outcome.
The two are the same,               The two are the same,
But after they are produced,        But after they are produced,
    they have different names.        they have different names.
                                     >
                                     > They both may be called deep and
                                     > Deeper and more profound,
                                     > The door of all subtleties!
```

## 1.31 diff.info/Scripts

Making Edit Scripts

=====

Several output modes produce command scripts for editing from-file to produce to-file.

```

ed Scripts      Using diff to produce commands for ed.
Forward ed      Making forward ed scripts.
RCS             A special diff output format used by RCS.
```

## 1.32 diff.info/ed Scripts

ed Scripts

-----

diff can produce commands that direct the ed text editor to change the first file into the second file. Long ago, this was the only output mode that was suitable for editing one file into another automatically; today, with patch, it is almost obsolete. Use the -e or -ed option to select this output format.

Like the normal format (see Normal), this output format does not show any context; unlike the normal format, it does not include the information necessary to apply the diff in reverse (to produce the first file if all you have is the second file and the diff).

If the file d contains the output of diff -e old new, then the command (cat d && echo w) | ed - old edits old to make it a copy of new. More generally, if d1, d2, ..., dN contain the outputs of



`diff -e old new1, diff -e new1 new2, ..., diff -e newN-1 newN,`  
 respectively, then the command `(cat d1 d2 ... dN && echo w) | ed - old`  
 edits `old` to make it a copy of `newN`.

Detailed ed        A detailed description of ed format.  
 Example ed        A sample ed script.

## 1.33 diff.info/Detailed ed

Detailed Description of ed Format

.....

The ed output format consists of one or more hunks of differences. The changes closest to the ends of the files come first so that commands that change the number of lines do not affect how ed interprets line numbers in succeeding commands. ed format hunks look like this:

```
change-command
to-file-line
to-file-line ...
.
```

Because ed uses a single period on a line to indicate the end of input, GNU diff protects lines of changes that contain a single period on a line by writing two periods instead, then writing a subsequent ed command to change the two periods into one. The ed format cannot represent an incomplete line, so if the second file ends in a changed incomplete line, diff reports an error and then pretends that a newline was appended.

There are three types of change commands. Each consists of a line number or comma-separated range of lines in the first file and a single character indicating the kind of change to make. All line numbers are the original line numbers in the file. The types of change commands are:

la        Add text from the second file after line l in the first file. For example, 8a means to add the following lines after line 8 of file 1.

rc        Replace the lines in range r in the first file with the following lines. Like a combined add and delete, but more compact. For example, 5,7c means change lines 5-7 of file 1 to read as the text file 2.

rd        Delete the lines in range r from the first file. For example, 5,7d means delete lines 5-7 of file 1.

## 1.34 diff.info/Example ed

Example ed Script

.....

Here is the output of `diff -e lao tzu` (see Sample diff Input, for the complete contents of the two files):

```
11a
They both may be called deep and profound.
Deeper and more profound,
The door of all subtleties!
.
4c
The named is the mother of all things.
.
1,2d
```

## 1.35 diff.info/Forward ed

Forward ed Scripts

-----

`diff` can produce output that is like an ed script, but with hunks in forward (front to back) order. The format of the commands is also changed slightly: command characters precede the lines they modify, spaces separate line numbers in ranges, and no attempt is made to disambiguate hunk lines consisting of a single period. Like ed format, forward ed format cannot represent incomplete lines.

Forward ed format is not very useful, because neither ed nor patch can apply diffs in this format. It exists mainly for compatibility with older versions of `diff`. Use the `-f` or `-forward-ed` option to select it.

## 1.36 diff.info/RCS

RCS Scripts

-----

The RCS output format is designed specifically for use by the Revision Control System, which is a set of free programs used for organizing different versions and systems of files. Use the `-n` or `-rcs` option to select this output format. It is like the forward ed format (see Forward ed), but it can represent arbitrary changes to the contents of a file because it avoids the forward ed format's problems with lines consisting of a single period and with incomplete lines. Instead of ending text sections with a line consisting of a single period, each command specifies the number of lines it affects; a

---

combination of the a and d commands are used instead of c. Also, if the second file ends in a changed incomplete line, then the output also ends in an incomplete line.

Here is the output of `diff -n lao tzu` (see Sample diff Input, for the complete contents of the two files):

```
d1 2
d4 1
a4 2
The named is the mother of all things.

a11 3
They both may be called deep and profound.
Deeper and more profound,
The door of all subtleties!
```

## 1.37 diff.info/If-then-else

Merging Files with If-then-else

=====

You can use `diff` to merge two files of C source code. The output of `diff` in this format contains all the lines of both files. Lines common to both files are output just once; the differing parts are separated by the C preprocessor directives `#ifdef name` or `#ifndef name`, `#else`, and `#endif`. When compiling the output, you select which version to use by either defining or leaving undefined the macro name.

To merge two files, use `diff` with the `-D name` or `-ifdef=name` option. The argument `name` is the C preprocessor identifier to use in the `#ifdef` and `#ifndef` directives.

For example, if you change an instance of `wait (&s)` to `waitpid (-1, &s, 0)` and then merge the old and new files with the `-ifdef=HAVE_WAITPID` option, then the affected part of your code might look like this:

```
do {
#ifdef HAVE_WAITPID
    if ((w = wait (&s)) < 0  &&  errno != EINTR)
#else /* HAVE_WAITPID */
    if ((w = waitpid (-1, &s, 0)) < 0  &&  errno != EINTR)
#endif /* HAVE_WAITPID */
        return w;
} while (w != child);
```

You can specify formats for languages other than C by using line group formats and line formats, as described in the next sections.

Line Group Formats	Formats for general if-then-else line groups.
Line Formats	Formats for each line in a line group.
Detailed If-then-else	A detailed description of if-then-else format.

Example If-then-else      Sample if-then-else format output.

## 1.38 diff.info/Line Group Formats

### Line Group Formats

-----

Line group formats let you specify formats suitable for many applications that allow if-then-else input, including programming languages and text formatting languages. A line group format specifies the output format for a contiguous group of similar lines.

For example, the following command compares the TeX files `old` and `new`, and outputs a merged file in which old regions are surrounded by `\begin{em}-\end{em}` lines, and new regions are surrounded by `\begin{bf}-\end{bf}` lines.

```
diff \
  --old-group-format='\begin{em}
%<\end{em}
' \
  --new-group-format='\begin{bf}
%>\end{bf}
' \
  old new
```

The following command is equivalent to the above example, but it is a little more verbose, because it spells out the default line group formats.

```
diff \
  --old-group-format='\begin{em}
%<\end{em}
' \
  --new-group-format='\begin{bf}
%>\end{bf}
' \
  --unchanged-group-format='%=' \
  --changed-group-format='\begin{em}
%<\end{em}
\begin{bf}
%>\end{bf}
' \
  old new
```

Here is a more advanced example, which outputs a diff listing with headers containing line numbers in a "plain English" style.

```
diff \
  --unchanged-group-format=' ' \
  --old-group-format='----- %dn line%(n=1?:s) deleted at %df:
%<' \
  --new-group-format='----- %dN line%(N=1?:s) added after %de:
%>' \
```

```

--changed-group-format='----- %dn line%(n=1?:s) changed at %df:
%<----- to:
%>' \
    old new

```

To specify a line group format, use diff with one of the options listed below. You can specify up to four line group formats, one for each kind of line group. You should quote format, because it typically contains shell metacharacters.

`-old-group-format=format`

These line groups are hunks containing only lines from the first file. The default old group format is the same as the changed group format if it is specified; otherwise it is a format that outputs the line group as-is.

`-new-group-format=format`

These line groups are hunks containing only lines from the second file. The default new group format is same as the the changed group format if it is specified; otherwise it is a format that outputs the line group as-is.

`-changed-group-format=format`

These line groups are hunks containing lines from both files. The default changed group format is the concatenation of the old and new group formats.

`-unchanged-group-format=format`

These line groups contain lines common to both files. The default unchanged group format is a format that outputs the line group as-is.

In a line group format, ordinary characters represent themselves; conversion specifications start with % and have one of the following forms.

%<

stands for the lines from the first file, including the trailing newline. Each line is formatted according to the old line format (see Line Formats).

%>

stands for the lines from the second file, including the trailing newline. Each line is formatted according to the new line format.

%=

stands for the lines common to both files, including the trailing newline. Each line is formatted according to the unchanged line format.

%%

stands for %.

%C'C'

where C is a single character, stands for C. C may not be a backslash or an apostrophe. For example, %c':' stands for a colon, even inside the then-part of an if-then-else format, which

a colon would normally terminate.

`%c'@{i}O'`

where O is a string of 1, 2, or 3 octal digits, stands for the character with octal code O. For example, `%c'\0'` stands for a null character.

`F n`

where F is a printf conversion specification and n is one of the following letters, stands for n's value formatted with F.

`e`

The line number of the line just before the group in the old file.

`f`

The line number of the first line in the group in the old file; equals `e + 1`.

`l`

The line number of the last line in the group in the old file.

`m`

The line number of the line just after the group in the old file; equals `l + 1`.

`n`

The number of lines in the group in the old file; equals `l - f + 1`.

`E, F, L, M, N`

Likewise, for lines in the new file.

The printf conversion specification can be `%d`, `%o`, `%x`, or `%X`, specifying decimal, octal, lower case hexadecimal, or upper case hexadecimal output respectively. After the % the following options can appear in sequence: a - specifying left-justification; an integer specifying the minimum field width; and a period followed by an optional integer specifying the minimum number of digits. For example, `%5dN` prints the number of new lines in the group in a field of width 5 characters, using the printf format `"%5d"`.

`(A=B?T:E)`

If A equals B then T else E. A and B are each either a decimal constant or a single letter interpreted as above. This format spec is equivalent to T if A's value equals B's; otherwise it is equivalent to E.

For example, `%(N=0?no:%dN) line%(N=1?:s)` is equivalent to no lines if N (the number of lines in the group in the new file) is 0, to 1 line if N is 1, and to `%dN` lines otherwise.

## 1.39 diff.info/Line Formats

### Line Formats

Line formats control how each line taken from an input file is output as part of a line group in if-then-else format.

For example, the following command outputs text with a one-column change indicator to the left of the text. The first column of output is - for deleted lines, | for added lines, and a space for unchanged lines. The formats contain newline characters where newlines are desired on output.

```
diff \
  --old-line-format='%l
', \
  --new-line-format='|l
', \
  --unchanged-line-format=' %l
', \
  old new
```

To specify a line format, use one of the following options. You should quote format, since it often contains shell metacharacters.

```
-old-line-format=format
  formats lines just from the first file.
```

```
-new-line-format=format
  formats lines just from the second file.
```

```
-unchanged-line-format=format
  formats lines common to both files.
```

```
-line-format=format
  formats all lines; in effect, it sets all three above options
  simultaneously.
```

In a line format, ordinary characters represent themselves; conversion specifications start with % and have one of the following forms.

```
%l
  stands for the the contents of the line, not counting its trailing
  newline (if any). This format ignores whether the line is
  incomplete; See Incomplete Lines.
```

```
%L
  stands for the the contents of the line, including its trailing
  newline (if any). If a line is incomplete, this format preserves
  its incompleteness.
```

```
%%
  stands for %.
```

`%c'C'`

where `C` is a single character, stands for `C`. `C` may not be a backslash or an apostrophe. For example, `%c':'` stands for a colon.

`%c'@{i}O'`

where `O` is a string of 1, 2, or 3 octal digits, stands for the character with octal code `O`. For example, `%c'\0'` stands for a null character.

`Fn`

where `F` is a `printf` conversion specification, stands for the line number formatted with `F`. For example, `%.5dn` prints the line number using the `printf` format `"%.5d"`. See Line Group Formats, for more about `printf` conversion specifications.

The default line format is `%l` followed by a newline character.

If the input contains tab characters and it is important that they line up on output, you should ensure that `%l` or `%L` in a line format is just after a tab stop (e.g. by preceding `%l` or `%L` with a tab character), or you should use the `-t` or `-expand-tabs` option.

Taken together, the line and line group formats let you specify many different formats. For example, the following command uses a format similar to `diff`'s normal format. You can tailor this command to get fine control over `diff`'s output.

```
diff \
  --old-line-format='< %l
', \
  --new-line-format='> %l
', \
  --old-group-format='%df%(f=l?:,%dl)d%dE
%<' \
  --new-group-format='%dea%dF%(F=L?:,%dL)
%>' \
  --changed-group-format='%df%(f=l?:,%dl)c%dF%(F=L?:,%dL)
%<---
%>' \
  --unchanged-group-format=' ' \
  old new
```

## 1.40 diff.info/Detailed If-then-else

### Detailed Description of If-then-else Format

---

For lines common to both files, `diff` uses the unchanged line group format. For each hunk of differences in the merged output format, if the hunk contains only lines from the first file, `diff` uses the old line group format; if the hunk contains only lines from the second file, `diff` uses the new group format; otherwise, `diff` uses the changed group format.

---



The old, new, and unchanged line formats specify the output format of lines from the first file, lines from the second file, and lines common to both files, respectively.

The option `-ifdef=name` is equivalent to the following sequence of options using shell syntax:

```
--old-group-format='#ifndef name
%<#endif /* not name */
' \
--new-group-format='#ifdef name
%>#endif /* name */
' \
--unchanged-group-format='%=' \
--changed-group-format='#ifndef name
%<#else /* name */
%>#endif /* name */
'
```

You should carefully check the diff output for proper nesting. For example, when using the `-D name` or `-ifdef=name` option, you should check that if the differing lines contain any of the C preprocessor directives `#ifdef`, `#ifndef`, `#else`, `#elif`, or `#endif`, they are nested properly and match. If they don't, you must make corrections manually. It is a good idea to carefully check the resulting code anyway to make sure that it really does what you want it to; depending on how the input files were produced, the output might contain duplicate or otherwise incorrect code.

The patch `-D name` option behaves just like the diff `-D name` option, except it operates on a file and a diff to produce a merged file; See patch Options.

## 1.41 diff.info/Example If-then-else

An Example of If-then-else Format

Here is the output of `diff -DTWO lao tzu` (see Sample diff Input, for the complete contents of the two files):

```
#ifndef TWO
The Way that can be told of is not the eternal Way;
The name that can be named is not the eternal name.
#endif /* not TWO */
The Nameless is the origin of Heaven and Earth;
#ifndef TWO
The Named is the mother of all things.
#else /* TWO */
The named is the mother of all things.

#endif /* TWO */
Therefore let there always be non-being,
    so we may see their subtlety,
```

```
And let there always be being,  
    so we may see their outcome.  
The two are the same,  
But after they are produced,  
    they have different names.  
#ifdef TWO  
They both may be called deep and profound.  
Deeper and more profound,  
The door of all subtleties!  
#endif /* TWO */
```

## 1.42 diff.info/Comparing Directories

### Comparing Directories

\*\*\*\*\*

You can use `diff` to compare some or all of the files in two directory trees. When both file name arguments to `diff` are directories, it compares each file that is contained in both directories, examining file names in alphabetical order. Normally `diff` is silent about pairs of files that contain no differences, but if you use the `-s` or `-report-identical-files` option, it reports pairs of identical files. Normally `diff` reports subdirectories common to both directories without comparing subdirectories' files, but if you use the `-r` or `-recursive` option, it compares every corresponding pair of files in the directory trees, as many levels deep as they go.

For file names that are in only one of the directories, `diff` normally does not show the contents of the file that exists; it reports only that the file exists in that directory and not in the other. You can make `diff` act as though the file existed but was empty in the other directory, so that it outputs the entire contents of the file that actually exists. (It is output as either an insertion or a deletion, depending on whether it is in the first or the second directory given.) To do this, use the `-N` or `-new-file` option.

If the older directory contains one or more large files that are not in the newer directory, you can make the patch smaller by using the `-P` or `-unidirectional-new-file` option instead of `-N`. This option is like `-N` except that it only inserts the contents of files that appear in the second directory but not the first (that is, files that were added). At the top of the patch, write instructions for the user applying the patch to remove the files that were deleted before applying the patch. See *Making Patches*, for more discussion of making patches for distribution.

To ignore some files while comparing directories, use the `-x` pattern or `-exclude=pattern` option. This option ignores any files or subdirectories whose base names match the shell pattern pattern. Unlike in the shell, a period at the start of the base of a file name matches a wildcard at the start of a pattern. You should enclose pattern in quotes so that the shell does not expand it. For example, the option `-x '*.ao]` ignores any file whose name ends with `.a` or `.o`.

---

This option accumulates if you specify it more than once. For example, using the options `-x 'RCS'` `-x '*,v'` ignores any file or subdirectory whose base name is RCS or ends with ,v.

If you need to give this option many times, you can instead put the patterns in a file, one pattern per line, and use the `-X file` or `-exclude-from=file` option.

If you have been comparing two directories and stopped partway through, later you might want to continue where you left off. You can do this by using the `-S file` or `-starting-file=file` option. This compares only the file file and all alphabetically later files in the topmost directory level.

## 1.43 diff.info/Adjusting Output

Making diff Output Prettier

\*\*\*\*\*

diff provides several ways to adjust the appearance of its output. These adjustments can be applied to any output format.

Tabs	Preserving the alignment of tabstops.
Pagination	Page numbering and timestamping diff output.

## 1.44 diff.info/Tabs

Preserving Tabstop Alignment

=====

The lines of text in some of the diff output formats are preceded by one or two characters that indicate whether the text is inserted, deleted, or changed. The addition of those characters can cause tabs to move to the next tabstop, throwing off the alignment of columns in the line. GNU diff provides two ways to make tab-aligned columns line up correctly.

The first way is to have diff convert all tabs into the correct number of spaces before outputting them; select this method with the `-t` or `-expand-tabs` option. diff assumes that tabstops are set every 8 columns. To use this form of output with patch, you must give patch the `-l` or `-ignore-white-space` option (see Changed White Space, for more information).

The other method for making tabs line up correctly is to add a tab character instead of a space after the indicator character at the beginning of the line. This ensures that all following tab characters are in the same position relative to tabstops that they were in the original files, so that the output is aligned correctly. Its

disadvantage is that it can make long lines too long to fit on one line of the screen or the paper. It also does not work with the unified output format, which does not have a space character after the change type indicator character. Select this method with the `-T` or `-initial-tab` option.

## 1.45 diff.info/Pagination

Paginating diff Output  
=====

It can be convenient to have long output page-numbered and time-stamped. The `-l` and `-paginate` options do this by sending the diff output through the `pr` program. Here is what the page header might look like for `diff -lc lao tzu`:

```
Mar 11 13:37 1991  diff -lc lao tzu Page 1
```

## 1.46 diff.info/diff Performance

diff Performance Tradeoffs  
\*\*\*\*\*

GNU diff runs quite efficiently; however, in some circumstances you can cause it to run faster or produce a more compact set of changes. There are two ways that you can affect the performance of GNU diff by changing the way it compares files.

Performance has more than one dimension. These options improve one aspect of performance at the cost of another, or they improve performance in some cases while hurting it in others.

The way that GNU diff determines which lines have changed always comes up with a near-minimal set of differences. Usually it is good enough for practical purposes. If the diff output is large, you might want diff to use a modified algorithm that sometimes produces a smaller set of differences. The `-d` or `-minimal` option does this; however, it can also cause diff to run more slowly than usual, so it is not the default behavior.

When the files you are comparing are large and have small groups of changes scattered throughout them, you can use the `-H` or `-speed-large-files` option to make a different modification to the algorithm that diff uses. If the input files have a constant small density of changes, this option speeds up the comparisons without changing the output. If not, diff might produce a larger set of differences; however, the output will still be correct.

Normally diff discards the prefix and suffix that is common to both files before it attempts to find a minimal set of differences. This

---

makes diff run faster, but occasionally it may produce non-minimal output. The `-horizon-lines=lines` option prevents diff from discarding the last lines lines of the prefix and the first lines lines of the suffix. This gives diff further opportunities to find a minimal output.

## 1.47 diff.info/Comparing Three Files

### Comparing Three Files

\*\*\*\*\*

Use the program `diff3` to compare three files and show any differences among them. (`diff3` can also merge files; see `diff3 Merging`).

The "normal" `diff3` output format shows each hunk of differences without surrounding context. Hunks are labeled depending on whether they are two-way or three-way, and lines are annotated by their location in the input files.

See `Invoking diff3`, for more information on how to run `diff3`.

Sample <code>diff3</code> Input	Sample <code>diff3</code> input for examples.
Detailed <code>diff3</code> Normal	A detailed description of normal output format.
<code>diff3</code> Hunks	The format of normal output format.
Example <code>diff3</code> Normal	Sample output in the normal format.

## 1.48 diff.info/Sample diff3 Input

### A Third Sample Input File

=====

Here is a third sample file that will be used in examples to illustrate the output of `diff3` and how various options can change it. The first two files are the same that we used for `diff` (see `Sample diff Input`). This is the third sample file, called `tao`:

```
The Way that can be told of is not the eternal Way;
The name that can be named is not the eternal name.
The Nameless is the origin of Heaven and Earth;
The named is the mother of all things.
```

```
Therefore let there always be non-being,
    so we may see their subtlety,
And let there always be being,
    so we may see their result.
The two are the same,
But after they are produced,
    they have different names.
```

-- The Way of Lao-Tzu, tr. Wing-tsit Chan

## 1.49 diff.info/Detailed diff3 Normal

Detailed Description of diff3 Normal Format

=====

Each hunk begins with a line marked ==. Three-way hunks have plain == lines, and two-way hunks have 1, 2, or 3 appended to specify which of the three input files differ in that hunk. The hunks contain copies of two or three sets of input lines each preceded by one or two commands identifying where the lines came from.

Normally, two spaces precede each copy of an input line to distinguish it from the commands. But with the -T or -initial-tab option, diff3 uses a tab instead of two spaces; this lines up tabs correctly. See Tabs, for more information.

Commands take the following forms:

file:la

This hunk appears after line l of file file, and contains no lines in that file. To edit this file to yield the other files, one must append hunk lines taken from the other files. For example, 1:1la means that the hunk follows line 11 in the first file and contains no lines from that file.

file:rc

This hunk contains the lines in the range r of file file. The range r is a comma-separated pair of line numbers, or just one number if the range is a singleton. To edit this file to yield the other files, one must change the specified lines to be the lines taken from the other files. For example, 2:11,13c means that the hunk contains lines 11 through 13 from the second file.

If the last line in a set of input lines is incomplete (see Incomplete Lines), it is distinguished on output from a full line by a following line that starts with \ .

## 1.50 diff.info/diff3 Hunks

diff3 Hunks

=====

Groups of lines that differ in two or three of the input files are called diff3 hunks, by analogy with diff hunks (see Hunks). If all three input files differ in a diff3 hunk, the hunk is called a three-way hunk; if just two input files differ, it is a two-way hunk.

As with diff, several solutions are possible. When comparing the

files A, B, and C, diff3 normally finds diff3 hunks by merging the two-way hunks output by the two commands diff A B and diff A C. This does not necessarily minimize the size of the output, but exceptions should be rare.

For example, suppose F contains the three lines a, b, f, G contains the lines g, b, g, and H contains the lines a, b, h. diff3 F G H might output the following:

```
====2
1:1c
3:1c
  a
2:1c
  g
====
1:3c
  f
2:3c
  g
3:3c
  h
```

because it found a two-way hunk containing a in the first and third files and g in the second file, then the single line b common to all three files, then a three-way hunk containing the last line of each file.

## 1.51 diff.info/Example diff3 Normal

An Example of diff3 Normal Format

=====

Here is the output of the command diff3 lao tzu tao (see Sample diff3 Input, for the complete contents of the files). Notice that it shows only the lines that are different among the three files.

```
====2
1:1,2c
3:1,2c
  The Way that can be told of is not the eternal Way;
  The name that can be named is not the eternal name.
2:0a
====1
1:4c
  The Named is the mother of all things.
2:2,3c
3:4,5c
  The named is the mother of all things.

====3
1:8c
2:7c
  so we may see their outcome.
```

```

3:9c
    so we may see their result.
====
1:11a
2:11,13c
    They both may be called deep and profound.
    Deeper and more profound,
    The door of all subtleties!
3:13,14c

    -- The Way of Lao-Tzu, tr. Wing-tsit Chan

```

## 1.52 diff.info/diff3 Merging

Merging From a Common Ancestor  
 \*\*\*\*\*

When two people have made changes to copies of the same file, diff3 can produce a merged output that contains both sets of changes together with warnings about conflicts.

One might imagine programs with names like diff4 and diff5 to compare more than three files simultaneously, but in practice the need rarely arises. You can use diff3 to merge three or more sets of changes to a file by merging two change sets at a time.

diff3 can incorporate changes from two modified versions into a common preceding version. This lets you merge the sets of changes represented by the two newer files. Specify the common ancestor version as the second argument and the two newer versions as the first and third arguments, like this:

```
diff3 mine older yours
```

You can remember the order of the arguments by noting that they are in alphabetical order.

You can think of this as subtracting older from yours and adding the result to mine, or as merging into mine the changes that would turn older into yours. This merging is well-defined as long as mine and older match in the neighborhood of each such change. This fails to be true when all three input files differ or when only older differs; we call this a conflict. When all three input files differ, we call the conflict an overlap.

diff3 gives you several ways to handle overlaps and conflicts. You can omit overlaps or conflicts, or select only overlaps, or mark conflicts with special <<<<<< and >>>>>> lines.

diff3 can output the merge results as an ed script that that can be applied to the first file to yield the merged output. However, it is usually better to have diff3 generate the merged output directly; this bypasses some problems with ed.



Which Changes	Selecting changes to incorporate.
Marking Conflicts	Marking conflicts.
Bypassing ed	Generating merged output directly.
Merging Incomplete Lines	How diff3 merges incomplete lines.
Saving the Changed File	Emulating System V behavior.

## 1.53 diff.info/Which Changes

### Selecting Which Changes to Incorporate

=====

You can select all unmerged changes from older to yours for merging into mine with the `-e` or `-ed` option. You can select only the nonoverlapping unmerged changes with `-3` or `-easy-only`, and you can select only the overlapping changes with `-x` or `-overlap-only`.

The `-e`, `-3` and `-x` options select only unmerged changes, i.e. changes where mine and yours differ; they ignore changes from older to yours where mine and yours are identical, because they assume that such changes have already been merged. If this assumption is not a safe one, you can use the `-A` or `-show-all` option (see Marking Conflicts).

Here is the output of the command `diff3` with each of these three options (see Sample `diff3` Input, for the complete contents of the files). Notice that `-e` outputs the union of the disjoint sets of changes output by `-3` and `-x`.

Output of `diff3 -e lao tzu tao:`

```
11a
    -- The Way of Lao-Tzu, tr. Wing-tsit Chan
.
8c
    so we may see their result.
.
```

Output of `diff3 -3 lao tzu tao:`

```
8c
    so we may see their result.
.
```

Output of `diff3 -x lao tzu tao:`

```
11a
    -- The Way of Lao-Tzu, tr. Wing-tsit Chan
.
```

## 1.54 diff.info/Marking Conflicts

## Marking Conflicts

=====

diff3 can mark conflicts in the merged output by bracketing them with special marker lines. A conflict that comes from two files A and B is marked as follows:

```
<<<<<<< A
lines from A
=====
lines from B
>>>>>>> B
```

A conflict that comes from three files A, B and C is marked as follows:

```
<<<<<<< A
lines from A
||||||| B
lines from B
=====
lines from C
>>>>>>> C
```

The `-A` or `-show-all` option acts like the `-e` option, except that it brackets conflicts, and it outputs all changes from older to yours, not just the unmerged changes. Thus, given the sample input files (see Sample diff3 Input), `diff3 -A lao tzu tao` puts brackets around the conflict where only tzu differs:

```
<<<<<<< tzu
=====
The Way that can be told of is not the eternal Way;
The name that can be named is not the eternal name.
>>>>>>> tao
```

And it outputs the three-way conflict as follows:

```
<<<<<<< lao
||||||| tzu
They both may be called deep and profound.
Deeper and more profound,
The door of all subtleties!
=====
-- The Way of Lao-Tzu, tr. Wing-tsit Chan
>>>>>>> tao
```

The `-E` or `-show-overlap` option outputs less information than the `-A` or `-show-all` option, because it outputs only unmerged changes, and it never outputs the contents of the second file. Thus the `-E` option acts like the `-e` option, except that it brackets the first and third files from three-way overlapping changes. Similarly, `-X` acts like `-x`, except it brackets all its (necessarily overlapping) changes. For example, for the three-way overlapping change above, the `-E` and `-X` options output the following:

```

<<<<<<< lao
=====

-- The Way of Lao-Tzu, tr. Wing-tsit Chan
>>>>>>> tao

```

If you are comparing files that have meaningless or uninformative names, you can use the `-L label` or `-label=label` option to show alternate names in the `<<<<<<<`, `|||||||` and `>>>>>>>` brackets. This option can be given up to three times, once for each input file. Thus `diff3 -A -L X -L Y -L Z A B C` acts like `diff3 -A A B C`, except that the output looks like it came from files named X, Y and Z rather than from files named A, B and C.

## 1.55 diff.info/Bypassing ed

### Generating the Merged Output Directly

With the `-m` or `-merge` option, `diff3` outputs the merged file directly. This is more efficient than using `ed` to generate it, and works even with non-text files that `ed` would reject. If you specify `-m` without an `ed` script option, `-A` (`-show-all`) is assumed.

For example, the command `diff3 -m lao tzu tao` (see Sample `diff3` Input for a copy of the input files) would output the following:

```

<<<<<<< tzu
=====
The Way that can be told of is not the eternal Way;
The name that can be named is not the eternal name.
>>>>>>> tao
The Nameless is the origin of Heaven and Earth;
The Named is the mother of all things.
Therefore let there always be non-being,
    so we may see their subtlety,
And let there always be being,
    so we may see their result.
The two are the same,
But after they are produced,
    they have different names.
<<<<<<< lao
||||||| tzu
They both may be called deep and profound.
Deeper and more profound,
The door of all subtleties!
=====

-- The Way of Lao-Tzu, tr. Wing-tsit Chan
>>>>>>> tao

```

## 1.56 diff.info/Merging Incomplete Lines

How diff3 Merges Incomplete Lines

=====

With `-m`, incomplete lines (see Incomplete Lines) are simply copied to the output as they are found; if the merged output ends in an conflict and one of the input files ends in an incomplete line, succeeding `||||||`, `=====` or `>>>>>>` brackets appear somewhere other than the start of a line because they are appended to the incomplete line.

Without `-m`, if an ed script option is specified and an incomplete line is found, diff3 generates a warning and acts as if a newline had been present.

## 1.57 diff.info/Saving the Changed File

Saving the Changed File

=====

Traditional Unix diff3 generates an ed script without the trailing `w` and `q` commands that save the changes. System V diff3 generates these extra commands. GNU diff3 normally behaves like traditional Unix diff3, but with the `-i` option it behaves like System V diff3 and appends the `w` and `q` commands.

The `-i` option requires one of the ed script options `-AeExX3`, and is incompatible with the merged output option `-m`.

## 1.58 diff.info/Interactive Merging

Interactive Merging with `sdiff`

\*\*\*\*\*

With `sdiff`, you can merge two files interactively based on a side-by-side `-y` format comparison (see Side by Side). Use `-o file` or `-output=file` to specify where to put the merged text. See Invoking `sdiff`, for more details on the options to `sdiff`.

Another way to merge files interactively is to use the Emacs Lisp package `emerge`. See `emerge`, for more information.

`sdiff` Option Summary    Summary of `sdiff` options.

Merge Commands        Merging two files interactively.

## 1.59 diff.info/sdiff Option Summary

Specifying diff Options to sdiff

=====

The following sdiff options have the same meaning as for diff. See diff Options, for the use of these options.

```
-a -b -d -i -t -v
-B -H -I regexp

--ignore-blank-lines  --ignore-case
--ignore-matching-lines=regexp  --ignore-space-change
--left-column  --minimal  --speed-large-files
--suppress-common-lines  --expand-tabs
--text  --version  --width=columns
```

For historical reasons, sdiff has alternate names for some options. The `-l` option is equivalent to the `-left-column` option, and similarly `-s` is equivalent to `-suppress-common-lines`. The meaning of the sdiff `-w` and `-W` options is interchanged from that of diff: with sdiff, `-w` columns is equivalent to `-width=columns`, and `-W` is equivalent to `-ignore-all-space`. sdiff without the `-o` option is equivalent to diff with the `-y` or `-side-by-side` option (see Side by Side).

## 1.60 diff.info/Merge Commands

Merge Commands

=====

Groups of common lines, with a blank gutter, are copied from the first file to the output. After each group of differing lines, sdiff prompts with % and pauses, waiting for one of the following commands. Follow each command with RET.

- e
 

Discard both versions. Invoke a text editor on an empty temporary file, then copy the resulting file to the output.
- eb
 

Concatenate the two versions, edit the result in a temporary file, then copy the edited result to the output.
- el
 

Edit a copy of the left version, then copy the result to the output.
- er
 

Edit a copy of the right version, then copy the result to the output.
- l
 

Copy the left version to the output.

```

q      Quit.

r      Copy the right version to the output.

s      Silently copy common lines.

v      Verbosely copy common lines.  This is the default.

```

The text editor invoked is specified by the EDITOR environment variable if it is set. The default is system-dependent.

## 1.61 diff.info/Merging with patch

Merging with patch

\*\*\*\*\*

patch takes comparison output produced by diff and applies the differences to a copy of the original file, producing a patched version. With patch, you can distribute just the changes to a set of files instead of distributing the entire file set; your correspondents can apply patch to update their copy of the files with your changes. patch automatically determines the diff format, skips any leading or trailing headers, and uses the headers to determine which file to patch. This lets your correspondents feed an article or message containing a difference listing directly to patch.

patch detects and warns about common problems like forward patches. It saves the original version of the files it patches, and saves any patches that it could not apply. It can also maintain a patchlevel.h file to ensure that your correspondents apply diffs in the proper order.

patch accepts a series of diffs in its standard input, usually separated by headers that specify which file to patch. It applies diff hunks (see Hunks) one by one. If a hunk does not exactly match the original file, patch uses heuristics to try to patch the file as well as it can. If no approximate match can be found, patch rejects the hunk and skips to the next hunk. patch normally replaces each file f with its new version, saving the original file in f.orig, and putting reject hunks (if any) into f.rej.

See Invoking patch, for detailed information on the options to patch. See Backups, for more information on how patch names backup files. See Rejects, for more information on where patch puts reject hunks.

patch Input	Selecting the type of patch input.
Imperfect	Dealing with imperfect patches.

Empty Files        Removing empty files after patching.  
Multiple Patches    Handling multiple patches in a file specially.  
patch Messages     Messages and questions patch can produce.

## 1.62 diff.info/patch Input

### Selecting the patch Input Format

=====

patch normally determines which diff format the patch file uses by examining its contents. For patch files that contain particularly confusing leading text, you might need to use one of the following options to force patch to interpret the patch file as a certain format of diff. The output formats listed here are the only ones that patch can understand.

-c  
-context  
    context diff.

-e  
-ed  
    ed script.

-n  
-normal  
    normal diff.

-u  
-unified  
    unified diff.

## 1.63 diff.info/Imperfect

### Applying Imperfect Patches

=====

patch tries to skip any leading text in the patch file, apply the diff, and then skip any trailing text. Thus you can feed a news article or mail message directly to patch, and it should work. If the entire diff is indented by a constant amount of white space, patch automatically ignores the indentation.

However, certain other types of imperfect input require user intervention.

Changed White Space    When tabs and spaces don't match exactly.  
Reversed Patches       Applying reversed patches correctly.  
Inexact                Helping patch find close matches.

## 1.64 diff.info/Changed White Space

### Applying Patches with Changed White Space

---

Sometimes mailers, editors, or other programs change spaces into tabs, or vice versa. If this happens to a patch file or an input file, the files might look the same, but patch will not be able to match them properly. If this problem occurs, use the `-l` or `-ignore-white-space` option, which makes patch compare white space loosely so that any sequence of white space in the patch file matches any sequence of white space in the input files. Non-white-space characters must still match exactly. Each line of the context must still match a line in the input file.

## 1.65 diff.info/Reversed Patches

### Applying Reversed Patches

---

Sometimes people run diff with the new file first instead of second. This creates a diff that is "reversed". To apply such patches, give patch the `-R` or `-reverse` option. patch then attempts to swap each hunk around before applying it. Rejects come out in the swapped format. The `-R` option does not work with ed scripts because there is too little information in them to reconstruct the reverse operation.

Often patch can guess that the patch is reversed. If the first hunk of a patch fails, patch reverses the hunk to see if it can apply it that way. If it can, patch asks you if you want to have the `-R` option set; if it can't, patch continues to apply the patch normally. This method cannot detect a reversed patch if it is a normal diff and the first command is an append (which should have been a delete) since appends always succeed, because a null context matches anywhere. But most patches add or change lines rather than delete them, so most reversed normal diffs begin with a delete, which fails, and patch notices.

If you apply a patch that you have already applied, patch thinks it is a reversed patch and offers to un-apply the patch. This could be construed as a feature. If you did this inadvertently and you don't want to un-apply the patch, just answer `n` to this offer and to the subsequent "apply anyway" question--or type `C-c` to kill the patch process.

## 1.66 diff.info/Inexact

---



## Helping patch Find Inexact Matches

-----

For context diffs, and to a lesser extent normal diffs, patch can detect when the line numbers mentioned in the patch are incorrect, and it attempts to find the correct place to apply each hunk of the patch. As a first guess, it takes the line number mentioned in the hunk, plus or minus any offset used in applying the previous hunk. If that is not the correct place, patch scans both forward and backward for a set of lines matching the context given in the hunk.

First patch looks for a place where all lines of the context match. If it cannot find such a place, and it is reading a context or unified diff, and the maximum fuzz factor is set to 1 or more, then patch makes another scan, ignoring the first and last line of context. If that fails, and the maximum fuzz factor is set to 2 or more, it makes another scan, ignoring the first two and last two lines of context are ignored. It continues similarly if the maximum fuzz factor is larger.

The `-F lines` or `-fuzz=lines` option sets the maximum fuzz factor to lines. This option only applies to context and unified diffs; it ignores up to lines lines while looking for the place to install a hunk. Note that a larger fuzz factor increases the odds of making a faulty patch. The default fuzz factor is 2; it may not be set to more than the number of lines of context in the diff, ordinarily 3.

If patch cannot find a place to install a hunk of the patch, it writes the hunk out to a reject file (see Rejects, for information on how reject files are named). It writes out rejected hunks in context format no matter what form the input patch is in. If the input is a normal or ed diff, many of the contexts are simply null. The line numbers on the hunks in the reject file may be different from those in the patch file: they show the approximate location where patch thinks the failed hunks belong in the new file rather than in the old one.

As it completes each hunk, patch tells you whether the hunk succeeded or failed, and if it failed, on which line (in the new file) patch thinks the hunk should go. If this is different from the line number specified in the diff, it tells you the offset. A single large offset may indicate that patch installed a hunk in the wrong place. patch also tells you if it used a fuzz factor to make the match, in which case you should also be slightly suspicious.

patch cannot tell if the line numbers are off in an ed script, and can only detect wrong line numbers in a normal diff when it finds a change or delete command. It may have the same problem with a context diff using a fuzz factor equal to or greater than the number of lines of context shown in the diff (typically 3). In these cases, you should probably look at a context diff between your original and patched input files to see if the changes make sense. Compiling without errors is a pretty good indication that the patch worked, but not a guarantee.

patch usually produces the correct results, even when it must make many guesses. However, the results are guaranteed only when the patch is applied to an exact copy of the file that the patch was generated from.

## 1.67 diff.info/Empty Files

### Removing Empty Files =====

Sometimes when comparing two directories, the first directory contains a file that the second directory does not. If you give diff the `-N` or `-new-file` option, it outputs a diff that deletes the contents of this file. By default, patch leaves an empty file after applying such a diff. The `-E` or `-remove-empty-files` option to patch deletes output files that are empty after applying the diff.

## 1.68 diff.info/Multiple Patches

### Multiple Patches in a File =====

If the patch file contains more than one patch, patch tries to apply each of them as if they came from separate patch files. This means that it determines the name of the file to patch for each patch, and that it examines the leading text before each patch for file names and prerequisite revision level (see Making Patches, for more on that topic).

For the second and subsequent patches in the patch file, you can give options and another original file name by separating their argument lists with a `+`. However, the argument list for a second or subsequent patch may not specify a new patch file, since that does not make sense.

For example, to tell patch to strip the first three slashes from the name of the first patch in the patch file and none from subsequent patches, and to use `code.c` as the first input file, you can use:

```
patch -p3 code.c + -p0 < patchfile
```

The `-S` or `-skip` option ignores the current patch from the patch file, but continue looking for the next patch in the file. Thus, to ignore the first and third patches in the patch file, you can use:

```
patch -S + + -S + < patch file
```

## 1.69 diff.info/patch Messages

### Messages and Questions from patch =====

patch can produce a variety of messages, especially if it has trouble decoding its input. In a few situations where it's not sure how to proceed, patch normally prompts you for more information from the keyboard. There are options to suppress printing non-fatal messages and stopping for keyboard input.

The message Hmm... indicates that patch is reading text in the patch file, attempting to determine whether there is a patch in that text, and if so, what kind of patch it is.

You can inhibit all terminal output from patch, unless an error occurs, by using the `-s`, `-quiet`, or `-silent` option.

There are two ways you can prevent patch from asking you any questions. The `-f` or `-force` option assumes that you know what you are doing. It assumes the following:

- \* skip patches that do not contain file names in their headers;
- \* patch files even though they have the wrong version for the Prereq: line in the patch;
- \* assume that patches are not reversed even if they look like they are.

The `-t` or `-batch` option is similar to `-f`, in that it suppresses questions, but it makes somewhat different assumptions:

- \* skip patches that do not contain file names in their headers (the same as `-f`);
- \* skip patches for which the file has the wrong version for the Prereq: line in the patch;
- \* assume that patches are reversed if they look like they are.

patch exits with a non-zero status if it creates any reject files. When applying a set of patches in a loop, you should check the exit status, so you don't apply a later patch to a partially patched file.

## 1.70 diff.info/Making Patches

### Tips for Making Patch Distributions

\*\*\*\*\*

Here are some things you should keep in mind if you are going to distribute patches for updating a software package.

Make sure you have specified the file names correctly, either in a context diff header or with an `Index:` line. If you are patching files in a subdirectory, be sure to tell the patch user to specify a `-p` or `-strip` option as needed. Take care to not send out reversed patches, since these make people wonder whether they have already applied the patch.

---

To save people from partially applying a patch before other patches that should have gone before it, you can make the first patch in the patch file update a file with a name like `patchlevel.h` or `version.c`, which contains a patch level or version number. If the input file contains the wrong version number, `patch` will complain immediately.

An even clearer way to prevent this problem is to put a `Prereq:` line before the patch. If the leading text in the patch file contains a line that starts with `Prereq:`, `patch` takes the next word from that line (normally a version number) and checks whether the next input file contains that word, preceded and followed by either white space or a newline. If not, `patch` prompts you for confirmation before proceeding. This makes it difficult to accidentally apply patches in the wrong order.

Since `patch` does not handle incomplete lines properly, make sure that all the source files in your program end with a newline whenever you release a version.

To create a patch that changes an older version of a package into a newer version, first make a copy of the older version in a scratch directory. Typically you do that by unpacking a tar or shar archive of the older version.

You might be able to reduce the size of the patch by renaming or removing some files before making the patch. If the older version of the package contains any files that the newer version does not, or if any files have been renamed between the two versions, make a list of `rm` and `mv` commands for the user to execute in the old version directory before applying the patch. Then run those commands yourself in the scratch directory.

If there are any files that you don't need to include in the patch because they can easily be rebuilt from other files (for example, TAGS and output from yacc and makeinfo), replace the versions in the scratch directory with the newer versions, using `rm` and `ln` or `cp`.

Now you can create the patch. The de-facto standard diff format for patch distributions is context format with two lines of context, produced by giving `diff` the `-C 2` option. Do not use less than two lines of context, because `patch` typically needs at least two lines for proper operation. Give `diff` the `-P` option in case the newer version of the package contains any files that the older one does not. Make sure to specify the scratch directory first and the newer directory second.

Add to the top of the patch a note telling the user any `rm` and `mv` commands to run before applying the patch. Then you can remove the scratch directory.

## 1.71 diff.info/Invoking cmp

Invoking cmp  
\*\*\*\*\*

---

The `cmp` command compares two files, and if they differ, tells the first byte and line number where they differ. Its arguments are as follows:

```
cmp options ... from-file [to-file ]
```

The file name `-` is always the standard input. `cmp` also uses the standard input if one file name is omitted.

An exit status of 0 means no differences were found, 1 means some differences were found, and 2 means trouble.

cmp Options          Summary of options to `cmp`.

## 1.72 diff.info/cmp Options

Options to `cmp`  
=====

Below is a summary of all of the options that GNU `cmp` accepts. Most options have two equivalent names, one of which is a single letter preceded by `-`, and the other of which is a long name preceded by `-`. Multiple single letter options (unless they take an argument) can be combined into a single command line word: `-cl` is equivalent to `-c -l`.

- `-c`  
Print the differing characters. Display control characters as a ^ followed by a letter of the alphabet and precede characters that have the high bit set with M- (which stands for "meta").
  - `-ignore-initial=bytes`  
Ignore any differences in the the first bytes bytes of the input files. Treat files with fewer than bytes bytes as if they are empty.
  - `-l`  
Print the (decimal) offsets and (octal) values of all differing bytes.
  - `-print-chars`  
Print the differing characters. Display control characters as a ^ followed by a letter of the alphabet and precede characters that have the high bit set with M- (which stands for "meta").
  - `-quiet`
  - `-s`
  - `-silent`  
Do not print anything; only return an exit status indicating whether the files differ.
  - `-verbose`  
Print the (decimal) offsets and (octal) values of all differing
-

bytes.

-v

-version

Output the version number of cmp.

## 1.73 diff.info/Invoking diff

Invoking diff

\*\*\*\*\*

The format for running the diff command is:

```
diff options ... from-file to-file
```

In the simplest case, diff compares the contents of the two files from-file and to-file. A file name of - stands for text read from the standard input. As a special case, diff - - compares a copy of standard input to itself.

If from-file is a directory and to-file is not, diff compares the file in from-file whose file name is that of to-file, and vice versa. The non-directory file must not be -.

If both from-file and to-file are directories, diff compares corresponding files in both directories, in alphabetical order; this comparison is not recursive unless the -r or -recursive option is given. diff never compares the actual contents of a directory as if it were a file. The file that is fully specified may not be standard input, because standard input is nameless and the notion of "file with the same name" does not apply.

diff options begin with -, so normally from-file and to-file may not begin with -. However, - as an argument by itself treats the remaining arguments as file names even if they begin with -.

An exit status of 0 means no differences were found, 1 means some differences were found, and 2 means trouble.

diff Options      Summary of options to diff.

## 1.74 diff.info/diff Options

Options to diff

=====

Below is a summary of all of the options that GNU diff accepts. Most options have two equivalent names, one of which is a single letter preceded by -, and the other of which is a long name preceded by -.

Multiple single letter options (unless they take an argument) can be combined into a single command line word: `-ac` is equivalent to `-a -c`. Long named options can be abbreviated to any unique prefix of their name. Brackets ([ and ]) indicate that an option takes an optional argument.

`-lines`

Show `lines` (an integer) lines of context. This option does not specify an output format by itself; it has no effect unless it is combined with `-c` (see Context Format) or `-u` (see Unified Format). This option is obsolete. For proper operation, patch typically needs at least two lines of context.

`-a`

Treat all files as text and compare them line-by-line, even if they do not seem to be text. See Binary.

`-b`

Ignore changes in amount of white space. See White Space.

`-B`

Ignore changes that just insert or delete blank lines. See Blank Lines.

`-brief`

Report only whether the files differ, not the details of the differences. See Brief.

`-c`

Use the context output format. See Context Format.

`-C lines`

`-context[=lines ]`

Use the context output format, showing `lines` (an integer) lines of context, or three if `lines` is not given. See Context Format. For proper operation, patch typically needs at least two lines of context.

`-changed-group-format=format`

Use `format` to output a line group containing differing lines from both files in if-then-else format. See Line Group Formats.

`-d`

Change the algorithm perhaps find a smaller set of changes. This makes diff slower (sometimes much slower). See diff Performance.

`-D name`

Make merged `#ifdef` format output, conditional on the preprocessor macro `name`. See If-then-else.

`-e`

`-ed`

Make output that is a valid ed script. See ed Scripts.

`-exclude=pattern`

When comparing directories, ignore files and subdirectories whose basenames match `pattern`. See Comparing Directories.

---

- 
- exclude-from=file  
When comparing directories, ignore files and subdirectories whose basenames match any pattern contained in file. See Comparing Directories.
  - expand-tabs  
Expand tabs to spaces in the output, to preserve the alignment of tabs in the input files. See Tabs.
  - f  
Make output that looks vaguely like an ed script but has changes in the order they appear in the file. See Forward ed.
  - F regexp  
In context and unified format, for each hunk of differences, show some of the last preceding line that matches regexp. See Specified Headings.
  - forward-ed  
Make output that looks vaguely like an ed script but has changes in the order they appear in the file. See Forward ed.
  - h  
This option currently has no effect; it is present for Unix compatibility.
  - H  
Use heuristics to speed handling of large files that have numerous scattered small changes. See diff Performance.
  - horizon-lines=lines  
Do not discard the last lines lines of the common prefix and the first lines lines of the common suffix. See diff Performance.
  - i  
Ignore changes in case; consider upper- and lower-case letters equivalent. See Case Folding.
  - I regexp  
Ignore changes that just insert or delete lines that match regexp. See Specified Folding.
  - ifdef=name  
Make merged if-then-else output using format. See If-then-else.
  - ignore-all-space  
Ignore white space when comparing lines. See White Space.
  - ignore-blank-lines  
Ignore changes that just insert or delete blank lines. See Blank Lines.
  - ignore-case  
Ignore changes in case; consider upper- and lower-case to be the same. See Case Folding.
-



- ignore-matching-lines=regex  
Ignore changes that just insert or delete lines that match regex.  
See Specified Folding.
  - ignore-space-change  
Ignore changes in amount of white space. See White Space.
  - initial-tab  
Output a tab rather than a space before the text of a line in normal or context format. This causes the alignment of tabs in the line to look normal. See Tabs.
  - l  
Pass the output through pr to paginate it. See Pagination.
  - L label  
Use label instead of the file name in the context format (see Context Format) and unified format (see Unified Format) headers.  
See RCS.
  - label=label  
Use label instead of the file name in the context format (see Context Format) and unified format (see Unified Format) headers.
  - left-column  
Print only the left column of two common lines in side by side format. See Side by Side Format.
  - line-format=format  
Use format to output all input lines in if-then-else format. See Line Formats.
  - minimal  
Change the algorithm to perhaps find a smaller set of changes.  
This makes diff slower (sometimes much slower). See diff Performance.
  - n  
Output RCS-format diffs; like -f except that each command specifies the number of lines affected. See RCS.
  - N
  - new-file  
In directory comparison, if a file is found in only one directory, treat it as present but empty in the other directory. See Comparing Directories.
  - new-group-format=format  
Use format to output a group of lines taken from just the second file in if-then-else format. See Line Group Formats.
  - new-line-format=format  
Use format to output a line taken from just the second file in if-then-else format. See Line Formats.
  - old-group-format=format  
Use format to output a group of lines taken from just the first
-

file in if-then-else format. See Line Group Formats.

`-old-line-format=format`

Use format to output a line taken from just the first file in if-then-else format. See Line Formats.

`-P`

Show which C function each change is in. See C Function Headings.

`-P`

When comparing directories, if a file appears only in the second directory of the two, treat it as present but empty in the other. See Comparing Directories.

`-paginate`

Pass the output through pr to paginate it. See Pagination.

`-q`

Report only whether the files differ, not the details of the differences. See Brief.

`-r`

When comparing directories, recursively compare any subdirectories found. See Comparing Directories.

`-rcs`

Output RCS-format diffs; like `-f` except that each command specifies the number of lines affected. See RCS.

`-recursive`

When comparing directories, recursively compare any subdirectories found. See Comparing Directories.

`-report-identical-files`

Report when two files are the same. See Comparing Directories.

`-s`

Report when two files are the same. See Comparing Directories.

`-S file`

When comparing directories, start with the file file. This is used for resuming an aborted comparison. See Comparing Directories.

`-sdiff-merge-assist`

Print extra information to help sdiff. sdiff uses this option when it runs diff. This option is not intended for users to use directly.

`-show-c-function`

Show which C function each change is in. See C Function Headings.

`-show-function-line=regexp`

In context and unified format, for each hunk of differences, show some of the last preceding line that matches regexp. See Specified Headings.

---

- side-by-side  
Use the side by side output format. See Side by Side Format.
  - speed-large-files  
Use heuristics to speed handling of large files that have numerous scattered small changes. See diff Performance.
  - starting-file=file  
When comparing directories, start with the file file. This is used for resuming an aborted comparison. See Comparing Directories.
  - suppress-common-lines  
Do not print common lines in side by side format. See Side by Side Format.
  - t  
Expand tabs to spaces in the output, to preserve the alignment of tabs in the input files. See Tabs.
  - T  
Output a tab rather than a space before the text of a line in normal or context format. This causes the alignment of tabs in the line to look normal. See Tabs.
  - text  
Treat all files as text and compare them line-by-line, even if they do not appear to be text. See Binary.
  - u  
Use the unified output format. See Unified Format.
  - unchanged-group-format=format  
Use format to output a group of common lines taken from both files in if-then-else format. See Line Group Formats.
  - unchanged-line-format=format  
Use format to output a line common to both files in if-then-else format. See Line Formats.
  - unidirectional-new-file  
When comparing directories, if a file appears only in the second directory of the two, treat it as present but empty in the other. See Comparing Directories.
  - U lines  
-unified[=lines ]  
Use the unified output format, showing lines (an integer) lines of context, or three if lines is not given. See Unified Format. For proper operation, patch typically needs at least two lines of context.
  - v
  - version  
Output the version number of diff.
  - w
-

Ignore white space when comparing lines. See White Space.

-W columns

-width=columns

Use an output width of columns in side by side format. See Side by Side Format.

-x pattern

When comparing directories, ignore files and subdirectories whose basenames match pattern. See Comparing Directories.

-X file

When comparing directories, ignore files and subdirectories whose basenames match any pattern contained in file. See Comparing Directories.

-y

Use the side by side output format. See Side by Side Format.

## 1.75 diff.info/Invoking diff3

Invoking diff3

\*\*\*\*\*

The diff3 command compares three files and outputs descriptions of their differences. Its arguments are as follows:

diff3 options ... mine older yours

The files to compare are mine, older, and yours. At most one of these three file names may be -, which tells diff3 to read the standard input for that file.

An exit status of 0 means diff3 was successful, 1 means some conflicts were found, and 2 means trouble.

diff3 Options      Summary of options to diff3.

## 1.76 diff.info/diff3 Options

Options to diff3

=====

Below is a summary of all of the options that GNU diff3 accepts. Multiple single letter options (unless they take an argument) can be combined into a single command line argument.

-a

Treat all files as text and compare them line-by-line, even if they

do not appear to be text. See Binary.

-A

Incorporate all changes from older to yours into mine, surrounding all conflicts with bracket lines. See Marking Conflicts.

-e

Generate an ed script that incorporates all the changes from older to yours into mine. See Which Changes.

-E

Like -e, except bracket lines from overlapping changes' first and third files. See Marking Conflicts. With -e, an overlapping change looks like this:

```
<<<<<<< mine
lines from mine
=====
lines from yours
>>>>>>> yours
```

-ed

Generate an ed script that incorporates all the changes from older to yours into mine. See Which Changes.

-easy-only

Like -e, except output only the nonoverlapping changes. See Which Changes.

-i

Generate w and q commands at the end of the ed script for System V compatibility. This option must be combined with one of the -AeExX3 options, and may not be combined with -m. See Saving the Changed File.

-initial-tab

Output a tab rather than two spaces before the text of a line in normal format. This causes the alignment of tabs in the line to look normal. See Tabs.

-L label

-label=label

Use the label label for the brackets output by the -A, -E and -X options. This option may be given up to three times, one for each input file. The default labels are the names of the input files. Thus diff3 -L X -L Y -L Z -m A B C acts like diff3 -m A B C, except that the output looks like it came from files named X, Y and Z rather than from files named A, B and C. See Marking Conflicts.

-m

-merge

Apply the edit script to the first file and send the result to standard output. Unlike piping the output from diff3 to ed, this works even for binary files and incomplete lines. -A is assumed if no edit script option is specified. See Bypassing ed.

---

- overlap-only  
Like -e, except output only the overlapping changes. See Which Changes.
- show-all  
Incorporate all unmerged changes from older to yours into mine, surrounding all overlapping changes with bracket lines. See Marking Conflicts.
- show-overlap  
Like -e, except bracket lines from overlapping changes' first and third files. See Marking Conflicts.
- T  
Output a tab rather than two spaces before the text of a line in normal format. This causes the alignment of tabs in the line to look normal. See Tabs.
- text  
Treat all files as text and compare them line-by-line, even if they do not appear to be text. See Binary.
- v
- version  
Output the version number of diff3.
- x  
Like -e, except output only the overlapping changes. See Which Changes.
- X  
Like -E, except output only the overlapping changes. In other words, like -x, except bracket changes as in -E. See Marking Conflicts.
- 3  
Like -e, except output only the nonoverlapping changes. See Which Changes.

## 1.77 diff.info/Invoking patch

Invoking patch

\*\*\*\*\*

Normally patch is invoked like this:

```
patch <patchfile
```

The full format for invoking patch is:

```
patch options ... [origfile [patchfile ]] [+ options ... [origfile ]]...
```

If you do not specify patchfile, or if patchfile is -, patch reads the patch (that is, the diff output) from the standard input.

---

You can specify one or more of the original files as `orig` arguments; each one and options for interpreting it is separated from the others with a `+`. See [Multiple Patches](#), for more information.

If you do not specify an input file on the command line, `patch` tries to figure out from the leading text (any text in the patch that comes before the diff output) which file to edit. In the header of a context or unified diff, `patch` looks in lines beginning with `***`, `--`, or `+++`; among those, it chooses the shortest name of an existing file. Otherwise, if there is an `Index:` line in the leading text, `patch` tries to use the file name from that line. If `patch` cannot figure out the name of an existing file from the leading text, it prompts you for the name of the file to patch.

If the input file does not exist or is read-only, and a suitable RCS or SCCS file exists, `patch` attempts to check out or get the file before proceeding.

By default, `patch` replaces the original input file with the patched version, after renaming the original file into a backup file (see [Backups](#), for a description of how `patch` names backup files). You can also specify where to put the output with the `-o output-file` or `-output=output-file` option.

```
patch Directories  Changing directory and stripping paths.
Backups           Backup file names.
Rejects           Reject file names.
patch Options      Summary table of options to patch.
```

## 1.78 diff.info/patch Directories

### Applying Patches in Other Directories

=====

The `-d directory` or `-directory=directory` option to `patch` makes `directory` the current directory for interpreting both file names in the patch file, and file names given as arguments to other options (such as `-B` and `-o`). For example, while in a news reading program, you can patch a file in the `/usr/src/emacs` directory directly from the article containing the patch like this:

```
| patch -d /usr/src/emacs
```

Sometimes the file names given in a patch contain leading directories, but you keep your files in a directory different from the one given in the patch. In those cases, you can use the `-p[number]` or `-strip=[number]` option to set the file name strip count to `number`. The strip count tells `patch` how many slashes, along with the directory names between them, to strip from the front of file names. `-p` with no number given is equivalent to `-p0`. By default, `patch` strips off all leading paths, leaving just the base file names, except that when a file name given in the patch is a relative path and all of its leading

directories already exist, patch does not strip off the leading path. (A relative path is one that does not start with a slash.)

patch looks for each file (after any slashes have been stripped) in the current directory, or if you used the -d directory option, in that directory.

For example, suppose the file name in the patch file is /gnu/src/emacs/etc/NEWS. Using -p or -p0 gives the entire file name unmodified, -p1 gives gnu/src/emacs/etc/NEWS (no leading slash), -p4 gives etc/NEWS, and not specifying -p at all gives NEWS.

## 1.79 diff.info/Backups

### Backup File Names

=====

Normally, patch renames an original input file into a backup file by appending to its name the extension .orig, or ~ on systems that do not support long file names. The -b backup-suffix or -suffix=backup-suffix option uses backup-suffix as the backup extension instead.

Alternately, you can specify the extension for backup files with the SIMPLE\_BACKUP\_SUFFIX environment variable, which the options override.

patch can also create numbered backup files the way GNU Emacs does. With this method, instead of having a single backup of each file, patch makes a new backup file name each time it patches a file. For example, the backups of a file named sink would be called, successively, sink.~1~, sink.~2~, sink.~3~, etc.

The -V backup-style or -version-control=backup-style option takes as an argument a method for creating backup file names. You can alternately control the type of backups that patch makes with the VERSION\_CONTROL environment variable, which the -V option overrides. The value of the VERSION\_CONTROL environment variable and the argument to the -V option are like the GNU Emacs version-control variable (see emacs, for more information on backup versions in Emacs). They also recognize synonyms that are more descriptive. The valid values are listed below; unique abbreviations are acceptable.

t

numbered

Always make numbered backups.

nil

existing

Make numbered backups of files that already have them, simple backups of the others. This is the default.

never

simple

Always make simple backups.



Alternately, you can tell patch to prepend a prefix, such as a directory name, to produce backup file names. The `-B backup-prefix` or `-prefix=backup-prefix` option makes backup files by prepending `backup-prefix` to them. If you use this option, patch ignores any `-b` option that you give.

If the backup file already exists, patch creates a new backup file name by changing the first lowercase letter in the last component of the file name into uppercase. If there are no more lowercase letters in the name, it removes the first character from the name. It repeats this process until it comes up with a backup file name that does not already exist.

If you specify the output file with the `-o` option, that file is the one that is backed up, not the input file.

## 1.80 diff.info/Rejects

Reject File Names  
=====

The names for reject files (files containing patches that patch could not find a place to apply) are normally the name of the output file with `.rej` appended (or `#` on systems that do not support long file names).

Alternatively, you can tell patch to place all of the rejected patches in a single file. The `-r reject-file` or `-reject-file=reject-file` option uses `reject-file` as the reject file name.

## 1.81 diff.info/patch Options

Options to patch  
=====

Here is a summary of all of the options that patch accepts. Older versions of patch do not accept long-named options or the `-t`, `-E`, or `-V` options.

Multiple single-letter options that do not take an argument can be combined into a single command line argument (with only one dash). Brackets (`[` and `]`) indicate that an option takes an optional argument.

`-b backup-suffix`

Use `backup-suffix` as the backup extension instead of `.orig` or `~`.  
See Backups.

`-B backup-prefix`

Use `backup-prefix` as a prefix to the backup file name. If this

---

option is specified, any -b option is ignored. See Backups.

-batch

Do not ask any questions. See patch Messages.

-c

-context

Interpret the patch file as a context diff. See patch Input.

-d directory

-directory=directory

Makes directory directory the current directory for interpreting both file names in the patch file, and file names given as arguments to other options. See patch Directories.

-D name

Make merged if-then-else output using format. See If-then-else.

-debug=number

Set internal debugging flags. Of interest only to patch patchers.

-e

-ed

Interpret the patch file as an ed script. See patch Input.

-E

Remove output files that are empty after the patches have been applied. See Empty Files.

-f

Assume that the user knows exactly what he or she is doing, and do not ask any questions. See patch Messages.

-F lines

Set the maximum fuzz factor to lines. See Inexact.

-force

Assume that the user knows exactly what he or she is doing, and do not ask any questions. See patch Messages.

-forward

Ignore patches that patch thinks are reversed or already applied. See also -R. See Reversed Patches.

-fuzz=lines

Set the maximum fuzz factor to lines. See Inexact.

-help

Print a summary of the options that patch recognizes, then exit.

-ifdef=name

Make merged if-then-else output using format. See If-then-else.

-ignore-white-space

-l

Let any sequence of white space in the patch file match any sequence of white space in the input file. See

Changed White Space.

-n

-normal

Interpret the patch file as a normal diff. See patch Input.

-N

Ignore patches that patch thinks are reversed or already applied.  
See also -R. See Reversed Patches.

-o output-file

-output=output-file

Use output-file as the output file name. See patch Options.

-p[number ]

Set the file name strip count to number. See patch Directories.

-prefix=backup-prefix

Use backup-prefix as a prefix to the backup file name. If this option is specified, any -b option is ignored. See Backups.

-quiet

Work silently unless an error occurs. See patch Messages.

-r reject-file

Use reject-file as the reject file name. See Rejects.

-R

Assume that this patch was created with the old and new files swapped. See Reversed Patches.

-reject-file=reject-file

Use reject-file as the reject file name. See Rejects.

-remove-empty-files

Remove output files that are empty after the patches have been applied. See Empty Files.

-reverse

Assume that this patch was created with the old and new files swapped. See Reversed Patches.

-s

Work silently unless an error occurs. See patch Messages.

-S

Ignore this patch from the patch file, but continue looking for the next patch in the file. See Multiple Patches.

-silent

Work silently unless an error occurs. See patch Messages.

-skip

Ignore this patch from the patch file, but continue looking for the next patch in the file. See Multiple Patches.

-strip[=number ]

---

Set the file name strip count to number. See patch Directories.

`-suffix=backup-suffix`  
Use backup-suffix as the backup extension instead of .orig or ~.  
See Backups.

`-t`  
Do not ask any questions. See patch Messages.

`-u`  
`-unified`  
Interpret the patch file as a unified diff. See patch Input.

`-v`  
Output the revision header and patch level of patch.

`-V backup-style`  
Select the kind of backups to make. See Backups.

`-version`  
Output the revision header and patch level of patch, then exit.

`-version=control=backup-style`  
Select the kind of backups to make. See Backups.

`-x number`  
Set internal debugging flags. Of interest only to patch patchers.

## 1.82 diff.info/Invoking sdiff

Invoking sdiff  
\*\*\*\*\*

The sdiff command merges two files and interactively outputs the results. Its arguments are as follows:

```
sdiff -o outfile options ... from-file to-file
```

This merges from-file with to-file, with output to outfile. If from-file is a directory and to-file is not, sdiff compares the file in from-file whose file name is that of to-file, and vice versa. from-file and to-file may not both be directories.

sdiff options begin with -, so normally from-file and to-file may not begin with -. However, - as an argument by itself treats the remaining arguments as file names even if they begin with -. You may not use - as an input file.

An exit status of 0 means no differences were found, 1 means some differences were found, and 2 means trouble.

sdiff without -o (or -output) produces a side-by-side difference. This usage is obsolete; use diff -side-by-side instead.

---

sdiff Options      Summary of options to diff.

## 1.83 diff.info/sdiff Options

Options to sdiff  
=====

Below is a summary of all of the options that GNU sdiff accepts. Each option has two equivalent names, one of which is a single letter preceded by -, and the other of which is a long name preceded by -. Multiple single letter options (unless they take an argument) can be combined into a single command line argument. Long named options can be abbreviated to any unique prefix of their name.

- a  
Treat all files as text and compare them line-by-line, even if they do not appear to be text. See Binary.
  - b  
Ignore changes in amount of white space. See White Space.
  - B  
Ignore changes that just insert or delete blank lines. See Blank Lines.
  - d  
Change the algorithm to perhaps find a smaller set of changes. This makes sdiff slower (sometimes much slower). See diff Performance.
  - H  
Use heuristics to speed handling of large files that have numerous scattered small changes. See diff Performance.
  - expand-tabs  
Expand tabs to spaces in the output, to preserve the alignment of tabs in the input files. See Tabs.
  - i  
Ignore changes in case; consider upper- and lower-case to be the same. See Case Folding.
  - I regexp  
Ignore changes that just insert or delete lines that match regexp. See Specified Folding.
  - ignore-all-space  
Ignore white space when comparing lines. See White Space.
  - ignore-blank-lines  
Ignore changes that just insert or delete blank lines. See Blank Lines.
-

`-ignore-case`  
Ignore changes in case; consider upper- and lower-case to be the same. See Case Folding.

`-ignore-matching-lines=regexp`  
Ignore changes that just insert or delete lines that match regexp. See Specified Folding.

`-ignore-space-change`  
Ignore changes in amount of white space. See White Space.

`-l`

`-left-column`  
Print only the left column of two common lines. See Side by Side Format.

`-minimal`  
Change the algorithm to perhaps find a smaller set of changes. This makes `sdiff` slower (sometimes much slower). See diff Performance.

`-o file`

`-output=file`  
Put merged output into file. This option is required for merging.

`-s`

`-suppress-common-lines`  
Do not print common lines. See Side by Side Format.

`-speed-large-files`  
Use heuristics to speed handling of large files that have numerous scattered small changes. See diff Performance.

`-t`  
Expand tabs to spaces in the output, to preserve the alignment of tabs in the input files. See Tabs.

`-text`  
Treat all files as text and compare them line-by-line, even if they do not appear to be text. See Binary.

`-v`

`-version`  
Output the version number of `sdiff`.

`-w columns`

`-width=columns`  
Use an output width of columns. See Side by Side Format. Note that for historical reasons, this option is `-W` in `diff`, `-w` in `sdiff`.

`-W`  
Ignore horizontal white space when comparing lines. See White Space. Note that for historical reasons, this option is `-w` in `diff`, `-W` in `sdiff`.

---

## 1.84 diff.info/Incomplete Lines

### Incomplete Lines

\*\*\*\*\*

When an input file ends in a non-newline character, its last line is called an incomplete line because its last character is not a newline. All other lines are called full lines and end in a newline character. Incomplete lines do not match full lines unless differences in blank lines are ignored (see Blank Lines).

An incomplete line is normally distinguished on output from a full line by a following line that starts with \ . However, the RCS format (see RCS) outputs the incomplete line as-is, without any trailing newline or following line. The side by side format normally represents incomplete lines as-is, but in some cases uses a \ or / gutter marker; See Side by Side. The if-then-else line format preserves a line's incompleteness with %L, and discards the newline with %l; See Line Formats. Finally, with the ed and forward ed output formats (see Output Formats) diff cannot represent an incomplete line, so it pretends there was a newline and reports an error.

For example, suppose F and G are one-byte files that contain just f and g, respectively. Then diff F G outputs

```
1c1
< f
\ No newline at end of file
---
> g
\ No newline at end of file
```

(The exact message may differ in non-English locales.) diff -n F G outputs the following without a trailing newline:

```
d1 1
a1 1
g
```

diff -e F G reports two errors and outputs the following:

```
1c
g
.
```

## 1.85 diff.info/Projects

### Future Projects

\*\*\*\*\*

Here are some ideas for improving GNU diff and patch. The GNU project has identified some improvements as potential programming projects for volunteers. You can also help by reporting any bugs that

you find.

If you are a programmer and would like to contribute something to the GNU project, please consider volunteering for one of these projects. If you are seriously contemplating work, please write to `gnu@prep.ai.mit.edu` to coordinate with other volunteers.

Shortcomings	Suggested projects for improvements.
Bugs	Reporting bugs.

## 1.86 diff.info/Shortcomings

Suggested Projects for Improving GNU diff and patch

=====

One should be able to use GNU diff to generate a patch from any pair of directory trees, and given the patch and a copy of one such tree, use patch to generate a faithful copy of the other. Unfortunately, some changes to directory trees cannot be expressed using current patch formats; also, patch does not handle some of the existing formats. These shortcomings motivate the following suggested projects.

Changing Structure	Handling changes to the directory structure.
Special Files	Handling symbolic links, device special files, etc.
Unusual File Names	Handling file names that contain unusual characters.
Arbitrary Limits	Patching non-text files.
Large Files	Handling files that do not fit in memory.
Ignoring Changes	Ignoring certain changes while showing others.

## 1.87 diff.info/Changing Structure

Handling Changes to the Directory Structure

-----

diff and patch do not handle some changes to directory structure. For example, suppose one directory tree contains a directory named D with some subsidiary files, and another contains a file with the same name D. `diff -r` does not output enough information for patch to transform the the directory subtree into the file.

There should be a way to specify that a file has been deleted without having to include its entire contents in the patch file. There should also be a way to tell patch that a file was renamed, even if there is no way for diff to generate such information.

These problems can be fixed by extending the diff output format to represent changes in directory structure, and extending patch to understand these extensions.



## 1.88 diff.info/Special Files

Files that are Neither Directories Nor Regular Files

-----

Some files are neither directories nor regular files: they are unusual files like symbolic links, device special files, named pipes, and sockets. Currently, diff treats symbolic links like regular files; it treats other special files like regular files if they are specified at the top level, but simply reports their presence when comparing directories. This means that patch cannot represent changes to such files. For example, if you change which file a symbolic link points to, diff outputs the difference between the two files, instead of the change to the symbolic link.

diff should optionally report changes to special files specially, and patch should be extended to understand these extensions.

## 1.89 diff.info/Unusual File Names

File Names that Contain Unusual Characters

-----

When a file name contains an unusual character like a newline or white space, diff -r generates a patch that patch cannot parse. The problem is with format of diff output, not just with patch, because with odd enough file names one can cause diff to generate a patch that is syntactically correct but patches the wrong files. The format of diff output should be extended to handle all possible file names.

## 1.90 diff.info/Arbitrary Limits

Arbitrary Limits

-----

GNU diff can analyze files with arbitrarily long lines and files that end in incomplete lines. However, patch cannot patch such files. The patch internal limits on line lengths should be removed, and patch should be extended to parse diff reports of incomplete lines.

## 1.91 diff.info/Large Files

## Handling Files that Do Not Fit in Memory

-----

diff operates by reading both files into memory. This method fails if the files are too large, and diff should have a fallback.

One way to do this is to scan the files sequentially to compute hash codes of the lines and put the lines in equivalence classes based only on hash code. Then compare the files normally. This does produce some false matches.

Then scan the two files sequentially again, checking each match to see whether it is real. When a match is not real, mark both the "matching" lines as changed. Then build an edit script as usual.

The output routines would have to be changed to scan the files sequentially looking for the text to print.

## 1.92 diff.info/Ignoring Changes

### Ignoring Certain Changes

-----

It would be nice to have a feature for specifying two strings, one in from-file and one in to-file, which should be considered to match. Thus, if the two strings are foo and bar, then if two lines differ only in that foo in file 1 corresponds to bar in file 2, the lines are treated as identical.

It is not clear how general this feature can or should be, or what syntax should be used for it.

## 1.93 diff.info/Bugs

### Reporting Bugs

=====

If you think you have found a bug in GNU cmp, diff, diff3, sdiff, or patch, please report it by electronic mail to bug-gnu-utils@prep.ai.mit.edu. Send as precise a description of the problem as you can, including sample input files that produce the bug, if applicable.

Because Larry Wall has not released a new version of patch since mid 1988 and the GNU version of patch has been changed since then, please send bug reports for patch by electronic mail to both bug-gnu-utils@prep.ai.mit.edu and lwall@netlabs.com.

## 1.94 diff.info/Concept Index

### Concept Index

\*\*\*\*\*

cmp invocation	Invoking cmp
cmp options	cmp Options
diff3 hunks	diff3 Hunks
diff3 invocation	Invoking diff3
diff3 options	diff3 Options
diff3 sample input	Sample diff3 Input
diff invocation	Invoking diff
diff options	diff Options
diff sample input	Sample diff Input
ed script output format	ed Scripts
ifdef output format	If-then-else
patch input format	patch Input
patch invocation	Invoking patch
patch messages and questions	patch Messages
patch options	patch Options
sdiff invocation	Invoking sdiff
sdiff options	sdiff Options
sdiff output format	sdiff Option Summary
! output format	Context
+ - output format	Unified Format
<<<<<< for marking conflicts	Marking Conflicts
< output format	Normal
aligning tabstops	Tabs
alternate file names	Alternate Names
backup file names	Backups
binary file diff	Binary
binary file patching	Arbitrary Limits
blank and tab difference suppression	White Space
blank line difference suppression	Blank Lines
brief difference reports	Brief
bug reports	Bugs
C function headings	C Function Headings
C if-then-else output format	If-then-else
case difference suppression	Case Folding
columnar output	Side by Side
comparing three files	Comparing Three Files
conflict	diff3 Merging
conflict marking	Marking Conflicts
context output format	Context
diagnostics from patch	patch Messages
diff merging	Interactive Merging
directories and patch	patch Directories
directory structure changes	Changing Structure
empty files, removing	Empty Files
file name alternates	Alternate Names
file names with unusual characters	Unusual File Names
format of diff3 output	Comparing Three Files
format of diff output	Output Formats
formats for if-then-else line groups	Line Group Formats
forward ed script output format	Forward ed
full lines	Incomplete Lines

---

function headings, C	C Function Headings
fuzz factor when patching	Inexact
headings	Sections
hunks	Hunks
hunks for diff3	diff3 Hunks
if-then-else output format	If-then-else
imperfect patch application	Imperfect
incomplete line merging	Merging Incomplete Lines
incomplete lines	Incomplete Lines
inexact patches	Inexact
interactive merging	Interactive Merging
introduction	Comparison
invoking cmp	Invoking cmp
invoking diff3	Invoking diff3
invoking diff	Invoking diff
invoking patch	Invoking patch
invoking sdiff	Invoking sdiff
large files	Large Files
line formats	Line Formats
line group formats	Line Group Formats
merge commands	Merge Commands
merged diff3 format	Bypassing ed
merged output format	If-then-else
merging from a common ancestor	diff3 Merging
merging interactively	Merge Commands
messages from patch	patch Messages
multiple patches	Multiple Patches
newline treatment by diff	Incomplete Lines
normal output format	Normal
options for cmp	cmp Options
options for diff3	diff3 Options
options for diff	diff Options
options for patch	patch Options
options for sdiff	sdiff Options
output formats	Output Formats
overlap	diff3 Merging
overlapping change, selection of	Which Changes
overview of diff and patch	Overview
paginating diff output	Pagination
patch making tips	Making Patches
patching directories	patch Directories
performance of diff	diff Performance
projects for directories	Shortcomings
RCS script output format	RCS
regular expression matching headings	Specified Headings
regular expression suppression	Specified Folding
reject file names	Rejects
removing empty files	Empty Files
reporting bugs	Bugs
reversed patches	Reversed Patches
sample input for diff3	Sample diff3 Input
sample input for diff	Sample diff Input
script output formats	Scripts
section headings	Sections
side by side	Side by Side
side by side format	Side by Side Format
special files	Special Files

---

---

specified headings	Specified Headings
summarizing which files differ	Brief
System V diff3 compatibility	Saving the Changed File
tab and blank difference suppression	White Space
tabstop alignment	Tabs
text versus binary diff	Binary
tips for patch making	Making Patches
two-column output	Side by Side
unified output format	Unified Format
unmerged change	Which Changes
white space in patches	Changed White Space

---