

788395_paste.eps ↗

Entry Number:

Title: **The Dell DG/X**

Entry Date: **12 April 1993**

Product Vendor: **Dell Computer Corporation**

Vendor Contact Information:

Hardware Platform: **Intel Processor Family**

Reported in Software Version: **NEXTSTEP Release 3.1**

Keywords: **Dell, Jaws**

DELL_Logo3.eps ↗

Usage Commentary:

The Dell DG/X provides 1120 x 832 in 16 bit color under NEXTSTEP. NEXTSTEP also supports SVGA on the Dell DG/X at 1024 x 768.

The Dell DG/X should be compatible with NeXT color monitors. This compatibility is not guaranteed by NeXT.

Setup and Installation:

The Dell DG/X may come with two 1/4 height floppy drives in a single unit. Only one floppy drive should be enabled, and it should be the 3 1/2" set to be drive A in both the CMOS setup and the EISA Configuration Utility (ECU).

The following ECU settings were recorded by the Quality Assurance Group from a Dell DG/X known to have successfully installed and run NEXTSTEP Release 3.1 for Intel Processors. The system was running off of a SCSI hard disk with a DPT 2012 SCSI controller.

EISA Configuration Utility Setup

System - Dell Powerline (TM) Workstation 450 DE/2 (TM) System Board
Memory

- SIMM Memory 16MB
- Extended Memory 15360 KB
- Board Memory : 640 KB
- Base Memory : 640 KB

Fast Video : Cached

CPU Options

- 486 Cache : On
- CPU Speed : 50 MHz

Boot Options

- Primary Display : VGA/EGA
- Keyboard : Installed
- Num Lock : On
- Reset Button : Enabled
- Speaker Volume : High
- SmartVu : System Messages
- Hard Disk Autosense : Off
- Boot Sequence : Diskette First
- Password Entry : Before Boot

Password : Not Enabled

Integrated Mouse : Enabled

Integrated VGA : Graphics : Color or Mon without retrace

Integrated Hard Disk Interface : Auto

Hard Drives

- Drive 0 : Not Installed
- Drive 1 : Not Installed

Integrated Serial Interface

- Serial Port 1 : Auto
- Serial Port 2 : Auto

Integrated Parallel Port Interface : Auto

EXP4 - DPT SCSI Host Bus Adapter (PM 2012B2/9X) - Banyan Vines

HARDWARE CONFIGURATION

Hardware Mapping

- IO Ports : Secondary/Disabled

Interrupt Number : 15 Edge
Floppy Drive : Disabled
Option ROM : Enabled @ D800h
HBA SCSI ID : 7

WD1003 EMULATION MAPPINGS

Drive 0

SCSI ID : Disabled
SCSI LUN : 0

Drive 1

SCSI ID : Disabled
SCSI LUN : 0

CONTROLLER PARAMETERS

SCSI Parameters

Maximum Transfer Rate : 10 MB/s
External Cable Detection : Yes - 5 MB/s
Command Queuing : Enabled
Command Timeout : Enabled - 5 sec

Cache Parameters

Cache : Enabled (Write-Back)
Max. Percentage Dirty : 80%
Max. Percentage Look-Ahead : 80%
Look-Ahead : Enabled (8 blocks)
Cache Threshold : 16 blocks
Caching Parameters : Use Values Stored on Device

!DPTA402.CGF Version 005D

EXP6 - Dell DGX Video Subsystem

Frame Buffer Location Cacheability : 20000000h, cached
Video Interrupt Selection : IRQ2, Disable
Color Mode : Normal

Known Problems:

- The Ultrascan monitor shipped with the Dell DG/X and the NEC 5FG both reportedly have some difficulty displaying 1120 x 832 video correctly. This can result in fuzziness and faded colors. The NEC 6FG does not apparently suffer from this problem.
- Some early DG/X systems have a single jumper on the Jaws Graphics board that will when

jumped incorrectly prevent the cursor from being movable by the mouse while running NEXTSTEP.

One DG/X system the Quality Assurance Group tested demonstrated sensitivity to fast SCSI transfer rates. This manifested as multiple read errors during the installation process when installing from either a DPT 2012 or Adaptec 1542C SCSI adapter onto a Seagate SCSI hard disk. This problem was not observed on other DG/X systems.