

# Julian

INHERITS FROM                      Object

WRITTEN BY                              Charles G. Bennett

Version 1.1, , This class is in the Public Domain. No guaranties are made to its usefulness or correctness.

## CLASS DESCRIPTION

The Julian Class is an Interface Builder Module to implement julian day functions.

## FEATURES

- Rich set of class methods allows you to treat Julian as a function library.
- Fractional Days supported for easy time tracking and comparison.
- Instance variable and methods allow you to create lists of dates.

## INSTANCE VARIABLES

*Declared in Julian*                      double                      julianDayVal

## METHOD TYPES

### Initialization

- (BOOL) initDay::
- (BOOL) initDay:::

### Archiving

- read:
- write:

### Converting to and from julian dates

- + (double) getCurrentDate
- + (double) julianDay::
- + (double) julianDay:::
- + (void) calendarDay::
- + (void) calendarDay:::

### Testing for valid dates

- + (BOOL) validDay::
- + (BOOL) validDay:::

### misc

+ (int) dow::  
+ (int) doy::  
+ (double) wkd::

Internal Methods

None.

## CLASS METHODS

### **getCurrentDate**

+ (double) **getCurrentDate**

Returns the julian day for the current month, day, year, hour, min, and second.  
This routine calls the unix localTime function.

### **julianDay:::**

+ (double) **julianDay**  
:(int) day  
:(int) month  
:(int) year

Returns the julian day for the given month day and year;

### **julianDay:::::**

+ (double) **julianDay**  
:(int) day  
:(int) month  
:(int) year  
:(int) hour  
:(int) min  
:(int) sec

Returns the julian day and fractional day for the given month, day, year, hour, min, and second.

### **calendarDay:::::**

+ (void) **calendarDay**  
:(double) julian  
:(int\*) day  
:(int\*) month  
:(int\*) year

Returns the month, day, and year for the given julian day.

### **calendarDay:::::**

+ (void) **calendarDay**  
:(double) julian  
:(int) day  
:(int) month  
:(int) year  
:(int) hour  
:(int) min  
:(int) sec

Returns the month, day, year, hour, minute, and second for the given julian day and fractional day.

**validDay:::**

+ (BOOL) **validDay**  
:(int) day  
:(int) month  
:(int) year

Returns YES if the day month and year are valid, NO otherwise.

**validDay:::::**

+ (BOOL) **validDay**  
:(int) day  
:(int) month  
:(int) year  
:(int) hour  
:(int) min  
:(int) sec

This routine extends the testing to include hour, min and seconds.

**dow:**

+ (int) **dow**:(long) julian

This method **returns** the Day Of Week value. The Day Of Week is defined as 0 = Sunday, 1=Monday .... 6=Saturday

**doy:::**

+ (int) **doy**  
:(int) day  
:(int) month  
:(int) year

This method **returns** the Day Of Year value. The Day Of Year is defined as 1= Jan 1

**wkd:::**

+ (double) **wkd**  
:(int) day  
:(int) month  
:(int) year

This method **returns** the number of weekdays since some time in the past. Use this method to find the number of "workdays" between dates.

NOTE: a day is defined as 12:00 NOON to 12:00 NOON so there is .5 days difference between Friday and Saturday of the same week.

INSTANCE METHODS

- **initDay:::**

- (BOOL) **initDay**
  - :(int) month
  - :(int) day
  - :(int) year

This method will initialize the instance variable to the given date. It returns **YES** if the date is valid or **NO** if not. If the date is invalid the instance variable is **NOT** changed.

- **initDay::::::**

- (BOOL) **initDay**
  - :(int) month
  - :(int) day
  - :(int) year
  - :(int) hour
  - :(int) min
  - :(int) sec

This method will initialize the instance variable to the given date. It returns **YES** if the date is valid or **NO** if not. If the date is invalid the instance variable is **NOT** changed.

- **read:(NXTypedStream \*)stream**

- **read**

Reads the Julian instance variable from *stream*. A **read:** message is sent during unarchiving. You never invoke this method directly.

- **write:**

- **write:(NXTypedStream \*)stream**

Writes the Julian instance variable to *stream*. A **write:** message is sent during archiving. You never invoke this method directly.

- **getJulianDay**

- (double) **getJulianDay**

This method **returns** the value of the julian day instance variable.

- **setJulianDay:**

- (BOOL) **setJulianDay:(double) day**

This method **sets** the value of the julian day instance variable. **Caution!** Use this with care since this directly sets the instance variable. Always returns **YES**

- **setJulianDay:::**

- (BOOL) **setJulianDay**  
:(int) month  
:(int) day  
:(int) year

This method **sets** the value of the julian day instance variable. Using the month, day and year parameters. Returns **YES** if the date was valid, **NO** if not., and the instance variable is NOT changed

- **setJulianDay:.....:**

- (BOOL) **setJulianDay**  
:(int) month  
:(int) day  
:(int) year  
:(int) hour  
:(int) min  
:(int) sec

This method **sets** the value of the julian day instance variable. Using the month, day, year, hour, min, and sec parameters. Returns **YES** if the date was valid, **NO** if not., and the instance variable is NOT changed

CONSTANTS AND DEFINED TYPES

None.