

```
//
// FILENAME: eText.PlainText.m
// SUMMARY: Implementation of PlainText markup formats of eText (ASCII, C)
// CATEGORY: PlainText
// PROTOCOLS: <ASCIISupport>, <CSupport>
// INTERFACE: None
// AUTHOR: Rohit Khare
// COPYRIGHT: ©1993,94 California Institute of Technology, eText Project
//
// Implementation Comments
//     These methods are pretty much syntactic sugar.
//     I can't decide whether 'C' should unravel 8-bit characters into ascii
//     equivalents. OTOH, who programs with ligatures? -- and if they do, leave
//     it alone!
//
// History
// 10/17/94: Cleaned up for eText5.
// 08/05/94: Completely Rearchitected for 5.0. RK
//
// Imported Interfaces
//
// #import "eText.PlainText.h"
//
// Encoder API
//
void ASCIIIEncoder(NXStream *s, unsigned char *item, int len) {
    int i; char *out;

    if(!len) len=strlen((unsigned char*)item);
    for (i=0; i<len; i++) {
        out = NXToAscii(item[i]);
        NXWrite(s, out, strlen(out));
    }
}

@implementation eText(PlainText)
//
// Path Operators
//
- readASCIIfromPath:(const char *)path {
    NXStream *memstream;

    memstream = NXMapFile(path, NX_READONLY);
    if (memstream){
        [self readASCII: memstream];
        NXCloseMemory(memstream, NX_FREEBUFFER);
    }
}

```



```

    return [self writeASCII:s from:0 to:[self textLength]];
- writeASCII: (NXStream *)s from:(int) start to:(int) end {
    int                k,N,cnt=0;
    NXRun              *curr;
    NXTextBlock        *currBlock;
    int                currentOffset,targetOffset;
    id                 compList;

    N = theRuns->chunk.used/sizeof(NXRun);
    curr = theRuns->runs;
    currBlock = [self firstTextBlock];
    compList = [[List alloc] init];
    currentOffset = 0;
    for(k=0; (k < N) && (currentOffset < end); k++) {

        targetOffset = currentOffset + curr->chars;

        if ((targetOffset > start) && (curr->info)) {
            if ([curr->info respondsToSelector:@selector(writeASCIIRef:forView:)]) {
                NXPrintf(s,"%d]", cnt++);
                [compList addObject:(curr->info)];
            }
            if ([curr->info respondsToSelector:@selector(writeASCII:forView:)]) {
                [curr->info writeASCII:s forView:self];
            }
        }

        // consume full blocks
        while (currBlock && (targetOffset >= currBlock->chars)) {

            if ((targetOffset > start) &&
                (curr->info == nil) &&
                (targetOffset > currentOffset))

                ASCIIEncoder(s, currBlock->text + MAX(currentOffset,start),
                            MIN(end,currBlock->chars) - MAX(currentOffset,start));

            targetOffset -= currBlock->chars;
            start -= currBlock->chars;
            end -= currBlock->chars;
            currentOffset=0;
            currBlock = currBlock->next;
        }

        // consume partial block
        if (currBlock)

```

```

        if ((targetOffset > start) &&
            (curr->info == nil) &&
            (targetOffset > currentOffset))

            ASCIIEncoder(s, currBlock->text + MAX(currentOffset, start),
                        MIN(end, targetOffset) - MAX(currentOffset, start));

        currentOffset=targetOffset;
        curr++;
    }

    // compList
    N=[compList count];
    if (N) {
        NXPrintf(s, "\n\nREFERENCES\n\n");
        for (k=0; k < N; k++) {
            NXPrintf(s, "[%d]\t", k);
            [[compList objectAtIndex:k] writeASCIIRef:s forView:self];
            NXPutc(s, '\n');
        }
    }
    [compList free];
    return self;
}

- readC: (NXStream *)s {
    return [self readText:s];}
- writeC: (NXStream *)s {
    return [self writeC:s from:0 to:[self textLength]];}
- writeC: (NXStream *)s from:(int) start to:(int) end {
    int                k,N;
    NXRun              *curr;
    NXTextBlock         *currBlock;
    int                currentOffset, targetOffset;

    N = theRuns->chunk.used/sizeof(NXRun);
    curr = theRuns->runs;
    currBlock = [self firstTextBlock];
    currentOffset = 0;
    for (k=0; k < N; k++) {
        if (curr->info) {
            if ([curr->info respondsToSelector:@selector(writeC:forView:)]) {
                [curr->info writeC:s forView:self];
            }
        }
        // encode the text corresponding to the run
        // mission is to write (cumulative) curr->chars chars beginning

```

```

// at currentCount. boundaries may map onto > 1 block
targetOffset = currentOffset + curr->chars;
// consume full blocks
while ((currBlock) && (targetOffset >= (currBlock->chars))) {
    if (!(curr->info)) // throw annotated bits in bucket
        if(targetOffset>currentOffset) // don't pass len=0 to encoder
            NXWrite(s, currBlock->text+currentOffset,
                    currBlock->chars - currentOffset);
    targetOffset -= currBlock->chars;
    currBlock = currBlock->next;
    currentOffset=0;
}
// consume partial block
if (currBlock && (! curr->info)) // throw annotated bits in bucket
    if(targetOffset>currentOffset) // don't pass len=0 to encoder
        NXWrite(s, currBlock->text + currentOffset,
                targetOffset-currentOffset);
currentOffset=targetOffset;
curr++;
}
return self;
}

```

@end