

|   |  |
|---|--|
| <code>runModal</code>   | Displays the panel and begins its event loop. The panel's values are recorded in the shared <code>NSPrintInfo</code> object.   |
| <code>runModalWithPrintInfo:(NSPrintInfo *)pInfo</code>                                 | Displays the panel and begins its event loop. The panel's values are recorded in the <code>pInfo</code> , the supplied <code>NSPrintInfo</code> object.  |
| <code>accessoryView</code>  | Returns the <code>NSPageLayout</code> 's accessory View.   |
| <code>setAccessoryView:(NSView *)aView</code>   | Adds a View to the panel.  |
| <code>convertOldFactor:(float *)old<br/>                  newFactor:(float *)new</code> | Returns by reference the ratio between a point and the currently chosen unit of measurement. If invoked within the <code>pickedUnits:</code> method, <code>old</code> refers to the ratio before the user's choice and <code>new</code> refers to the new ratio. |
| <code>pickedButton:(id)sender</code>  | Stops the event loop.  |
| <code>pickedOrientation:(id)sender</code>   | Updates the panel with the selected orientation.   |
| <code>pickedPaperSize:(id)sender</code>   | Updates the panel when a paper size is selected.   |
| <code>pickedUnits:(id)sender</code>   | Updates the panel when a new unit is selected.   |
| <code>printInfo</code>  | Returns the <code>NSPrintInfo</code> object that used when the panel is run.   |
| <code>readPrintInfo</code>  | Reads the <code>NSPageLayout</code> 's values from the <code>NSPrintInfo</code> object.  |
| <code>writePrintInfo</code>   | Writes the <code>NSPageLayout</code> 's values to the <code>NSPrintInfo</code> object.   |