

<code>initWithFile:(NSString *)filename</code>	Initializes a new instance corresponding to filename.
<code>initWithSourceSelection:(NSSelection *)selection managedBy:(NSDataLinkManager *)linkManager supportingTypes:(NSArray *)newTypes</code>	Initializes a newly allocated instance corresponding to a selection in the source document selection. <code>linkManager</code> is the source document's link manager. <code>newTypes</code> is a set of types that <code>linkManager</code> 's delegate is willing to provide when a destination of the link requests the data described by selection.
<code>initWithContentsOfFile:(NSString *)filename</code>	Initializes a new instance from filename.
<code>initWithPasteboard:(NSPasteboard *)pasteboard</code>	Initializes a new instance from pasteboard.
<code>(BOOL)saveLinkIn:(NSString *)directoryName</code>	Saves the link in a filename provided by the user the <code>NSSavePanel</code> 's initial directory is in <code>directoryName</code> .
<code>(BOOL)writeToFile:(NSString *)filename</code>	Writes the link into the file <code>filename</code> , returning <code>NO</code> if the file can't be written.
<code>(void)writeToPasteboard:(NSPasteboard *)pasteboard</code>	Writes the link onto the pasteboard <code>pasteboard</code> .
<code>(NSDataLinkDisposition)disposition</code>	Identifies the link's type.
<code>(NSDataLinkNumber)linkNumber</code>	Returns the link's number.
<code>(NSDataLinkManager *)manager</code>	Returns the link's manager.
<code>(NSDate *)lastUpdateTime</code>	Returns the last time the link was updated.
<code>(BOOL)openSource</code>	Opens the source document of the link and makes the source selection visible.
<code>(NSString *)sourceApplicationName</code>	Returns the name of the application that owns the source document.
<code>(NSString *)sourceFilename</code>	Returns the file name of the source document.

selection ->destinationSelection

Returns the destination selection.

(OO)break

Breaks the link

(OO)noteSourceEdited

Informs a source link that the data referred to by its source

(OO)setUpdateMode:(NSDataLinkUpdateMode)mode

Sets the link's update mode to mode.

(OO)updateDestination

Updates the data referred to by the link's destination selection referred to by the source selection.

(NSDataLinkUpdateMode)updateMode

Returns the link's update mode.