

`initWithDictionary:(NSDictionary *)aDict`

Initializes a newly allocated `NSPrintInfo` object by assigning it the parameters specified in `aDict`. This is the designated initializer for the class.

`bottomMargin`

Returns the height of the bottom margin.

`leftMargin`

Returns the width of the left margin.

`printingOrientation`

Returns whether the orientation is Portrait or Landscape.

`paperName`

Returns the paper type, such as `Letter` or `Legal`. Paper names are implementation specific.

`paperSize`

Returns the size of the paper.

`rightMargin`

Returns the width of the right margin.

`setBottomMargin:(float)value`

Sets the bottom margin to value.

`setLeftMargin:(float)value`

Sets the left margin to value.

`setOrientation:(NSPrintingOrientation)mode`

Sets the orientation as Portrait or Landscape.

`setPaperName:(NSString *)name`

Sets the paper type. name identifies the type of paper, such as `Letter` or `Legal`. Paper names are implementation specific.

`setPaperSize:(NSSize)size`

Sets the width and height of the paper.

`setRightMargin:(float)value`

Sets the right margin to value.

`setTopMargin:(float)value`

Sets the top margin to value.

<code>printingPage)verticalPage</code>	Sets the vertical pagination mode.
<code>verticalPage</code>	Returns the vertical pagination mode.
<code>isHorizontallyCentered</code>	Returns whether the image is centered horizontally.
<code>isVerticallyCentered</code>	Returns whether the image is centered vertically.
<code>setHorizontallyCentered:(BOOL)flag</code>	Sets whether the image is centered horizontally.
<code>setVerticallyCentered:(BOOL)flag</code>	Sets whether the image is centered vertically.
<code>printer</code>	Returns the <code>NSPrinter</code> that's used for printing.
<code>setPrinter:(NSPrinter *)aPrinter</code>	Sets the printer that's used in subsequent printing jobs.
<code>jobDisposition</code>	Returns the action specified for the job: printing, faxing, or saving. See <code>setJobDisposition:</code> .
<code>setJobDisposition:(NSString *)disposition</code>	Sets the action specified for the job. <code>disposition</code> can be one of <code>NSPrintJob</code> , <code>NSPrintFaxJob</code> , <code>NSPrintPreviewJob</code> , <code>NSPrintSaveJob</code> , or <code>NSPrintNone</code> .
<code>setUpPrintOperationDefaultValues</code>	Allows the receiver to set any attribute that hasn't been printed.
<code>dictionary</code>	Returns the <code>NSPrintInfo</code> object's dictionary.