MiscPaperViewInspector

Inherits From:	IBInspector
Declared In:	MiscPaperViewInspector.h
Depends On:	MiscPaperView.h

Class Description

InterfaceBuilder uses this inspector if you select a MiscPaperView.

Instance Variables

id **firstID**;
id **secondID**;

firstID	Just a temp.
secondID	Another temp.

Method Types

- myMethod

Class Methods

Instance Methods

gridColorChanged:

- gridColorChanged:*sender*

Sets the inspected objects grid color according to the color well.

See also: - sidelineColorChanged:,

gridHOffsetChanged:
   - gridHOffsetChanged:*sender*

Forces an update of the horizontal grid offset.

See also: - myReference

gridOriginChanged:
   - gridOriginChanged:*sender*

Forces an update of the grids origin.

See also: - myReference

gridTypeChanged:
   - gridTypeChanged:*sender*

Forces an update of the grids type. The sender is assumed to be the matrix.

See also: - myReference

gridVOffsetChanged:
   - gridVOffsetChanged:*sender*

Forces an update of the grids vertical offset.

See also: - myReference

init
   - init

Loads the NIB which holds the inspectors window.

revert:
    - **revert:***sender*

Initializes all the controls inside the inspectors window.

See also: - **revert:** (IBInspector), - **ok:** (IBInspector)

sidelineColorChanged:
    - **sidelineColorChanged:***sender*

Updates the sideline color.

See also: - **myReference**

sidelineOffsetChanged:
    - **sidelineOffsetChanged:***sender*

Triggers an update of the sidelines offset.

See also: - **myReference**

sidelineTypeChanged:
    - **sidelineTypeChanged:***sender*

Gets all the selected cells inside the senders and makes a sum of their tags. This will create the right type value.

See also: - **gridTypeChanged:**, - **gridOriginChanged:**

wantsButtons
    - (BOOL)**wantsButtons**

Returns NO. We don't need the Ok/Revert buttons. Therefore every change (e.g.
- **sidelineTypeChanged:**) is followed by an **ok:** message which is send to our

superclass.