

```

//
// SAVEALL.WCM -- save all docs that need saving.
// <rreiner@nexus.yorku.ca> 6 April 1992.
//
// Named documents that have been modified are saved silently, overwriting
the previous
// version on disk; unnamed documents that have been modified are saved
via the Save As
// dialog, so that the user may supply a filename.
//
// At macro termination, the user's context is exactly what it was at macro
invocation.
//
// Suggestion: put this on your Button Bar, next to a Save or Save As...
button.
//
// Author: Richard Reiner <rreiner@nexus.yorku.ca>
//
// Revision history:
//   3 May 1992      RjR   Initial version
//

//*****
// Main program
//
APPLICATION(WP;WPWP;Default)
GetWPData(InitialCurrent;CurrentDocument!)

// Loop over docs
REPEAT
    DocNext()
    CALL (DoSave@)
UNTIL (Current = InitialCurrent)
QUIT

//*****
// DoSave: save the current doc in the appropriate way
//
LABEL(DoSave@)
    GetWPData(Current;CurrentDocument!)
    GetWPData(Modified;DocumentModified!)
    GetWPData(FName;Name!)
    GetWPData(Path;Path!)
    Name := Path + FName
    IF (Modified)

```

```
IF (FName <> "")
    MacroStatusPrompt(On!; "Saving document: " + Name +
".")
    FileSave(Name; WordPerfect51!; Yes!)
ELSE
    MacroStatusPrompt(On!; "Saving unnamed document.")
    FileSaveAsDlg()
ENDIF
ELSE
    MacroStatusPrompt(On!; Name + " unmodified.")
ENDIF
RETURN
```