

```

/* Multiplexing Daemon
*
* -Thanx to Ballbach, Iretd, Muffin.
*
* This is a server that allows multiple connections at once. It is not really "robust" but
* more of a skeleton, so you can add on however you like. What happens to the data
* is up to you. It's probably easiest if you have the functions that mess with the data in
* another file, that is what I did. Compiles fine under linux.
*
* -Seti
*/

```

```

#include <stdio.h>
#include <stdlib.h>
#include <errno.h>
#include <string.h>
#include <sys/time.h>
#include <sys/types.h>
#include <netinet/in.h>
#include <sys/socket.h>
#include <sys/wait.h>
#include <time.h>
#include <fcntl.h>
#include <unistd.h>

/* Some stuff to determine what to do with the data we get
   #include "login_functions.c"
   #include "decode.c"
*/

```

```

#define PORT 4019
#define MAX_CONNECTIONS 15

char welcomeMessage[] = "Multiplexing Daemon\n";
void setup(fd_set *, int *, int *, int);
int free_slot(int *, int *);

main()

int sockfd, fds[MAX_CONNECTIONS], bytes, retval, freei, x=0, connections=0;
int len = sizeof(struct sockaddr_in);
struct sockaddr_in my_addr, their_addr;
fd_set in;
struct timeval timeout;
char buf[50];

timeout.tv_sec = 5;
timeout.tv_usec = 0;

my_addr.sin_family = AF_INET;
my_addr.sin_port = htons(PORT);
my_addr.sin_addr.s_addr = INADDR_ANY;
bzero(&(my_addr.sin_zero), 8);

if((sockfd = socket(AF_INET, SOCK_STREAM, 0)) == -1)

```

```

    exit(1);

    if(bind(sockfd, (struct sockaddr *)&my_addr, sizeof(struct sockaddr)) == -1)
        exit(1);

    if(listen(sockfd, MAX_CONNECTIONS) == -1)
        exit(1);

while(1)

    setup(&in, &sockfd, fds, connections);
    retval = select(MAX_CONNECTIONS, &in, NULL, NULL, &timeout);

    if(retval)

        if(FD_ISSET(sockfd, &in))

            printf("Accepting new connection...\n");
            freei = free_slot(&fds, &connections);

            if(!(freei == -1) && !(freei == MAX_CONNECTIONS))

                printf("Creating socket fds[%d]: FD #:%d\n", freei, fds[freei]);
                fds[freei] = accept(sockfd, (struct sockaddr *)&their_addr, &len);
                FD_SET(fds[freei], &in);
                send(fds[freei], welcomeMessage, strlen(welcomeMessage), 0);

/* Check for incoming data and exceptions */

setup(&in, &sockfd, fds, connections);
retval = select(MAX_CONNECTIONS, &in, NULL, NULL, &timeout);

if(retval)

    for(x=0; x<connections; x++)

        if(FD_ISSET(fds[x], &in))

            printf("Data Available\n");
            if((bytes = read(fds[x], buf, sizeof(buf))) <=0)

                close(fds[x]);
                FD_CLR(fds[x], &in);
                fds[x] = 0;

            else

                buf[bytes] = '\0';

```

```

        printf("Data Received on fd[%d]: %s\n", x, buf);
        //this is in decode.c
        //decode(buf, fds[x]);
}

/** Initialize & Setup file descriptors
 */
void setup(fd_set *in, int *mainsock, int *fds, int i)

int x;

FD_ZERO(in);
FD_SET(*mainsock, in);

for(x=0; x<i; x++)
    FD_SET(fds[x], in);

/** Return a free connection slot, if one is available
 */
int free_slot(int *fds, int *connections)

int x;
int tmp[MAX_CONNECTIONS];

for(x=0; x<(*connections); x++)
    if(fds[x] == 0)

        fds[x] = tmp[x]; //fix it later
        return x;

if((*connections) < MAX_CONNECTIONS)
    return (*connections)+++;

if((*connections) == MAX_CONNECTIONS)
    return (*connections);

return -1;

```