```
+-----------------------------------------------------------------
+
!
!
!      H A C K I N G   H I G H S C H O O L   N E T W O R K
S    !
!
!
!                          PART
1                                !
!
!
!             fortress                at
ease                       !
!             foolproof
mandarin                     !
!
!
!
!
!                  a l i e n b i n a r
y                        !
+-----------------------------------------------------------------
+
```

*~*~*~

Oddly enough, these are used as dummy terminals on a NetWare UNIX machine.
Therefore, if you hack the terminal you are at, you hack the whole thing.

The first thing to do is to check to make sure you are alone. Then open
netscape navigator. Go to the "Network Preferences", it should be under the
options menu in netscape. Change the telnet application from telnet.exe to
winfile.exe. Close the preferences and type in "telnet://x" in the location
menu. Press return and you should have the file manager. From there, you have
the whole computer at your fingertips. More on what you can do with this in
the Mandarin section.

*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*

A T  E A S E

*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*~*

The first way, and easiest is to hold down the shift key when you startup.
This will disable extensions. Then go to the extensions folder and drag at
ease to the trash. DO NOT DELETE IT.

If that does not work, go to the control panels. Then go to the extensions
manager ang uncheck at ease. Then save and restart. At ease should then be
gone.

There are many at ease crackers. These are programs that disable at ease. They
mostly run on hypercard. A few of these programs are "at peace", "dis-ease",
"at ease hacker", "enable", "disable", "un ease". I'm not overly fond of
these, but if you really need to get in, and none of the other methods work,

oh well.

And of course, the Applescript method. Here is a script I wrote for cracking
At Ease.

```
tell application "Finder"
 activate
 select startup disk
 open selection
 select folder "System Folder" of startup disk
 open selection
 close container window of startup disk
 select folder "Extensions" of folder "System Folder" of startup
disk
 open selection
 select file "at ease" of folder "Extensions" of folder "System
Folder" of
startup disk
 delete selection
 empty trash
 close container window of folder "Extensions" of folder "System
Folder" of
startup disk
 close container window of folder "System Folder" of startup disk

end tell
```

I don't know if that program works, I just wrote it, unfortunately, I already
deleted "at ease" on my computer.

*~*~*~

>unfool.exe\". Then
there will be a shimmer, and a picture of a man dressed in motley chained to a
rock will appear. Next a DOS-style alert will appear:

"Are you sure you want to uninstall foolproof?"

[ Yes ]  [ NO ]

click on yes.

Another shimmer, and your in. No more foolproof.

*NOTE: IF THE DOSPROMPT IS UNAVAILABLE, USE THE FORTESS METHOD TO CHANGE
THAT.*

*~*~*~

*~*

IF YOU GET EXPELLED, ARRESTED, OR ANYTHING ELSE, I AM NOT AT FAULT.

*~*~*~