
NSEntityMigrationPolicy Class Reference

Data Management



2010-02-24



Apple Inc.
© 2010 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, iPhone, Mac, Mac OS, and Xcode are trademarks of Apple Inc., registered in the United States and other countries.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, **APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE**

ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

NEntityManagerPolicy Class Reference 5

Overview 5

Tasks 5

 Customizing Stages of the Mapping Life Cycle 5

Instance Methods 6

 beginEntityManagerPolicy: 6

 createDestinationInstancesForSourceInstance:entityManagerPolicy: 6

 createRelationshipsForDestinationInstance:entityManagerPolicy: 7

 endEntityManagerPolicy: 8

 endInstanceCreationForEntityManagerPolicy: 9

 endRelationshipCreationForEntityManagerPolicy: 9

 performCustomValidationForEntityManagerPolicy: 10

Constants 11

 Value Expression Keys 11

Document Revision History 13

NEntityManagerPolicy Class Reference

Inherits from	NSObject
Conforms to	NSObject (NSObject)
Framework	/System/Library/Frameworks/CoreData.framework
Availability	Available in iOS 3.0 and later.
Companion guide	Core Data Model Versioning and Data Migration Programming Guide
Declared in	NEntityManagerPolicy.h

Overview

Instances of `NEntityManagerPolicy` customize the migration process for an entity mapping.

You set the policy for an entity mapping by passing the name of the migration policy class as the argument to `setEntityManagerPolicyClassName:` (typically you specify the name in the Xcode mapping model editor).

Tasks

Customizing Stages of the Mapping Life Cycle

- [beginEntityMapping:manager:error:](#) (page 6)
Invoked by the migration manager at the start of a given entity mapping.
- [createDestinationInstancesForSourceInstance:entityMapping:manager:error:](#) (page 6)
Creates the destination instance(s) for a given source instance.
- [endInstanceCreationForEntityMapping:manager:error:](#) (page 9)
Indicates the end of the creation stage for the specified entity mapping, and the precursor to the next migration stage.
- [createRelationshipsForDestinationInstance:entityMapping:manager:error:](#) (page 7)
Constructs the relationships between the newly-created destination instances.
- [endRelationshipCreationForEntityMapping:manager:error:](#) (page 9)
Indicates the end of the relationship creation stage for the specified entity mapping.

- [performCustomValidationForEntityMapping:manager:error:](#) (page 10)
Invoked during the validation stage of the entity migration policy, providing the option of performing custom validation on migrated objects.
- [endEntityMapping:manager:error:](#) (page 8)
Invoked by the migration manager at the end of a given entity mapping.

Instance Methods

beginEntityMapping:manager:error:

Invoked by the migration manager at the start of a given entity mapping.

- (BOOL)beginEntityMapping:(NSEntityMapping *)*mapping*
manager:(NSMigrationManager *)*manager*
error:(NSError **)*error*

Parameters

mapping

The mapping object in use.

manager

The migration manager performing the migration.

error

If an error occurs, upon return contains an NSError object that describes the problem.

Return Value

YES if the method completes successfully, otherwise NO.

Discussion

This method is the precursor to the creation stage. In a custom class, you can implement this method to set up any state information that will be useful for the duration of the migration.

Availability

Available in iOS 3.0 and later.

See Also

- [createDestinationInstancesForSourceInstance:entityMapping:manager:error:](#) (page 6)
- [endEntityMapping:manager:error:](#) (page 8)

Declared In

NSEntityMigrationPolicy.h

createDestinationInstancesForSourceInstance:entityMapping:manager:error:

Creates the destination instance(s) for a given source instance.

- (BOOL)createDestinationInstancesForSourceInstance:(NSManagedObject *)*sInstance*
entityMapping:(NSEntityMapping *)*mapping*
manager:(NSMigrationManager *)*manager*
error:(NSError **)*error*

Parameters

sInstance

The source instance for which to create destination instances.

mapping

The mapping object in use.

manager

The migration manager performing the migration.

error

If an error occurs, upon return contains an `NSError` object that describes the problem.

Return Value

YES if the method completes successfully, otherwise NO.

Discussion

This method is invoked by the migration manager on each source instance (as specified by the `sourceExpression` in the mapping) to create the corresponding destination instance(s). It also associates the source and destination instances by calling `NSMigrationManager's associateSourceInstance:withDestinationInstance:forEntityMapping: method`.

Special Considerations

If you override this method and do not invoke `super`, you must invoke `NSMigrationManager's associateSourceInstance:withDestinationInstance:forEntityMapping:` to associate the source and destination instances as required. .

Availability

Available in iOS 3.0 and later.

See Also

- [beginEntityMapping:manager:error:](#) (page 6)
- [endInstanceCreationForEntityMapping:manager:error:](#) (page 9)

Declared In

`NSEntityMigrationPolicy.h`

createRelationshipsForDestinationInstance:entityMapping:manager:error:

Constructs the relationships between the newly-created destination instances.

```
- (BOOL)createRelationshipsForDestinationInstance:(NSManagedObject *)dInstance
    entityMapping:(NSEntityMapping *)mapping manager:(NSMigrationManager *)manager
    error:(NSError **)error
```

Parameters

dInstance

The destination instance for which to create relationships.

mapping

The mapping object in use.

manager

The migration manager performing the migration.

error

If an error occurs, upon return contains an `NSError` object that describes the problem.

Return Value

YES if the relationships are constructed correctly, otherwise NO.

Discussion

You can use this stage to (re)create relationships between migrated objects—you use the association lookup methods on the `NSMigrationManager` instance to determine the appropriate relationship targets.

Availability

Available in iOS 3.0 and later.

See Also

- [endInstanceCreationForEntityMapping:manager:error:](#) (page 9)
- [endRelationshipCreationForEntityMapping:manager:error:](#) (page 9)

Declared In

`NSEntityMigrationPolicy.h`

endEntityMapping:manager:error:

Invoked by the migration manager at the end of a given entity mapping.

```
- (BOOL)endEntityMapping:(NSEntityMapping *)mapping
    manager:(NSMigrationManager *)manager
    error:(NSError **)error
```

Parameters

mapping

The mapping object in use.

manager

The migration manager performing the migration.

error

If an error occurs, upon return contains an `NSError` object that describes the problem.

Return Value

YES if the method completes correctly, otherwise NO.

Discussion

This is the end to the given entity mapping. You can implement this method to perform any clean-up at the end of the migration (from any of the three phases of the mapping).

Availability

Available in iOS 3.0 and later.

See Also

- [performCustomValidationForEntityMapping:manager:error:](#) (page 10)
- [beginEntityMapping:manager:error:](#) (page 6)

Declared In

`NSEntityMigrationPolicy.h`

endInstanceCreationForEntityMapping:manager:error:

Indicates the end of the creation stage for the specified entity mapping, and the precursor to the next migration stage.

```
- (BOOL)endInstanceCreationForEntityMapping:(NSEntityMapping *)mapping
      manager:(NSMigrationManager *)manager
      error:(NSError **)error
```

Parameters

mapping

The mapping object in use.

manager

The migration manager performing the migration.

error

If an error occurs, upon return contains an `NSError` object that describes the problem.

Return Value

YES if the relationships are constructed correctly, otherwise NO.

Discussion

You can override this method to clean up state from the creation of destination or to prepare state for the creation of relationships.

Availability

Available in iOS 3.0 and later.

See Also

- [createDestinationInstancesForSourceInstance:entityMapping:manager:error:](#) (page 6)
- [createRelationshipsForDestinationInstance:entityMapping:manager:error:](#) (page 7)

Declared In

NSEntityMigrationPolicy.h

endRelationshipCreationForEntityMapping:manager:error:

Indicates the end of the relationship creation stage for the specified entity mapping.

```
- (BOOL)endRelationshipCreationForEntityMapping:(NSEntityMapping *)mapping
      manager:(NSMigrationManager *)manager
      error:(NSError **)error
```

Parameters

mapping

The mapping object in use.

manager

The migration manager performing the migration.

error

If an error occurs, upon return contains an `NSError` object that describes the problem.

Return Value

YES if the method completes correctly, otherwise NO.

Discussion

This method is invoked after

[createRelationshipsForDestinationInstance:entityMapping:manager:error:](#) (page 7); you can override it to clean up state from the creation of relationships, or prepare state for custom validation in [performCustomValidationForEntityMapping:manager:error:](#) (page 10).

Availability

Available in iOS 3.0 and later.

See Also

- [createRelationshipsForDestinationInstance:entityMapping:manager:error:](#) (page 7)
- [performCustomValidationForEntityMapping:manager:error:](#) (page 10)

Declared In

NSEntityMigrationPolicy.h

performCustomValidationForEntityMapping:manager:error:

Invoked during the validation stage of the entity migration policy, providing the option of performing custom validation on migrated objects.

```
- (BOOL)performCustomValidationForEntityMapping:(NSEntityMapping *)mapping
      manager:(NSMigrationManager *)manager
      error:(NSError **)error
```

Parameters

mapping

The mapping object in use.

manager

The migration manager performing the migration.

error

If an error occurs, upon return contains an `NSError` object that describes the problem.

Return Value

YES if the method completes correctly, otherwise NO.

Discussion

This method is called before the default save validation is performed by the framework.

If you implement this method, you must manually obtain the collection of objects you are interested in validating.

Availability

Available in iOS 3.0 and later.

See Also

- [endRelationshipCreationForEntityMapping:manager:error:](#) (page 9)
- [endEntityMapping:manager:error:](#) (page 8)

Declared In

NSEntityMigrationPolicy.h

Constants

Value Expression Keys

Keys used in value expression right hand sides.

```
NSString *NSMigrationManagerKey;
NSString *NSMigrationSourceObjectKey;
NSString *NSMigrationDestinationObjectKey;
NSString *NSMigrationEntityMappingKey;
NSString *NSMigrationPropertyMappingKey;
NSString *NSMigrationEntityPolicyKey;
```

Constants

`NSMigrationManagerKey`

Key for the migration manager.

To access this key in a custom value expression string in the Xcode mapping model editor use `$manager`.

Available in iOS 3.0 and later.

Declared in `NSEntityMigrationPolicy.h`.

`NSMigrationSourceObjectKey`

Key for the source object.

To access this key in a custom value expression string in the Xcode mapping model editor use `$source`.

Available in iOS 3.0 and later.

Declared in `NSEntityMigrationPolicy.h`.

`NSMigrationDestinationObjectKey`

Key for the destination object.

To access this key in a custom value expression string in the Xcode mapping model editor use `$destination`.

Available in iOS 3.0 and later.

Declared in `NSEntityMigrationPolicy.h`.

`NSMigrationEntityMappingKey`

Key for the entity mapping object.

To access this key in a custom value expression string in the Xcode mapping model editor use `$entityMapping`.

Available in iOS 3.0 and later.

Declared in `NSEntityMigrationPolicy.h`.

`NSMigrationPropertyMappingKey`

Key for the property mapping object.

To access this key in a custom value expression string in the Xcode mapping model editor use `$propertyMapping`.

Available in iOS 3.0 and later.

Declared in `NSEntityMigrationPolicy.h`.

`NSMigrationEntityPolicyKey`

Key for the entity migration policy object.

To access this key in a custom value expression string in the Xcode mapping model editor use `$entityPolicy`.

Available in iOS 3.0 and later.

Declared in `NSEntityMigrationPolicy.h`.

Discussion

You can use these keys in the right hand sides of a value expression.

Document Revision History

This table describes the changes to *NSEntityMigrationPolicy Class Reference*.

Date	Notes
2010-02-24	Added keys for custom value expression strings to Value Expressions.
2009-05-01	Corrected typographical errors.
2009-02-19	Updated for iOS 3.0.
2008-06-02	Updated for Mac OS X v10.6.
2007-05-22	New document that describes the Core Data class uses to customize the migration process for an entity mapping.

REVISION HISTORY

Document Revision History