
SafariExtensionBar Class Reference

User Experience



2010-07-13



Apple Inc.
© 2010 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, and Safari are trademarks of Apple Inc., registered in the United States and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY

DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

SafariExtensionBar Class Reference 5

Overview	5
Tasks	5
Bar Visibility	5
Accessing Windows	5
Identifying Bars	6
Properties	6
browserWindow	6
contentWindow	6
identifier	6
label	6
visible	7
Methods	7
hide	7
show	7

Document Revision History 9

SafariExtensionBar Class Reference

Inherits from	<code>SafariEventTarget</code>
Technology area:	Safari Extensions
Availability	Available in Safari 5.0 and later.

Overview

Instances of the `SafariExtensionBar` class represent a bar that your extension provides. An extension can add any number of bars to Safari. Adding bars is optional.

Safari creates a separate instance of the bars from your extensions for every window. Thus, if the user opens multiple Safari windows, there are multiple `SafariExtensionBar` objects representing the same bar — one in each window. Also, if the user doesn't have any Safari windows open, there are no `SafariExtensionBar` objects.

To access the array of all bars added by your extension, use the `SafariExtension` method `bars`.

Tasks

Bar Visibility

`visible` (page 7)

A Boolean value that indicates whether the bar is visible.

`hide` (page 7)

Hides the bar.

`show` (page 7)

Shows the bar.

Accessing Windows

`browserWindow` (page 6)

The browser window containing the bar.

`contentWindow` (page 6)

The DOM window object of the bar.

Identifying Bars

[identifier](#) (page 6)

The unique identifier of the bar.

[label](#) (page 6)

The title of the bar.

Properties

browserWindow

The browser window containing the bar.

readonly attribute SafariBrowserWindow browserWindow

Availability

Available in Safari 5.0 and later.

contentWindow

The DOM window object of the bar.

readonly attribute DOMWindow contentWindow

Availability

Available in Safari 5.0 and later.

identifier

The unique identifier of the bar.

readonly attribute DOMString identifier

Availability

Available in Safari 5.0 and later.

label

The title of the bar.

attribute DOMString label

Discussion

Setting an empty string, null, or undefined has no effect.

Availability

Available in Safari 5.0 and later.

visible

A Boolean value that indicates whether the bar is visible.

```
readonly attribute boolean visible
```

Availability

Available in Safari 5.0 and later.

Methods

hide

Hides the bar.

```
void hide (in boolean doNotRemember);
```

Parameters

doNotRemember

If `true`, new bars with the same identifier should be also be hidden in the future. Defaults to `false`.

Discussion

If the bar is already hidden, does nothing.

Availability

Available in Safari 5.0 and later.

show

Shows the bar.

```
void show (in boolean doNotRemember);
```

Parameters

doNotRemember

If `true`, new bars with the same identifier should also be shown. Defaults to `false`.

Discussion

If the bar is already being shown, does nothing.

Availability

Available in Safari 5.0 and later.

Document Revision History

This table describes the changes to *SafariExtensionBar Class Reference*.

Date	Notes
2010-07-13	Minor editorial changes throughout.
2010-05-13	New document that describes a class that represents a bar provided by a Safari Extension.

REVISION HISTORY

Document Revision History