
SafariExtensionToolbarItem Class Reference

User Experience



2010-07-13



Apple Inc.
© 2010 Apple Inc.
All rights reserved.

No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, mechanical, electronic, photocopying, recording, or otherwise, without prior written permission of Apple Inc., with the following exceptions: Any person is hereby authorized to store documentation on a single computer for personal use only and to print copies of documentation for personal use provided that the documentation contains Apple's copyright notice.

The Apple logo is a trademark of Apple Inc.

Use of the "keyboard" Apple logo (Option-Shift-K) for commercial purposes without the prior written consent of Apple may constitute trademark infringement and unfair competition in violation of federal and state laws.

No licenses, express or implied, are granted with respect to any of the technology described in this document. Apple retains all intellectual property rights associated with the technology described in this document. This document is intended to assist application developers to develop applications only for Apple-labeled computers.

Every effort has been made to ensure that the information in this document is accurate. Apple is not responsible for typographical errors.

Apple Inc.
1 Infinite Loop
Cupertino, CA 95014
408-996-1010

Apple, the Apple logo, and Safari are trademarks of Apple Inc., registered in the United States and other countries.

Simultaneously published in the United States and Canada.

Even though Apple has reviewed this document, APPLE MAKES NO WARRANTY OR REPRESENTATION, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THIS DOCUMENT, ITS QUALITY, ACCURACY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE. AS A RESULT, THIS DOCUMENT IS PROVIDED "AS IS," AND YOU, THE READER, ARE ASSUMING THE ENTIRE RISK AS TO ITS QUALITY AND ACCURACY.

IN NO EVENT WILL APPLE BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM ANY

DEFECT OR INACCURACY IN THIS DOCUMENT, even if advised of the possibility of such damages.

THE WARRANTY AND REMEDIES SET FORTH ABOVE ARE EXCLUSIVE AND IN LIEU OF ALL OTHERS, ORAL OR WRITTEN, EXPRESS OR IMPLIED. No Apple dealer, agent, or employee is authorized to make any modification, extension, or addition to this warranty.

Some states do not allow the exclusion or limitation of implied warranties or liability for incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

Contents

SafariExtensionToolbarItem Class Reference 5

Overview	5
Tasks	5
Setting Up the Appearance	5
Handling Click Events	5
Properties	6
badge	6
browserWindow	6
command	6
disabled	6
identifier	7
image	7
label	7
paletteLabel	7
toolTip	8
Methods	8
validate	8

Document Revision History 9

SafariExtensionToolbarItem Class Reference

Inherits from	<code>SafariEventTarget</code>
Technology area:	Safari Extensions
Availability	Available in Safari 5.0 and later.

Overview

Instances of the `SafariExtensionToolbarItem` represent items that your extension adds to the Safari toolbar. Users can select which toolbar items are shown by selecting Customize Toolbar in the same way they can add and remove toolbar items that are provided by Safari.

Tasks

Setting Up the Appearance

- `badge` (page 6)
The current badge number.
- `image` (page 7)
The current image URL.
- `label` (page 7)
The label of the toolbar item, as shown in the toolbar's overflow menu.
- `paletteLabel` (page 7)
The label of the toolbar item, as shown in the Customize palette.
- `toolTip` (page 8)
The tooltip (help tag) of the toolbar item.

Handling Click Events

- `browserWindow` (page 6)
The containing browser window.
- `command` (page 6)
The command identifier that the toolbar item sends when it is clicked.
- `disabled` (page 6)
A Boolean value that indicates whether the toolbar item is disabled.

[identifier](#) (page 7)

The unique identifier of the toolbar item.

[validate](#) (page 8)

Dispatches a validate event for this toolbar item.

Properties

badge

The current badge number.

attribute long badge

Discussion

The default value is 0, which hides the badge. If you set a value that is too long, the beginning and end of the value will be shown with an ellipsis in the middle.

Setting a value of `NaN` or `Infinity` is treated as 0. Non-integer values are rounded to the nearest integer.

Availability

Available in Safari 5.0 and later.

browserWindow

The containing browser window.

readonly attribute SafariBrowserWindow browserWindow

Availability

Available in Safari 5.0 and later.

command

The command identifier that the toolbar item sends when it is clicked.

attribute DOMString command

Discussion

This attribute is optional; its value defaults to the value of `identifier`.

Setting a value of `null`, `undefined`, or the empty string has no effect.

Availability

Available in Safari 5.0 and later.

disabled

A Boolean value that indicates whether the toolbar item is disabled.

attribute boolean disabled

Discussion

The default value is `false`. Nothing happens when the user tries to interact with a toolbar item that is disabled.

Availability

Available in Safari 5.0 and later.

identifier

The unique identifier of the toolbar item.

readonly attribute DOMString identifier

Discussion

This attribute is required.

Availability

Available in Safari 5.0 and later.

image

The current image URL.

attribute DOMString image

Discussion

This attribute can be changed to the URL of an image in the extension bundle. Setting a value of `null`, `undefined`, or the empty string has no effect.

Availability

Available in Safari 5.0 and later.

label

The label of the toolbar item, as shown in the toolbar's overflow menu.

attribute DOMString label

Discussion

This attribute is required. Setting a value of `null`, `undefined`, or the empty string has no effect.

Availability

Available in Safari 5.0 and later.

paletteLabel

The label of the toolbar item, as shown in the Customize palette.

```
readonly attribute DOMString paletteLabel
```

Discussion

This attribute is optional; its value defaults to the value of `label`.

Availability

Available in Safari 5.0 and later.

toolTip

The tooltip (help tag) of the toolbar item.

```
attribute DOMString toolTip
```

Discussion

This attribute is optional; its value defaults to the value of `label`.

Setting a value of `null`, `undefined`, or the empty string has no effect.

Availability

Available in Safari 5.0 and later.

Methods

validate

Dispatches a `validate` event for this toolbar item.

```
void validate (void);
```

Discussion

You should call this method after a state change occurs that is relevant to your `validate`-event listeners. Safari also automatically sends `validate` events for many common browser actions, such as switching tabs and navigating to a new page.

Availability

Available in Safari 5.0 and later.

Document Revision History

This table describes the changes to *SafariExtensionToolbarItem Class Reference*.

Date	Notes
2010-07-13	Minor editorial changes throughout.
2010-05-19	New document that describes a class that represents toolbar items.

REVISION HISTORY

Document Revision History