1 of 2

General Information

Why Use 4WIN?

<u>4WIN.INI</u>

Running External Applications

Virus Protection

Why Register?
Shareware Notice & Disclaimer

Commands

ABOUT

ATTRIB

CD/CHDIR

CDD

<u>CLS</u>

COLOR

<u>COPY</u>

DATE

DEL/ERASE

DIR

DISK

<u>ENV</u>

<u>EXIT</u>

<u>HELP</u>

MD/MKDIR

MEMORY

MOVE

<u>PATH</u>

PROFILE

PROMPT

RD/RMDIR

REN/RENAME

TIME

TYPE

<u>VER</u>

VERIFY

<u>VOL</u>

Miscellaneous

4WIN Help Index

2 of 2

Keyboard Topics
Windows Keys

The Index contains a list of all Help topics available for 4WIN. For information on how to use F F1 or choose Using Help from the Help menu.	lelp, press

Why Use 4WIN?

4WIN is Windows application that minimizes, if not eliminates, the need to run a DOS shell such as COMMAND.COM. This is especially useful when not running Windows in enhanced mode, although there is still much to be gained using it there, too. Because 4WIN is a Windows application, you can avoid the problems and inefficiencies associated with running DOS applications under Windows.

4WIN.INI

4WIN.INI is a file that, in order to be read, must reside in the same directory as 4WIN.EXE and is of the following form:

[4WIN]

;encoded name of owner

Owner=

;panning window tracks cursor

AutoTracking=TRUE

;check for <Ctrl+C> or <Ctrl+Break>

CheckBreak=TRUE

;color, gray or mono icon

IconName=color

;default prompt

Prompt=\$p\$g

:RGB values of text color

TextColor=192 192 192

;RGB values of background color

BackgroundColor=0 0 0

;virtual text screen width

ScreenWidth=80

;virtual text screen height

ScreenHeight=100

;title of window

WindowTitle=4WIN

;decimal value of ASCII character for <HistoryDownKey>

HistoryDownKey=24

;decimal value of ASCII character for <HistoryUpKey>

HistoryUpKey=5

;decimal value of ASCII character for <HistorySearchKey>

HistorySearchKey=9

The values shown above are the defaults. Registered users are given an encoded string for the Owner variable which results in the suppression of the registration requests. None of the variables are required, nor does 4WIN.INI need to exist.

Running External Applications

Both Windows and DOS applications may be run from the 4WIN prompt. However, you should ensure that the .PIF file for a given DOS application does not close its window on exit if there is output that you care to view after the DOS program has terminated. If you run .BAT or .COM files that have no corresponding .PIF files, you must include their extensions. 4WIN honors the [Extensions] sections of WIN.INI, but if a given file extension does not have an association, trying to execute it will usually corrupt the system.

Virus Protection

If 4WIN detects that it has been modified in any way, it will refuse to run.

Why Register?

The main reason to purchase any program is because it is ethically correct. Not registering is an abuse of the shareware concept and in the long run will cause this method of distribution to disappear. 4WIN represents a large investment of time and money and as such the author expects compensation if you use 4WIN beyond the trial period. You need only register once for all 1.x versions of 4WIN.

Shareware Notice & Disclaimer

4WIN 1.00 Copyright (c) 1991-1991 Terratech. All rights reserved.					
——————————————————————————————————————					
If you continue to use this program after the 7 day trial period, please remit \$20 to:					
—— Terratech —— 19817 61st Ave. S.E. Snohomish, WA 98290					

A disk will be sent to you containing a registered version. You are encouraged to copy this program as described below.

- ** NOTICE: Users of this program are granted a limited license to make copies of this program for trial use by others on a private non-commercial basis. This limited license does not include:
- 1. Distributing this program in connection with any other product without written permission from Terratech
 - 2. Making the program available for any consideration other than a minimal 'disk fee'
 - 3. Distributing the program in modified form

TERRATECH DISCLAIMS ALL WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCT. SHOULD THE PROGRAM PROVE DEFECTIVE, THE PURCHASER ASSUMES THE RISK OF PAYING THE ENTIRE COST OF ALL NECESSARY SERVICING, REPAIR, OR CORRECTION AND ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. IN NO EVENT WILL TERRATECH BE LIABLE FOR ANY DAMAGES WHATSOEVER (INCLUDING WITHOUT LIMITATION DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, LOSS OF BUSINESS INFORMATION AND THE LIKE) ARISING OUT OF THE USE OR THE INABILITY TO USE THIS PRODUCT EVEN IF TERRATECH HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

?		
Syntax:		
?		
Purpose:		

Displays the available commands.

ABOUT
Syntax:
about
Purpose:
Displays information concerning 4WIN.

ATTRIB

Syntax:

attrib [{+|-}{A|S|H|R}]... [drive:][path][filename]

Purpose:

Displays and optionally changes file attributes.

Comments:

The file attributes are as follows:

A Archive S System H Hidden

R Read-only

Note:

You may display, but not change, the attributes on any file that Windows has open if SHARE is loaded.

CD/CHDIR
Syntax:
cd [drive:][path]
Purpose:
Changes a directory to a different path; displays the working directory.

CDD
Syntax:
cdd [drive:][path]
Purpose:

Changes the drive and directory.

CLS		
Syntax:		
cls		

Purpose:

Clears the screen.

COLOR
Syntax:
color [text RGB values] [background RGB values]
Purpose:

. ... pooo.

Changes the text and background colors.

Note:

The RGB values are a triplet of integers that specify the relative intensities of red, green and blue, respectively. These settings can range from 0 (minimum intensity) to 255 (maximum intensity). Entering COLOR with no arguments sets the colors to the default values.

Some combinations of the background RGB values result in a dithered, rather than a pure color. This causes an undesirable effect during window scrolling. By manually resizing the window height, this condition can be negated.

COPY
Syntax:
copy [drive:][path]sourcefile [drive:][path][targetfile]
Purpose:
Copies one or more files to another location.

DATE
Syntax:
date [mm-dd-yy]
Purpose:

Displays or sets the date.

Syntax:

DEL/ERASE

del [drive:][path][filename]...

Purpose:

Deletes one or more files.

DIR
Syntax:
dir [drive:][path][filename]

Purpose:

Lists the files in a directory.

DIS	K				
Syr	ıtax:				
disk	([dri	ve:]			
Pur	pos	e:			
				.	

Displays the status of the disk.

ENV
Syntax:
env [4win[save]] dos]
Purpose:
Displays the 4WIN or DOS environment and optionally saves the current 4WIN settings.
Note:
4WIN is used if no parameter is given.

EXIT
Syntax:
exit [windows]
Purpose:
Closes 4WIN and optionally exits Windows if all the loaded applications agree.

HELP
Syntax:
help
Purpose:
Invokes the Windows help engine.

MD/MKDIR Syntax:

md [drive:]path

Purpose:

Makes a directory.

MEMORY
Syntax:
memory
Purpose:
Displays a report of the system memory.

Purpose:	
move [drive:][path]sourcefile [drive:][path][targetfile]	
Syntax:	
MOVE	

Copies one or more files to another location. The source file or files are deleted if possible.

Note:

To logically copy files from one directory to another on the same drive, use the <u>REN/RENAME</u> command.

PATH
Syntax:
path
Purpose:
D: 1

Displays the current path.

Syntax:
profile section [[drive:][path][filename]]
Purpose:
Displays the section of the initialization file.
Note:

WIN.INI is used if no file is given. The path is searched unless it is overridden.

PROFILE

PROMPT

Syntax:

prompt [text][\$character]...

Purpose:

Changes the 4WIN command prompt.

Comments:

PROMPT supports the following meta characters:

- \$\$ The \$ character
- **RETURN-LINEFEED**
- \$_ \$4 The 4WIN version
- \$b The | character
- \$d The current date
- \$e **ESCAPE**
- \$g The > character
- \$h **BACKSPACE**
- The < character \$1
- The default drive \$n
- \$p The current directory of the default drive
- The = character \$q
- \$t The current time
- \$v The DOS version
- The Windows version \$w

Note:

Entering PROMPT with no arguments sets the prompt to \$p\$g.

RD/RMDIR	
Syntax:	
rd [drive:]path	
Purpose:	

Deletes a directory.

REN/ERASE

Syntax:

ren [drive:][path]oldfilename [drive:][path]newfilename

or

ren [drive:][path]oldirectoryname [drive:][path]newdirectoryname /d

Purpose:

Changes the names of one or more files; changes the name of a directory

Note:

You are allowed to rename files to another directory as long as they are on the same drive. To copy files to a different drive, use the \underline{MOVE} command.

You may not rename any file that Windows has open if SHARE is loaded.

TIME
Syntax:
time [hours[:minutes[:seconds[.hundredths]]]
Purpose:

Displays or sets the time.

TYPE
Syntax:
type [drive:][path]filename
Purpose:
Displays the contents of one or more files as text on the screen.

VER
Syntax:
ver
Purpose:
Prints the DOS Windows and 4WIN version numbers

Prints the DOS, Windows and 4WIN version numbers.

VERIFY
Syntax:
verify [on off]
Purpose:
Turns the verify switch on of off when writing to a disk; displays the current verify setting.

VOL
Syntax:
vol [drive:]
Purpose:
Displays the disk volume label.

Miscellaneous

- <Ctrl+S> will pause a command.
- <Esc> will abort a command.

The following history keys may be redefined in $\underline{4WIN.INI}$:

- <Ctrl+E> will retrieve commands from the newest to oldest.
- <Ctrl+X> will retrieve commands from the oldest to newest.
- <Tab> will retrieve the newest command that matches as many characters as are currently displayed.

Windows Keys

The keyboard topics below come from Help for Windows. Choose from the following list to review the keys used in Windows:

Cursor Movement Keys
Dialog Box Keys
Editing Keys
Help Keys
Menu Keys
System Keys
Text Selection Keys
Window Keys

Cursor Movement Keys

Key(s)	Function
DIRECTION key	Moves the cursor left, right, up, or down in a field.
End or Ctrl+Right Arrow	Moves to the end of a field.
Home or CTRL+Left Arrow	Moves to the beginning of a field.
PAGE UP or PAGE DOWN	Moves up or down in a field, one screen at a time.

Dialog Box Keys

Key(s)	Function
TAB	Moves from field to field (left to right and top to bottom).
SHIFT+TAB	Moves from field to field in reverse order.
ALT+letter	Moves to the option or group whose underlined letter matches the one you type.
DIRECTION key	Moves from option to option within a group of options.
ENTER	Executes a command button. Or, chooses the selected item in a list box and executes the command.
ESC	Closes a dialog box without completing the command. (Same as Cancel)
ALT+DOWN ARROW	Opens a drop-down list box.
ALT+UP or DOWN ARROW	Selects item in a drop-down list box.
SPACEBAR	Cancels a selection in a list box. Selects or clears a check box.
CTRL+SLASH	Selects all the items in a list box.
CTRL+BACKSLASH	Cancels all selections except the current selection.
SHIFT+ DIRECTION key	Extends selection in a text box.
SHIFT+ HOME	Extends selection to first character in a text box.
SHIFT+ END	Extends selection to last character in a text box

Editing Keys

Key(s)	Function
Backspace	Deletes the character to the left of the cursor.
	Or, deletes selected text.
Delete	Deletes the character to the right of the cursor.
	Or, deletes selected text.

Help Keys

Key(s)	Function
F1	Gets Help and displays the Help Index for the application. If the Help window is already open, pressing F1 displays the "Using Windows Help" topics.
	In some Windows applications, pressing F1 displays a Help topic on the selected command, dialog box option, or system message.
SHIFT+F1 (This feature is not	Changes the pointer to so you can get Help on a specific command, screen region, or key. You can then choose a command, click the screen region, or press a key or key combination you want to know more about. available in all Windows applications.)

Menu Keys

Key(s)	Function
Alt	Selects the first menu on the menu bar.
Letter key	Chooses the menu, or menu item, whose underlined letter matches the one you type.
Alt+letter key	Pulls down the menu whose underlined letter matches the one you type.
LEFT or RIGHT ARROW	Moves among menus.
UP or DOWN ARROW	Moves among menu items.
Enter	Chooses the selected menu item.

System Keys

The following keys can be used from any window, regardless of the application you are using.

Key(s)	Function
Ctrl+Esc	Switches to the Task List.
Alt+Esc	Switches to the next application window or minimized icon, including full-screen programs.
Alt+TAB	Switches to the next application window, restoring applications that are running as icons.
Alt+PrtSc	Copies the entire screen to Clipboard.
Ctrl+F4	Closes the active window.
F1	Gets Help and displays the Help Index for the application. (See $\underline{\text{Help}}$ $\underline{\text{Keys}}$)

Text Selection Keys

Key(s)	Function
SHIFT+LEFT or RIGHT ARROW	Selects text one character at a time to the left or right.
SHIFT+DOWN or UP	Selects one line of text up or down.
SHIFT+END	Selects text to the end of the line.
SHIFT+HOME	Selects text to the beginning of the line.
SHIFT+PAGE DOWN	Selects text down one window.
	Or, cancels the selection if the next window is already selected.
SHIFT+PAGE UP	Selects text up one window.
	Or, cancels the selection if the previous window is already selected.
CTRL+SHIFT+LEFT or RIGHT ARROW	Selects text to the next or previous word.
CTRL+SHIFT+UP or DOWN ARROW	Selects text to the beginning (UP ARROW) or end (DOWN ARROW) of the paragraph.
CTRL+SHIFT+END	Selects text to the end of the document.
CTRL+SHIFT+HOME	Selects text to the beginning of the document.

Window Keys

Key(s)	Function
ALT+SPACEBAR	Opens the Control menu for an application window.
ALT+Hyphen	Opens the Control menu for a document window.
Alt+F4	Closes a window.
Alt+Esc	Switches to the next application window or minimized icon, including full-screen programs.
Alt+TAB	Switches to the next application window, restoring applications that are running as icons.
Alt+ENTER	Switches a non-Windows application between running in a window and running full screen.
DIRECTION key	Moves a window when you have chosen Move from the Control menu. Or, changes the size of a window when you have chosen Size from the Control menu.