SAFETY DATA SHEET

PAGE: 1 of 4

PRINT DATE: 05/08/1997

REF: EML200F/S,400D

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE **COMPANY/UNDERTAKING CONTACT CLEANER LUBRICANT** Product name: EML200F/S,400D Product code: Supplier: **ELECTROLUBE** H.K. Wentworth Ltd., Wentworth House, Blakes Road, Wargrave, Berkshire, RG10 8AW, United Kingdom. Fax No: 0118 9403084 **Emergency telephone number:** 0118 9404031 2. COMPOSITION/INFORMATION ON INGREDIENTS Identification of the preparation CAS-No **EEC-No Chemical Name** Class Weight % ~PENTANE~ F; R11 109-66-0 203-692-4 80 (Sweden: V: R320/322, R313) F; R11 ~PROPAN-2-OL 67-63-0 200-746-9 <5 (Sweden: V: R320/322, R313) CARBON DIOXIDE 124-38-9 3-5 NON HAZARDOUS MATERIAL <15 3. HAZARDS IDENTIFICATION Most important hazards: Highly flammable **Specific hazards** High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects. Prolonged skin contact may defat the skin and produce dermatitis. 4. FIRST AID MEASURES General advice: Remove from exposure, lie down. Inhalation: Move to fresh air. Consult a physician after significant exposure. Skin contact: Wash off immediately with soap and plenty of water. Treatment : skin cream. Eye contact: Rinse immediately with plenty of water for at least 15 minutes. Consult a physician for severe cases. Ingestion: Immediately give large quantities of water to drink. If symptoms persist, call a physician. 5. FIRE-FIGHTING MEASURES Suitable extinguishing media: Extinguish with dry chemical or foam, carbon dioxide (CO2). Extinguishing media which must not be used for safety reasons: Do not use water jet. Specific hazards: Fire or intense heat may cause violent rupture of packages.Water mist may be used to cool closed containers. Special protective equipment for firefighters:

In the event of fire, wear self-contained breathing apparatus.

Product name:

CONTACT CLEANER LUBRICANT

PAGE: 2 of 4

PRINT DATE: 05/08/1997

REF: EML200F/S,400D

Personal precautions:			Remove all sources of ignition.					
Environmental precautions:			Do not contaminate surface water.					
Methods for cleaning up:			Soak up with inert absorbent material. Shovel into suitable container for disposal.					
7. HANDLING AN	D STORAGE							
Handling:	-	Use only in well-ventilated areas. Do not breath vapours or spray mist. When using, do not eat, drink or smoke.						
Storage:		Store in a cool and shaded area. Ensure adequate ventilation. Keep away from heat an sources of ignition.						
8. EXPOSURE CO	ONTROLS / PEF	RSONA	L PRO	TECTI	ON			
Chemical Name:		National occupational exposure limits:						
~PENTANE~			Long term (8 hrs) = 600ppm / 1800mgm ⁻³ Short term (15 min) = 750ppm / 2250mgm ⁻³					
~PROPAN-2-OL			Long term (8 hrs) = 400ppm Short term (15 min) = 500ppm					
CARBON DIOXIDE			Long term (8 hrs) = 5000ppm Short term (15 min) = 15000ppm					
NON HAZARDOUS	MATERIAL							
Engineering meas	ures							
Ensure adequate ve		in confin	ed area	s.				
Personal protection								
 Respiratory protection: 			not required under normal use.					
- Hand protection:			solvent-resistant gloves (butylrubber)					
- Eye protection:			safety glasses					
- Skin and body protection:		not rec	not required under normal use					
Hygiene measures		_						
When using, do not								
9. PHYSICAL AND	D CHEMICAL PI	ROPER	TIES					
Form:		liquid		FOR PENTANE)				
Colour:		colour						
Odour:		charac	teristic					
Boiling point/rang				36		°C		
Melting point/rang	e:			<-130		°C		
Flash point:				-48		°C		
Autoignition temp	erature:	_		309		°C		
Explosion limits:		- lowe	-	1.4		vol. %		
		- uppe		7.8		vol. %		
Vapour pressure:		(19		533.2		hPa		
Relative density:		(20	°C)	>= 0	.63			
•								
Solubility:	14	1 00	° ^ `		- 11 - 1	((1))		
•	•	(20	°C)	immis	cible	(g/l)		

CONTACT CLEANER LUBRICANT

PAGE: 3 of 4

PRINT DATE: 05/08/1997

REF: EML200F/S,400D

	Do not spray on a naked flame or any other incandescent material.				
	oxidizing agents				
products:	none under normal use.				
IFORMATIC	DN .				
	IPA: LD50/oral/rat = 5.05g/kg Pentane: Concentrations substantially above the OEL value may cause narcotic effects (120,000 ppm <1hr). Prolonged exposure (>130,000ppm) - fatality				
	May cause skin irritation	May cause skin irritation in susceptible persons			
	May cause sensitization	by skin contact			
	Liver injury may occur				
	Effects of excessive exp	Effects of excessive exposures may include liver toxicity			
RMATION					
	No data is available on the product itself				
ility:	Readily biodegradable, according to appropriate OECD test				
-					
	No data is available on t	the product itself			
ERATIONS					
sed products	: In accordance with lo	cal and national regulations.			
	Do not pierce or burn even when empty				
MATION					
1950	Marine pollutant:	NO			
2	Item:	5° F			
	HI/UN No:	1950			
e: Aerosol d	ispensers				
2	IMDG Page:	2102			
2-13	MFAG:	620			
Aerosol dispe	ensers				
2.1	UN/ID No:	1950			
Aerosols, flar					
RMATION					
	iractive on classification	of hazardous proparations 00/102/EE			
		1 01 11a2a10005 preparations 50/452/EE			
	RMATION ility: ERATIONS sed products MATION 1950 2 he: Aerosol d 2 2-13 Aerosol dispe 2.1 Aerosols, flat RMATION	material. oxidizing agents none under normal use. IFORMATION IPA: LD50/oral/rat = 5.0 Pentane: Concentration cause narcotic effects ((>130,000ppm) - fatality May cause skin irritation May cause sensitization Liver injury may occur Effects of excessive exp RMATION No data is available on the Readily biodegradable, Not applicable No data is available on the ERATIONS sed products: In accordance with lo Do not pierce or burn MATION 1950 Marine pollutant: 2 Item: HI/UN No: ne: Aerosol dispensers 2.1 UN/ID No: Aerosols, flammable, n.o.s			

- Contains:

Product name:

- Symbol(s):



F - Highly flammable R11 - Highly flammable.

R-phrase(s):

		PAGE:	4 of 4				
Product name:	CONTACT CLEANER LUBRICANT	PRINT DATE:	05/08/1997				
		REF: E	EML200F/S,400D				
S-phrase(s):	S3 - Keep in a cool place S9 - Keep container in a well-ventilated place S16 - Keep away from sources of ignition - No smoking. S33 - Take precautionary measures against static discharges						
16. OTHER INFORI	MATION						
Recommended use	:						
Recommended rest	rictions:						
Revision number:	1						
Further information	: CN no. 34039990						
	Contact Name: Carolyn Booth						
	Department: Technical						

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text