

Informations about the ISDN device

Using the ISDN device

ISDN protocol options

ISDN global options

Tested ISDN boards

Informations about the ISDN device

The ISDN device lets ZOC access CAPI V2.0 DLLs.

Topics:

- o Using the ISDN device
- o ISDN protocol options
- o ISDN global options
- o Tested ISDN boards

ISDN protocol options

The ISDN device has some options. The options dialog offers three buttons to set the most commonly used combinations of settings.

B1/B2/B3

Here you can select the used layer-1, layer-2 and layer-3 protocol. However, not all manufacturers implement all protocols. The default for layer-1 is 64K-HDLC, for layer2 X.75 and for layer-3 TRANS.

CEPT telematic

This option must be selected for using CEPT-based protocols (like the german T-Online) because of their special packet handling.

Framesize

The frame size (block size) can be set from 128 to 2050 bytes. Frame sizes greater 2048 bytes (plus overhead) are not allowed in CAPI V2.0 and should not be used.

Window size

The window size can be selected between two and seven and sets the number of ISDN messages that can be sent from the remote host without acknowledgement from ZOC.

Predefined

These buttons set the above parameters to predefined configurations. 'Standard' will work in most cases (especially if you call hosts which use CFOS or ISDNCOM).

Global

This button opens the ISDN global options window, where you can set general options for your ISDN board.

ISDN global options

This window is opened with the Global-Options button. The parameters set here are used in all ISDN sessions (and not just in the entry from where you opened this window).

Listen MSN

Here you can list all numbers (MSNs) for which ZOC will accept incoming calls. Multiple MSNs must be separated by "|" characters, like in "7406933|7406934". If no MSN is listed, ZOC will accept digital data calls for all MSNs.

Source MSN

This field defines the phone number (MSN) that will be used as the caller id when you make a call. If you do not list a number here, the ISDN network will provide the main MSN of your ISDN socket.

Controller ID

If you are using more than one ISDN board simultaneously, select the board ID here (default is 1).

Set system time to ISDN time

Since ISDN transfers the exact system time when a call is made, you can select, to set your computer's time accordingly.

Tested ISDN boards

ISDN boards of the following manufacturers are tested with this ZOC.

- o AVM
- o BINTEC
- o CREATIX
- o DIEHL
- o ELSA
- o HST
- o HYSDN
- o ITK
- o NCP
- o STOLLMANN
- o TELES

