

**S-RCS- HOW-TO document for Linux (Source Code Control S**

# Table of Contents

<a href="#"><u>CVS–RCS– HOW–TO document for Linux (Source Code Control System)</u></a> .....	1
Al Dev (Alavor Vasudevan) <a href="mailto:alavor@yahoo.com">alavor@yahoo.com</a> .....	1
1. <a href="#"><u>Introduction</u></a> .....	1
2. <a href="#"><u>Which one is for me? CVS or RCS</u></a> .....	1
3. <a href="#"><u>Setting up CVS</u></a> .....	1
4. <a href="#"><u>Intro to CVS commands</u></a> .....	1
5. <a href="#"><u>Shell Scripts</u></a> .....	2
6. <a href="#"><u>CVS Documentation</u></a> .....	2
7. <a href="#"><u>RCS Shell scripts</u></a> .....	2
8. <a href="#"><u>Problem Reporting System</u></a> .....	2
9. <a href="#"><u>Other Formats of this Document</u></a> .....	2
10. <a href="#"><u>Copyright and License</u></a> .....	2
11. <a href="#"><u>sget</u></a> .....	2
12. <a href="#"><u>sedit</u></a> .....	2
13. <a href="#"><u>scommit</u></a> .....	2
14. <a href="#"><u>supdate</u></a> .....	2
15. <a href="#"><u>sunlock</u></a> .....	2
16. <a href="#"><u>slist</u></a> .....	3
17. <a href="#"><u>sinfo</u></a> .....	3
18. <a href="#"><u>slog</u></a> .....	3
19. <a href="#"><u>sdif</u></a> .....	3
20. <a href="#"><u>sadd</u></a> .....	3
21. <a href="#"><u>sdelete</u></a> .....	3
22. <a href="#"><u>sfreeze</u></a> .....	3
1. <a href="#"><u>Introduction</u></a> .....	3
2. <a href="#"><u>Which one is for me? CVS or RCS</u></a> .....	4
3. <a href="#"><u>Setting up CVS</u></a> .....	5
3.1 <a href="#"><u>Environment variables</u></a> .....	5
3.2 <a href="#"><u>Migrate RCS to CVS</u></a> .....	6
4. <a href="#"><u>Intro to CVS commands</u></a> .....	7
4.1 <a href="#"><u>checkout</u></a> .....	7
4.2 <a href="#"><u>update</u></a> .....	8
4.3 <a href="#"><u>add</u></a> .....	8
4.4 <a href="#"><u>remove</u></a> .....	8
4.5 <a href="#"><u>commit</u></a> .....	9
4.6 <a href="#"><u>diff</u></a> .....	9
4.7 <a href="#"><u>Emacs Editor</u></a> .....	9
5. <a href="#"><u>Shell Scripts</u></a> .....	9
6. <a href="#"><u>CVS Documentation</u></a> .....	11
7. <a href="#"><u>RCS Shell scripts</u></a> .....	11
7.1 <a href="#"><u>cotree.sh</u></a> .....	12
7.2 <a href="#"><u>cofiles.sh</u></a> .....	14
7.3 <a href="#"><u>ciall.sh</u></a> .....	15
8. <a href="#"><u>Problem Reporting System</u></a> .....	16
9. <a href="#"><u>Other Formats of this Document</u></a> .....	16
10. <a href="#"><u>Copyright and License</u></a> .....	18
11. <a href="#"><u>sget</u></a> .....	18

# Table of Contents

<a href="#">12.sedit</a> .....	20
<a href="#">13.scommit</a> .....	24
<a href="#">14.supdate</a> .....	28
<a href="#">15.sunlock</a> .....	29
<a href="#">16.slist</a> .....	32
<a href="#">17.sinfo</a> .....	34
<a href="#">18.slog</a> .....	37
<a href="#">19.sdif</a> .....	38
<a href="#">20.sadd</a> .....	40
<a href="#">21.sdelete</a> .....	43
<a href="#">22.sfreeze</a> .....	45

# CVS–RCS– HOW–TO document for Linux (Source Code Control System)

AI Dev (Alavor Vasudevan) [alavor@yahoo.com](mailto:alavor@yahoo.com)

v14.0, 22 July 2000

---

*This document is a "practical guide" to very quickly setup CVS/RCS source code control system. This document also has custom shell scripts which are wrappers on top of CVS. These scripts provide a easy user interface for CVS. The information in this document applies to Linux and as well as to all other flavors of Unix liks Solaris, HPUX, AIX, SCO, Sinix, BSD, SCO, etc..*

---

## [1.Introduction](#)

## [2.Which one is for me? CVS or RCS](#)

## [3.Setting up CVS](#)

- [3.1 Environment variables](#)
- [3.2 Migrate RCS to CVS](#)

## [4.Intro to CVS commands](#)

- [4.1 checkout](#)
- [4.2 update](#)
- [4.3 add](#)
- [4.4 remove](#)
- [4.5 commit](#)
- [4.6 diff](#)
- [4.7 Emacs Editor](#)

## **5.Shell Scripts**

## **6.CVS Documentation**

## **7.RCS Shell scripts**

- [7.1 cotree.sh](#)
- [7.2 cofiles.sh](#)
- [7.3 ciall.sh](#)

## **8.Problem Reporting System**

## **9.Other Formats of this Document**

## **10.Copyright and License**

## **11.sget**

## **12.sedit**

## **13.scommit**

## **14.supdate**

## **15.sunlock**

## 16.[slist](#)

## 17.[sinfo](#)

## 18.[slog](#)

## 19.[sdif](#)

## 20.[sadd](#)

## 21.[sdelete](#)

## 22.[sfreeze](#)

---

## 1.[Introduction](#)

Source code control system is a **MUST** to manage the changes occurring to software project during development. Developers need a complete history of changes to backtrack to previous versions in case of any problems. Since source code is the most vital component of any software project and software development takes a huge amount of time and money, it is very important to spend some time in *safe-guarding* the source code by using source code control systems like CVS and RCS.

CVS (Concurrent Version Control System) is a powerful tool which allows concurrent development of software by multiple users. It uses RCS underneath and has application layer interface as a wrapper on top RCS.

CVS can record the history of your files (usually, but not always, source code). CVS only stores the differences between versions, instead of every version of every file you've ever created. CVS also keeps a log of who, when and why changes occurred, among other aspects.

CVS is very helpful for managing releases and controlling the concurrent editing of source files among multiple authors. Instead of providing version control for a collection of files in a single directory, CVS provides version control for a hierarchical collection of directories consisting of revision controlled files.

These directories and files can then be combined together to form a software release.

CVS can be used for storing "C", "C++", Java, Perl, HTML and other files.

---

## 2. Which one is for me? CVS or RCS

CVS actually uses RCS underneath. CVS is a lot more powerful tool and can control a complete source code tree. It is *very strongly* recommended that you use CVS, because you can greatly customize CVS with scripting languages like PERL, korn and bash shells. See the sample korn shell scripts at [Shell Scripts](#) .

### Advantages of CVS

- CVS is de–centralised a user checks out files/directories from the repository and has his own separate stable source directory tree.
- CVS can "STAMP" releases of entire project source tree.
- CVS can enable concurrent editing of files.
- CVS can be greatly customized to enable strong locking of files or enable concurrent editing of files using shell scripts or PERL.

### Disadvantages of CVS

- Needs a little more administration than RCS
- Very highly sophisticated and complex system. It is the "State of the Art" technology. The cvs software is very advanced and capable system developed over very long period of time (it took several years!!).
- Has a large number of commands and command options, hence a steeper learning curve for beginners. The shell scripts at [Shell Scripts](#) can ease usage.

### Advantages of RCS

- RCS is very simple to setup, with less administrative work.
- RCS is used in a centralized area where everyone works.
- RCS is useful for simple systems.
- Very strong locking of files – concurrency eliminated.

### Downside of RCS

- Concurrent development by multiple developers is not possible due to file locking and being limited to a single working directory. Because of the single working directory limitation changes to files by multiple developers can cause failure of the 'make' command.
- Cannot stamp releases of an entire software project.

This document also has shell scripts which provide simple commands to check–out, check–in, commit files. See shell scripts at [Shell Scripts](#)

For RCS see the RCS mini–howto on the linux cdrom –

---

```
cd /mnt/cdrom/Redhat/RPMS
ls -l howto-6.0-*.noarch.rpm
rpm -qpl howto-6* | grep -i rcs
```

---

or visit <http://www.LinuxDoc.org/HOWTO/mini/RCS.html>

See also the RCS shell scripts at [rcs scripts](#)

---

## 3. Setting up CVS

First you need to install the CVS package, on Redhat linux use

---

```
cd /mnt/cdrom/Redhat/RPMS
rpm -i rcs*.rpm
rpm -i cvs*.rpm
To see the list of files installed do -
rpm -qpl cvs*.rpm | less
```

---

and browse output using j,k, CTRL+f, CTRL+D, CTRL+B, CTRL+U or using arrow keys, page up/down keys. See 'man less'.

On other flavors of unix, you may need to download the RCS and CVS tar balls and follow README, INSTALL files to setup CVS. Visit <http://www.cyclic.com> and <http://www.loria.fr/~molli/cvs-index.html>

### 3.1 Environment variables

The following environment variables need to be setup in /etc/profile – default values required for all users. If not set in /etc/profile, than you should add these to your local profile file `/.bash_profile`.

---

```
export EDITOR=/bin/vi
export CVSROOT=/home/cvsroot
export CVSREAD=yes
```

---

Create a directory to store the source code repository and give read, write access to unix group/user. Also make sure that the directory name of CVSROOT does not contain any blank spaces. For example CVSROOT should not be like '/home/my rootcvs'.

---

```
export CVSROOT=/home/cvsroot
mkdir $CVSROOT
chmod o-rwx $CVSROOT
chmod ug+rwx $CVSROOT
```

---

Now, change the group of \$CVSROOT to group–name of users who want to use cvs sytem.

---

```
chgrp users $CVSROOT
```

---

To initialize the CVS and to put in source code files do –

---

```
cvs init
# Change directory is a must
```



```
cd $HOME/my_source_code_dir

# Must give vendor tag and revision tag
cvs import my_source_code_dir V1_0 R1_0
```

---

## 3.2 Migrate RCS to CVS

To migrate the existing RCS files to CVS, use the following script. Make sure that you installed korn shell package `pdksh*.rpm` from Linux contrib cdrom.

**NOTE :** *Korn shell /bin/ksh is obtained by installing `pdksh*.rpm` from Linux contrib cdrom*

---

```
#!/bin/ksh

#####
# Program to Migrate the existing source code in RCS to CVS
#
# Needs the korn shell RPM package  pdksh*.rpm from Linux
# contrib cdrom
#####

#
# rcs2cvs - convert source tree from RCS to CVS
#

# project to convert
PROJECT='project'

# current RCS root
RCSROOT="$HOME/rcs"

if cd "$RCSROOT/$PROJECT"
then
    cd "$RCSROOT"
else
    echo >&2 "`basename "$0"`: can't change to RCS directory '$RCSROOT/$PROJECT'."
    exit 1
fi

# current CVS root
CVSROOT="$HOME/cvs"

# create new CVS directory for project 'project'
if mkdir "$CVSROOT/$PROJECT"
then
    :
else
    echo >&2 "`basename "$0"`: can't create CVS directory '$CVSROOT/$PROJECT'."
    exit 2
fi

# create CVS project tree from RCS tree
find "$PROJECT" -type d -name RCS -print |
while read RCS
do
    CVS=`dirname "$RCS"`
    (if cd "$RCS"
```

```

then
#       if find . -type f -name '*,v' -print | cpio -pdmv "$CVSROOT/$CVS"
       if find . -type f -print | cpio -pdmv "$CVSROOT/$CVS"
       then
           :
       else
           echo >&2 "`basename "$0"`: can't convert RCS subdirectory '$RCSROOT/$RCS'
       fi
else
       echo >&2 "`basename "$0"`: can't change to RCS subdirectory '$RCSROOT/$RCS'."
fi)
done

```

---

Now the RCS is migrated to CVS as 'project'. You can start using the CVS commands on module 'project'.

---

## 4. Intro to CVS commands

cvcs provides a rich variety of commands (cvcs\_command in the Synopsis), each of which often has a wealth of options, to satisfy the many needs of source management in distributed environments. However, you don't have to master every detail to do useful work with cvcs; in fact, five commands are sufficient to use (and contribute to) the source repository. The most commonly used CVS commands are **checkout**, **update**, **add**, **remove**, **commit** and **diff**.

### 4.1 checkout

**cvcs checkout modules...** A necessary preliminary for most cvcs work: creates your private copy of the source for modules (named collections of source; you can also use a path relative to the source repository here). You can work with this copy without interfering with others' work. At least one subdirectory level is always created.

---

```

bash$ cvcs --help checkout
Usage:
  cvcs checkout [-ANPRcflnps] [-r rev | -D date] [-d dir]
  [-j rev1] [-j rev2] [-k kopt] modules...
  -A      Reset any sticky tags/date/kopts.
  -N      Don't shorten module paths if -d specified.
  -P      Prune empty directories.
  -R      Process directories recursively.
  -c      "cat" the module database.
  -f      Force a head revision match if tag/date not found.
  -l      Local directory only, not recursive
  -n      Do not run module program (if any).
  -p      Check out files to standard output (avoids stickiness).
  -s      Like -c, but include module status.
  -r rev  Check out revision or tag. (implies -P) (is sticky)
  -D date Check out revisions as of date. (implies -P) (is sticky)
  -d dir  Check out into dir instead of module name.
  -k kopt Use RCS kopt -k option on checkout.
  -j rev  Merge in changes made between current revision and rev.
(Specify the --help global option for a list of other help options)

```

---

## 4.2 update

**cvs update** Execute this command from within your private source directory when you wish to update your copies of source files from changes that other developers have made to the source in the repository.

---

```
bash$ cvs --help update
Usage: cvs update [-APdflRp] [-k kopt] [-r rev|-D date] [-j rev]
      [-I ign] [-W spec] [files...]
      -A      Reset any sticky tags/date/kopts.
      -P      Prune empty directories.
      -d      Build directories, like checkout does.
      -f      Force a head revision match if tag/date not found.
      -l      Local directory only, no recursion.
      -R      Process directories recursively.
      -p      Send updates to standard output (avoids stickiness).
      -k kopt Use RCS kopt -k option on checkout.
      -r rev  Update using specified revision/tag (is sticky).
      -D date Set date to update from (is sticky).
      -j rev  Merge in changes made between current revision and rev.
      -I ign  More files to ignore (! to reset).
      -W spec Wrappers specification line.
(Specify the --help global option for a list of other help options)
```

---

## 4.3 add

**cvs add file...** Use this command to enroll new files in cvs records of your working directory. The files will be added to the repository the next time you run `cvs commit'. Note: You should use the `cvs import' command to bootstrap new sources into the source repository. `cvs add' is only used for new files to an already checked-out module.

---

```
bash$ cvs --help add
Usage: cvs add [-k rcs-kflag] [-m message] files...
      -k      Use "rcs-kflag" to add the file with the specified kflag.
      -m      Use "message" for the creation log.
(Specify the --help global option for a list of other help options)
```

---

## 4.4 remove

**cvs remove file...** Use this command (after erasing any files listed) to declare that you wish to eliminate files from the repository. The removal does not affect others until you run `cvs commit'.

---

```
bash$ cvs --help remove
Usage: cvs remove [-flR] [files...]
      -f      Delete the file before removing it.
      -l      Process this directory only (not recursive).
      -R      Process directories recursively.
(Specify the --help global option for a list of other help options)
```

---

## 4.5 commit

**cvs commit file...** Use this command when you wish to ``publish'' your changes to other developers, by incorporating them in the source repository.

---

```
bash$ cvs --help commit
Usage: cvs commit [-nRlf] [-m msg | -F logfile] [-r rev] files...
    -n      Do not run the module program (if any).
    -R      Process directories recursively.
    -l      Local directory only (not recursive).
    -f      Force the file to be committed; disables recursion.
    -F file Read the log message from file.
    -m msg  Log message.
    -r rev  Commit to this branch or trunk revision.
(Specify the --help global option for a list of other help options)
```

---

## 4.6 diff

**cvs diff file...** Show differences between files in working directory and source repository, or between two revisions in source repository. (Does not change either repository or working directory.)

---

```
bash$ cvs --help diff
Usage: cvs diff [-lNR] [rcsdiff-options]
    [[-r rev1 | -D date1] [-r rev2 | -D date2]] [files...]
    -l      Local directory only, not recursive
    -R      Process directories recursively.
    -D d1   Diff revision for date against working file.
    -D d2   Diff rev1/date1 against date2.
    -N      include diffs for added and removed files.
    -r rev1 Diff revision for rev1 against working file.
    -r rev2 Diff rev1/date1 against rev2.
    --ifdef=arg  Output diffs in ifdef format.
(consult the documentation for your diff program for rcsdiff-options.
The most popular is -c for context diffs but there are many more).
(Specify the --help global option for a list of other help options)
```

---

## 4.7 Emacs Editor

Emacs is a powerful editor and it supports CVS/RCS – especially for revision merging and comparing. Emacs main site is at <http://www.emacs.org>.

## 5. Shell Scripts

The following are wrappers around the basic CVS commands. The scripts are written for Korn shell since korn shell is always available on all flavors of unixes, but you can translate to bash or PERL if needed. You can customize these scripts to your taste. They are basically CVS commands but features are added to make it site specific. For example, sedit script provides locking so that users will know some-one is editing the file. Of course users can directly use the CVS commands to by-pass these scripts. These scripts demonstrate how

CVS can be customized to a great extent.

**NOTE:** *The wrapper shell scripts assume that the user's home directory as the root and check out the tree from cvs to build the tree underneath user's home directory.*

**TIP:** *In shell scripts, every target filename is composed of 3 parts – Home directory, sub-directory and the filename. The full-path is \$HOME/\$subdir/\$fname And in CVS the same directory structure is maintained (by variable \$subdir) therefore in cvs there will be something like \$CVSROOT/\$subdir/\$fname. In all scripts, these 4 variables \$HOME, \$CVSROOT, \$subdir and \$fname play a important role. For example, sample values can be like HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot and fname=foo.cpp*

Copy these scripts to /usr/local/bin and this should be in the user's PATH environment.

1. **sget** [-r revision\_number] <file/directory name> To get a file or entire directory from CVS in READ ONLY mode. Click [sget](#)
2. **sedit** [-r revision\_number] <filename> To edit a file in order to make changes to code. This will lock the file so that nobody else can checkout. Ofcourse you can change the script to your requirement – make no locking, warning message or very strong locking. Click [sedit](#)
3. **scommit** [-r revision\_number] <filename> To commit the changes you made to filename or entire directory. Upload your changes to CVS Click [scommit](#)
4. **supdate** <filename/directory> To update a filename or to update a entire directory by getting the latest files from CVS Click [supdate](#)
5. **sunlock** [-r revision\_number] <filename> To unlock the file got by sedit. Will release the lock. Click [sunlock](#)
6. **slist** To see the list of files currently being edited by you. Does 'ls -l | grep | ...' command. Click [slist](#) . Note that there is also another unix command by name slist (list available Netware servers), you should make sure cvs script slist comes before other in your PATH environment.
7. **sinfo** <filename/directory> To get the information of changes/revisions to a file Click [sinfo](#)
8. **slog** <filename> To get the history of changes/revisions to a file from CVS Click [slog](#)
9. **sdif** <filename>

**sdif** -r rev1 -r rev2 <filename> To get the diff of your file with CVS. Click [sdif](#)

NOTE: sdif has only one 'f' because there is already another unix command called 'sdiff'

10. **sadd** <filename> To add a new file to CVS repository Click [sadd](#)
11. **sdelete** <filename> To delete a file from CVS repository Click [sdelete](#)
12. **sfreeze** <revision name> <directory name> To freeze the code, that is make release of entire source tree. Click [sfreeze](#)

For example :

---

```
cd $HOME;
sfreeze REVISION_1_0 srctree
```

---

This will freeze code with tag REVISION\_1\_0 so that you can later checkout the entire tree by using with revision name

\*\*\*\*\*

## 6. [CVS Documentation](#)

At unix prompt type –

1. cvs --help
2. cvs --help-options
3. cvs --help-commands
4. cvs -H checkout
5. cvs -H commit
6. man cvs
7. man tkcvs
8. Visit <http://www.cyclic.com>
9. Visit <http://www.loria.fr/~molli/cvs-index.html>

The tkcvs <http://www.tkcvs.org> is the Tcl/Tk GUI interface to CVS. It also has online help.

- cd \$HOME/src/foo.cpp
- tkcvs
- Click on foo.cpp
- Click on 'Revision Log Icon' which is located next to 'spectacle' icon
- This will display the branch TREE in the window. Now RIGHT Mouse button click on the text '1.3' and LEFT Mouse button click on text '1.1'. Then click on "Diff" button. This will display 2 pane-window!!
- Click on "Next" button to step thru more diffs. Click on "Center" to center the text.

There is also a Windows 95 client for CVS, and is called WinCVS <http://www.wincvs.org> WinCVS can be used along with Samba – <http://www.samba.org>

The essential command are –

- cvs checkout <filename >
  - cvs update <filename>
  - cvs add <file, ..>
  - cvs remove <file, ..>
  - cvs commit <file>
  - cvs status <filename>
  - cvs log <filename>
  - cvs diff -r1.4 -r1.5 <filename> This gives diff between version 1.4 and 1.5 on filename.
- 

## 7. [RCS Shell scripts](#)

If you want to use RCS instead of CVS then you can use the following shell scripts.

## 7.1 cotree.sh

---

```
#!/bin/ksh

# cotree.sh (Check Out Tree shell script)
# cotree.sh - Check out the entire RCS directory

# Usage :
# This will get the all the directories
#     unix> cotree.sh
#
# This will get just one single directory tree
#     unix> cotree.sh <directory name>

# See also cfiles.sh

#####
# Setting up RCS (Revision Control System)
# Install the RCS programs - which gives command co, ci, rcslog
# Create a rcs home directory where you want to put all the
# source code repository. Call this $RCS_DIR=/home/rcs_version_control
# Setup up a environment variable RCS_DIR=/home/rcs_version_control
# in $HOME/.profile file. Like -
#     export RCS_DIR=/home/rcs_version_control
# Create a directory structure under $RCS_DIR and check in all your
# files using ci . See 'man ci'
# Now create a link from your home directory to your project
# under $RCS_DIR
#     cd $HOME
#     mkdir $HOME/myproject
#     cd $HOME/myproject
# and run this script to get all the files and directory tree
#     cotree.sh
# This script will create the entire source-tree under user's
# home and also will have a soft link to RCS directories. Each
# user will run this script under his home directory.
#####

check_out_directory()
{
    # Root directory of RCS (revision control system)
    # like RCS_DIR=/home/rcs_version_control
    RCS_DIR=$1
    DIRNAME=$2

    # The given directory name must exist in rcs root directory
    if [ "$DIRNAME" = "" -o ! -d $RCS_DIR/$DIRNAME ]; then
        print "\nDirectory DIRNAME=$DIRNAME does not exist!!"
        print "\nAborting the program ... and exiting...\n"
        exit
    fi

    mkdir -p $DIRNAME
    ln -s $RCS_DIR/$DIRNAME/RCS $DIRNAME
    (
        cd $DIRNAME

        # This fails in case of filename=sample,vv
        # which inside RCS will be RCS/sample,vv,v
        # ls RCS | cut -d',' -f1 | xargs co
    )
}

```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
# Use match to end of name $, as below -
# Use ls RCS/* to avoid getting the names ./ and ../
#ls RCS/* | cut -d '/' -f2 | sed -e 's/,v$//g' | xargs co
if [ -d RCS ]; then
    ls RCS/* | cut -d '/' -f2 | sed -e 's/,v$//g' | \
    while read ii
    do
        #echo "ii is : $ii"
        if [ -f "RCS/$ii,v" ]; then
            co $ii
        fi
    done
fi
)
}

# Root directory of RCS (revision control system)
# like RCSDIR=/home/rcs_version_control
if [ "$RCSDIR" = "" -o ! -d $RCSDIR ]; then
    print "\nDirectory RCSDIR=$RCSDIR does not exist!!"
    print "\nAborting the program ... and exiting...\n"
    exit
fi
#echo "rcsdir is : $RCSDIR"

# If a directory argument is passed, then check out all
# files for this directory only and exit.
if [ "$1" != "" ]; then
    (cd $RCSDIR; find $1 -type d -print ) |
    while read DIRNAME
    do
        #echo DIRNAME=$DIRNAME
        #DIRNAME=c_src
        # Send rcs root directory and dir name relative to rcs root dir
        tmpaa=`basename $DIRNAME`
        if [ "$tmpaa" != "RCS" ]; then
            check_out_directory $RCSDIR $DIRNAME
        fi
    done
else
    (cd $RCSDIR; find * -type d -print ) |
    while read DIRNAME
    do
        echo DIRNAME=$DIRNAME
        #DIRNAME=c_src
        # Send rcs root directory and dir name relative to rcs root dir
        tmpaa=`basename $DIRNAME`
        if [ "$tmpaa" != "RCS" ]; then
            check_out_directory $RCSDIR $DIRNAME
        fi
    done
fi
```

---



## 7.2 cofiles.sh

---

```
#!/bin/ksh

# cofiles.sh (Check Out files shell script)
# cofiles.sh - Check out all the files in current directory from RCS
# See also cotree.sh and 'man rcsclean'

if [ ! -d RCS ]; then
    print "\nDirectory RCS does not exist!!"
    print "\nAborting the program ... and exiting...\n"
    exit
fi

#echo "No. of args = " $# " and all args " $@

while true
do
    print -n "\n\nCheck-out all files in read-write mode? <y/n> [n]: "
    read ans
    if [ "$ans" = "" -o "$ans" = "n" -o "$ans" = "N" ]; then
        ans="N"
        break
    elif [ "$ans" = "y" -o "$ans" = "Y" ]; then
        ans="Y"
        break
    else
        print "\nWrong entry! Try again!!"
    fi
done
#echo "The ans is : " $ans

if [ $# -eq 0 ]; then
    # The 'ls RCS' fails in case of filename=sample,vv in RCS/sample,vv,v
    # ls RCS | cut -d',' -f1 | xargs co
    # Use match to end of name $, as below -
    if [ "$ans" = "Y" ]; then
        ls RCS | sed -e's/,v$/g' | xargs co -l
    else
        ls RCS | sed -e's/,v$/g' | xargs co
    fi
elif [ $# -eq 1 ]; then
    if [ -f "RCS/$1,v" ]; then
        # Here, in this case $1 will be like dbalter.sql
        # and not like db*.sql....
        #echo "One arg, no. of args = " $# " and all args " $@
        if [ "$ans" = "Y" ]; then
            co -l "$1"
        else
            co "$1"
        fi
    else
        # For case where $1=db*.sql and there is no db*.sql in
        # current directory
        #echo "No files... no. of args = " $# " and all args " $@
        tmpaa="RCS/$1,v" # will be like RCS/db*.sql,v
        ls $tmpaa | \
        while read ii
        do
            #echo "ii is : $ii"
        done
    fi
fi
```

```

        if [ "$ans" = "Y" ]; then
            co -l "$ii"
        else
            co "$ii"
        fi
    done
fi
else
    for ii in $@
    do
        #echo "ii is : $ii,v"
        if [ "$ans" = "Y" ]; then
            co -l "$ii"
        else
            co "$ii"
        fi
    done
fi

```

---

## 7.3 ciall.sh

---

```

#!/bin/ksh

# ciall.sh (Check in files shell script)
# ciall.sh - Check in all the files in current directory into RCS
# This script is very useful for checking in enmass large number
# of new files into RCS. Saves time by avoiding to type the
# 'description' for every file
# And for files already in RCS, it does regular check-in command

# To convert filenames to lower case filenames, use this
# technique - use 'tr', see 'man tr'
#ls * | \
#while read ii
#do
#    jj=`echo $ii | tr [A-Z] [a-z] `
#    echo "ii is : $ii"
#    echo "jj is : $jj"
#    mv $ii $jj
#done

if [ ! -d RCS ]; then
    print "\nDirectory RCS does not exist!!"
    print "\nWill be creating RCS directory now ... \n"
    mkdir RCS
fi

print "\n\nNOTE: This is not log message!"
print "Please enter description (will be used for"
print -n "all the files checked in) : "
read description

#find * -prune -type f |

# The number of args is zero or more....
if [ $# -eq 0 ]; then

```

```
listoffiles=""*"  
else  
listoffiles="$@"  
fi  
  
find $listoffiles -prune -type f |  
while read ii  
do  
#echo $ii  
if [ -f "RCS/$ii,v" ]; then  
#print "The file $ii already in RCS"  
ci -m"$description" $ii  
else  
#print "The file $ii is new file"  
ci $ii << EOF  
$description  
EOF  
fi  
done
```

---

---

## [8. Problem Reporting System](#)

Along with CVS, you may want to use Project Tracking system or Problem Reporting system. Every software project needs a Problem Reporting System where in bugs are tracked and assigned to various developers. Visit the site <http://www.stonekeep.com> for Project tracking system.

---

## [9. Other Formats of this Document](#)

This document is published in 11 different formats namely – DVI, Postscript, Latex, Adobe Acrobat PDF, LyX, GNU-info, HTML, RTF(Rich Text Format), Plain-text, Unix man pages and SGML.

- You can get this HOWTO document as a single file tar ball in HTML, DVI, Postscript or SGML formats from – <ftp://sunsite.unc.edu/pub/Linux/docs/HOWTO/other-formats/>
- Plain text format is in: <ftp://sunsite.unc.edu/pub/Linux/docs/HOWTO>
- Translations to other languages like French, German, Spanish, Chinese, Japanese are in <ftp://sunsite.unc.edu/pub/Linux/docs/HOWTO> Any help from you to translate to other languages is welcome.

The document is written using a tool called "SGML-Tools" which can be got from – <http://www.sgmltools.org> Compiling the source you will get the following commands like

- `sgml2html CVS-HOWTO.sgml` (to generate html file)
- `sgml2rtf CVS-HOWTO.sgml` (to generate RTF file)
- `sgml2latex CVS-HOWTO.sgml` (to generate latex file)

LaTeX documents may be converted into PDF files simply by producing a Postscript output using `sgml2latex` ( and `dvips`) and running the output through the Acrobat `distill` ( <http://www.adobe.com>) command as follows:

---

```
bash$ man sgml2latex
bash$ sgml2latex filename.sgm1
bash$ man dvips
bash$ dvips -o filename.ps filename.dvi
bash$ distill filename.ps
bash$ man ghostscript
bash$ man ps2pdf
bash$ ps2pdf input.ps output.pdf
bash$ acroread output.pdf &
```

---

Or you can use Ghostscript command **ps2pdf**. ps2pdf is a work-alike for nearly all the functionality of Adobe's Acrobat Distiller product: it converts PostScript files to Portable Document Format (PDF) files. **ps2pdf** is implemented as a very small command script (batch file) that invokes Ghostscript, selecting a special "output device" called **pdfwrite**. In order to use ps2pdf, the pdfwrite device must be included in the makefile when Ghostscript was compiled; see the documentation on building Ghostscript for details.

This howto document is located at –

- <http://sunsite.unc.edu/LDP/HOWTO/CVS-HOWTO.html>

Also you can find this document at the following mirrors sites –

- <http://www.caldera.com/LDP/HOWTO/CVS-HOWTO.html>
- <http://www.WGS.com/LDP/HOWTO/CVS-HOWTO.html>
- <http://www.cc.gatech.edu/linux/LDP/HOWTO/CVS-HOWTO.html>
- <http://www.redhat.com/linux-info/ldp/HOWTO/CVS-HOWTO.html>
- Other mirror sites near you (network-address-wise) can be found at <http://sunsite.unc.edu/LDP/hmirrors.html> select a site and go to directory /LDP/HOWTO/CVS-HOWTO.html

In order to view the document in dvi format, use the xdvi program. The xdvi program is located in tetex-xdvi\*.rpm package in Redhat Linux which can be located through ControlPanel | Applications | Publishing | TeX menu buttons. To read dvi document give the command –

```
xdvi -geometry 80x90 howto.dvi
man xdvi
```

And resize the window with mouse. To navigate use Arrow keys, Page Up, Page Down keys, also you can use 'f', 'd', 'u', 'c', 'l', 'r', 'p', 'n' letter keys to move up, down, center, next page, previous page etc. To turn off expert menu press 'x'.

You can read postscript file using the program 'gv' (ghostview) or 'ghostscript'. The ghostscript program is in ghostscript\*.rpm package and gv program is in gv\*.rpm package in Redhat Linux which can be located through ControlPanel | Applications | Graphics menu buttons. The gv program is much more user friendly than ghostscript. Also ghostscript and gv are available on other platforms like OS/2, Windows 95 and NT, you view this document even on those platforms.

- Get ghostscript for Windows 95, OS/2, and for all OSes from <http://www.cs.wisc.edu/~ghost>

To read postscript document give the command –

```
gv howto.ps
ghostscript howto.ps
```

You can read HTML format document using Netscape Navigator, Microsoft Internet explorer, Redhat Baron Web browser or any of the 10 other web browsers.

You can read the latex, LyX output using LyX a X-Windows front end to latex.

---

## 10. [Copyright and License](#)

Copyright Al Dev (Alavoor Vasudevan) 1998–2000.

License is GNU GPL, but it is requested that you retain the author's name and email on all copies.

---

## 11. [sget](#)

**NOTE :** *Korn shell /bin/ksh is got by installing pdksh\*.rpm from Linux contrib cdrom*

Save this file as text file and chmod a+rx on it.

---

```
#!/bin/ksh

# CVS program sget
# Program to check out the file from CVS read-only

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#          spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`

Usage()
{
    print "\nUsage: $cmdname [-r revision_number/symbolic_tag_name] <file/directory name> "
    print "The options -r are optional "
    print "For example - "
    print " $cmdname -r 1.1 foo.cpp"
    print " $cmdname foo.cpp "
    print " $cmdname some_directory "
```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
    print "Extract by symbolic revision tag like - "  
    print " $cmdname -r REVISION_1 some_directory "  
    print " "  
    exit  
}  
  
# Command getopt will not supported in next major release.  
# Use getopts instead.  
while getopts r: ii  
do  
    case $ii in  
        r) FLAG1=$ii; OARG1="$OPTARG";;  
        ?) Usage; exit 2;;  
    esac  
done  
shift `expr $OPTIND - 1`  
  
#echo FLAG1 = $FLAG1 , OARG1 = $OARG1  
  
if [ $# -lt 1 ]; then  
    Usage  
fi  
  
bkextn=sget_bak  
  
homedir=`echo $HOME | cut -f1 -d' '`  
if [ "$homedir" = "" ]; then  
    print "\nError: $HOME is not set!!\n"  
    exit  
fi  
  
cur_dir=`pwd`  
#echo $cur_dir  
  
len=${#homedir}  
len=$((len + 2))  
#echo $len  
  
subdir=`echo $cur_dir | cut -b $len-2000`  
#echo "subdir is : " $subdir  
tmpaa=`dirname $1`  
if [ "$tmpaa" = "." ]; then  
    fname=$1  
    if [ "$subdir" = "" ]; then  
        subdir=$tmpaa  
    fi  
else  
    fname=`basename $1`  
    if [ "$subdir" = "" ]; then  
        subdir=$tmpaa  
    else  
        subdir="$subdir/$tmpaa"  
    fi  
fi  
#echo "subdir is : " $subdir  
#echo "fname is : " $fname  
  
# Check if file already exists....  
if [ -f "$HOME/$subdir/$fname" ]; then  
    tmpaa="$HOME/$subdir/$fname"  
    user_perms=" "  
    group_perms=" "
```

```

other_perms=" "
user_perms=`ls -l $tmpaa | awk '{print $tmpaa }' | cut -b3-3 `
group_perms=`ls -l $tmpaa | awk '{print $tmpaa }' | cut -b6-6 `
other_perms=`ls -l $tmpaa | awk '{print $tmpaa }' | cut -b9-9 `
if [ "$user_perms" = "w" -o "$group_perms" = "w" \
    -o "$other_perms" = "w" ]; then
    print "\nError: The file is writable. Aborting $cmdname ....."
    print "        You should either backup, scommit or delete the file and"
    print "        try $cmdname again\n"
    exit
fi

fi

# Move the file
mkdir -p "$HOME/$subdir"
touch "$HOME/$subdir/$fname" 2>/dev/null
\mv -f "$HOME/$subdir/$fname" "$HOME/$subdir/$fname.$bkextn"

# Create subshell
(
    cd $homedir

    # Use -A option to clear all sticky flags
    if [ "$FLAG1" = "" ]; then
        if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
            cvs -r checkout -A $fname
        else
            cvs -r checkout -A "$subdir/$fname"
        fi
    else
        if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
            cvs -r checkout -A -$FLAG1 $OARG1 $fname
        else
            cvs -r checkout -A -$FLAG1 $OARG1 "$subdir/$fname"
        fi
    fi

)
#pwd

if [ -f "$HOME/$subdir/$fname" ]; then
    print "\nREAD-ONLY copy of the file $subdir/$fname obtained."
    print "Done $cmdname"
    #print "\nTip (Usage): $cmdname <file/directory name> \n"
fi

```

---



---

## 12.sedit

**NOTE : Korn shell /bin/ksh is got by installing *pdksh\*.rpm* from *Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

```

#!/bin/ksh

# CVS program sedit
# Program to check out the file from CVS read/write mode with locking

```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#           spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`

Usage()
{
    print "\nUsage: $cmdname [-r revision_number] [-F] <filename>"
    print "The options -r, -F are optional "
    print "The option -F is FORCE edit even if file is "
    print "locked by another developer"

    print "\nUsage: $cmdname [-r revision_number] <filename>"
    print "The options -r are optional "

    print "For example - "
    print " $cmdname -r 1.1 foo.cpp"
    print " $cmdname foo.cpp "
    # print " $cmdname -F foo.cpp "
    print " "
}

# Command getopt will not supported in next major release.
# Use getopt instead.
#while getopt r:F ii
while getopt r: ii
do
    case $ii in
        r) FLAG1=$ii; OARG1="$OPTARG";;
        # F) FLAG2=$ii; OARG2="$OPTARG";;
        ?) Usage; exit 2;;
    esac
done
shift ` expr $OPTIND - 1 `

#echo FLAG1 = $FLAG1 , OARG1 = $OARG1

if [ $# -lt 1 ]; then
    Usage
    exit
fi

homedir=` echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: \ $HOME is not set!!\n"
    exit
fi

bkextn=sedit_bak

cur_dir=`pwd`
#echo $cur_dir
```



```

len=${#homedir}
len=$(( $len + 2 ))
#echo $len

subdir=` echo $cur_dir | cut -b $len-2000 `
tmpaa=`dirname $1`
if [ "$tmpaa" = "." ]; then
    fname=$1
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    fi
else
    fname=`basename $1`
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    else
        subdir="$subdir/$tmpaa"
    fi
fi
# echo "subdir is : " $subdir
# echo "fname is : " $fname

# If file is already checked out by another developer...
cvs_root=` echo $CVSROOT | cut -f1 -d' ' `
if [ "$cvs_root" = "" ]; then
    print "\nError: \ $CVSROOT is not set!!\n"
    exit
fi
mkdir -p "$CVSROOT/$subdir/Locks" 2>/dev/null

if [ ! -e "$CVSROOT/$subdir/$fname,v" ]; then
    print "\nError: File $fname does not exist in CVS repository!!\n"
    exit
fi

# CVS directory in your local directory is required for all commands..
if [ ! -d "$homedir/$subdir/CVS" ]; then
    tmpaa=` (cd "$CVSROOT/$subdir"; find * -prune -type f -print | head -1 ) `
    tmpbb=`basename $tmpaa | cut -d',' -f1 `
    if [ "$tmpaa" = "" -o ! -f "$CVSROOT/$subdir/$tmpbb,v" ]; then
        print "\nThe directory $homedir/$subdir/CVS does not exist"
        print "You must do a sget on `basename $subdir` directory. Give -"
        print "      cd $homedir/`dirname $subdir` "
        print "      sget `basename $subdir` "
        exit
    else
        # Now try to create CVS in local dir by sget
        (
            cd "$homedir"
            if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
                cvs -r checkout -A $tmpbb
            else
                cvs -r checkout -A "$subdir/$tmpbb"
            fi
        )
    fi
fi

# Get the tip revision number of the file...
# Use tmpfile as the arg cannot be set inside the sub-shell
tmpfile=$homedir/sedit-lock.tmp

```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```

\rm -f $tmpfile 2>/dev/null
if [ "$FLAG1" = "" ]; then
(
  cd $homedir
    if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
      cvs log $fname | head -6 | grep head: | awk '{print $2}' > $tmpfile
    else
      cvs log "$subdir/$fname" | head -6 | grep head: | awk '{print $2}' > $tmpfile
    fi
  )
  OARG1=`cat $tmpfile`
  \rm -f $tmpfile 2>/dev/null
fi

lockfile="$CVSROOT/$subdir/Locks/$fname-$OARG1"
#echo "lockfile is : " $lockfile
#if [ -e $lockfile -a "$FLAG2" = "" ]; then
if [ -e $lockfile ]; then
  print "\nError: File $fname Revision $OARG1 already locked by another developer !!"
  aa=`ls -l $lockfile | awk '{print "Locking developers unix login name is = " $3}'`
  print $aa
  print "That developer should do scommit OR sunlock to release the lock"
  print " "
#   print "You can also use -F option to force edit the file even if"
#   print "the file is locked by another developer. But you must talk to"
#   print "other developer to work concurrently on this file."
#   print "For example - this option is useful if you work on a seperate"
#   print "C++ function in the file which does not interfere with other"
#   print "developer."
#   print " "
  exit
fi

# Get read-only copy now...
if [ ! -e "$HOME/$subdir/$fname" ]; then
(
  cd $homedir
    if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
      cvs -r checkout $fname 1>/dev/null
    else
      cvs -r checkout "$subdir/$fname" 1>/dev/null
    fi
  )
fi

# Check if file already exists....
tmpaa="$HOME/$subdir/$fname"
if [ -f $tmpaa ]; then
  user_perms=" "
  group_perms=" "
  other_perms=" "
  user_perms=`ls -l $tmpaa | awk '{print $tmpaa}' | cut -b3-3`
  group_perms=`ls -l $tmpaa | awk '{print $tmpaa}' | cut -b6-6`
  other_perms=`ls -l $tmpaa | awk '{print $tmpaa}' | cut -b9-9`
  if [ "$user_perms" = "w" -o "$group_perms" = "w" \
    -o "$other_perms" = "w" ]; then
    print "\nError: The file is writable. Aborting $cmdname ....."
    print "      You must backup, scommit or delete file and"
    print "      try $cmdname again\n"
    exit
  fi
  #print "\nNote: The file $tmpaa is read-only."

```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
#print "Hence I am moving it to $tmpaa.$bkextn ....\n"
\mv -f $tmpaa $tmpaa.$bkextn
chmod 444 $tmpaa.$bkextn
elif [ -d $tmpaa ]; then
    print "\nError: $tmpaa is a directory and NOT a file. Aborting $cmdname ....\n"
    exit
fi

# Create subshell
print "\nNow getting the file $fname from CVS repository ... \n"
(
    cd $homedir
    # Use -A option to clear the sticky tag and to get
    # the HEAD revision version
    if [ "$FLAG1" = "" ]; then
        if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
            cvs -w checkout -A $fname
        else
            cvs -w checkout -A "$subdir/$fname"
        fi
    else
        if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
            cvs -w checkout -A -$FLAG1 $OARG1 $fname
        else
            cvs -w checkout -A -$FLAG1 $OARG1 "$subdir/$fname"
        fi
    fi
)

if [ -e "$HOME/$subdir/$fname" ]; then
    # The lockfile is $CVSROOT/$subdir/Locks/$fname-$OARG1
    touch $lockfile
fi

#pwd

print "\nDone $cmdname"
#print "\nTip (Usage): $cmdname <filename> \n"
```

---

---

## 13.scommit

**NOTE :** *Korn shell /bin/ksh is got by installing `pdksh*.rpm` from Linux contrib cdrom*

Save this file as text file and chmod a+rx on it.

---

```
#!/bin/ksh

# CVS program scommit
# Program to commit the changes and check in the file into CVS

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname
```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#           spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`

Usage()
{
    print "\nUsage: $cmdname [-r revision_number] <filename>"
    print "The options -r are optional "
    print "For example - "
    print " $cmdname -r 1.1 foo.cpp"
    print " $cmdname foo.cpp "
    print " "
}

# Command getopt will not supported in next major release.
# Use getopt instead.
while getopts r: ii
do
    case $ii in
        r) FLAG1=$ii; OARG1="$OPTARG";;
        ?) Usage; exit 2;;
    esac
done
shift ` expr $OPTIND - 1 `

#echo FLAG1 = $FLAG1 , OARG1 = $OARG1

if [ $# -lt 1 ]; then
    Usage
    exit 2
fi

if [ -d $1 ]; then
    Usage
    exit 2
fi

homedir=` echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: \ $HOME is not set!!\n"
    exit
fi

# Find sub-directory
cur_dir=`pwd`
#echo $cur_dir
len=${#homedir}
len=$(( $len + 2 ))
#echo $len

subdir=` echo $cur_dir | cut -b $len-2000 `
tmpaa=`dirname $1`
if [ "$tmpaa" = "." ]; then
    fname=$1
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    fi
fi
```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
else
    fname=`basename $1`
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    else
        subdir="$subdir/$tmpaa"
    fi
fi
# echo "subdir is : " $subdir
# echo "fname is : " $fname

# If file is already checked out by another user....
cvs_root=` echo $CVSROOT | cut -f1 -d' ' `
if [ "$cvs_root" = "" ]; then
    print "\nError: \ $CVSROOT is not set!!\n"
    exit
fi
mkdir -p "$CVSROOT/$subdir/Locks" 2>/dev/null

# CVS directory in your local directory is required for all commands..
if [ ! -d "$homedir/$subdir/CVS" ]; then
    tmpaa=` (cd "$CVSROOT/$subdir"; find * -prune -type f -print | head -1 ) `
    tmpbb=`basename $tmpaa | cut -d',' -f1 `
    if [ "$tmpaa" = "" -o ! -f "$CVSROOT/$subdir/$tmpbb,v" ]; then
        print "\nThe directory $homedir/$subdir/CVS does not exist"
        print "You must do a sget on `basename $subdir` directory. Give -"
        print "          cd $homedir/`dirname $subdir` "
        print "          sget `basename $subdir` "
        exit
    else
        # Now try to create CVS in local dir by sget
        (
            cd "$homedir"
            if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
                cvs -r checkout -A $tmpbb
            else
                cvs -r checkout -A "$subdir/$tmpbb"
            fi
        )
    fi
fi

# Get the working revision number of the file....
# Use tmpfile as the arg cannot be set inside the sub-shell
tmpfile=$homedir/sedit-lock.tmp
\rm -f $tmpfile 2>/dev/null
if [ "$FLAG1" = "" ]; then
    (
        cd $homedir
        if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
            cvs status $fname 2>/dev/null | grep "Working revision:" | awk '{print $3}'
        else
            cvs status "$subdir/$fname" 2>/dev/null | grep "Working revision:" | awk
        fi
    )
    OARG1=`cat $tmpfile`
    \rm -f $tmpfile 2>/dev/null
fi

if [ "$OARG1" = "" ]; then
    print "The file $subdir/$fname is NEW, it is not in the CVS repository"
else
```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
lockfile="$CVSROOT/$subdir/Locks/$fname-$OARG1"

if [ -e $lockfile ]; then
    # Check if this revision is owned by you...
    aa=`ls -l $lockfile | awk '{print $3}' `
    userid=`id | cut -d'(' -f2 | cut -d')' -f1 `
    if [ "$aa" != "$userid" ]; then
        print " "
        print "The file $subdir/$fname is NOT locked by you!!"
        print "It is locked by unix user name $aa and your login name is $userid"
        print "If you are working concurrently with other developer"
        print "and you used -F option with sedit."
        print "You need to wait untill other developer does scommit"
        print "or sunlock"
        print "Aborting the $cmdname ...."
        print " "
        exit 2
    fi
else
    # The file must exist in cvs
    if [ -f "$CVSROOT/$subdir/$fname,v" ]; then
        print "You did not lock the file $subdir/$fname with sedit!!"
        print "Aborting the $cmdname ...."
        exit 2
    else
        print "\nThe file $subdir/$fname does not exist in CVS repository yet!!"
        print "You should have done sadd on $subdir/$fname ...."
        exit 2
    fi
fi

fi

# Operate inside sub-shell - and operate from root directory
(
    cd $homedir

    # Do not allow directory commits for now ...
    #if [ -d "$subdir/$fname" ]; then
    #    cvs commit "$subdir/$fname"
    #fi

    if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
        cvs commit $fname
    else
        cvs commit "$subdir/$fname"
    fi
    exit_status=$?

    if [ $exit_status -eq 0 ]; then
        lockfile="$CVSROOT/$subdir/Locks/$fname-$OARG1"
        if [ -e $lockfile ]; then
            \rm -f $lockfile
        fi

        # Must change the permissions on file in case
        # there are no changes to file
        chmod a-w "$HOME/$subdir/$fname"
        print "\nDone $cmdname. $cmdname successful"
        #print "\nTip (Usage): $cmdname <filename/directory name>\n"
    fi
)
)
```

## 14.[supdate](#)

**NOTE :** *Korn shell /bin/ksh is got by installing `pksh*.rpm` from *Linux contrib cdrom**

Save this file as text file and `chmod a+rx` on it.

```
#!/bin/ksh

# CVS program supdate
# Program to update the file from CVS read/write mode

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#          spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`

if [ $# -lt 1 ]; then
    print "\nUsage: $cmdname <filename>"
    exit
fi

# Put double quotes to protect spaces in $1
tmpaa="$1"

# Check if file already exists....
if [ $# -gt 0 -a -f $tmpaa ]; then
    user_perms=" "
    group_perms=" "
    other_perms=" "
    user_perms=`ls -l $tmpaa | awk '{print $tmpaa }' | cut -b3-3 `
    group_perms=`ls -l $tmpaa | awk '{print $tmpaa }' | cut -b6-6 `
    other_perms=`ls -l $tmpaa | awk '{print $tmpaa }' | cut -b9-9 `
    if [ "$user_perms" = "w" -o "$group_perms" = "w" \
        -o "$other_perms" = "w" ]; then
        while :
        do
            print "\n$cmdname will backup your working file "
            print "$tmpaa to $tmpaa.supdate_bak before doing any merges."
            print "Are you sure you want the merge the changes from"
            print -n "CVS repository to your working file ? <y/n> [n]: "
            read ans
            if [ "$ans" = "y" -o "$ans" = "Y" ]; then
                if [ -f $tmpaa.supdate_bak ]; then
                    print "\nWarning : File $tmpaa.supdate_bak already exists"
                    print "Please examine the file $tmpaa.supdate_bak and del"
                    print "and than re-try this $cmdname "
                fi
            fi
        done
    fi
fi
```

```

                                print "Aborting $cmdname ...."
                                exit
                                else
                                cp $tmpaa $tmpaa.supdate_bak
                                break
                                fi
                                elif [ "$ans" = "n" -o "$ans" = "N" -o "$ans" = "" -o "$ans" = " " ]; then
                                exit
                                fi
                                done
                                fi
                                fi

if [ -d $tmpaa ]; then
    print "\nDirectory update is disabled because cvs update"
    print "merges the changes from repository to your working directory."
    print "Hence give the filename to update - as shown below: "
    print " Usage: $cmdname <filename>"
    exit
#    cvs update
else
    cvs update $tmpaa
fi

print "\nDone $cmdname. $cmdname successful"
print "\n\nThe original file is backed-up to $tmpaa.supdate_bak"
print "\nHence your original file is SAVED to $tmpaa.supdate_bak"
print "\n\n"
#print "\nTip (Usage): $cmdname <filename/directory name>\n"

```

---



---

## 15.[sunlock](#)

**NOTE :** Korn shell /bin/ksh is got by installing *pdksh\*.rpm* from *Linux contrib cdrom*

Save this file as text file and chmod a+rx on it.

```

#!/bin/ksh

# CVS program sunlock
# Program to unlock the file to release the lock done by sedit

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#          spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`

```



```

Usage()
{
    print "\nUsage: $cmdname [-r revision_number] <filename>"
    print " The options -r is optional "
    print "For example - "
    print " $cmdname -r 1.1 foo.cpp"
    print " $cmdname foo.cpp "
    print " "
}

# Command getopt will not supported in next major release.
# Use getopt instead.
while getopts r: ii
do
    case $ii in
        r) FLAG1=$ii; OARG1="$OPTARG";;
        ?) Usage; exit 2;;
    esac
done
shift `expr $OPTIND - 1`

if [ $# -lt 1 ]; then
    Usage
    exit
fi

homedir=`echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: \ $HOME is not set!!\n"
    exit
fi

cur_dir=`pwd`
#echo $cur_dir

len=${#homedir}
len=$((len + 2))
#echo $len

subdir=`echo $cur_dir | cut -b $len-2000 `
#echo "subdir is : " $subdir
tmpaa=`dirname $1`
if [ "$tmpaa" = "." ]; then
    fname=$1
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    fi
else
    fname=`basename $1`
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    else
        subdir="$subdir/$tmpaa"
    fi
fi
#echo "subdir is : " $subdir
#echo "fname is : " $fname

cvs_root=`echo $CVSROOT | cut -f1 -d' ' `
if [ "$cvs_root" = "" ]; then
    print "\nError: \ $CVSROOT is not set!!\n"
    exit

```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
fi

if [ ! -e "$CVSROOT/$subdir/$fname,v" ]; then
    print "\nError: File $fname does not exist in CVS repository!!\n"
    exit
fi

# CVS directory in your local directory is required for all commands..
if [ ! -d "$homedir/$subdir/CVS" ]; then
    tmpaa=`(cd "$CVSROOT/$subdir"; find * -prune -type f -print | head -1)`
    tmpbb=`basename $tmpaa | cut -d',' -f1`
    if [ "$tmpaa" = "" -o ! -f "$CVSROOT/$subdir/$tmpbb,v" ]; then
        print "\nThe directory $homedir/$subdir/CVS does not exist"
        print "You must do a sget on `basename $subdir` directory. Give -"
        print "      cd $homedir/`dirname $subdir`"
        print "      sget `basename $subdir`"
        exit
    else
        # Now try to create CVS in local dir by sget
        (
            cd "$homedir"
            if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
                cvs -r checkout -A $tmpbb
            else
                cvs -r checkout -A "$subdir/$tmpbb"
            fi
        )
    fi
fi

# Get the tip revision number of the file....
# Use tmpfile as the arg cannot be set inside the sub-shell
tmpfile=$homedir/sunlock-lock.tmp
\rm -f $tmpfile 2>/dev/null
if [ "$FLAG1" = "" ]; then
    # Operate inside sub-shell - from root directory
    (
        cd $homedir
        if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
            cvs log $fname | head -6 | grep head: | awk '{print $2}' > $tmpfile
        else
            cvs log "$subdir/$fname" | head -6 | grep head: | awk '{print $2}' > $tmpfile
        fi
    )
    OARG1=`cat $tmpfile`
    \rm -f $tmpfile 2>/dev/null
fi

lockfile="$CVSROOT/$subdir/Locks/$fname-$$$OARG1"
#echo lockfile is : $lockfile
if [ ! -e $lockfile ]; then
    print "\nFile $fname revision $$$OARG1 is NOT locked by anyone"
    print " "
    exit
fi

ans=""
while :
do
    print "\n\n*****"
    print "WARNING: $cmdname will release lock and enable other"
    print "      developers to edit the file. It is advisable"
```

```

print "          to save your changes with scommit command"
print "*****"
print -n "\nAre you sure you want to unlock the file <y/n>? [n]: "
read ans
if [ "$ans" = "" -o "$ans" = " " -o "$ans" = "n" -o "$ans" = "N" ]; then
    print "\nAborting $cmdname ...."
    exit
fi
if [ "$ans" = "y" -o "$ans" = "Y" ]; then
    print "\n\n\n\n\n "
    print "CAUTION: You may lose all the changes made to file!!"
    print -n "Are you sure? Do you really want to unlock the file <y/n>? [n]: "
    read ans
    if [ "$ans" = "y" -o "$ans" = "Y" ]; then
        break
    elif [ "$ans" = "" -o "$ans" = " " -o "$ans" = "n" -o "$ans" = "N" ]; then
        exit
    else
        print "\n\nWrong entry. Try again..."
        sleep 1
    fi
else
    print "\n\nWrong entry. Try again..."
    sleep 1
fi
done

if [ -e $lockfile ]; then
    \rm -f $lockfile
    print "\nDone $cmdname"
else
    print "\nFile $fname is NOT locked by anyone"
    print " "
fi

```

---



---

## 16.[slist](#)

**NOTE :** *Korn shell /bin/ksh is got by installing `pksh*.rpm` from Linux contrib cdrom*

Save this file as text file and `chmod a+rx` on it.

Note that there is also another unix command by name `slist` (list available Netware servers), you should make sure `cvs script slist` comes before other in your `PATH` environment.

---

```

#!/bin/ksh

# CVS program slist
# Program to list all edited source files from CVS

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname

```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#           spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

# Usage:
#           $ slist      (All files and sub-directories)
#           $ slist *.*  (All files)
#           $ slist *    (All files and sub-directories)
#           $ slist ab*  (All files starting with ab wild-card)

homedir=` echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: \ $HOME is not set!!\n"
    exit
fi

cur_dir=`pwd`
#echo $cur_dir

len=${#homedir}
len=$(( $len + 2 ))
#echo $len

subdir=` echo $cur_dir | cut -b $len-2000 `
#echo "subdir is : " $subdir

# If file is already checked out by another developer....
cvs_root=` echo $CVSROOT | cut -f1 -d' ' `
if [ "$cvs_root" = "" ]; then
    print "\nError: \ $CVSROOT is not set!!\n"
    exit
fi

# If the current directory tree is not in cvs-root then exit
if [ ! -d $CVSROOT/$subdir ]; then
    print "\nThe directory $subdir does not exist in $CVSROOT"
    exit
fi

#echo "no of params : " $#
#echo "The arg $ 1 is : " $1
#echo "all args : " $@

if [ $# -eq 0 ]; then
    tmpbb=` find * -prune -type d `
elif [ $# -eq 1 ]; then
    if [ "$1" = "." ]; then
        tmpbb=` find * -prune -type d `
    else
        if [ -d $1 -a ! -d $CVSROOT/$subdir/$1 ]; then
            print "\nThe directory $subdir/$1 does not exist in $CVSROOT"
            exit
        fi
        tmpbb=$@
    fi
else
    tmpbb=$@
fi
```

```

#echo "The tmpbb is : " $tmpbb

# Now, remove all the directory names which are not in cvs-root
dirnames=""
for ii in $tmpbb ; do
    if [ -d $CVSROOT/$subdir/$ii ]; then
        dirnames="$dirnames $ii "
    fi
done
#echo "The dirnames is : " $dirnames

if [ "$dirnames" != "" ]; then
    find $dirnames -type f |
    while read ii
    do
        # List only those files which are in cvs system
        if [ -f "$CVSROOT/$subdir/$ii,v" ]; then
            #echo "ii is : " $ii
            ls -l $ii | grep ^\-rw
        fi
    done;
fi

# Get all the files in the current directory
listfiles=`ls $tmpbb `
find * -prune -type f |
while read ii
do
    for jj in $listfiles ; do
        if [ "$jj" = "$ii" ]; then
            # List only those files which are in cvs system
            if [ -f "$CVSROOT/$subdir/$ii,v" ]; then
                #echo "ii is : " $ii
                ls -l $ii | grep ^\-rw
            fi
        fi
    done
done;

```

---

## 17.[sinfo](#)

**NOTE :** *Korn shell /bin/ksh is got by installing `pksh*.rpm` from `Linux contrib cdrom`*

Save this file as text file and `chmod a+rx` on it.

---

```

#!/bin/ksh

# CVS program sinfo
# Program to get the status of files in working directory

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname

```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#           spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`

if [ $# -lt 1 ]; then
    print "\nUsage: $cmdname [file/directory name] "
    print "For example - "
    print " $cmdname foo.cpp"
    print " $cmdname some_directory "
    print " "
    exit
fi

homedir=` echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: \ $HOME is not set!!\n"
    exit
fi

cur_dir=`pwd`
#echo $cur_dir

len=${#homedir}
len=$((len + 2))
#echo $len

subdir=` echo $cur_dir | cut -b $len-2000 `
#echo "subdir is : " $subdir
tmpaa=`dirname $1`
if [ "$tmpaa" = "." ]; then
    fname=$1
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    fi
else
    fname=`basename $1`
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    else
        subdir="$subdir/$tmpaa"
    fi
fi
#echo "subdir is : " $subdir
#echo "fname is : " $fname

# CVS directory in your local directory is required for all commands..
if [ ! -d "$homedir/$subdir/CVS" ]; then
    tmpaa=` (cd "$CVSROOT/$subdir"; find * -prune -type f -print | head -1 ) `
    tmpbb=`basename $tmpaa | cut -d',' -f1 `
    if [ "$tmpaa" = "" -o ! -f "$CVSROOT/$subdir/$tmpbb,v" ]; then
        print "\nThe directory $homedir/$subdir/CVS does not exist"
        print "You must do a sget on `basename $subdir` directory. Give -"
        print "          cd $homedir/`dirname $subdir` "
        print "          sget `basename $subdir` "
        exit
    else
        # Now try to create CVS in local dir by sget
    fi
fi
```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
(
    cd "$homedir"
    if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
        cvs -r checkout -A $tmpbb
    else
        cvs -r checkout -A "$subdir/$tmpbb"
    fi
)
fi

# Create subshell
if [ -f $1 ]; then
    (
        cd $homedir
        clear
        print "\ncvs status is : "
        cvs status "$subdir/$fname"
    )
elif [ -d $1 ]; then
    (
        cd $homedir
        clear
        print "\ncvs status is : "
        tmpfile="$homedir/cvs_sinfo.tmp"
        rm -f $tmpfile
        echo " " >> $tmpfile
        echo " *****" >> $tmpfile
        echo " Overall Status of Directory" >> $tmpfile
        echo " *****" >> $tmpfile
        cvs release "$subdir/$fname" 1>>$tmpfile 2>>$tmpfile << EOF
N
EOF
        echo "\n -----\n" >> $tmpfile

aa=`cat $tmpfile | grep ^"M " | awk '{print $2}' `
for ii in $aa
do
    jj="(cd $homedir; cvs status \"$subdir/$ii\" );"
    echo $jj | /bin/sh \
        | grep -v Sticky | awk '{if (NF != 0) print $0}' \
        1>>$tmpfile 2>>$tmpfile
done

cat $tmpfile | grep -v ^? | grep -v "Are you sure you want to release" \
| less
rm -f $tmpfile
)
else
print "\nArgument $1 if not a file or directory"
exit
fi
```

---

---

## 18.slog

**NOTE :** Korn shell `/bin/ksh` is got by installing `pdksh*.rpm` from *Linux contrib cdrom*

Save this file as text file and `chmod a+rx` on it.

---

```
#!/bin/ksh

# CVS program slog
# Program to list history of the file in CVS

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#          spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`

if [ $# -lt 1 ]; then
    print "\nUsage: $cmdname <filename> \n"
    exit
fi

# Check if file does not exist....
if [ ! -f "$1" ]; then
    print "\nError: $1 is NOT a file. Aborting $cmdname ....."
    exit
fi

homedir=` echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: \ $HOME is not set!!\n"
    exit
fi

cur_dir=`pwd`
#echo $cur_dir

len=${#homedir}
len=$(( $len + 2 ))
#echo $len

subdir=` echo $cur_dir | cut -b $len-2000 `
#echo "subdir is : " $subdir
tmpaa=`dirname $1`
if [ "$tmpaa" = "." ]; then
    fname="$1"
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    fi
else
    fname=`basename $1`
```



## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
if [ "$subdir" = "" ]; then
    subdir=$tmpaa
else
    subdir="$subdir/$tmpaa"
fi
fi
#echo "subdir is : " $subdir
#echo "fname is : " $fname

# CVS directory in your local directory is required for all commands..
if [ ! -d "$homedir/$subdir/CVS" ]; then
    tmpaa=`(cd "$CVSROOT/$subdir"; find * -prune -type f -print | head -1 )`
    tmpbb=`basename $tmpaa | cut -d',' -f1`
    if [ "$tmpaa" = "" -o ! -f "$CVSROOT/$subdir/$tmpbb,v" ]; then
        print "\nThe directory $homedir/$subdir/CVS does not exist"
        print "You must do a sget on `basename $subdir` directory. Give -"
        print "          cd $homedir/`dirname $subdir` "
        print "          sget `basename $subdir` "
        exit
    else
        # Now try to create CVS in local dir by sget
        (
            cd "$homedir"
            if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
                cvs -r checkout -A $tmpbb
            else
                cvs -r checkout -A "$subdir/$tmpbb"
            fi
        )
    fi
fi

# Operate inside a sub-shell
(
    cd $homedir
    cvs log "$homedir/$subdir/$fname" | less
)

print "\nDone $cmdname. $cmdname successful"
#print "\nTip (Usage): $cmdname <filename>\n"
```

---

---

## 19.sdif

**NOTE : Korn shell /bin/ksh is got by installing *pksh\*.rpm* from *Linux contrib cdrom***

Save this file as text file and chmod a+rx on it.

---

```
#!/bin/ksh

# CVS program sdif
# Program to see difference of the working file with CVS copy

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#           spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`

Usage()
{
    print "\nUsage: $cmdname <filename> "
    print "$cmdname -r<rev1> -r<rev2> <filename> \n"
    exit
}

homedir=` echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: \ $HOME is not set!!\n"
    exit
fi

FLAG1=""
FLAG2=""
OARG1=""
OARG2=""
# Command getopt will not supported in next major release.
# Use getopt instead.
while getopt r:r: ii
do
    case $ii in
        r)
            if [ "$FLAG1" = "" ]; then
                FLAG1=$ii;
                OARG1="$OPTARG"
            else
                FLAG2=$ii;
                OARG2="$OPTARG"
            fi
            ;;
        ?) Usage; exit 2;;
    esac
done
shift ` expr $OPTIND - 1 `

if [ "$FLAG2" = "" ]; then
    FLAG2=r
    OARG2=HEAD
fi

cur_dir=`pwd`
#echo $cur_dir

len=${#homedir}
len=$(( $len + 2 ))
#echo $len

subdir=` echo $cur_dir | cut -b $len-2000 `
#echo "subdir is : " $subdir
tmpaa=`dirname $1`
```

```

if [ "$tmpaa" = "." ]; then
    fname="$1"
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    fi
else
    fname=`basename $1`
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    else
        subdir="$subdir/$tmpaa"
    fi
fi
#echo "subdir is : " $subdir
#echo "fname is : " $fname

# CVS directory in your local directory is required for all commands..
if [ ! -d "$homedir/$subdir/CVS" ]; then
    tmpaa=`(cd "$CVSROOT/$subdir"; find * -prune -type f -print | head -1 )`
    tmpbb=`basename $tmpaa | cut -d',' -f1`
    if [ "$tmpaa" = "" -o ! -f "$CVSROOT/$subdir/$tmpbb,v" ]; then
        print "\n\nThe directory $homedir/$subdir/CVS does not exist"
        print "You must do a sget on `basename $subdir` directory. Give -"
        print "      cd $homedir/`dirname $subdir`"
        print "      sget `basename $subdir`"
        exit
    else
        # Now try to create CVS in local dir by sget
        (
            cd "$homedir"
            if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
                cvs -r checkout -A $tmpbb
            else
                cvs -r checkout -A "$subdir/$tmpbb"
            fi
        )
    fi
fi

# Operate inside sub-shell
(
    cd $homedir
    if [ "$FLAG1" = "" ]; then
        cvs diff -r HEAD "$homedir/$subdir/$fname" | less
    else
        cvs diff -$FLAG1 $OARG1 -$FLAG2 $OARG2 "$homedir/$subdir/$fname" | less
    fi
)

```

---



---

## 20.sadd

**NOTE :** Korn shell /bin/ksh is got by installing *pdksh\*.rpm* from *Linux contrib cdrom*

Save this file as text file and chmod a+rx on it.

---

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
#!/bin/ksh

# CVS program sadd
# Program to add the file to CVS

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#          spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`
if [ $# -lt 1 ]; then
    print "\nUsage: $cmdname <filename/directory> \n"
    exit
fi

onearg="$1"
if [ ! -f "$onearg" -a ! -d "$onearg" ]; then
    print "\nArgument $onearg is not a file or a directory!"
    print "Usage: $cmdname <filename/directory> \n"
    exit
fi

# Argument is a directory name .....
homedir=`echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: \ $HOME is not set!!\n"
    exit
fi

cvs_root=`echo $CVSROOT | cut -f1 -d' ' `
if [ "$cvs_root" = "" ]; then
    print "\nError: \ $CVSROOT is not set!!\n"
    exit
fi

cur_dir=`pwd`
len=${#homedir}
len=$((len + 2))
subdir=`echo $cur_dir | cut -b $len-2000 `
#echo "subdir is : " $subdir
tmpaa=`dirname "$onearg" `
if [ "$tmpaa" = "." ]; then
    fname="$onearg"
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    fi
else
    fname=`basename "$onearg" `
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    else
        subdir="$subdir/$tmpaa"
    fi
fi
```

## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
#echo "subdir is : " $subdir
#echo "fname is : " $fname

# CVS directory in your local directory is required for all commands..
if [ ! -d "$homedir/$subdir/CVS" ]; then
    tmpaa=`(cd "$CVSROOT/$subdir"; find * -prune -type f -print | head -1 ) `
    tmpbb=`basename $tmpaa | cut -d',' -f1 `
    if [ "$tmpaa" = "" -o ! -f "$CVSROOT/$subdir/$tmpbb,v" ]; then
        print "\n\nThe directory $homedir/$subdir/CVS does not exist"
        print "You must do a sget on `basename $subdir` directory. Give -"
        print "      cd $homedir/`dirname $subdir` "
        print "      sget `basename $subdir` "
        exit
    else
        # Now try to create CVS in local dir by sget
        (
            cd "$homedir"
            if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
                cvs -r checkout -A $tmpbb
            else
                cvs -r checkout -A "$subdir/$tmpbb"
            fi
        )
    fi
fi

# Check if file exists ....
if [ $# -eq 1 ]; then
    if [ -f "$onearg" ]; then
        cvs add "$onearg"
        exit
    fi
elif [ $# -gt 1 ]; then
    print "\n\nAdding all the files in the current directory to CVS"
    print "Directories will not be added"
    print -n "Hit return to continue or CTRL+C to abort..."
    read ans
    for ii in $@
    do
        if [ -f "$ii" ]; then
            cvs add "$ii"
        fi
    done;
    exit
fi

# When $subdir is "." then you are at the root directory
if [ "$subdir" = "." ]; then
    # The $onearg is a directory and not a file at this point...
    if [ -d "$CVSROOT/$onearg" ]; then
        print "\n\nDirectory $onearg already exists in CVSROOT"
        exit
    else
        # You are adding at root directory $CVSROOT
        if [ "$2" = "" -o "$3" = "" ]; then
            print "\nUsage: $cmdname <directory> <vendor tag> <release tag>"
            print "For example - "
            print " $cmdname foo_directory V_1_0 R_1_0"
            exit
        else
            (
                cd "$homedir/$subdir";
```

```

        cvs import "$onearg" $2 $3
    )
    fi
fi
else
# If current directory exists in CVS...
if [ -d "$CVSROOT/$subdir/$onearg" ]; then
    print "\nDirectory $onearg already in CVS repository!"
    exit
else
    (
        if [ -d "$homedir/$subdir/$onearg/CVS" ]; then
            print "\nError: Directory $homedir/$subdir/$onearg/CVS exists!!"
            print "\nAborting now ...."
            exit
        fi

        # For import you MUST change to target directory
        # and you MUST specify full-path starting with $subdir
        cd "$homedir/$subdir/$onearg";
        cvs import "$subdir/$onearg" Ver_1 Rel_1
    )
fi
fi

```

---



---

## 21.[sdelete](#)

**NOTE :** *Korn shell /bin/ksh is got by installing `pksh*.rpm` from Linux contrib cdrom*

Save this file as text file and `chmod a+rx` on it.

---

```

#!/bin/ksh

# CVS program sdelete
# Program to delete the file from CVS

# Every filename is composed of 3 parts - Home directory, sub-directory
# and the filename. The full-path is $HOME/$subdir/$fname
# And in CVS the same directory structure is maintained (by
# variable $subdir) therefore in cvs we will have $CVSROOT/$subdir/$fname
# In this program these 4 variables $HOME, $CVSROOT, $subdir and $fname
# play a important role. For example, sample values can be like
# HOME=/home/aldev, subdir=myproject/src CVSROOT=/home/cvsroot
# and fname=foo.cpp

# Caution: Put double-quotes to protect the variables having
#          spaces, like "$HOME/$subdir" if subdir is 'some foo.cpp'

cmdname=`basename $0`

if [ $# -lt 1 ]; then
    print "\nUsage: $cmdname <filename> \n"
    exit
fi

```

```

onearg="$1"

homedir=` echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: $HOME is not set!!\n"
    exit
fi

cur_dir=`pwd`
len=${#homedir}
len=$((len + 2))
subdir=` echo $cur_dir | cut -b $len-2000 `
#echo "subdir is : " $subdir
tmpaa=`dirname "$onearg" `
if [ "$tmpaa" = "." ]; then
    fname="$onearg"
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    fi
else
    fname=`basename "$onearg" `
    if [ "$subdir" = "" ]; then
        subdir=$tmpaa
    else
        subdir="$subdir/$tmpaa"
    fi
fi
#echo "subdir is : " $subdir
#echo "fname is : " $fname

# CVS directory in your local directory is required for all commands..
if [ ! -d "$homedir/$subdir/CVS" ]; then
    tmpaa=` (cd "$CVSROOT/$subdir"; find * -prune -type f -print | head -1 ) `
    tmpbb=`basename $tmpaa | cut -d',' -f1 `
    if [ "$tmpaa" = "" -o ! -f "$CVSROOT/$subdir/$tmpbb,v" ]; then
        print "\nThe directory $homedir/$subdir/CVS does not exist"
        print "You must do a sget on `basename $subdir` directory. Give -"
        print "      cd $homedir/`dirname $subdir` "
        print "      sget `basename $subdir` "
        exit
    else
        # Now try to create CVS in local dir by sget
        (
            cd "$homedir"
            if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
                cvs -r checkout -A $tmpbb
            else
                cvs -r checkout -A "$subdir/$tmpbb"
            fi
        )
    fi
fi

# Operate inside a sub-shell ...
(
    cd $homedir

    # Check if file does not exist....
    if [ ! -f "$subdir/$fname" ]; then
        # Try to get the file from CVS
        sget "$subdir/$fname"
        if [ ! -f "$subdir/$fname" ]; then

```

```

        print "\nError: $subdir/$fname does NOT exist in CVS repository."
        print "\nAborting $cmdname ....."
        exit
    fi
fi

bkextn=cvs_sdelete_safety_backup
\mv -f "$subdir/$fname" "$subdir/$fname.$bkextn"

cvs remove "$subdir/$fname"

print "\nsdelete command removes the file from CVS repository"
print "and archives the file in CVS Attic directory. In case"
print "you need this file in future than contact your CVS administrator"
print " "

print "\nDone $cmdname. $cmdname successful"
print "Run scommit on $homedir/$subdir/$fname to"
print "make this change permanent"
\mv -f "$subdir/$fname.$bkextn" "$subdir/$fname"
)

```

---

## 22.sfreeze

**NOTE :** *Korn shell /bin/ksh is got by installing pdksh\*.rpm from Linux contrib cdrom*

Save this file as text file and chmod a+rx on it.

---

```

#!/bin/ksh

# CVS program sfreeze
# Program to freeze and cut out the release of source tree from CVS

cmdname=`basename $0`

Usage()
{
    clear
    print "\nUsage: $cmdname symbolic_tag <directory name> "

    print "\nFor example :- "
    print "    cd \${HOME}"
    print "    $cmdname REVISION_1 myprojectsource_directory"
    print "To see the list of revisons do -"
    print "slog <filename> and see the symbolic name and do -"
    print "cvs history -T"

    print "\nTo create a branch off-shoot from main trunk, use"
    print "the -b and -r options which makes the tag a branch tag. This is"
    print "useful for creating a patch to previously released software"
    print "For example :- "
    print "    cd \${HOME}"
    print "    cvs rtag -b -r REVISION_1 REVISION_1_1 myprojectsource_directory"
    print " "
}

```



## CVS-RCS- HOW-TO document for Linux (Source Code Control System)

```
# print "\nTag info is located at \${CVSROOT}/CVSROOT/taginfo,v"
# print "You can do - cd $HOME; sget CVSROOT"
# print "to see this file"
    exit
}

# Command getopt will not supported in next major release.
# Use getopt instead.
#while getopt r: ii
#do
#    case $ii in
#        r) FLAG1=$ii; OARG1="$OPTARG";;
#        ?) Usage; exit 2;;
#    esac
#done
#shift `expr $OPTIND - 1 `

#echo FLAG1 = $FLAG1 , OARG1 = $OARG1

if [ $# -lt 2 ]; then
    Usage
fi

if [ ! -d $2 ]; then
    print "\nError: Second argument $2 is not a directory!"
    print "        Aborting $cmdname...."
    print " "
    exit
fi

homedir=`echo $HOME | cut -f1 -d' ' `
if [ "$homedir" = "" ]; then
    print "\nError: $HOME is not set!!\n"
    exit
fi

cur_dir=`pwd`
len=${#homedir}
len=$((len + 2))
subdir=`echo $cur_dir | cut -b $len-2000 `
#echo "subdir is : " $subdir

# CVS directory in your local directory is required for all commands..
if [ ! -d "$homedir/$subdir/CVS" ]; then
    tmpaa=`(cd "$CVSROOT/$subdir"; find * -prune -type f -print | head -1) `
    tmpbb=`basename $tmpaa | cut -d',' -f1 `
    if [ "$tmpaa" = "" -o ! -f "$CVSROOT/$subdir/$tmpbb,v" ]; then
        print "\nThe directory $homedir/$subdir/CVS does not exist"
        print "You must do a sget on `basename $subdir` directory. Give -"
        print "        cd $homedir/`dirname $subdir` "
        print "        sget `basename $subdir` "
        exit
    else
        # Now try to create CVS in local dir by sget
        (
            cd "$homedir"
            if [ "$subdir" = "." ]; then # don't use dot, will mess up cvs
                cvs -r checkout -A $tmpbb
            else
                cvs -r checkout -A "$subdir/$tmpbb"
            fi
        )
    fi
fi
```

```
        fi
fi

if [ "$cur_dir" != "$homedir" ]; then
    print "\nYou are not in home directory $homedir!!"
    print "You must give the sfreeze command "
    print "from home directory $homedir"
    exit
fi

# cvs rtag symbolic_tag <directory name>
cvs rtag $1 $2

print "\nDone $cmdname. $cmdname successful"


---




---


```