

Most_engl

COLLABORATORS

	<i>TITLE :</i> Most_engl		
<i>ACTION</i>	<i>NAME</i>	<i>DATE</i>	<i>SIGNATURE</i>
WRITTEN BY		January 25, 2023	

REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME

Contents

1	Most_engl	1
1.1	Most_engl.guide	1
1.2	Most_engl.guide/Copyright	2
1.3	Most_engl.guide/Background	2
1.4	Most_engl.guide/Configuration	3
1.5	Most_engl.guide/FILES	5
1.6	Most_engl.guide/PORTNAME	5
1.7	Most_engl.guide/PUBSCREEN	6
1.8	Most_engl.guide/STARTUP	6
1.9	Most_engl.guide/WINDOWX	6
1.10	Most_engl.guide/WINDOWY	7
1.11	Most_engl.guide/WINDOWW	7
1.12	Most_engl.guide/WINDOWH	7
1.13	Most_engl.guide/SCREENMODE	7
1.14	Most_engl.guide/FONT	8
1.15	Most_engl.guide/FONTHEIGHT	8
1.16	Most_engl.guide/APPICON	9
1.17	Most_engl.guide/ICONX	9
1.18	Most_engl.guide/ICONY	9
1.19	Most_engl.guide/BUFLLEN	9
1.20	Most_engl.guide/PIPELEN	10
1.21	Most_engl.guide/QUOTES	10
1.22	Most_engl.guide/DIRS	10
1.23	Most_engl.guide/ENDS	11
1.24	Most_engl.guide/STACKSIZE	11
1.25	Most_engl.guide/Keyboard commands	11
1.26	Most_engl.guide/Scrolling	12
1.27	Most_engl.guide/Searching	13
1.28	Most_engl.guide/Open file	13
1.29	Most_engl.guide/Info requester	13

1.30	Most_engl.guide/Help	14
1.31	Most_engl.guide/Edit file	14
1.32	Most_engl.guide/Quit file	14
1.33	Most_engl.guide/Menus	14
1.34	Most_engl.guide/Project	15
1.35	Most_engl.guide/Move	16
1.36	Most_engl.guide/Menu Search	16
1.37	Most_engl.guide/Extras	16
1.38	Most_engl.guide/Settings	17
1.39	Most_engl.guide/The main window	17
1.40	Most_engl.guide/The search requester	18
1.41	Most_engl.guide/The AppIcon	18
1.42	Most_engl.guide/XPK support	19
1.43	Most_engl.guide/Pipe support	20
1.44	Most_engl.guide/ARexx Port	20
1.45	Most_engl.guide/GetFileList	22
1.46	Most_engl.guide/GetScreenName	23
1.47	Most_engl.guide/Quit	23
1.48	Most_engl.guide/Request	23
1.49	Most_engl.guide/Set	24
1.50	Most_engl.guide/OpenNew	24
1.51	Most_engl.guide/Open	25
1.52	Most_engl.guide/Close	25
1.53	Most_engl.guide/ToFront	25
1.54	Most_engl.guide/GetWindowDims	26
1.55	Most_engl.guide/Edit	26
1.56	Most_engl.guide/Info	26
1.57	Most_engl.guide/FirstPage	27
1.58	Most_engl.guide/LastPage	27
1.59	Most_engl.guide/NextPage	27
1.60	Most_engl.guide/PrevPage	27
1.61	Most_engl.guide/NextLine	28
1.62	Most_engl.guide/PrevLine	28
1.63	Most_engl.guide/NextColumn	28
1.64	Most_engl.guide/PrevColumn	28
1.65	Most_engl.guide/NextTab	29
1.66	Most_engl.guide/PrevTab	29
1.67	Most_engl.guide/Goto	29
1.68	Most_engl.guide/Search	30

1.69	Most_engl.guide/Known bugs	30
1.70	Most_engl.guide/Ideas - Bug reports	30
1.71	Most_engl.guide/Current version	31
1.72	Most_engl.guide/Greetings	31
1.73	Most_engl.guide/Index	32

Chapter 1

Most_engl

1.1 Most_engl.guide

```
Most V1.56
*****

Copyright
    Guess what...

Background
    General background information to Most

Configuration
    How to start Most

Keyboard commands
    Shortcuts, cursor movements and so on

Menus
    Which menus are available

The main window
    The main window and its functions

The search requester
    The second important window

The AppIcon
    How to use it.

XPK support
    How Most supports XPK

Pipe support
    Most can read out of a pipe
```

ARexx Port
The wonderful world of ARexx

Known bugs
Hopefully mostly empty...

Ideas - Bug reports
It's your turn

Current version
Where to get the latest Most

Greetings
Who helped me

Index

1.2 Most_engl.guide/Copyright

Copyright

Most 1.56 is published under the concept of GiftWare! So if you find Most a useful tool (and of course use it) please make me a present of any kind - and make me very happy.

Beside this I keep my Copyright:

Copyright (C) 1992/93/94 by Uwe Röhm

You must get my agreement if you wish to publish Most in a commercial product. Especially it is not allowed to use Most for military purposes of any kind which includes using Most in companies which plan or only support military products.

You are allowed to include Most in PD packages which cost less than \$10.- ! But I ask you to keep the archive together. You have to include the documentation with each version. Thank you!

1.3 Most_engl.guide/Background

Background

There are some goals I try to achieve with Most:

- full workbench support
- easy to use with mouse and keyboard

- flexibility
- memory friendly :-)

So Most uses a window for each text - there is no possibility to use it like Commodore's More in a shell. Of course you can choose another screen to open on or even an own CustomScreen. How much windows are opened by Most and where they are is absolut without interest and only limited by the amount of free (chip-) memory!

As each text is displayed in his own window there is also its own process behind. Cause of the windows are absolut independent of each other. Especially you can send ARexx commands to different windows simultaneous and you are free to open new Most windows even if previously opened windows are "busy" - there is Most's main process which handles all texts and some global ARexx commands (see ARexx Port).

To be memory friendly and to display very huge texts even on a 500KB system Most does buffering. Small texts, which fit completly into the buffer, are read only once and closed than so that you can e.g. edit and save it again. But if the text is larger than the configurated buffer length (yes, of course you can change the buffer size, but read on :-)) Most will do some sort of "paging". So memory usage will be limited by the buffer size you specified (little memory -> small buffer). On the other hand this slows scrolling and searching down!!! Sorry for this, but if you have enough memory just increase to buffer size to - let's say - 2 MB. Don't be afraid. Of course Most only uses the amount of memory it needs if a text is smaller than the buffer ;-)

There is one exception of the paging method: XPK packed files. In the current version Most does no paging to XPK files but reads the complete file into memory (see XPK support). Perhaps this will change in future, perhaps it will stay...

Oh, I nearly forgot that Most can display all ANSI sequences. Without this it wouldn't be a real text viewer. As I don't want to do old work again and again I decided to use the console.device. This enables you to mark lines and copy them with Amiga C into the clipboard! I regret that there are also some problems:

- You can only mark text inside the visible text portion.
- Scrolling is quiet annoying on an Amiga without 680x0 (x > 1).
- Don't load binary files. I warned you!!!

1.4 Most_engl.guide/Configuration

Configuration

Most does the following configuration steps on startup:

1. internal defaults
2. Environments Most/Most and Most/FileReq (When used from shell local environments will be read first!)
3. Shell-start: parse command line
 WB-start : parse ToolTypes
4. NEW since Most 1.53: For each text loaded Most will read the project icon (if exists) and use the new tooltypes. You can also include all ARexx commands in the tooltypes which will be executed just after loading the new text! So you can write local ARexx scripts directly into the icons of texts. For a list of the possible commands see
 ARexx Port
 .

And now, ladys and gentlemen, here are the options to be used in 2.), 3.) and 4.):

FILES
 list of filenames to be displayed

PORTNAME
 name of global ARexx port.

PUBSCREEN
 name of a PubScreen to open Most's window on

STARTUP
 ARexx script to be executed

WINDOWX
 x-coordinate of window

WINDOWY
 y-coordinate of window

WINDOWW
 width of window

WINDOWH
 height of window

SCREENMODE
 screenmode to open an own screen with

FONT
 fontname to use

FONTHEIGHT
 height of a given font

APPICON
 to show the AppIcon

ICONX
 x-coordinate of AppIcon

ICONY
 y-coordinate of AppIcon

BUFLEN
 length of read buffer

PIPELEN
 length of pipe buffer

QUOTES
 possible characters for include file recognition

DIRS
 search paths for includes

ENDS
 endings of include files

STACKSIZE
 adjust editor's stack size

1.5 Most_engl.guide/FILES

FILES
=====

Usage

A list of filenames to be displayed (only on shell command line!).
You can use any AmigaDOS wildcards. Since version 1.55 Most also
finds files with names, which include wildcards itself (like
"(test)").

1.6 Most_engl.guide/PORTNAME

PORTNAME
=====

Usage

Custom name of global

ARexx Port
of Most. Overrides the default
name.

Default
MOSTPORT

1.7 Most_engl.guide/PUBSCREEN

PUBSCREEN
=====

Usage
Name of PubScreen where Most will open its windows on.

1.8 Most_engl.guide/STARTUP

STARTUP
=====

Usage
Name of an ARexx script which will be executed every time Most
opens a window. (see
ARexx Port
).

Remember that you can use directly all ARexx commands as tooltypes
in project icons of text files (as a sort of "tooltype script").

1.9 Most_engl.guide/WINDOWX

WINDOWX
=====

Shortcut
WX

Usage
X-coordinate of
The main window

1.10 Most_engl.guide/WINDOWY

WINDOWY

=====

Shortcut

WY

Usage

Y-coordinate of
The main window
. -1 for centered windows

1.11 Most_engl.guide/WINDOWW

WINDOWW

=====

Shortcut

WW

Usage

Width of windows. If you specify negative values or 0, the width of the screen will be used instead.

Default

600

1.12 Most_engl.guide/WINDOWH

WINDOWH

=====

Shortcut

WH

Usage

Height of windows. If you specify negative values or 0, the height of the screen (without its title bar) will be used instead.

Default

400

1.13 Most_engl.guide/SCREENMODE

SCREENMODE

=====

Shortcut

SM

Usage

A valid screenmode Most will use to open its on screen with (which will be a PubScreen named Most). You can get a list of the available screenmodes of your system if you start Prefs/ScreenMode.

Attention! The names of the screenmodes are different for most versions of the monitor files. Remember that you must specify a valid name, which means, that you must spell it exactly as in the monitor files. If in doubt start Prefs/ScreenMode and read the listview.

Example

```
SCREENMODE "Pal:HighRes"
```

1.14 Most_engl.guide/FONT

FONT

=====

Usage

name of a font to be used. The name must include the .font postfix. The height of the font can be adjusted with the

FONTHEIGHT

option. Be careful with proportional fonts.

Example

```
FONT "helvetica.font"
```

1.15 Most_engl.guide/FONTHEIGHT

FONTHEIGHT

=====

Usage

Tells Most which font height it should use. Works only together with the

FONT

option. If not specified Most uses the system default font's height.

1.16 Most_engl.guide/APPICON

APPICON

=====

Usage

A switch, which lets Most use an AppIcon on workbench. If you start Most with the APPICON option and without further file names, Most will only put its AppIcon onto workbench and stay in background. (see
The AppIcon
)

1.17 Most_engl.guide/ICONX

ICONX

=====

Usage

X-coordinate of Most's
APPICON
on workbench

1.18 Most_engl.guide/ICONY

ICONY

=====

Usage

Y-coordinate of Most's
APPICON
on workbench

1.19 Most_engl.guide/BUFLEN

BUFLEN

=====

Usage

Very interesting option to justify Most's buffer size. In general: On small systems use small values, on larger systems try higher buffer sizes. BUFLEN defaults to 50 KB (which is quiet small :-). Texts smaller than the buffer size will be read

complete into memory and use only the necessary amount of memory.

Default

50 000 Bytes

1.20 Most_engl.guide/PIPELEN

PIPELEN

=====

Usage

Most can also read out of a pipe. Normally it would allocate a buffer of

BUFLLEN

/10 Bytes for reading. With this option you can justify the buffer length for pipes by hand.

Example

PIPELEN 8192

1.21 Most_engl.guide/QUOTES

QUOTES

=====

Usage

You can specify a sequence of quote characters. These characters will be used for the "click-and-load" option: If you doubleclick on a word which stands between a quote character Most will try to load a text named like this word. This is very useful for programmers as you can view include files very easy!

Default

"' <> () {} []

1.22 Most_engl.guide/DIRS

DIRS

=====

Usage

Specify one or more directories Most will search through if you use the "click-and-load" function (see

QUOTES

). All directories must be separated by |.

Example

```
DIRS "Include:|TexInputs:|LC:Include/"
```

1.23 Most_engl.guide/ENDS

```
ENDS
```

====

Usage

Postfixes to be appended on include files with the "click-and-load" function in the given order (see

```
DIRS
, see
QUOTES
).
```

Example

```
ENDS ".c.h.tex"
```

1.24 Most_engl.guide/STACKSIZE

```
STACKSIZE
```

=====

Usage

Adjust the size of the editor's stack. Useful for example for the emacs ("Eight Megabytes And Constantly Swapping"?)...

Example

```
STACKSIZE 50000
```

Default

```
8192 bytes
```

1.25 Most_engl.guide/Keyboard commands

```
Keyboard commands
```

```
*****
```

In the current version Most supports all (and more!) keyboard shortcuts well known from More. Future versions will allow custom keyboard commands...

Scrolling
Searching
Open file
Edit file
Info requester
Help
Quit file

1.26 Most_engl.guide/Scrolling

Scrolling

=====

one line forwards

CURSOR DOWN NUMERICPAD 2 RETURN ENTER

one line backwards

CURSOR UP NUMERICPAD 8 DELETE

one page forwards

SHIFT CURSOR DOWN SPACE PAGE DOWN

one page backwards

SHIFT CURSOR UP BACKSPACE PAGE UP b

Jump to beginning of text

HOME <

Jump to end of text

END >

oen column to the right

CURSOR RIGHT NUMERICPAD 6

one column to the left

CURSOR LEFT NUMERICPAD 4

8 columns to the right

SHIFT CURSOR RIGHT

8 columns to the left

SHIFT CURSOR LEFT

jump to first column

NUMERICPAD 5

1.27 Most_engl.guide/Searching

Searching

=====

search actual searchstring again
n

ignore upper/lower case

.

searching with distinction of upper/lower case
/

Open the search requester
f s

1.28 Most_engl.guide/Open file

Open file

=====

Load new text with l (a filerequester shows up).

1.29 Most_engl.guide/Info requester

Info requester

=====

Beside the usual

Copyright

you find here some information about the
current text: Its filename, the filelength, the number of lines and the
visual number of lines, and also the name of the XPK packer (or just
"---" if the file isn't packed). At last there's a message indicating
that the current text has been read completely into memory or - if not -
the length of the used read buffer.

The Info requester can be opened with h.

1.30 Most_engl.guide/Help

Help

====

If you press HELP, the AmigaGuide will be started with the documentation of Most. Of course this requires the AmigaGuide be installed correctly. If Most can't open the amigaguide.library it will open the

Info requester

.

AmigaGuide searches its documents in the current directory and also in the paths listed in the environment variable AmigaGuide/Path.

1.31 Most_engl.guide/Edit file

Edit file

=====

If you press e, the current text will be loaded into an editor. The editor will be started in the background. The name of the editor must be configurated in the environment variable EDITOR. You can adjust the editor's stack size with the

STACKSIZE

option.

1.32 Most_engl.guide/Quit file

Quit file

=====

Close the text window with ESCAPE, CTRL-C or q.

1.33 Most_engl.guide/Menus

Menus

There are the following menus available:

Project

Commands to open, edit, print, close and info about the text ↔

Move
different movements in the text

Menu Search
searching in the text

Extras
misc

Settings
save settings

1.34 Most_engl.guide/Project

Project

=====

New...

Opens a new window and brings up a filerequester where you can choose a text file to be displayed in the new window. If you cancel the filerequester the window will be closed. The position and dimensions of the filerequester can be stored in Settings

.

Open...

Asks you for a new file to be loaded into the current window.

Edit...

Starts the editor with the current text via RUN. The name of the editor can be configurated in ENV:Editor (see

Edit
) , its stack

size can be adjusted with the STACKSIZE option.

Print

Simply prints the current text to PRT:.

Info...

Pops up the Info requester where you find some useful information to the current text like name, length, line count, visible lines, XPK packername and a short comment if the text has been loaded completely into memory or if it uses an buffer.

Quit

Quits the current window (and if it was the last one Most at all)

1.35 Most_engl.guide/Move

Move

====

Move through the current text as the menus describe.

With the menu "Jump to line..." you can specify a certain line number in a requester where you will jump to.

1.36 Most_engl.guide/Menu Search

Menu Search

=====

searching...

The search requester

will be opened with its stringgadget activated.

If the search requester is open this menu is disabled.

forwards/backwards

Search string forwards/backwards (only with open search requester)

1.37 Most_engl.guide/Extras

Extras

=====

Refresh page

Reset console and redraw page

Set tabulator width...

Enter new numeric value for the tabulator width (per default every 8th character there's a tab).

Execute ARexx Macro...

Asks for an ARexx Macro to be executed (see ARexx Port).

1.38 Most_engl.guide/Settings

Settings

=====

save

global Prefs

Save actual settings in two environments in ENV: and ENVARC:.
A subdirectory Most will be created automatically. All known
options from workbench or shell start are saved and also the
dimensions and position and the pattern string of the file
requester.

local Prefs

Does the same as above, but uses local shell variables. This
only works if you started Most from a Shell!

1.39 Most_engl.guide/The main window

The main window

Title

In the title the filename and on the right hand side the current
column and line numbers are displayed. Format:

<filename> <column>/<line>

Gadgets

Beside the system gadgets there are three further ones which
control text scrolling:

You can use the scroller continuously by click-and-dragging or for
scrolling one page forwards/backwards if you click under/above the
knob. The knob's position represents the current text position, its
height the relation between the visible and the total text length.
Use the arrows to scroll one line in the correspondending
direction.

Mouse

"Click-And-Load" function.

If you doubleclick into the window Most will look at this position
to find a word which is limited by one of the configurated quote
characters (see

QUOTES

). This word (can include spaces!!) will be

treated as a filename for which Most searches first in the current
directory and than in each further configurated (see

DIRS

)

directory. Most will also try the plain filename and than (if not
found) append each prefix given with the

ENDS

option. The first found file will be displayed in a new window. If no name matches, the screen will flash (DisplayBeep).

Example:

Doubleclick on ``#include <exec/exec.h>'' between ``<'' and ``>''. the file Include:Exec/Exec.h will be loaded, if you specified ``DIRS Include:'' on startup.

Clipboard

You can easy mark any text in the visible text by click-and-dragging (drag without releasing the mouse button). Copy the marked block with Amiga-C into the clipboard. The current version doesn't support paste from the clipboard.

AppWindow

Take any "real" icon (no AppIcon) on workbench and drop it in Most's window. It will be loaded into the current window. If you drop more than one icons Most will open further windows.

1.40 Most_engl.guide/The search requester

The search requester

Here you can enter a search string and also manipulate the three search option. Therefor you can use the mouse and/or the keyboard shortcuts indicated by the underlined characters. Additionally you have the same functionality as in the main window! So no annoying re-activation of

The main window

.

- All menus are available as in the text window. Only the Menu Search will be disabled and instead "search forwards" and "search backwards" are unghosted.
- Beside the mentioned Requester shortcuts you can use all normal Keyboard commands like scrolling with the cursor keys!!! (Be sure the string gadget isn't activated)

1.41 Most_engl.guide/The AppIcon

The AppIcon

The AppIcon has two functions

Doubleclick

A filerequester will come up where you can choose a file to be loaded and displayed. If you select "Cancel" Most will show a security requester where you can quit Most.

Icons

Drag-and-drop one or more icons on the AppIcon and they will be loaded.

Comments:

Most uses his own program icon as its
APPICON
. Perhaps I will
support custom icons in the future but not yet ;-)
The coordinates of the AppIcon can be saved in the menu
Settings
. Use the options

ICONX
and
ICONY
for exact placement of the AppIcon.

1.42 Most_engl.guide/XPk support

XPk support *****

Main goal of Most's XPk support is to hide any consequences of packed data from the user. This means, that any packed file (with XPk) will automatically be unpacked from Most if the XPk packages is correct installed. The only hint you get is in the information requester, where the line "XPk-packer:" will show you the used packer (usually you see "---" there). There is only one thing special with XPk packed data: The file will be loaded completely into memory and no buffering will be done!

If Most finds an encrypted files (with XPk of course), it opens a password requester and prompts you for the password. Be careful, because this is your only chance! If you give the wrong answer, you will see the encrypted file and have to reload it.

On the other hand if you don't have XPk you can use Most without any difference. The xpkmaster.library is not required by Most to run at all. Of course in this case XPk packed data will not be unpacked :-)

1.43 Most_engl.guide/Pipe support

Pipe support

As a special feature Most 1.42 supports pipes. This means, that you can type something like "type foo | Most" at your (W)Shell prompt and Most will show the output of the first type command in its window!

As I said this feature is brand new. So I regret that I couldn't test it for all possibilities. Please report me any failure.

There are two small problems:

1. XPK doesn't work with pipes.
2. Second there is the problem with pipes that you cannot know how much data therein will be... So one effect is, that you cannot scroll back to the start of an file if you scrolled over the bounds of a buffer and the other one is that the size of the buffer will be (maximum BUFLen / 10) every time (you can set the pipe's buffer size with the PIPELEN option). If the pipe's data fits completely into the buffer you have no restrictions for scrolling. But if the data is to large - Sorry.

1.44 Most_engl.guide/ARexx Port

ARexx Port

Beside the global ARexx port MOSTPORT (or the name you gave it with the option

PORTNAME

on startup) of Most's main process each text window has his own private ARexx port. To select a window first send the command

GetFileList

to the global port. You will receive a list of the available windows and its portnames.

All following ARexx commands can be send to a private window port, but Most's main port does only understand the first 6 commands

GetFileList

,

GetScreenName

,

Quit

,

```
OpenNew
,
Set
and
Request
.
```

In RC Most will return an errorcode of

- * 0 for no errors

- * 5 if it couldn't open a new text with
Open
or
OpenNew
 - * 10 if the parameters for a command were wrong

- * 20 for an unknown ARexx command

All other commands will return an errorcode of 20 if send to MOSTPORT. Sorry, but the ARexx port isn't complete today. But I'm working on it :-)

The following ARexx commands are supported:

```
GetFileList
    get a list of available text windows and their portnames

GetScreenName
    ask for the name of the screen, where Most is running on

Quit
    quit Most

Request
    open a custom requester

Set
    set some options

OpenNew
    open a text in a new window

Open
    load a new text in the current window

Close
    close the current window

ToFront
    get the current window in front of you and visible

GetWindowDims
    ask for position and dimensions of the current window

Edit
```

```
edit the current text

Info
    open the information requester

FirstPage
    jump to first page

LastPage
    jump to last page

NextPage
    show next page

PrevPage
    show previous page

NextLine
    scroll down up line

PrevLine
    scroll down one line

NextColumn
    scroll to the left

PrevColumn
    scroll to the right

NextTab
    scroll 8 chars to the left

PrevTab
    scroll 8 chars to the right

Goto
    goto a certain line and column

Search
    search
```

1.45 Most_engl.guide/GetFileList

```
GetFileList
=====
```

```
Template
    GetFileList
```

```
Result
    In RESULT you get a list of all available text windows and their
    port names. RESULT looks like this: {<window's name> <port name>
    }^+
```

Example

```
GetFileList
RESULT: "Most.dok MOST.0 Most.doc MOST.1"
```

1.46 Most_engl.guide/GetScreenName

GetScreenName
=====

Template

```
GetScreenName
```

Result

```
RESULT contains screen name.
```

Usage

```
Get the name of the screen, where the current window is on.
```

Example

```
GetScreenName
RESULT - "Workbench"
```

1.47 Most_engl.guide/Quit

Quit
====

Template

```
Quit
```

Usage

```
Quits Most and closes all windows.
The AppIcon
of Most will be
deleted - if there is one at all.
```

Example

```
Quit
```

1.48 Most_engl.guide/Request

Request
=====

Template

Request TITLE/K/A TEXT/K/A GADGETS/K/A

Resultat

RESULT contains number of selected gadget:

0
the most right gadget (should be "Cancel")

1 bis n-1
the other gadgets from left to right

Usage

A simple method of asking the user silly questions via requester. Title and text are simple strings. With GADGETS you specify the texts of the gadgets (and how much gadgets there are), separated with '|'.
Example

```
Request TITLE "Test" TEXT "All OK?" GADGETS "YES|No"
RESULT - 1 if YES has been selected, else 0
```

1.49 Most_engl.guide/Set

Set

===

Template

Set CASE/S WORD/S BACK/S

Usage

Set some internal parameters like

CASE
ignore upper/lower case on/off

WORD
search only for whole words on/off

BACK
search backwards on/off All parameters will be set if specified, and disabled otherwise.

Example

```
Set CASE ON
Enables casesensitiv searching, but disables the other two options.
```

1.50 Most_engl.guide/OpenNew

OpenNew

=====

Template

```
OpenNew FILE/K
```

Usage

Load a new text in a new window. The filename is optional. If you don't specify a name a filerequester opens.

You don't need to select a current window before. This command doesn't return until the new window is closed again!

Example

```
OpenNew FILE Most.dok
```

1.51 Most_engl.guide/Open

Open

```
====
```

Template

```
Open FILE/K
```

Usage

Load a new text in the current window. The filename is optional. If you don't specify a name a filerequester opens. This command doesn't return until the window is closed again!

Example

```
Open FILE Most.dok
```

1.52 Most_engl.guide/Close

Close

```
=====
```

Template

```
Close
```

Usage

Closes the current window.

1.53 Most_engl.guide/ToFront

ToFront

```
=====
```

Template

```
ToFront
```

Usage

Makes the current visible: It will be made the frontmost window and the screen it's on will be activated and go to front.

1.54 Most_engl.guide/GetWindowDims

GetWindowDims

=====

Template

GetWindowDims

Result

In RESULT stands <xpos> <ypos> <breite> <höhe>

Usage

Get the position and dimensions of the current window in RESULT

Example

```
GetWindowDims
RESULT - "40 40 600 180"
```

1.55 Most_engl.guide/Edit

Edit

=====

Template

Edit

Usage

```
Edit
the current text (runs editor).
```

1.56 Most_engl.guide/Info

Info

=====

Template

Info

Usage

Opens the

Info requester
to the current window.

1.57 Most_engl.guide/FirstPage

FirstPage
=====

Template
 FirstPage

Usage
 Show the first page of the current text.

1.58 Most_engl.guide/LastPage

LastPage
=====

Template
 LastPage

Usage
 Show the last page of the current text.

1.59 Most_engl.guide/NextPage

NextPage
=====

Template
 NextPage

Usage
 Show the next page of the current text.

1.60 Most_engl.guide/PrevPage

PrevPage
=====

Template

PrevPage

Usage

Show the previous page of the current text.

1.61 Most_engl.guide/NextLine

NextLine

=====

Template

NextLine

Usage

Scroll up one line.

1.62 Most_engl.guide/PrevLine

PrevLine

=====

Template

PrevLine

Usage

Scroll down one line.

1.63 Most_engl.guide/NextColumn

NextColumn

=====

Template

NextColumn

Usage

Scroll left one column.

1.64 Most_engl.guide/PrevColumn

PrevColumn

=====

Template
 PrevColumn

Usage
 Scroll right one column.

1.65 Most_engl.guide/NextTab

NextTab
=====

Template
 NextTab

Usage
 Scroll left 8 columns.

1.66 Most_engl.guide/PrevTab

PrevTab
=====

Template
 PrevTab

Usage
 Scroll right 8 columns.

1.67 Most_engl.guide/Goto

Goto
=====

Template
 Goto LINE/K/N/A COLUMN/K/N

Usage
 Jump to the specified line. Optional you can specify a new first column.

Example
 Goto LINE 142

1.68 Most_engl.guide/Search

Search

=====

Template

Search TEXT/K

Usage

Without argument:

The search requester
opens or if allready open
the current string will be search again.

With searchstring: Search for the given string.

Example

Search TEXT foobar

1.69 Most_engl.guide/Known bugs

Known bugs

- Several control sequences for cursor movements trash the display.
- Most has problems with the pipe of WShell.
- An Enforcer-hit with Most 1.53 has been reported which may be still there. The input buffer seems to overflow after havy input...
- Bruno Lacombe reported a Mungwall hit with Most 1.53 I couldn't reproduce here...

1.70 Most_engl.guide/Ideas - Bug reports

Ideas - Bug reports

As mentioned before Most isn't complete today. There are some points I will improve in the future but I can't promise it. Please remember that I write Most in my spare time without gaining any money for it!

Nevertheless I'm absolutely interested in any kind of responds - ideas, enhancements requests, criticism or bug reports. Call me, write me, mail me. I will hear you! YOU make Most alive and better for the future.

My address:

Uwe Roehm
Woerthstr. 18
D - 94032 Passau
Germany

E-Mail:

bugs@roemer.deg.sub.org

Fido:

2:2494/22.5

1.71 Most_engl.guide/Current version

Current version

You can download the current version of Most from ftp.uni-passau.de (132.231.1.10) in the directory pub/amiga/local/UweR. You will also find other interesting software in pub/amiga/local ...

I try to upload new releases of Most on AmiNet and on our local BBS "Die Box Passau" (2:2494/22.0) as soon as possible.

1.72 Most_engl.guide/Greetings

Greetings

Till now I worked about two years on Most. And still there're old (and new bugs) to be found. If there weren't the response from you, the user, I couldn't make Most to what it is now. There've been many enhancements I included in new releases and a lot of bugs I removed. I can't mention everyone who wrote me but want to list the most important ones:

Karl "Charly" Skibinski, David Göhler, Uli Zukowski, Stefan Sticht,
Matthias "Tron" Scheler, Jan Holler, Dirk Federlein, Markus Uhlendahl

If you want to send me new translations for Most, please do this via snail mail or at least use uuencode sending an e-mail! I received some translations which I couldn't use or unpack. Sorry! The current translations are done by:

- Paul van der Heu (holländisch)
- Frank Geider (french)
- Francesco Dipietromaria (italian)

- Magnus Holmgren (swedish)
- Antonio Joaquin Gomez Gonzalez (spanish)

A special thanks to Urban for his sugesstions and XPK. And a great thank you to everyone who wrote me bug reports, suggestions and of course sent me gifts!!!!

1.73 Most_engl.guide/Index

Index

XPK	XPK support
AINSI Sequences	Background
AmigaGuide	Help
AppIcon	The AppIcon
AppWindow	The main window
ARexx	ARexx Port
ARexx Port	ARexx Port
Author	Ideas - Bug reports
Background	Background
Bugs	Known bugs
Clipboard	The main window
Commandline	Configuration
Configuration	Configuration
Copyright	

	Copyright
Criticism	Ideas - Bug reports
Current version	Current version
Default values	Configuration
Edit	Edit file
encrypted files	XPK support
Environments	Configuration
Extras	Extras
Gadgets	The main window
Giftware	Copyright
Greetings	Greetings
Help	Help
Ideas	Ideas - Bug reports
Includefiles	The main window
Info requester	Info requester
Keyboard commands	Keyboard commands
Macros	Extras
Memory managment	Background
Menu Search	Menu Search
Menus	

	Menus
Mouse	The main window
Move	Move
packed files	XPK support
Paging	Background
Parameter	Configuration
Pipe support	Pipe support
Processes	Background
Project	Project
Refreshing	Extras
Scripts	ARexx Port
Search	The search requester
search requester	The search requester
Searching	Searching
Settings	Settings
Shell start	Configuration
Startup	Configuration
Suggestions	Ideas - Bug reports
Text managment	Background
Text marking	

	The main window
Thanks	Greetings
Title	The main window
ToolTypes	Configuration
Variables	Configuration
Window	The main window
Workbench start	Configuration
