

Sheet1

Loudspeaker Enclosure Designer... data file template, v1.0A

Driver:

Brand:

Fs:

Vas:

Qts:

Qms:

Qes:

Sd:

Xmax:

Revc:

Znom:

Pmax:

Comments:

Sheet1

MM4510  
Polk

Driver's model #.  
Driver's brand name.  
139.0000 Hz (Free air resonance)  
0.0398 ft<sup>3</sup> (Compliance volume)  
1.1280 Total Q  
5.8110 Mechanical Q  
1.4000 Electrical Q  
0.0059 M<sup>2</sup> (Piston area)  
2.1335 mm (Cone excursion)  
3.4600 ohms (DC resistance)  
4.0000 ohms (Nominal impedance)  
50.0000 watts maximum rated power

Polk 4.5" mid driver. Butyl rubber surround, aluminum VC.

Press <ALT-S> to save this file.

Sheet1

{HOME}{GOTO B3}/fs{up}\aseasy\led\drivers\~{dn}{BEEP}{?}~{BEEP}

	#NAME?
Convert for Vas:	0.0000
	0.0000
Derive Qes from Qts/Qms:	
derived Qes:	
Convert for Sd:	0.0000
Convert for Xmax:	0.0000
◆◆◆◆◆◆◆◆	

