

Sheet1

Loudspeaker Enclosure Designer... data file template, v1.0A

Driver:  
Brand:  
Fs:  
Vas:  
Qts:  
Qms:  
Qes:  
Sd:  
Xmax:  
Revc:  
Znom:  
Pmax:

Comments:

Sheet1

MM5510  
Polk

Driver's model #.  
Driver's brand name.  
62.8150 Hz (Free air resonance)  
0.2042 ft<sup>3</sup> (Compliance volume)  
0.4730 Total Q  
3.0150 Mechanical Q  
0.5610 Electrical Q  
0.0089 M<sup>2</sup> (Piston area)  
5.0000 mm (Cone excursion)  
3.5250 ohms (DC resistance)  
4.0000 ohms (Nominal impedance)  
100.0000 watts maximum rated power

Polk Audio 5.25" autosound driver. Butyl rubber surround.  
Aluminum VC former.

Press <ALT-S> to save this file.

Sheet1

{HOME}{GOTO B3}/fs{up}\aseasy\led\drivers\~{dn}{BEEP}{?}~{BEEP}

	#NAME?
Convert for Vas:	0.0000
	0.0000
Derive Qes from Qts/Qms:	
derived Qes:	
Convert for Sd:	0.0000
Convert for Xmax:	0.0000
◆◆◆◆◆◆◆◆	

