

Sheet1

Loudspeaker Enclosure Designer... data file template, v1.0A

Driver:

Brand:

Fs:

Vas:

Qts:

Qms:

Qes:

Sd:

Xmax:

Revc:

Znom:

Pmax:

Comments:

Sheet1

MM8002  
Polk

Driver's model #.  
Driver's brand name.  
41.7200 Hz (Free air resonance)  
1.8198 ft<sup>3</sup> (Compliance volume)  
0.3890 Total Q  
2.2370 Mechanical Q  
0.4720 Electrical Q  
0.0221 M<sup>2</sup> (Piston area)  
6.2500 mm (Cone excursion)  
3.4800 ohms (DC resistance)  
4.0000 ohms (Nominal impedance)  
100.0000 watts maximum rated power

Polk Audio 8" autosound driver. Aluminum VC former.  
Butyl rubber surround.

Press <ALT-S> to save this file.

Sheet1

{HOME}{GOTO B3}/fs{up}\aseasy\led\drivers\~{dn}{BEEP}{?}~{BEEP}

	#NAME?
Convert for Vas:	0.0000
	0.0000
Derive Qes from Qts/Qms:	
derived Qes:	
Convert for Sd:	0.0000
Convert for Xmax:	0.0000
◆◆◆◆◆◆◆◆◆◆	

