

# 3M Model 6750 Projection Panel

## *Multimedia presentations in true-to-life XGA resolution*

The 3M Model 6750 LCD Projection Panel is the key to stunning presentations. It displays XGA resolution images from your PC, Mac or workstation, along with multimedia video and sound to help your presentations come to life. Combined with today's most powerful presentation software, the Model 6750 gives you complete control of your images from almost anywhere in the room — thanks to its wireless PC mouse, the "VirtualMouse" remote. Six unique Presentation Tools let you zoom in, freeze, blank or reveal your images point by point. See for yourself just how easy it is to bring your computer-based presentations to life.

### Key Features

- 16.7 million colors
- Large 10.4" Active Matrix TFT LCD display
- 1024 x 768 XGA resolution
- Supports up to 1280 x 1024 resolution
- Six built-in presentation tools
- VirtualMouse remote control
- Automated image optimization
- Front or rear projection
- Multilingual on-screen menu system
- Accepts direct video input
- Audio control

### Computer Compatibility

- IBM®, VESA, graphics workstations, and Macintosh® standards with resolutions of 640 x 480 up to 1280 x 1024
- Workstation resolutions between 1024 x 768 and 1280 x 1024 are supported by the choice of image compression or window panning

### Video Compatibility

- NTSC, PAL, SECAM, S-VHS

### Presentation Tools

- Six function keys: F1: Reveal, F2: Blank, F3: Freeze, F4: Timer, F5: Magnification, F6: Pointer

### Accessories Included

- VGA/SVGA/XGA video cable, Mac and Power Mac video and monitor cables, serial mouse cable with Mac and PS2 adapters
- BNC cable for IBM/DEC/HP with 5 x BNC fem - fem adapters
- SUN (13W3) cable set
- Video (RCA) cable, audio (RCA) cable, S-VHS cable
- Remote control
- Power supply and cord
- Multilingual Operator Reference Guide

### Technical Specifications

**LCD Type:** Active-Matrix Thin Film Transistor (TFT)

**Active Display Area:** 211 mm x 158 mm (8.3" x 6.2") x 10.4" diagonal

**Resolution:** 1024 (w) x 768 (h) pixels

**Colors:** 16.7 million maximum

**Contrast Ratio:** 100:1 typical

**Aspect Ratio:** 1.3:1

**Response Time:** 50 ms typical

**Physical Dimensions:** 390 mm x 315 mm x 68 mm (15.35" x 12.4" x 2.67")

**Weight:** 3.5 kg (7.9 lbs)

**Operating Temperature:** Maximum 60°C (140°F) on projector stage

**Storage Temperature:** -10° to 50°C (14° to 135°F)

**Power Supply:** Universal (100-250V, 50/60 Hz) with detachable cord


**Regulatory Approvals:** FCC Part 15, Subpart B

**Warranty:** One-year limited warranty on parts and labor

**Order Number:** XX-0034-1503-9

*Specifications subject to change without notice.*

*We're easy to reach*



800-328-1371



<http://www.mmm.com/office>  
e-mail: [presentations@mmm.com](mailto:presentations@mmm.com)

3M Austin Center  
Building A145-5N-01  
6801 River Place Blvd.  
Austin, TX 78726-9000

3M Canada  
P.O. Box 5757  
London, Ontario, Canada  
N6A 4T1

3M Mexico, S.A. de C.V.  
Apartado Postal 14-139  
Mexico, D.F. 07070  
Mexico

Let us help you make the most of your next presentation. We offer everything from presentation supplies to tips for better meetings. And we're the only transparency manufacturer that offers a recycling program for your used transparencies. For late-breaking news, handy references and free product samples, call us toll-free in the continental United States and Canada, 7:30 a.m. to 5:30 p.m. (CST). Or visit our Internet Web site.



Printed on 50% recycled wastepaper,  
including 10% post-consumer wastepaper

Litho in U.S.A. © 3M 1996  
78-6970-6609-6 (06615.0)LP