



## PRODUCT FACT SHEET

<b>MODEL NAME:</b>	<b>ProVista™ 14</b>
<b>MODEL NUMBER:</b>	PV-448
<b>LIST PRICE (MSRP):</b>	US\$359.00
<b>IDEALLY SUITED FOR:</b>	Entry level business, Basic Windows applications, Home education/entertainment
<b>PICTURE TUBE:</b>	14" (13.3" diagonal viewable area) high-contrast dark tinted CRT, 575mm radius, 90 degree deflection, 0.28mm trio dot pitch, dot type black matrix, medium-short persistence phosphor
<b>RESOLUTION:</b>	Maximum: 1024 x 768@60Hz    Recommended: 800 x 600@75Hz
<b>COMPATIBILITY:</b> (most common)	640x480: 60-90 Hz vertical refresh 800x600: 60-76 Hz vertical refresh 1024x768: 60 Hz vertical refresh VESA 640x480: 60/72/75/85 Hz vertical refresh VESA 800x600: 60/72/75 Hz vertical refresh VESA 1024x768: 60 Hz vertical refresh
<b>DISPLAY SIZE:</b> (Factory Setting)	250 mm x 187 mm (Dependent on signal timing used)
<b>DISPLAY SIZE:</b> (Active Area)	276 mm x 202 mm (Dependent on signal timing used)
<b>INPUT SIGNAL:</b>	Video: ANALOG 0.7 V <sub>p-p</sub> /75 Ohms Positive Sync: Separate sync, TTL Level, 3 V <sub>p-p</sub> typical
<b>INPUT CONNECTOR:</b>	15-Pin D-Sub Type
<b>VIDEO BANDWIDTH:</b>	50 MHz
<b>SCANNING FREQUENCIES:</b>	HORIZONTAL 30 - 50 KHz                      VERTICAL 50 - 100 Hz
<b>DISPLAY COLORS:</b>	Analog Input; Unlimited colors (Dependent on video card used)
<b>POWER SOURCE/CONSUMPTION:</b>	90 - 264 VAC (Universal Power Supply)/85 Watts (maximum)
<b>POWER MANAGEMENT:</b>	EPA/Energy Star; NUTEK/TCO; VESA/DPMS-compliance
<b>FRONT PANEL CONTROLS:</b>	Power ON/OFF, Brightness, Contrast, Reset, H-Phase, H-Size, V-Size, V-Phase
<b>TILT/SWIVEL BASE:</b>	Included
<b>DIMENSIONS/WEIGHT:</b>	14.3" (H) x 14.3" (W) x 15.3" (D) / 29 lbs
<b>REGULATORY COMPLIANCE:</b>	DHHS, UL, CSA, TUV/GS, SEMKO, NEMKO, FIMKO, DEMKO FCC Class B, BZT, CISPR 22, CE
<b>SWEDAC/MPR II:</b>	Not available in US or Canada
<b>PLUG-N-PLAY COMPATIBILITY:</b>	Not available
<b>WARRANTY:</b>	Two-Year Limited Warranty/Parts & Labor

