

**CTX**

## Multimedia Series Monitors

- Integrated Stereo Dome Speakers
- Front-Panel Microphone & Headphone Jacks
- Full-Function On-Screen Display (OSD)
- PC and Mac Compatibility
- Windows @ 95 Plug & Play Operation
- Wide-Range Rotary Volume Control

### Specifications

*(specifications are subject to change without notice)*

<b>Model</b>	<b>MS600</b>
<b>Display Type:</b>	17" Flat Square CRT (15.7" viewable size), Invar Shadow Mask, 90° Deflection, 0.39mm dot pitch
<b>Resolution</b>	
<b>Maximum</b>	1024x768, 70Hz
<b>Recommended</b>	800x600, 90Hz
<b>Frequency</b>	
<b>Horizontal</b>	30-56KHz
<b>Vertical</b>	50-120Hz
<b>User Controls</b>	Complete On-Screen Menu Adjustments
<b>Safety Regulations</b>	FCC Class B/MPR-II/TUV, UL/CSA/TUV/CE, DHHS ISO9241-3
<b>Input Signal</b>	
<b>Video</b>	Analog, 0.7 Vp-p/75 Ohms
<b>Sync</b>	Separate TTL H/V sync, composite sync +/-, sync on green
<b>Cable</b>	15-Pin Mini D-sub Connector
<b>Audio</b>	3W x 2 Speakers, 70Hz-20Khz, front microphone, auxiliary 3.5mm headset/mic. jack, rear L&R RCA jacks
<b>Plug &amp; Play</b>	DDC1/2B
<b>Power Requirements</b>	AC 100-250V, 50/60Hz, 110W(max), <=70W (stand-by), <=10W (suspend)
<b>Power Management</b>	VESA/DPMS
<b>Dimensions (WxHxD)</b>	17.4"x17.3"x17.1"
<b>Weight</b>	43.2 lbs