

ida 224-2T IBM 4226

Technical Specifications

Emulation:

IBM 4214-2
 IBM 4234-2
 IBM 4245-T12
 IBM 5224
 IBM 5225
 IBM 5256

Print Speed:

Fast draft 533 CPS
 Normal draft 400 CPS
 Letter Quality 100 CPS

Print Method:

9-pin matrix

Attachments:

IBM System /34, /36, /38, AS/400
 IBM 5259 Migration Data Link
 IBM 5251 Model 12 controller
 IBM 5294 Controller
 IBM 5394 Controller
 Equivalent PCM controller

Setup and Operation:

Setup of the printer performed by commands from the system

Supported IBM Features:

Auto-terminating twinax attachment
 IBM Virtual Printer Transparency
 LAC1 + LAC2 graphics support
 Support of IBM Page Presentation Media command

Extra Features:

Optional suppression of IBM formats
 Internally generated bar code printing in user-defined enlargements of the following bar code types:

- * EAN 8 and 13
- * Interleaved 2 of 5
- * Industrial 2 of 5
- * Codabar
- * MSI
- * Plessey
- * Code 3 of 9

Connection:

Build-in card connected via printer's Centronics parallel port

All specifications are subject to change without prior notice due to improvement or alteration of design.

i-data a-s is the world-leading printer interface manufacturer for the IBM 3270, 3X and AS/400 environment. Using the latest technology, i-data offers all popular IBM printer emulations with features such as support of AFP, IPDS, and LAC. Since 1981, more than 350,000 units have been installed through a worldwide distributor network.

i-data a-s
 Vadstrupvej 35-43
 DK-2880 Bagsværd, Denmark
 Phone: +45 44 44 00 77
 Telex: 37 504 digi dk
 Telefax: +45 44 44 07 24

TWINAX

High-Performance Matrix Printer for Heavy-Duty Printing

T
H
E

S
T
R
A
I
G
H
T

L
I
N
E

ida 224-2T-IBM 4226

The IBM 4226 matrix printer together with an i-data interface provide low-cost host printing at a speed of 533 characters per second.

With the capability of printing up to 6 part forms and with a 15-million-character ribbon, it is the ideal solution for departments that require a printer for heavy system printing.

The ida 224-2T IBM 4226 features are:

- * IBM 4214-2, 4234-2, 4245-T12, 5224, 5225 and 5256 printer emulations
- * Three print qualities

- * Graphics through BGU and APF support
- * Support of IBM Virtual Printer Transparency
- * Easy printer setup from the host with i-data Function Selection via the Line (FSL)
- * Non-volatile memory for permanent storage of settings

The ida 224-2T IBM 4226 interface provides additional facilities such as bar code printing. Seven different types of internally generated bar codes may be selected.

With 533 characters per second (CPS) in fast draft, 400 CPS in normal draft and 100 CPS in Letter Quality, the IBM 4226 provides listing print at the desired speed and quality.

In short, the combination of IBM's 4226 printer and the i-data interface gives the professional user a flexible and solid printer solution for direct attachment to the IBM twinax system.

