

## MICROPOLIS TOMAHAWK FAMILY

## Ultra SCSI Interface 3.5 - Inch Disk Drive

The Micropolis Tomahawk 9 and Tomahawk 4LP are nextgeneration drives designed to
deliver exceptional performance
and higher capacities in a 3.5-inch
package. The new drives combine
Magneto Resistive (MR) recording
head technology with the new
digital PRML Data Channel and
ID-less sector formats to achieve
greater throughput and 9.10 GB
and 4.55 GB formatted capacities.

The combination of the drives' 7200 rpm spindle speed, 7.9 ms average seek time, up to 125 MHz internal data rate and high-performance Ultra SCSI controller provide significant performance improvements over existing technologies.

By offering ease of integration, enhanced data integrity/reliability, and world-class manufacturing, the Micropolis Tomahawk drives deliver robust performance for all high end data storage needs.

4.55 and 9.1 gigabyte
7200 rpm spindle speed
Ultra SCSI Interface
7.9 ms average seek time
76 to 125MHz internal date rates
Sustained data rates over 10MB/s
Maximum data rates up to 40MB/s

The Micropolis Tomahawk 9
and Tomahawk 4LP provide
enhanced data integrity through
round-trip CRC data protection
throughout the entire data path,
automatic retries, and a state-ofthe-art ECC with on-the-fly
correction. Rugged construction
and advanced proprietary hybridservo technology protect against
shock and environmental variations.

New S.M.A.R.T technology enables the drives to trigger an alert condition to the host when any of the vital statistics fall below an acceptable threshold.

Reliability has also been enhanced to 1,000,000 hours MTBF and Micropolis backs the Tomahawk family with a 5-year warranty.

And with the \$5 billion
financial backing of our new
parent, Singapore Technologies, you
can count on us to constantly
improve our operations - from
design to production - ensuring that
every Micropolis disk drive comes
with the quality built in.





## TOMAHAWK SPECIFICATIONS



Tomahawk 4LP



Tomahawk 9

Formatted Capacity	Model 4345	Model 3391
Per Drive	4.55 GB	9.10 GB
Per Sector	512 B	512 B
Sectors/Track	Variable	Variable
Cylinders	4811	4811
Data Heads	11	22
Performance		
Seek Time		
Track-to-Track	1.0 ms	1.0 ms
Average	7.9 ms	7.9 ms
Maximum	19 ms	19 ms
Rotational Speed	7200 RPM	7200 RPM
Average Latency	4.17 ms	4.17 ms
Internal Data Rates		
Inner/Outer Zone	76/125 MHz	76/125 MHz
Ultra SCSI Interface		
Ultra SCSI narrow single ended	4345NS	3391NS
Ultra SCSI wide single ended*	4345WS	3391WS
Ultra SCSI wide differential*	4345WD	3391WD
Ultra SCSI wide single ended SCA	4345SS	3391SS
Ultra SCSI wide differential SCA	4345SD	3391SD
*Utilize 68-pin Unitized Connector	10 1002	503 122
Transfer Rate at Host Interface		
Wide Synchronous	40 MB/s	40 MB/s
Narrow Synchronous	20 MB/s	20 MB/s
Asynchronous	10 MB/s	10 MB/s
Cache Buffer Size	512 KB	512 KB
	<del></del>	
Power Dissipation Peak Start Current	1.75A peak	2.50A peak
Idle/Seek	10/12 Watts	14/17 Watts
Acoustic Noise (typical)		
Idle	33 dBA (4.5 Bels)	36 dBA (4.8 Bels)
Seek	36 dBA (4.8 Bels)	45 dBA (5.7 Bels)
Environmental		
Operating		
Temperature	5° C to 50° C	5° C to 50° C
Shock	10 g for 11 ms	10 g for 11 ms
Vibration	2 g peak	2 g peak
Non Operating	*	
Temperature	-40° C to 65° C	-40° C to 65° C
Shock	60 g for 11ms	60 g for 11ms
Vibration	5 g peak	5 g peak
Physical Dimensions		
H x W x D (in)	1 x 4 x 5.75	1.62 x 4 x 5.75
HxWxD(mm)	25.4 x 101.6 x 146.1	41,2 x 101,6 x 146.
Weight (lb/kg)	1.4/.64	2.0/.91
Drive Features		
Ultra SCSI Compliant	Magneto-Resistive (MR) Heads	
PRML Read Channel	ID-less Sectors	
S.M.A.R.T Compliant	Multi-Segmented Read Ahead Caching	
Tagged Command Queuing with Write Coalescing	Write Caching option	
Through CRC Data Protection	Downloadable SCSI Code	
ECC with on-the-fly error correction	Automatic Sector Reallocation: (ARRE, AWRE) option	
Active Termination, jumpers enable/disable	On-board or remote LED option	
Industry standard mounting in any orientation	5. Year Warranty	

FOR MORE INFORMATION CALL 1-800-395-DRIVE



Micropolis (USA) Inc 21211 Nordhoff Street Chatsworth, CA 91311 Tel: 818-709-3300 World Wide Web: http://www.micropolis.com

Industry standard mounting in any orientation

U.S. Sales Offices

•Irvine, CA 714-476-0411 •San Jose, CA 408-441-0333 •Lawrenceville, GA 770-963-4841 •North Potomac, MD 301-948-6099 •Salem, NH 603-898-3550

5-Year Warranty

•Dallas, TX 214-985-5535 •Charlottesville, VA 804-975-3394

**European Offices** 

Reading, England 44/118-9751315
Paris, France 33/01-6920-15-18
Munich, Germany 49/89-899-3930
Milan, Italy 39/2-33200635
Stockholm, Sweden 46/8580-32095

Asia/Pacific Offices

•Singapore 65/482-4191 •Tokyo, Japan 81/3-3543-8961





