



Now Mac users can share up to 4.5 gigabyts of invaluable CD-ROM based data with Procom Technology's CD Tower-7Mac. Whether it's digitized photo images, statistical information, software applications, or archived data, the CD Tower-7Mac's seven quad- or six-speed drives allow all net worked users to simultaneously access all the information.

Procom Technology has equipped the CD Tower-7Mac with the intelligent "Smart SCSI CD" board, which maps seven CD-ROM drives to a single SCSI ID. This allows additional CD Towers or other SCSI peripherals to be attached to your Macintosh.

Procom Technology's CD Tower-7Mac opens new horizons for CD-ROM data distribution, further advancing the capacities of this exciting media.

The CD Tower-7Mac is backed with an unmatched service program that includes toll-free technical support and the convenience of optional On-Site repair by certified field service engineers.

Features	Benefits		
 Contains up to 	 UP to 4,500 megabytes of data storage; 		
seven CD-ROM	perfect for sharing reference materials,		
drives per tower	records, contracts, and archives		
1	published in CD-ROM format across		
• Choice of 4X,	the Macintosh network		
8X or 12X			
CD-ROM drives	 Meets performance and budget 		
	requirements		
 Up to seven 	1.		
CD-ROM drives	 Six remaining SCSI IDs available for 		
can be mapped to			
single SCSI ID			
	 Supports all major CD-ROM formats 		
Includes	including Kodak Multi-session		
powerful	Photo-CD, HFS, ISO-9660; also		
CD-ROM driver	supports SCSI Manager 4.3		
software			
2,011.11.22	 Hassle-free installation and maintenance 		
No system			
extensions or			

trap patching

All Procom Technology products incorporate meticulous design and superior engineering to ensure all solutions deliver uncompromising quality. Each Procom Technology product is rigorously tested under the most adverse conditions.

FOR THE ENTERPRISE



CD Tower-7Mac Specifications				
	Quad-Speed (T4X)	Eight-Speed (T8X)	Twelve-Speed (12X)	
PERFO	DRMANCE_			
Average Access Time (ms)	150	< 140	125	
Sustained Data Transfer Rate (KB/sec)	600	1200	1800	
Burst Data Transfer Rate (MB/sec)	4.2	4.2	10	
GENERAL S	PECIFICATION	ONS		
Formatted Capacity (MB per drive)	650			
CD-ROM Interface	SCSI-2			
Drive Form Factor (inches)	5.25			
Embedded Cache Buffer (KB)	256			
MECHANICAL (CHARACTER	RISTICS		
Loading Mechanism	Tray			
Eject Mechanism	Electronic			
	DISCS			
	ISO 9660			
Acceptable Formats	High Sierra			
Acceptable Formats	HFS (Mac Format)			
	Kodak Photo CD			
PHYSICAL CH	T		· · · · · · · · · · · · · · · · · · ·	
H x W x D (inches)	19.3 x 15.5 x 17.82			
H x W x D (cm)	48.1 x 39.4 x 44.9			
Weight (w/o drives) (lbs/kgs)	28/12.7			
Weight (w/drives) (lbs/kgs)	46/21			
RELIABILITY	SPECIFICAT	TIONS		
MTBF (hrs)	100,000			
Warranty (yrs)	1			