



Procom Technology's CD-Tower-Rax is designed to meet enterprise and broadband networks' online CD-ROM requirements for complete flexibility and non-stop operation integration.

Based upon the standard 19" rack, the CD Tower-Rax is completely modular solution. The CD Tower-Rax includes up to nine CD-ROM modules, each featuring seven hot-swappable,

quad-speed, eight-speed or twelve speed CD-ROM drives, redundant hot-swappable power supplies and fans, and drive module takes up only one SCSI ID.

To provide maximum flexibility while meeting growth and budget requirements, CD-ROM modules can be purchased separately and integrated into existing standard 19" racks.

An optional CPU module incorporating a high-performance, Pentium based processor is also available. This module features up to 128 MB of RAM, a floppy drive, a hard drive and a network card to match your network's topology.

Meeting the demand for high-capacity storage and modular design, Procom Technology delivers both in this dynamic solution to CD networking for client/Server applications.

The CD Tower-Rax is backed by an unmatched service program that includes toll-free technical support and the convenience of optional On-Site repair by certified field service engineer.

Modular Design-Fault Tolerance

The CD-ROM and CPU modules are designed for flexible integration into any standard 19" rack mount enclosure. Each CD-ROM module maintains its own fault tolerant with redundant and hot-swappable power supplies and fans, and hot-swappable CD-ROM drives.

Future Expansion

Purchase the CD Tower-Rax in a minimum configuration and then add CD-ROM drives as your company expands. In a matter of minutes, you can add sufficient CD-ROM storage to your network.



Features	Benefits
<ul style="list-style-type: none"> • Standard 19" rack design • Up to 63 on-line CD-ROM drives with a dedicated CPU • Hardware and software configured at the factory specifically for your network • Pre-loaded CD-ROM management software • Modular Design-Fault Tolerance: CD-ROM and CPU modules designed for flexible integration into any standard 19" rack mount enclosure. Each CD-ROM module maintains its own fault tolerancy with redundant and hot-swappable power supplies and fans, and hot-swappable CD-ROM drives 	<ul style="list-style-type: none"> • Purchase CD-ROM or CPU module separately and add to existing rack, or to CD Tower-Rax • Provides instantaneous access to over 40.9 GB of CD-ROM data without taxing the file server • Instantly integrates into existing rack or connects directly to office network, eliminating downtime • Available for Novell NetWare, OS/2 LanServer, NT Advanced Server, Banyan Vines and UNIX

All Procom Technology products incorporate meticulous design and superior engineering to ensure all solutions deliver uncompromising quality. Each Procom Technology product is rigorously tested under the most adverse conditions.

CD Tower-Rax Specifications			
	Quad-Speed T4X	Eight-Speed T8X	Twelve-Speed 12X
PERFORMANCE			
Average Access Time (ms)	150	< 140	125
Sustained Data Transfer Rate (KB/sec)	600	1200	1800
Burst Data Transfer Rate (MB/sec)	4.2	4.2	10
GENERAL SPECIFICATIONS			
Formatted Capacity (MB per drive)	650		
CD-ROM Interface	SCSI-2		
Drive Form Factor (inches)	5.25		
Embedded Cache Buffer (KB)	256		
MECHANICAL CHARACTERISTICS			
Loading Mechanism	Tray		
Eject Mechanism	Electronic		
DISCS			
Acceptable Formats	ISO 9660 High Sierra Yellow Book		
PHYSICAL CHARACTERISTICS			
CPU...H x W x D (inches)	10.5 x 19 x 21.54		
CPU...H x W x D (cm)	26.7 x 48.3 x 54.6		
CD-ROM...H x W x D (inches)	7 x 19 x 21		
CD-ROM...H x W x D (cm)	17.8 x 48.3 x 53.3		
CPU Module Weight (lbs/kgs)	28/12.7		
CD-ROM Module Weight (lbs/kgs)	35/16		
RELIABILITY SPECIFICATIONS			
MTBF (hrs)	100,000		
Warranty (yrs)	1		