



The CD Tower-Plus is perfectly designed to meet the needs of organizations requiring a high-capacity, scalable, CD-ROM information distribution system. Equipped with up to 7 or 14 of the world's fastest quad, eight or twelve speed CD-ROM drives, the CD Tower-Plus can deliver 9GB of information - the equivalent of four million pages of text - to every user on the network.

The locking front door provides security and protects your software investment. Start with as few as eight CD-ROM drives and add up to six more as your needs grow. The locking front door provides security and protects your software investment.

Procom Technology has equipped the CD Tower-Plus with its intelligent "Smart SCSI CD" board, which allows seven CD-ROM drives to occupy only one SCSI ID. SO even fully-equipped, the CD Tower-7Plus will occupy only one SCSI and the CD Tower-14Plus only two IDs on a SCSI bus. This allows additional CD Towers or other vital SCSI devices to be attached to your system without exhausting its resources.

The CD Tower-Plus is backed with an unmatched service program that includes toll-free technical support and the convenience of optional On-Site repair by certified field service engineers.

Features	Benefits
<ul style="list-style-type: none"> <li>● Stores and distributes up to 4.5 or 9GB of data</li> <li>● Choice of 4X, 8X or 12X CD-ROM drives</li> <li>● Occupies maximum of only 2 SCSI IDs on a SCSI-bus</li> <li>● Software drivers for DOS, Windows NT, OS/2, Banyan Vines or Novell NetWare available</li> <li>● Attaches directly to a fileserver or work station via peer-to-peer software</li> </ul>	<ul style="list-style-type: none"> <li>● Perfect storage medium for networking bulky reference materials, records, contracts and other large files and archives</li> <li>● Instant access to the data you need</li> <li>● Operates from a single SCSI host adapter</li> <li>● Compatible with most popular networks; CD-ROM driver is easy to install with Procom Technology's SCSI host adapters</li> <li>● Allows flexible configuration of CD-ROMs in network environment; shared CD-ROM databases can be added to existing file servers; allows network administrator to monitor CD-ROM drive activities, network user logins and user session activity; Avoids taxing the file server by using peer-to-peer software for NetWare, OS/2, Windows NT and Banyan Vines environments; peer-to-peer software loads on a workstation</li> </ul>

All Procom Technology products incorporate meticulous design and superior engineering to ensure all solutions deliver uncompromising quality. Each Procom Technology product is rigorously tested under the most adverse conditions.



<b>CD Tower-Plus Specifications</b>			
	<b>Quad-Speed T4X</b>	<b>Eight-Speed T8X</b>	<b>Twelve-Speed 12X</b>
<b>PERFORMANCE</b>			
Average Access Time (ms)	150	< 140	125
Sustained Data Transfer Rate (KB/sec)	600	1200	1800
Burst Data Transfer Rate (MB/sec)	4.2	4.2	10
<b>GENERAL SPECIFICATIONS</b>			
Formatted Capacity (MB per drive)	650		
CD-ROM Interface	SCSI-2		
Drive Form Factor (inches)	5.25		
Embedded Cache Buffer (KB)	256		
<b>MECHANICAL CHARACTERISTICS</b>			
Loading Mechanism	Tray		
Eject Mechanism	Electronic		
<b>DISCS</b>			
Acceptable Formats	CD-Audio, CD-ROM CD-ROM XA, Photo CD CD-I, VIDEO CD CD+(plus)		
<b>PHYSICAL CHARACTERISTICS</b>			
<b>CDT-7Plus</b>			
H x W x D (inches)	18.75 x 8.75 x 13		
H x W x D (cm)	47.62 x 22.22 x 33.02		
Weight (w/o drives) (lbs/kgs)	28/12.7		
Weight (w/drives) (lbs/kgs)	46/21		
<b>CDT-14Plus</b>			
H x W x D (inches)	20.2 x 15.5 x 17.82		
H x W x D (cm)	51.3 x 39.4 x 44.9		
Weight (w/o drives) (lbs/kgs)	51/23.2		
Weight (w/drives) (lbs/kgs)	78/35.5		
<b>RELIABILITY SPECIFICATIONS</b>			
MTBF (hrs)	100,000		
Warranty (yrs)	1		