



Procom Technology has engineered the revolutionary CD Tower-E1 with simple installation and use in mind. The CD Tower-E1, designed to include Procom Technology's innovative "Smart Ethernet CD/XL" board, connects directly to your office's Novell NetWare or Windows NT Server network Ethernet cabling.

It's the easiest and most efficient way to give each network user access to 9 GB of critical reference materials, records, archives, databases, and other large files.

The CD Tower-E1 requires no network downtime during installation, no confusing SCSI host adapters, and no troubling network cards. And with each CD Tower-E1, you receive DiscView Pro, an easy-to-use Windows/DOS based utility program that manages CD-ROMs for an unlimited number of users. DiscView-Pro features "Virtual Volume," which can mount all CD-ROMs as one drive letter, with subdirectories for each CD-ROM title.

The CD Tower-E1 is backed by an unmatched service program that includes toll-free technical support and the convenience of optional On-Site repair by certified field service engineers.

Features	Benefits
<ul style="list-style-type: none"> <li>● contains up to 7 or 14 CD-ROM drives per CD Tower</li> </ul>	<ul style="list-style-type: none"> <li>● Up to 9 GB of data storage</li> </ul>
<ul style="list-style-type: none"> <li>● Choice of 4X, 8X or 12X CD-ROM drives</li> </ul>	<ul style="list-style-type: none"> <li>● Meets performance and budget requirements</li> </ul>
<ul style="list-style-type: none"> <li>● Simple installation via Ethernet connectivity</li> </ul>	<ul style="list-style-type: none"> <li>● Mounts all CD-ROMs as one drive letter</li> </ul>
<ul style="list-style-type: none"> <li>● Includes DiscView Pro with aggregate mount for NetWare</li> </ul>	<ul style="list-style-type: none"> <li>● No network downtime</li> </ul>
<ul style="list-style-type: none"> <li>● Macintosh HFS CD-ROM support, when used in Netware environment</li> </ul>	<ul style="list-style-type: none"> <li>● Macintosh users can access HFS CD-ROMs via Appleshare</li> </ul>
<ul style="list-style-type: none"> <li>● Now with Windows NT Server support</li> </ul>	

All Procom Technology products incorporate meticulous design and superior engineering to ensure all solutions deliver uncompromising quality. Each Procom Technology product is rigorously tested under the most adverse conditions.



<b>CD Tower-E1 Specifications</b>			
	<b>Quad-Speed T4X</b>	<b>Eight-Speed T8X</b>	<b>Twelve-Speed 12X</b>
<b>PERFORMANCE</b>			
Average Access Time (ms)	150	< 140	125
Sustained Data Transfer Rate (KB/sec)	600	1200	1800
Burst Data Transfer Rate (MB/sec)	4.2	4.2	10
<b>GENERAL SPECIFICATIONS</b>			
Formatted Capacity (MB per drive)	650		
CD-ROM Interface	SCSI-2		
Drive Form Factor (inches)	5.25		
Embedded Cache Buffer (KB)	256		
<b>MECHANICAL CHARACTERISTICS</b>			
Loading Mechanism	Tray		
Eject Mechanism	Electronic		
<b>DISCS</b>			
Acceptable Formats	ISO 9660 High Sierra HFS(Mac Format)		
<b>PHYSICAL CHARACTERISTICS</b>			
<b>CDT-7E1</b>			
H x W x D (inches)	18.75 x 8.75 x 13		
H x W x D (cm)	47.62 x 22.22 x 33.02		
Weight (w/o drives) (lbs/kgs)	28/12.7		
Weight (w/drives) (lbs/kgs)	46/21		
<b>CDT-14E1</b>			
H x W x D (inches)	20.2 x 15.5 x 17.82		
H x W x D (cm)	51.3 x 39.4 x 44.9		
Weight (w/o drives) (lbs/kgs)	51/23.2		
Weight (w/drives) (lbs/kgs)	78/35.5		
<b>RELIABILITY SPECIFICATIONS</b>			
MTBF (hrs)	100,000		
Warranty (yrs)	1		