

SCEPTRE®

TECHNOLOGIES, INC.

16800 E. Gale Ave.
 City of Industry, CA 91745
 Tel: (626) 369-3698 Fax: (626) 369-3488

P73G - Color Series Display

Model P73G - Charcoal Black Cabinet

Compatible Graphic	VGA, SVGA, 8514A, VESA, MAC 640 x 480 /110Hz, 800 x 600 /100Hz, 1024 x 768 /86Hz, 1280 x 1024 /65Hz
CRT	17" NG, .28DP, Flat Screen, INVAR Mask, w/Dynamic Focus E-E Overscan
Display Area (mm)	327H x 245V
DiagonalViewable	15.9"
Maximum Resolution	1280 x 1024
Scanning Frequency	Hor: 30 -70KHz, Ver: 50 -110Hz
Video Bandwidth	110MHz +/-3dB
Input Signal	Video: Analog, 0.7Vp-p, 75ohm Sync: TTL Separate / Composite, +/-
Power Source	AC 90-260V 50/60Hz
Power Management	Complies with EPA, VESA DPMS & TCO
Power Consumption	115W Max
Signal Cable	Captive w/15 pin Mini D-Sub Connector
Dimensions (mm)	395W x 406H x 420D
Weights (lbs)	43 Gross, 37 Net
User Controls	Slection Keys: On/Off,Manual,Adjust(+/-),Function(</>) On Screen: Brightness, Contrast, H-Size, V-Size, H-pos, V-pos, Pincushions/Barrel, Tilt/Rotation, Trapezoid, Manual Degaussing, RGB Color tuning, Recall, Scanning Frequency & Refresh rate
Warranty	3 Year Parts & 1 Year Labor
Regulations	CE/ UL/ CSA/ DHHS/ TUV/ GS/, FCC/B, FTZ/B, SEMKO,NEMKO, DEMKO, FIMKO, VCCI, VDE/B
Feature/Benefits	*Plug & Play (DDC 1/2B) *MPR II Low Radiation, TCO Low Radiation (Optional) *On Screen Display Control (OSD) *MPU Digital Controls:8 factory,12 user adjustable settings *Mac II Compatible