

OfficeLAN™ PCI 10/100 TX Fast Ethernet Adapter

SIEMENS

Quality, Performance and Reliability at an Affordable Price

Siemens OfficeLAN PCI 10/100-TX Fast Ethernet Adapter is a 32-bit 10/100 Mbps adapter designed for high performance, reliable and ultra-fast network connections.

Powerful Support for Demanding Applications

The OfficeLAN adapter is ideal for providing network access for the most demanding applications on PCs and servers in networks of all sizes, ranging from small offices and workgroups to large enterprises.

Migrates Seamlessly from Ethernet to Fast Ethernet

With its auto negotiation, the OfficeLAN adapter supports both Ethernet (10Mbps) and Fast Ethernet (100Mbps) network connections. The OfficeLAN adapter automatically adjusts itself to network speed and duplexity.

Supports Popular Operating Systems

Featuring a comprehensive set of software drivers,

Order Information

OfficeLAN PCI 10Base-T/100Base-TX Fast Ethernet Adapter

- **SD0581PA** Single card
- **SD0581PB** Twenty-pack
- **SD0581PC** Sixty-pack

the OfficeLAN adapter supports an extensive range of the most widely used operating systems, including Windows NT, Windows 95/98, Novell Netware, IBM LAN Server, Banyan VINES, SCO UNIX and more.

Simple Plug-and-Play Installation

Easy to install, OfficeLAN offers a genuine plug-and-play Fast Ethernet adapter. Troubleshooting is made simple with the OfficeLAN diagnostic tool's graphical user interface.

Maximum Throughput

The Siemens OfficeLAN PCI Adapter is designed with a bus master to optimize the 32-bit PCI bus, facilitating maximum throughput for your bandwidth-intensive network applications.

*The Siemens OfficeLAN Product Line
Combining quality, performance and reliability to
support your network for years to come.*

Product Specification	
Media Access	IEEE 802.3/IEEE 802.3u 10Base-T/100Base-TX
Cable	Type: 10Base-T/100Base-TX Categories 3, 4 / 5, UTP or STP Length (max): 100 m (330 ft) Connector: Unshielded/shielded 8-pin male RJ45
Network Operating Systems Supported	Microsoft Windows NT, Windows 95/98, LAN Manager, Novell Netware, Windows for Workgroups, IBM LAN Server, IBM LAN Support, NDIS Driver, DEC PATHWORKS, Banyan, IBM TCP/IP for DOS and OS/2, SCO UNIX, PacketDriver, FTP PC/TCP, NCSA TCP/IP
Bus Interface	32-bit bus master
Hardware Interrupts	PCI INTA
Base I/O Address	Assigned by BIOS
Boot ROM	Optional
LEDs	ACT Data transmission LINK Link signal integrity 100 100/10 Mbps speed
Power Consumption	Operation mode: 4.2 W Standby mode: 3.9 W
Dimensions	130 mm x 70 mm (5 1/2" x 2 3/4")
EMC	FCC Part 15, Class A CE EN55022 (1988) /CISPR22(1985) Class A
Safety	EN60950, UL 1950, cUL 1950

Headquarters

Siemens Data Communication, Ltd.
Newton House, Industrial Area 5, P.O. Box 323
Karmiel 21613, Israel
Tel: Intl+972-4-988-1314, Fax: Intl+972-4-998-1315
URL: <http://www.siemensdc.com>

United States

Siemens Data Communication, Ltd.
1 Cross Island Plaza—Dept. 105
Rosedale, New York 11422
US Toll Free: 888-242-6202
Tel: 718-276-8220, Fax: 718-276-8221

UK Distribution

Dynanet (UK) Ltd.
72a St. Mary's Road
Watford, Hertfordshire
WD1 8EF, U.K.
Tel: +44-1923244438, Fax: +44-1923245475