



## MODELS AND SPECIFICATIONS

MODEL	SCREEN SIZE	VISIBLE AREA	DOT PITCH	CRT	HORIZONTAL FREQUENCY	OPTIMUM RESOLUTION	ON SCREEN MENU CONTROL	MPR-II	TCO'95	PLUG 'N PLAY	BUILT-IN SPEAKERS	BUILT-IN VIDEO CAMERA
Multigraph 449Xa	15"	13.54"	.25	Trinitron	30 - 65 kHz	1024 x 768 @ 80 Hz	•	•	•	•	•	
Valuegraph 447L	17"	15.70"	.28	Inver Mask	31 - 64 kHz	1024 x 768 @ 80 Hz		•			•	
Multigraph 4472a	17"	16.0"	.27	Inver Mask	31 - 72 kHz	1024 x 768 @ 90 Hz		•	•	•	•	
Valuegraph 447W	17"	15.70"	.26	Inver Mask	31 - 85 kHz	1280 x 1024 @ 79 Hz	•	•		•	•	
Multigraph 447Xi	17"	15.71"	.25	Trinitron	31 - 92 kHz	1280 x 1024 @ 85 Hz	•	•	•	•		
Multigraph 447Xav	17"	15.71"	.25	Trinitron	31 - 92 kHz	1280 x 1024 @ 85 Hz	•	•	•	•	•	
Multigraph 447Xavc	17"	15.71"	.25	Trinitron	31 - 92 kHz	1280 x 1024 @ 85 Hz	•	•	•	•	•	•
Multigraph 445Xi	21"	19.69"	.22 horiz	Inver Mask	30 - 102 kHz	1600 x 1200 @ 80 Hz	•	•	•	•		
Multigraph 445Xav	21"	19.69"	.22 horiz	Inver Mask	30 - 102 kHz	1600 x 1200 @ 80 Hz	•	•	•	•	•	
Multigraph 445Xavc	21"	19.69"	.22 horiz	Inver Mask	30 - 102 kHz	1600 x 1200 @ 80 Hz	•	•	•	•	•	•

## RESOLUTIONS AND REFRESH RATES

MODEL	640 X 480	800 X 600	1024 X 768	1152 X 870	1280 X 1024	1600 X 1200
Multigraph 449Xa	120 Hz	100 Hz	80 Hz			
Valuegraph 447L	100 Hz	100 Hz	80 Hz			
Multigraph 4472a	120 Hz	110 Hz	90 Hz	78 Hz	65 Hz	
Valuegraph 447W	100 Hz	100 Hz	100 Hz	90 Hz	79 Hz	
Multigraph 447Xi	150 Hz	140 Hz	110 Hz	100 Hz	85 Hz	72 Hz
Multigraph 447Xav	150 Hz	140 Hz	110 Hz	100 Hz	85 Hz	72 Hz
Multigraph 447Xavc	150 Hz	140 Hz	110 Hz	100 Hz	85 Hz	72 Hz
Multigraph 445Xi	150 Hz	150 Hz	120 Hz	110 Hz	95 Hz	80 Hz
Multigraph 445Xav	150 Hz	150 Hz	120 Hz	110 Hz	95 Hz	80 Hz
Multigraph 445Xavc	150 Hz	150 Hz	120 Hz	110 Hz	95 Hz	80 Hz

Specifications subject to change.

ENGINEERED IN EUROPE FOR THE WORLD  
1.800.BY.NOKIA | [www.nokia-america.com](http://www.nokia-america.com)