



## P6L40-A4 Motherboard

**TD#: 771597**

### Specifications

<b>Processor</b>	SLOT 1 support Intel Pentium II Processor 233MHz ~ 300MHz
<b>Chipset</b>	INTEL 440LX PCIset
<b>BIOS</b>	Award PCI BIOS, support ACPI, DMI, Green PC, Plug-and-Play Boot from CD-ROM, SCSI, LS-120 , ZIP devices Symbios SCSI BIOS
<b>System Memory</b>	4 168-pin DIMM Sockets Support up to 512MB Memory Capacity Use 8/18/32/64/128 MB 168-pin Single or Double Side 3.3V SDRAM and 3.3V EDO Module ECC Supported
<b>On-board I/O Features</b>	1 Floppy Port ( Up to 2.88MB, 3 Mode, LS120 ) 1 Parallel Port ( EPP, ECP Port) 2 Serial Ports ( 16550 Fast UART Compatible) 2 IrDA TX/RX Header (FIR/CIR/SIR) 1 I2C Header
<b>Advanced Features</b>	Accelerated Graphics Port (AGP) Slot Supported AGP 66MHz/133MHz(Sideband) 3.3V Device Modem Ring-in Power on 3. Soft Power off
<b>PCI Bus Master IDE</b>	2 UltraDMA/33 IDE Ports Support UltraDMA/33: 33MB/Sec. , PIO mode 3,4 :17MB/Sec.
<b>Expansion Slot</b>	1 32-bit AGP Slot, 4 32-bit PCI Bus Master Slots, 3 16-bit ISA Slots
<b>ATX Double Decker</b>	2 USB Ports, 1 Parallel Port 1 PS/2 Keyboard Port 2 COM Ports 1 PS/2 Mouse Port
<b>ATX Power Connector</b>	3V, 5V and 12V 20 Pin ATX Power connector.
<b>Switching VR</b>	Switching Voltage Regulator to support 1.3V to 3.5V
<b>Form Factor</b>	ATX Form factor ( 7.7'' 12'' or 195mm 305mm )