

Tech Data part # 884684

For questions on this product Specification call Ramon Auders the Toshiba Systems Engineer at Tech Data 1-800-237-8931 ext. 80065

Tecra 550CDT Product Specification Summary

PROCESSOR	CPU	Pentium (2.0 volt) processor with MMX™ technology
	Clock Speed	266MHz
	Cache	32KB internal cache, 512KB pipelined burst SRAM Level 2 cache
MEMORY	Standard	32MB high-speed EDO DRAM
	Maximum	160MB EDO DRAM
BUS ARCHITECTURE		PCI Internal System Bus
		PCI External Expansion Bus (via Desk Station V Plus)
HDD	Capacity	4.0 billion byte (=3.82GB) hard disk drive
	HDD Type	Upgradeable 2.5" (12.7mm), enhanced IDE
SELECTBAY SUPPORT	Diskette Drive	3.5", 1.44MB (included, swapable with other modules)
	CD-ROM (17mm)	Toshiba 20X* max speed (included, swapable with other modules)
	Optional Modules	2nd Lithium Ion battery, 2 nd HDD (2.02GB); each swapable other modules
DISPLAY	Type	12.1" diagonal TFT active matrix color
	Internal LCD Resolution	1024 x 768
	Max. Color Support	16M at 1024 x 768 (64K at 1280 x 1024, 256 at 1600 x 1200)
	Ext. Video Support	16M at 1024 x 768/800 x 600/640 x 480, 64K at 1280 x 1024, 256 at 1600 x 1200
VIDEO	Graphics Controller	S3 ViRGE™/MX
	Video Memory	4MB Synchronous GRAM
	Graphics Acceleration	64-bit BitBLT
	Local-bus	32-bit PCI bus (w/ burst mode)
	Zoomed Video	Yes
	YUV-RGB Conversion	Yes
	Interpolation	Vertical and Horizontal
Standards Support		DirectVideo, Direct3D, OpenGL
	Simul. Display Support	1024 x 768, 800 x 600, 640 x 480
AUDIO	Chipset	Yamaha 3D sound effect-enabled OPL3-SA3
	Support	16-bit MIDI, .WAV, and Sound Blaster® Pro compatible; Internal stereo speakers and microphone; microphone, speaker/headphone, line-in jacks
COMMUNICATIONS		Built-in K56flex modem with DSVD support using V.80 & V.34 protocol for voice/ video/fax communications, cellular ready DAA support in Windows® 95, full duplex speakerphone; integrated telephony using RingCentral®
EXPANSION	PC Card Slots	Supports (2) Type II or (1) Type III PC Cards; ZV and CardBus Card support
	Plug and Play Interfaces	Yes USB, high-speed serial, ECP parallel, SVGA video, PS/2™ keyboard/mouse, diskette drive, microphone, speaker/headphone, line-in, fast infrared port (FIR= IrDA 1.1 4Mbps compatible), 240-pin docking connector, RJ-11 telephone jack, cellular telephone jack
KEYBOARD	Keys	Full-sized 84 Keys, 3mm travel
INTEGRATED POINTING DEVICE		AccuPoint™
DIMENSIONS	Weight	5.8 pounds with weight saver; 6.2 pounds with diskette; 6.3 pounds with CD-ROM
	Measurements	11.7" x 9.1" x 1.85"
OTHER	Operating System	Windows 95; optional Windows NT Workstation 4.0 driver and application support
	Bundled Software	LANDesk Client Manager, Internet Explorer 3.02, Puma IntelliSync™ 97, Mediomatics MPEG Arcade Pak™, RingCentral, America Online®, CompuServe®, Intel Indeo Video 4.1, Yamaha Station, SystemSoft Card Works, Toshiba Custom Utilities: MaxTime and Fn-esse. Tecra 550CDT electronic documentation
	DMI Security Features	DMI 2.0 BIOS support Lock slot, two level (user and supervisor) power-on password, Desk Station V Plus eject password, two cable lock ports, PC Card slot cable lock, main system memory and modem locked by hardware screws
OPTIONS	Desk Station V Plus	Hot docking and undocking, (2) full size 32-bit PCI/16-bit ISA cards, (1) half length dedicated PCI slot, (2) Type III (4 Type II) CardBus-ready PC Card slots, built-in SCSI-II/IDE interface, full-height SelectBay slot, standard half-height 5.25" drive bay, integrated stereo speakers/amp; Interfaces: serial, parallel, PS/2 keyboard, PS/2 mouse, external monitor, joystick/MIDI, microphone, speaker/headphone, line-in, line-out; lock slot
	NoteDock II	Hot docking and undocking (Windows 95), (2) Type III (4 Type II) CardBus-ready

**Enhanced
Port Replicator**

PC Card slots; Interfaces: serial, parallel, PS/2 keyboard, PS/2 mouse, DC in, external monitor, lock slot, joystick/MIDI, line-in, line-out, speaker/headphone, microphone

WARRANTY

3 year parts and labor; battery 1 year

For question on this product Specification call Ramon Auders the Toshiba Systems Engineer at Tech Data
1-800-237-8931 ext. 80065

Kingston Memory upgrades

Tech Data #

447935	KTT650/8	8MB EDO
447936	KTT650/16	16MB EDO
448026	KTT650/32	32MB EDO
448013	KTT650/64	64MB EDO
TBA	KTT650/128	128MB EDO

NOTEWORTHY ACCESSORIES

TBA	PA2710U	Desk Station V Plus Docking Station
TBA	PA2713U	Notedock II Port Replicator
884034	PA2906U	2.02GB Secondary hard disk drive
884031	PA2448UR	Battery pack (primary Lithium ION)
884032	PA2451UR	Second Lithium Ion Battery pack
884033	PA2449	Battery Charger (primary or Second)
884035	PA2450U	Universal AC adapter