

FEATURES & BENEFITS

0.28mm dot pitch

This fine dot pitch produces images that are crisp, even at the highest resolutions.

1,280 x 1,024 maximum resolution

The Optiquest Q53 displays resolutions up to 1,280 x 1,024 with an 87Hz refresh rate at 1,024 x 768.

Digital controls

This easy-to-use control system easily adjusts screen size, position and geometry for optimal viewing.

Anti-glare/anti-static screen

Special screen treatment that reduces reflection, glare and static, while maintaining high image quality.

Plug & Play †

Fully supports the Windows® 95 auto-installation standard.

MPR-II and EPA Energy Star™ compliant

Exceeds these strict standards for reduced emissions and power consumption.

Optiquest Q53

15" (13.8" viewable) FLAT SQUARE SCREEN WITH *Plug & Play* †

MODEL NO. VCDTS21359-1M

CRT	Type	15" (13.8" diagonal viewable area), 0.28mm dot pitch, 90° deflection
	Phosphor	RGB medium persistence
	Glass Surface	Tint (TM=57%), anti-glare/anti-static screen
INPUT SIGNAL	Video	RGB Analog (0.7/1.0Vp-p, 75 ohms)
	Sync	H/V Separate (TTL),
	Frequency	F _H :30-70KHz, F _V :50-90Hz
COMPATIBILITY	PC	IBM® XT, AT, 386, 486, Pentium® or PS/2 and compatibles (VGA to 1,280 x 1,024 non-interlaced)
CONNECTOR	Signal	15-pin mini D-sub
	Power	3-pin plug (IEC320)
POWER	Voltage	AC 90-264V
	Consumption	95W (maximum)
USER CONTROLS	Basic	Power on/off, contrast, brightness, H/V-position, H/V-size, pincushion, trapezoid, recall
VIDEO INPUT	Bandwidth	110MHz (typical)
MISCONVERGENCE		0.30mm (max) at center 0.40mm (max) at corner
DISPLAY AREA	Factory Setting	260mm (H) x 195mm (V) (Dependent upon
	Maximum Scan	283mm (H) x 212mm (V) signal timing used)
OPERATING CONDITION	Temperature	32°F to 104°F (0°C to 40°C)
	Humidity	5% to 95%
DIMENSIONS	Physical	380mm (W) x 374mm (H) x 392mm (D) (14.9" x 14.7" x 15.4")
WEIGHT	Net	12.5Kg (27.5 lbs.)
OTHER		DDC1, DDC2B
REGULATIONS		UL, CSA, DHHS, FCC-B, DOC-B, VCCI-II, EN60950, TUVGS, TUV ERGO, CE, PTB, ISO9241-3, MPR-II
POWER MANAGEMENT		Meets Energy Star™, VESA® DPMS™ and NUTEK standards
WARRANTY		Three year limited warranty on CRT, parts and one year labor 48 hour Express Exchange™ Service option available

OPTIQUEST.

A ViewSonic Company

20480 Business Parkway, Walnut, CA 91789

(800) 888-8583 • (909) 869-7976

Fax (909) 869-7958 • FaxSonic (909) 869-7318 (24-hour fax-on-demand)

Internet: www.viewsonic.com