

## Addendum

Take note of the following change in the PCI Devices screen on page 3-19 of the PI16 User's Guide.

PCI Devices	
PCI Device, Slot #1:	
Enable Master:	[Enabled]
Use Default Latency Timer Value:	[Yes]
Latency Timer Value:	[0040]
PCI Device, Slot #2:	
Enable Master:	[Enabled]
Use Default Latency Timer Value:	[Yes]
Latency Timer Value:	[0040]
PCI Device, Slot #3:	
Enable Master:	[Disabled]
Use Default Latency Timer Value:	[Yes]
Latency Timer Value:	[0040]
PCI Device, Slot #4:	
Enable Master:	[Disabled]
Use Default Latency Timer Value:	[Yes]
Latency Timer Value:	[0040]
PCI IRQ Line 1:	[Auto Select]
PCI IRQ Line 2:	[Auto Select]
PCI IRQ Line 3:	[Auto Select]
PCI IRQ Line 4:	[Auto Select]
↓ Move	Esc Exit
	F1 Help
PgUp	Previous Value
PgDn	Next Value
F5	Previous Configuration
F6	Default Configuration

### PCI IRQ Line 1 to Line 4

These parameters allow you to specify interrupts for PCI devices to avoid IRQ assignment conflict with non-PnP ISA devices. The selections for these parameters are 5, 6, 9, 10, 11, 12, 14, 15, Auto, and Disabled.



*Make sure not to assign a PCI device with any IRQ currently in use by a non-PnP ISA device.*

*Use the selection Auto Select only if no non-PnP ISA devices are installed in your system.*