

Resilient Tile Flooring 09658

(7) Bleach: No Change

(8) 5% Phenol: No Change

(9) Gasoline: Slight Change

(10) Sulfuric Acid: No Change

(11) Kerosene: Slight Change

(12) Olive Oil: No Change

f. Ambient Noise Reduction, Sabin/ft² (ASTM C423): 0.05

g. Thermal Conductivity, BTU-in/hr-ft² -°F (ASTM C518): approximately 0.445

Specifier Note: Below ECOpave™ product offers heavy duty molded surfaces of the highest quality and

endless design options. ECOpave™ is made from only premium quality 100% recycled SBR tire rubber

and is available in several thicknesses to suit traffic requirements. ECOpave™ is outstanding for abuse-oriented

spaces and extra heavy-duty use indoors and outdoors. It is unaffected by ice, water and extreme temperature and is safe and slip resistant.

F. Dodge-Regupol ECOpave Recycled Rubber Resilient Flooring:

1. Thickness:

a. Interlocking “dog-bone shaped” paver:

(1) Thickness: [Specify 7/8” (22.2mm) or 1 3/4” (44mm)].

(2) Weight: [Specify 1.25 lb/ft² (6kg/m²) or 2.50 lb/ft² (12 kg/m²)].

b. Rectangular Tile:

(1) Thickness: [Specify 5/8” (15.9mm) or 1 1/4” (32mm)].

(2) Weight: [Specify 2.5 lb/ft² (12kg/m²) or 4.9 lb/ft² (24 kg/m²)].

c. Embossed Square Tile

(1) Thickness: [Specify 5/8” (15.9mm) or 1 1/4” (32mm)].

(2) Weight: [Specify 4.9 lb/ft² (24 kg/m²) or 9.8 lb/ft² (48 kg/m²)].

2. Shape:

a. Interlocking “dog-bone shaped” paver: [Specify 7 3/4” x 6 1/4” x 4 1/2” (197mm x 159mm x 114mm)].

b. Rectangular Tile: [Specify 3.28’ x 1.64’ (1000mm x 500mm)].

c. Embossed square paver tile: [Specify 2’ x 2’ (610mm x 610 mm)].

3. Colors: [Specify color from manufacturer’s standard colors.].

4. Product Testing:

a. Tensile Strength, lb/in² (ASTM D412): 200 min.

b. Coefficient of Friction (ASTM 2047): greater than 0.6

Specifier Note: Edit article below to suit project requirements. If substitutions are permitted, edit test

below. Add text to refer to Division 1 Project Requirements (Product substitutions Procedures) Section.

2.02 PRODUCT SUBSTITUTIONS

A. Substitutions: No substitutions permitted.

2.03 RELATED MATERIALS